

Source: **TSG CN WG 1**

Title: **CRs to Rel-5 on Work Item IMS-CCR towards 24.229,- pack 3**

Agenda item: **8.1**

Document for: **APPROVAL**

Introduction:

This document contains **5 CRs, Rel-5 to Work Item "IMS-CCR"**, that have been agreed by **TSG CN WG1 in CN1#31 meeting**, and are forwarded to TSG CN Plenary meeting #21 for approval.

TDoc #	Tdoc Title	Spec	CR #	Rev	CAT	C_Version	Rel
N1-031314	Adding P-Asserted-Identity headers to NE initiated subscriptions	24.229	470	1	F	5.5.0	Rel-5
N1-031247	Replace USIM by ISIM for user identity storage	24.229	479	1	F	5.5.0	Rel-5
N1-031248	24.229 R5 CR: Corrections to Profile Tables	24.229	481	1	F	5.5.0	Rel-5
N1-031140	24.229 R5 CR: Setting of SUBSCRIBE expiration time	24.229	482		F	5.5.0	Rel-5
N1-031335	24.229 R5 CR: Alignment of IMS Compression with RFC 3486	24.229	483	3	F	5.5.0	Rel-5

CHANGE REQUEST

24.229 CR CR470 # rev 1 # Current version: 5.5.0

For **HELP** on using this form, see bottom of this page or look at the pop-up text over the # symbols.

Proposed change affects: UICC apps # ME Radio Access Network Core Network

Title:	# Adding P-Asserted-Identity headers to NE initiated subscriptions	
Source:	# Nokia	
Work item code:	# IMS-CCR	Date: # 18/08/2003
Category:	# F Use <u>one</u> of the following categories: F (correction) A (corresponds to a correction in an earlier release) B (addition of feature), C (functional modification of feature) D (editorial modification) Detailed explanations of the above categories can be found in 3GPP TR 21.900 .	Release: # Rel-5 Use <u>one</u> of the following releases: 2 (GSM Phase 2) R96 (Release 1996) R97 (Release 1997) R98 (Release 1998) R99 (Release 1999) Rel-4 (Release 4) Rel-5 (Release 5) Rel-6 (Release 6)

Reason for change:	# When P-CSCF and the ASs generate subscriptions to the reg event of the user, they must add a P-Asserted-Identity header in there to let know the S-CSCF who generated the request and authorise the subscriptions.
Summary of change:	# Procedures to add the P-Asserted-Identity into the SUBSCRIBE requests have been added.
Consequences if not approved:	# The S-CSCF will have no means to know the originator of the request and therefore will not be able to authorise the subscriptions.

Clauses affected:	#								
Other specs affected:	# <table border="1" style="display: inline-table; vertical-align: middle;"><tr><td>Y</td><td>N</td></tr><tr><td>X</td><td></td></tr><tr><td>X</td><td></td></tr><tr><td>X</td><td></td></tr></table> Other core specifications # <input type="checkbox"/> # <input type="checkbox"/> Test specifications # <input type="checkbox"/> # <input type="checkbox"/> O&M Specifications # <input type="checkbox"/>	Y	N	X		X		X	
Y	N								
X									
X									
X									
Other comments:	#								

How to create CRs using this form:

Comprehensive information and tips about how to create CRs can be found at <http://www.3gpp.org/specs/CR.htm>. Below is a brief summary:

- 1) Fill out the above form. The symbols above marked # contain pop-up help information about the field that they are closest to.
- 2) Obtain the latest version for the release of the specification to which the change is proposed. Use the MS Word "revision marks" feature (also known as "track changes") when making the changes. All 3GPP specifications can be downloaded from the 3GPP server under <ftp://ftp.3gpp.org/specs/> For the latest version, look for the directory name with the latest date e.g. 2001-03 contains the specifications resulting from the March 2001 TSG meetings.

- 3) With "track changes" disabled, paste the entire CR form (use CTRL-A to select it) into the specification just in front of the clause containing the first piece of changed text. Delete those parts of the specification which are not relevant to the change request.

5.2.3 Subscription to the user's registration-state event package

Upon receipt of a 200 (OK) response to the initial REGISTER request of an user, the P-CSCF shall subscribe to the reg event package at the users registrar (S-CSCF) as described in draft-ietf-sipping-reg-event-00 [43]. The P-CSCF shall:

- 1) generate a SUBSCRIBE request with the following elements:
 - a Request-URI set to the resource to which the P-CSCF wants to be subscribed to, i.e. to a SIP URI that contains the default public user identity of the user;
 - a From header set to the P-CSCF's SIP URI;
 - a To header, set to a SIP URI that contains the default public user identity of the user;
 - an Event header set to the "reg" event package; ~~and~~
 - an Expires header set to a value higher than the Expires header indicated in the 200 (OK) response to the REGISTER request; and
 - a P-Asserted-Identity header containing its own SIP URI the SIP URI of the P-CSCF. This SIP URI must be the same with the one which was inserted into the Path header during the registration of the user to whose registration state the P-CSCF subscribes to; and
- 2) determine the I-CSCF of the home network (e.g., by using DNS services);

before sending the SUBSCRIBE request to that I-CSCF, according to the procedures of RFC 3261 [26].

Upon receipt of a 2xx response to the SUBSCRIBE request, the P-CSCF shall store the information for the so established dialog and the expiration time as indicated in the Expires header of the received response.

If continued subscription is required the P-CSCF shall automatically refresh the subscription by the reg event package 600 seconds before the expiration time for a previously registered public user identity, either 600 seconds before the expiration time if the initial subscription was for greater than 1200 seconds, or when half of the time has expired if the initial subscription was for 1200 seconds or less.

5.4.2.1.1 Subscription to the event providing registration state

When an incoming SUBSCRIBE request addressed to S-CSCF arrives containing the Event header with the reg event package, the S-CSCF shall:

- 1) check if, based on the local policy, the request was generated by a subscriber who is authorised to subscribe to the registration state of this particular user. The authorized subscribers include:
 - all public user identities this particular user owns, that the S-CSCF is aware of, and which are not-barred;
 - all the entities identified by the Path header (i.e. the P-CSCF to which this user is attached to); and
 - all the ASs not belonging to third-party providers.

NOTE: the S-CSCF finds the identity of the originator of the SUBSCRIBE request in the P-Asserted-Identity header.
- 2) generate a 2xx response acknowledging the SUBSCRIBE request and indicating that the authorised subscription was successful as described in draft-ietf-sipping-reg-event-00 [43]. The S-CSCF shall populate the header fields as follows:
 - an Expires header, set to either the same or a decreased value as the Expires header in SUBSCRIBE request; and
 - a Contact header, set to is an identifier generated within the S-CSCF that will help to correlate refreshes for the SUBSCRIBE.

Afterwards the S-CSCF shall perform the procedures for notification about registration state as described in subclause 5.4.2.1.2.

5.7.1.1 Notification about registration status

The AS may support the REGISTER method in order to discover the registration status of the user. If a REGISTER request arrives containing information about the user's registration status and the AS supports the REGISTER method, the AS shall store the Expires parameter from the request and generate a 200 (OK) response or an appropriate failure response. For the success case, the 200 (OK) response shall contain Expires value equal to the value received in the REGISTER request. The AS shall store the values received in P-Charging-Function-Addresses header. Also, the AS shall store the values of the icid parameter in the P-Charging-Vector header from the REGISTER request.

Upon receipt of a third-party REGISTER request, the AS may subscribe to the reg event package for the public user identity registered at the users registrar (S-CSCF) as described in draft-ietf-sipping-reg-event-00 [43].

On sending a SUBSCRIBE request, the AS shall populate the header fields as follows:

- a) a Request URI set to the resource to which the AS wants to be subscribed to, i.e. to a SIP URI that contains the public user identity of the user that was received in the To header field of the third-party REGISTER request;
 - b) a From header field set to the AS's SIP URI;
 - c) a To header field, set to a SIP URI that contains the public user identity of the user that was received in the To header field of the third-party REGISTER request; and
 - d) an Event header set to the "reg" event package.
- e) P-Asserted-Identity header field containing the SIP URI of the AS, its own SIP URI. This SIP URI must be the same with the one, which identifies this AS in the initial filter criteria of the user to whose registration state the AS subscribes to.

Upon receipt of a 2xx response to the SUBSCRIBE request, the AS shall store the information for the so established dialog and the expiration time as indicated in the Expires header of the received response.

CHANGE REQUEST

⌘ 24.229 CR 479 ⌘ rev -1 ⌘ Current version: 5.5.0 ⌘

For **HELP** on using this form, see bottom of this page or look at the pop-up text over the ⌘ symbols.

Proposed change affects: UICC apps ⌘ ME ⌘ Radio Access Network ⌘ Core Network ⌘

Title:	⌘ Replace USIM by ISIM for user identity storage	
Source:	⌘ Qualcomm	
Work item code:	⌘ IMS-CCR	Date: ⌘ 19/08/2003
Category:	⌘ F <small>Use one of the following categories: F (correction) A (corresponds to a correction in an earlier release) B (addition of feature), C (functional modification of feature) D (editorial modification)</small> <small>Detailed explanations of the above categories can be found in 3GPP TR 21.900.</small>	Release: ⌘ Rel-5 <small>Use one of the following releases: 2 (GSM Phase 2) R96 (Release 1996) R97 (Release 1997) R98 (Release 1998) R99 (Release 1999) Rel-4 (Release 4) Rel-5 (Release 5) Rel-6 (Release 6)</small>

Reason for change:	⌘ Mistakes in the specification implying that IMS public user identity is stored in USIM need to be corrected.
Summary of change:	⌘ Remove the implication that USIM is the entity storing IMS public user identity, in clause 5.1.2A.1.
Consequences if not approved:	⌘ Incorrect specification may lead to confusion on how IMS public user identity is stored.

Clauses affected:	⌘ 5.1.2A.1								
Other specs affected:	⌘ <table border="1" style="display: inline-table; vertical-align: middle;"><tr><td>Y</td><td>N</td></tr><tr><td> </td><td> </td></tr><tr><td> </td><td> </td></tr><tr><td> </td><td> </td></tr></table> Other core specifications ⌘ Test specifications ⌘ O&M Specifications ⌘	Y	N						
Y	N								
Other comments:	⌘								

How to create CRs using this form:

Comprehensive information and tips about how to create CRs can be found at <http://www.3gpp.org/specs/CR.htm>. Below is a brief summary:

- 1) Fill out the above form. The symbols above marked ⌘ contain pop-up help information about the field that they are closest to.
- 2) Obtain the latest version for the release of the specification to which the change is proposed. Use the MS Word "revision marks" feature (also known as "track changes") when making the changes. All 3GPP specifications can be downloaded from the 3GPP server under <ftp://ftp.3gpp.org/specs/> For the latest version, look for the directory name with the latest date e.g. 2001-03 contains the specifications resulting from the March 2001 TSG meetings.

- 3) With "track changes" disabled, paste the entire CR form (use CTRL-A to select it) into the specification just in front of the clause containing the first piece of changed text. Delete those parts of the specification which are not relevant to the change request.

5.1.2A.1 Mobile-originating case

The procedures of this subclause are general to all requests and responses, except those for the REGISTER method.

In accordance with RFC 3325 [34] the UE may insert a P-Preferred-Identity header in any initial request for a dialog or request for a standalone transaction as a hint for creation of an asserted identity within the IM CN subsystem. The UE may include any of the following in the P-Preferred-Identity header:

- a public user identity **stored in the USIM** which has been registered by the user;
- a public user identity returned in a registration-state event package of a NOTIFY request as a result of an implicit registration that was not subsequently deregistered or has expired; or
- any other public user identity which the user has assumed by mechanisms outside the scope of this specification to have a current registration.

NOTE 1: The temporary public user identity specified in subclause 5.1.1.1 is not a public user identity suitable for use in the P-Preferred-Identity header.

NOTE 2: Procedures in the network require international public telecommunication numbers when telephone numbers are used in P-Preferred-Identity header.

Where privacy is required, in any initial request for a dialog or request for a standalone transaction, the UE shall set the From header to "Anonymous".

NOTE 3: The contents of the From header should not be relied upon to be modified by the network based on any privacy specified by the user either within the UE indication of privacy or by network subscription or network policy. Therefore the user should include the value "Anonymous" whenever privacy is explicitly required. As the user may well have privacy requirements, terminal manufacturers should not automatically derive and include values in this header from the public user identity or other values stored in **or derived from** the **USIM****UICC**. Where the user has not expressed a preference in the configuration of the terminal implementation, the implementation should assume that privacy is required. Users that require to identify themselves, and are making calls to SIP destinations beyond the IM CN subsystem, where the destination does not implement RFC 3325 [34], will need to include a value in the From header other than Anonymous.

The UE can indicate privacy of the P-Asserted-Identity that will be generated by the P-CSCF in accordance with RFC 3323 [33], and the additional requirements contained within RFC 3325 [34].

The UE shall insert a P-Access-Network-Info header into any request for a dialog, any subsequent request (except ACK requests and CANCEL requests) or response (except CANCEL responses) within a dialog or any request for a standalone method. This header shall contain information concerning the access network technology and, if applicable, the cell ID (see subclause 7.2A.4).

The UE shall build a proper preloaded Route header value for all new dialogs and standalone transactions. The UE shall build a list of Route header values made out of, in this order, the P-CSCF URI (containing the IP address or the FQDN learnt through the P-CSCF discovery procedures, and the protected port learnt during the registration procedure), and the values received in the Service-Route header saved from the 200 (OK) response to the last registration or re-registration.

CHANGE REQUEST

⌘ 24.229 CR 481 ⌘ rev 1 ⌘ Current version: 5.5.0 ⌘

For **HELP** on using this form, see bottom of this page or look at the pop-up text over the ⌘ symbols.

Proposed change affects: UICC apps ⌘ ME Radio Access Network ⌘ Core Network

Title:	⌘ 24.229 R5 CR: Corrections to Profile Tables	
Source:	⌘ Nokia	
Work item code: ⌘	IMS-CCR	Date: ⌘ 15/08/2003
Category: ⌘ F	Use <u>one</u> of the following categories: F (correction) A (corresponds to a correction in an earlier release) B (addition of feature), C (functional modification of feature) D (editorial modification)	Release: ⌘ Rel-5 Use <u>one</u> of the following releases: 2 (GSM Phase 2) R96 (Release 1996) R97 (Release 1997) R98 (Release 1998) R99 (Release 1999) Rel-4 (Release 4) Rel-5 (Release 5) Rel-6 (Release 6)
Reason for change: ⌘ The following changes have been identified:		

1) Table A.50 (Supported headers within INVITE responses): the Contact header is missing (see RFC 3261 – 12.1.1)
2) Table A.46 – Require header in INVITE – optional to be sent in RFC, but mandatory to be sent in Profile (due to several SIP extensions, e.g. sec-agree, preconditions). Therefore c.8 is deleted.
3) Table A.7 – Sending of Content-Type header in ACK is optional. Same is true for MESSAGE (Table A.62A).
4) Prerequisite A.6/34 in table A.52 does not point to 485 response. Prerequisite number corrected to A.6/35.
5) Condition c6 in A.119 (Supported headers within REGISTER request) – the UE is not mandated to receive the Path header in the REGISTER request, as the UE never receives a REGISTER.
6) Authorization header in REGISTER request (A.119) – due to RFC 3310 it is mandatory to include the Authorization header in the initial REG and in re-REG. Therefore its inclusion on the sending side is set to "o". The Authorization header can only be received by the S-CSCF, not by the UE itself, therefore condition c22 is changed to S-CSCF.
7) A.62C states that Content-Type header is mandatory to be sent for MESSAGE response, whilst RFC 3428 states that 200 OK to MESSAGE MUST NOT include any

	<p>content. Therefore all Content-* headers set to "x" for sending and to "n/a" for receiving.</p> <p><u>87</u>) Reference in A.134 for Event header and A.46 for Allow-Events header is wrong – section does not exist.</p> <p><u>98</u>) Max-Forwards header is mandatory to be sent (and received) in all requests, not optional.</p> <p><u>109</u>) P-Access-Network-Info header in REG is only set if SA exists – therefore a Note is added to c13 in A.119 (REGISTER request)</p> <p><u>119</u>) Supported header and Require header in A.50 (INVITE response), A.94 / A.95 (PRACK responses), A.62C/A.62D (MESSAGE responses) – these are optional to be sent. For normal IMS operation they are not sent.</p> <p><u>1240</u>) The contact header is mandatory to be set in the first response to an INVITE request, i.e. the 183 request MUST include the contact header, therefore table A.50 entry 4 is changed to "m".</p> <p><u>Changes in first revision:</u></p> <ul style="list-style-type: none"> - deleted paragraph that was not meant to go into the document - changed bullet numbering in this section - Max-Forwards header is n/a for UE role to receive (no action on it) - only the 2xx responses to MESSAGE must not include a body, all other responses are allowed
--	--

Summary of change:  Changes are introduced as outlined above

Consequences if not approved:  24.229 Profile Tables are not in-line with 24.229 text / RFC text

Clauses affected:	 Annex A								
Other specs affected:	<table border="1" data-bbox="452 1291 531 1414"> <tr> <td>Y</td> <td>N</td> </tr> <tr> <td>X</td> <td></td> </tr> <tr> <td>X</td> <td></td> </tr> <tr> <td>X</td> <td></td> </tr> </table>  Other core specifications   Test specifications   O&M Specifications 	Y	N	X		X		X	
Y	N								
X									
X									
X									
Other comments:									

How to create CRs using this form:

Comprehensive information and tips about how to create CRs can be found at <http://www.3gpp.org/specs/CR.htm>. Below is a brief summary:

- 1) Fill out the above form. The symbols above marked  contain pop-up help information about the field that they are closest to.
- 2) Obtain the latest version for the release of the specification to which the change is proposed. Use the MS Word "revision marks" feature (also known as "track changes") when making the changes. All 3GPP specifications can be downloaded from the 3GPP server under <ftp://ftp.3gpp.org/specs/> For the latest version, look for the directory name with the latest date e.g. 2001-03 contains the specifications resulting from the March 2001 TSG meetings.
- 3) With "track changes" disabled, paste the entire CR form (use CTRL-A to select it) into the specification just in front of the clause containing the first piece of changed text. Delete those parts of the specification which are not relevant to the change request.

Annex A (normative): Profiles of IETF RFCs for 3GPP usage

A.1 Profiles

A.1.1 Relationship to other specifications

This annex contains a profile to the IETF specifications which are referenced by this specification, and the PICS proformas underlying profiles do not add requirements to the specifications they are proformas for.

This annex provides a profile specification according to both the current IETF specifications for SIP, SDP and other protocols (as indicated by the "RFC status" column in the tables in this annex) which are referenced by this specification and to the 3GPP specifications using SIP (as indicated by the "Profile status" column in the tables in this annex).

In the "RFC status" column the contents of the referenced specification takes precedence over the contents of the entry in the column.

In the "Profile status" column, there are a number of differences from the "RFC status" column. Where these differences occur, these differences take precedence over any requirements of the IETF specifications. Where specification concerning these requirements exists in the main body of the present document, the main body of the present document takes precedence.

Where differences occur in the "Profile status" column, the "Profile status" normally gives more strength to a "RFC status" and is not be in contradiction with the "RFC status", e.g. it may change an optional "RFC status" to a mandatory "Profile status". If the "Profile status" weakens the strength of a "RFC status" then additionally this will be indicated by further textual description in the present document.

For all IETF specifications that are not referenced by this document or that are not mentioned within the 3GPP profile of SIP and SDP, the generic rules as defined by RFC 3261 [26] and in addition the rules in clauses 5 and 6 of this specification apply, e.g..

- a proxy which is built in accordance to this specification passes on any unknown method, unknown header field or unknown header parameter after applying procedures such as filtering, insertion of P-Asserted-Identity header, etc.;
- an UA which is built in accordance to this specification will
 - handle received unknown methods in accordance to the procedures defined in RFC 3261 [26], e.g. respond with a 400 (Bad Request) response; and
 - handle unknown header fields and unknown header parameters in accordance to the procedures defined in RFC 3261 [26], e.g. respond with a 420 (Bad Extension) if an extension identified by an option tag in the Require header of the received request is not supported by the UA.

A.1.2 Introduction to methodology within this profile

This subclause does not reflect dynamic conformance requirements but static ones. In particular, an condition for support of a PDU parameter does not reflect requirements about the syntax of the PDU (i.e. the presence of a parameter) but the capability of the implementation to support the parameter.

In the sending direction, the support of a parameter means that the implementation is able to send this parameter (but it does not mean that the implementation always sends it).

In the receiving direction, it means that the implementation supports the whole semantic of the parameter that is described in the main part of this specification.

As a consequence, PDU parameter tables in this subclause are not the same as the tables describing the syntax of a PDU in the reference specification, e.g. RFC 3261 [26] tables 2 and 3. It is not rare to see a parameter which is optional in the syntax but mandatory in subclause below.

The various statii used in this subclause are in accordance with the rules in table A.1.

Table A.1: Key to status codes

Status code	Status name	Meaning
m	mandatory	the capability shall be supported. It is a static view of the fact that the conformance requirements related to the capability in the reference specification are mandatory requirements. This does not mean that a given behaviour shall always be observed (this would be a dynamic view), but that it shall be observed when the implementation is placed in conditions where the conformance requirements from the reference specification compel it to do so. For instance, if the support for a parameter in a sent PDU is mandatory, it does not mean that it shall always be present, but that it shall be present according to the description of the behaviour in the reference specification (dynamic conformance requirement).
o	optional	the capability may or may not be supported. It is an implementation choice.
n/a	not applicable	it is impossible to use the capability. No answer in the support column is required.
x	prohibited (excluded)	It is not allowed to use the capability. This is more common for a profile.
c <integer>	conditional	the requirement on the capability ("m", "o", "n/a" or "x") depends on the support of other optional or conditional items. <integer> is the identifier of the conditional expression.
o.<integer>	qualified optional	for mutually exclusive or selectable options from a set. <integer> is the identifier of the group of options, and the logic of selection of the options.
i	irrelevant	capability outside the scope of the given specification. Normally, this notation should be used in a base specification ICS proforma only for transparent parameters in received PDUs. However, it may be useful in other cases, when the base specification is in fact based on another standard.

In the context of this specification the "i" status code mandates that the implementation does not change the content of the parameter. It is an implementation option if the implementation acts upon the content of the parameter (e.g. by setting filter criteria to known or unknown parts of parameters in order to find out the route a message has to take).

It must be understood, that this 3GPP SIP profile does not list all parameters which an implementation will treat as indicated by the status code "irrelevant". In general an implementation will pass on all unknown messages, header fields and header parameters, as long as it can perform its normal behaviour.

The following additional comments apply to the interpretation of the tables in this Annex.

NOTE 1: The tables are constructed according to the conventional rules for ICS proformas and profile tables.

NOTE 2: The notation (either directly or as part of a conditional) of "m" for the sending of a parameter and "i" for the receipt of the same parameter, may be taken as indicating that the parameter is passed on transparently, i.e. without modification. Where a conditional applies, this behaviour only applies when the conditional is met.

A.1.3 Roles

Table A.2: Roles

Item	Roles	Reference	RFC status	Profile status
1	User agent	[26]	0.1	0.1
2	Proxy	[26]	0.1	0.1
o.1: It is mandatory to support exactly one of these items.				
NOTE: For the purposes of the present document it has been chosen to keep the specification simple by the tables specifying only one role at a time. This does not preclude implementations providing two roles, but an entirely separate assessment of the tables shall be made for each role.				

Table A.3: Roles specific to this profile

Item	Roles	Reference	RFC status	Profile status
1	UE	5.1	n/a	o.1
2	P-CSCF	5.2	n/a	o.1
3	I-CSCF	5.3	n/a	o.1
3A	I-CSCF (THIG)	5.3	n/a	c1
4	S-CSCF	5.4	n/a	o.1
5	BGCF	5.6	n/a	o.1
6	MGCF	5.5	n/a	o.1
7	AS	5.7	n/a	o.1
7A	AS acting as terminating UA, or redirect server	5.7.2	n/a	c2
7B	AS acting as originating UA	5.7.3	n/a	c2
7C	AS acting as a SIP proxy	5.7.4	n/a	c2
7D	AS performing 3rd party call control	5.7.5	n/a	c2
8	MRFC	5.8	n/a	o.1
c1:	IF A.3/3 THEN o ELSE x - - I-CSCF.			
c2:	IF A.3/7 THEN o.2 ELSE n/a - - AS.			
o.1:	It is mandatory to support exactly one of these items.			
o.2:	It is mandatory to support at least one of these items.			
NOTE:	For the purposes of the present document it has been chosen to keep the specification simple by the tables specifying only one role at a time. This does not preclude implementations providing two roles, but an entirely separate assessment of the tables shall be made for each role.			

A.2 Profile definition for the Session Initiation Protocol as used in the present document

A.2.1 User agent role

A.2.1.1 Introduction

This subclause contains the ICS proforma tables related to the user role. They need to be completed only for UA implementations:

Prerequisite: A.2/1 - - user agent role.

A.2.1.2 Major capabilities

Table A.4: Major capabilities

Item	Does the implementation support	Reference	RFC status	Profile status
Capabilities within main protocol				
1	client behaviour for registration?	[26] subclause 10.2	m	c3
2	registrar?	[26] subclause 10.3	o	c4
2A	initiating a session?	[26] subclause 13	o	o
3	client behaviour for INVITE requests?	[26] subclause 13.2	c18	c18
4	server behaviour for INVITE requests?	[26] subclause 13.3	c18	c18
5	session release?	[26] subclause 15.1	c18	c18
6	timestamping of requests?	[26] subclause 8.2.6.1	o	o
7	authentication between UA and UA?	[26] subclause 22.2	o	o
8	authentication between UA and registrar?	[26] subclause 22.2	o	n/a
8A	authentication between UA and proxy?	[26] 20.28, 22.3	o	o
9	server handling of merged requests due to forking?	[26] 8.2.2.2	m	m
10	client handling of multiple responses due to forking?	[26] 13.2.2.4	m	m
11	insertion of date in requests and responses?	[26] subclause 20.17	o	o
12	downloading of alerting information?	[26] subclause 20.4	o	o
Extensions				
13	the SIP INFO method?	[25]	o	n/a
14	reliability of provisional responses in SIP?	[27]	c19	c18
15	the REFER method?	[36]	o	o
16	integration of resource management and SIP?	[30]	c19	c18
17	the SIP UPDATE method?	[29]	c5	c18
19	SIP extensions for media authorization?	[31]	o	c14
20	SIP specific event notification?	[28]	o	c13
21	the use of NOTIFY to establish a dialog?	[28] 4.2	o	n/a
22	acting as the notifier of event information?	[28]	c2	c15
23	acting as the subscriber to event information?	[28]	c2	c16
24	session initiation protocol extension header field for registering non-adjacent contacts?	[35]	o	c6
25	private extensions to the Session Initiation Protocol (SIP) for network asserted identity within trusted networks	[34]	o	m
26	a privacy mechanism for the Session Initiation Protocol (SIP)	[33]	o	m
26A	request of privacy by the inclusion of a Privacy header	[33]	c9	c11
26B	application of privacy based on the received Privacy header	[33]	c9	n/a
26C	passing on of the Privacy header transparently	[33]	c9	c12
26D	application of the privacy option "header" such that those headers which cannot be completely expunged of identifying information without the assistance of intermediaries are obscured?	[33] 5.1	c10	
26E	application of the privacy option "session" such that anonymization for the session(s) initiated by this message occurs?	[33] 5.2	c10	
26F	application of the privacy option "user"	[33] 5.3	c10	

	such that user level privacy functions are provided by the network?			
26G	application of the privacy option "id" such that privacy of the network asserted identity is provided by the network?	[34] 7	c10	n/a
27	a messaging mechanism for the Session Initiation Protocol (SIP)?	[50]	o	c7
28	session initiation protocol extension header field for service route discovery during registration?	[38]	o	c17
29	compressing the session initiation protocol?	[55]	o	c8
30	private header extensions to the session initiation protocol for the 3rd-Generation Partnership Project (3GPP)?	[52]	o	m
31	the P-Associated-URI header extension?	[52] 4.1	c21	c22
32	the P-Called-Party-ID header extension?	[52] 4.2	c21	c23
33	the P-Visited-Network-ID header extension?	[52] 4.3	c21	c24
34	the P-Access-Network-Info header extension?	[52] 4.4	c21	c25
35	the P-Charging-Function-Addresses header extension?	[52] 4.5	c21	c26
36	the P-Charging-Vector header extension?	[52] 4.6	c21	c26
37	security mechanism agreement for the session initiation protocol?	[48]	o	c20

c2:	IF A.4/20 THEN o.1 ELSE n/a - - SIP specific event notification extension.
c3:	IF A.3/1 OR A.3/4 THEN m ELSE n/a - - UE or S-CSCF functional entity.
c4:	IF A.3/4 OR A.3/7 THEN m ELSE n/a - - S-CSCF or AS functional entity.
c5:	IF A.4/16 THEN m ELSE o - - integration of resource management and SIP extension.
c6:	IF A.3/4 OR A.3/1 THEN m ELSE n/a. - - S-CSCF or UE.
c7:	IF A.3/4 THEN m ELSE (IF A.3/1 OR A.3/7B OR A.3/7D THEN o ELSE n/a - - S-CSCF or UA or AS acting as originating UA, or AS performing 3 rd party call control
c8:	IF A.3/1 THEN m ELSE n/a - - UE behaviour.
c9:	IF A.4/26 THEN o.2 ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).
c10:	IF A.4/26B THEN o.3 ELSE n/a - - application of privacy based on the received Privacy header.
c11:	IF A.3/1 OR A.3/6 THEN o ELSE n/a - - UE or MGCF.
c12:	IF A.3/7D THEN m ELSE n/a - - AS performing 3rd-party call control.
c13:	IF A.3/1 OR A.3/4 THEN m ELSE o - - UE behaviour or S-CSCF.
c14:	IF A.3/1 THEN m ELSE IF A.3/2 THEN o ELSE n/a - - UE or P-CSCF
c15:	IF A.4/20 and A.3/4 THEN m ELSE o - - SIP specific event notification extensions and S-CSCF.
c16:	IF A.4/20 and (A.3/1 OR A.3/2) THEN m ELSE o - - SIP specific event notification extension and UE or P-CSCF.
c17:	IF A.3/1 o A3./4 THEN m ELSE n/a - - UE or S-CSCF
c18:	IF A.4/2A THEN m ELSE n/a - - initiating sessions
c19:	IF A.4/2A THEN o ELSE n/a - - initiating sessions
c20:	IF A.3/1 THEN m ELSE n/a - - UE behaviour.
c21:	IF A.4/30 THEN o.4 ELSE n/a - - private header extensions to the session initiation protocol for the 3rd-Generation Partnership Project (3GPP).
c22:	IF A.4/30 AND (A.3/1 OR A.3/4) THEN m ELSE n/a - - private header extensions to the session initiation protocol for the 3rd-Generation Partnership Project (3GPP) and S-CSCF or UA.
c23:	IF A.4/30 AND A.3/1 THEN o ELSE n/a - - - private header extensions to the session initiation protocol for the 3rd-Generation Partnership Project (3GPP) and UE.
c24:	IF A.4/30 AND A.3/4) THEN m ELSE n/a - - private header extensions to the session initiation protocol for the 3rd-Generation Partnership Project (3GPP) and S-CSCF.
c25:	IF A.4/30 AND (A.3/1 OR A.3/4 OR A.3/7A OR A.3/7D) THEN m ELSE n/a - - private header extensions to the session initiation protocol for the 3rd-Generation Partnership Project (3GPP) and UE, S-CSCF or AS acting as terminating UA or AS acting as third-party call controller.
c26:	IF A.4/30 AND (A.3/6 OR A.3/7A OR A.3/7B or A.3/7D) THEN m ELSE n/a - - private header extensions to the session initiation protocol for the 3rd-Generation Partnership Project (3GPP) and MGCF, AS acting as a terminating UA, or AS acting as an originating UA, or AS acting as third-party call controller.
o.1:	At least one of these capabilities is supported.
o.2:	At least one of these capabilities is supported.
o.3:	At least one of these capabilities is supported.
o.4:	At least one of these capabilities is supported.

A.2.1.3 PDUs

Table A.5: Supported methods

Item	PDU	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	ACK request	[26] 13	m	m	[26] 13	m	m
2	BYE request	[26] 15.1	o		[26] 15.1	o	
3	BYE response	[26] 15.1	o		[26] 15.1	o	
4	CANCEL request	[26] 9	o		[26] 9	o	
5	CANCEL response	[26] 9	o		[26] 9	o	
8	INVITE request	[26] 13	m	m	[26] 13	m	m
9	INVITE response	[26] 13	m	m	[26] 13	m	m
9A	MESSAGE request	[50] 4	c7	c7	[50] 7	c7	c7
9B	MESSAGE response	[50] 4	c7	c7	[50] 7	c7	c7
10	NOTIFY request	[28] 8.1.2	c4	c4	[28] 8.1.2	c3	c3
11	NOTIFY response	[28] 8.1.2	c3	c3	[28] 8.1.2	c4	c4
12	OPTIONS request	[26] 11	m	m	[26] 11	m	m
13	OPTIONS response	[26] 11	m	m	[26] 11	m	m
14	PRACK request	[27] 6	c5	c5	[27] 6	c5	c5
15	PRACK response	[27] 6	c5	c5	[27] 6	c5	c5
16	REFER request	[36] 3	c1	c1	[36] 3	c1	c1
17	REFER response	[36] 3	c1	c1	[36] 3	c1	c1
18	REGISTER request	[26] 10	o		[26] 10	n/a	
19	REGISTER response	[26] 10	n/a		[26] 10	m	
20	SUBSCRIBE request	[28] 8.1.1	c3	c3	[28] 8.1.1	c4	c4
21	SUBSCRIBE response	[28] 8.1.1	c4	c4	[28] 8.1.1	c3	c3
22	UPDATE request	[30] 6.1	c6	c6	[30] 6.2	c6	c6
23	UPDATE response	[30] 6.2	c6	c6	[30] 6.1	c6	c6

c1: IF A.4/15 THEN m ELSE n/a - - the REFER method extension.
 c3: IF A.4/23 THEN m ELSE n/a - - recipient for event information.
 c4: IF A.4/22 THEN m ELSE n/a - - notifier of event information.
 c5: IF A.4/14 THEN m ELSE n/a - - reliability of provisional responses extension.
 c6: IF A.4/17 THEN m ELSE n/a - - the SIP update method extension.
 c7: IF A.4/27 THEN m ELSE n/a - - the SIP MESSAGE method.

Editor's note: Optional status of BYE in RFC status is given because RFC states **SHOULD** (client and server).

Editor's note: Optional status of REGISTER in RFC status is given because RFC states **RECOMMENDED** (client); for the UAS, not statement is made, but it is assumed that this therefore means n/a.

A.2.1.4 PDU parameters

A.2.1.4.1 Status-codes

Table A.6: Supported status-codes

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	100 (Trying)	[26] 21.1.1	n/a	n/a	[26] 21.1.1	m	m
2	180 (Ringing)	[26] 21.1.2	c2	c2	[26] 21.1.2	c1	c1
3	181 (Call Is Being Forwarded)	[26] 21.1.3	c2	c2	[26] 21.1.3	c1	c1
4	182 (Queued)	[26] 21.1.4	c2	c2	[26] 21.1.4	c1	c1
5	183 (Session Progress)	[26] 21.1.5	c1	c1	[26] 21.1.5	c1	c1
6	200 (OK)	[26] 21.2.1			[26] 21.2.1		
7	202 (Accepted)	[28] 8.3.1	c3	c3	[28] 8.3.1	c3	c3
8	300 (Multiple Choices)	[26] 21.3.1			[26] 21.3.1		
9	301 (Moved Permanently)	[26] 21.3.2			[26] 21.3.2		
10	302 (Moved Temporarily)	[26] 21.3.3			[26] 21.3.3		
11	305 (Use Proxy)	[26] 21.3.4			[26] 21.3.4		
12	380 (Alternative Service)	[26] 21.3.5			[26] 21.3.5		
13	400 (Bad Request)	[26] 21.4.1			[26] 21.4.1		
14	401 (Unauthorized)	[26] 21.4.2			[26] 21.4.2		
15	402 (Payment Required)	[26] 21.4.3			[26] 21.4.3		
16	403 (Forbidden)	[26] 21.4.4			[26] 21.4.4		
17	404 (Not Found)	[26] 21.4.5			[26] 21.4.5		
18	405 (Method Not Allowed)	[26] 21.4.6			[26] 21.4.6		
19	406 (Not Acceptable)	[26] 21.4.7			[26] 21.4.7		
20	407 (Proxy Authentication Required)	[26] 21.4.8			[26] 21.4.8		
21	408 (Request Timeout)	[26] 21.4.9			[26] 21.4.9		
22	410 (Gone)	[26] 21.4.10			[26] 21.4.10		
23	413 (Request Entity Too Large)	[26] 21.4.11			[26] 21.4.11		
24	414 (Request-URI Too Large)	[26] 21.4.12			[26] 21.4.12		
25	415 (Unsupported Media Type)	[26] 21.4.13			[26] 21.4.13		
26	416 (Unsupported URI Scheme)	[26] 21.4.14			[26] 21.4.14		
27	420 (Bad Extension)	[26] 21.4.15			[26] 21.4.15		
28	421 (Extension Required)	[26] 21.4.16			[26] 21.4.16		
29	423 (Interval Too Brief)	[26] 21.4.17	c4	c4	[26] 21.4.17	m	m
30	480 (Temporarily Unavailable)	[26] 21.4.18			[26] 21.4.18		
31	481 (Call/Transaction Does Not Exist)	[26] 21.4.19			[26] 21.4.19		
32	482 (Loop Detected)	[26] 21.4.20			[26] 21.4.20		
33	483 (Too Many Hops)	[26] 21.4.21			[26] 21.4.21		
34	484 (Address Incomplete)	[26] 21.4.22			[26] 21.4.22		
35	485 (Ambiguous)	[26] 21.4.23			[26] 21.4.23		
36	486 (Busy Here)	[26] 21.4.24			[26] 21.4.24		
37	487 (Request Terminated)	[26] 21.4.25			[26] 21.4.25		
38	488 (Not Acceptable Here)	[26] 21.4.26			[26] 21.4.26		
39	489 (Bad Event)	[28] 7.3.2	c3	c3	[28] 7.3.2	c3	c3
40	491 (Request Pending)	[26] 21.4.27			[26] 21.4.27		
41	493 (Undecipherable)	[26] 21.4.28			[26] 21.4.28		
41A	494 (Security Agreement Required)	[48] 2	c5	c5	[48] 2	c6	c6
42	500 (Internal Server Error)	[26] 21.5.1			[26] 21.5.1		
43	501 (Not Implemented)	[26] 21.5.2			[26] 21.5.2		
44	502 (Bad Gateway)	[26] 21.5.3			[26] 21.5.3		
45	503 (Service Unavailable)	[26] 21.5.4			[26] 21.5.4		
46	504 (Server Time-out)	[26] 21.5.5			[26] 21.5.5		

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
47	505 (Version not supported)	[26] 21.5.6			[26] 21.5.6		
48	513 (Message Too Large)	[26] 21.5.7			[26] 21.5.7		
49	580 (Precondition Failure)	[30] 8			[30] 8		
50	600 (Busy Everywhere)	[26] 21.6.1			[26] 21.6.1		
51	603 (Decline)	[26] 21.6.2			[26] 21.6.2		
52	604 (Does Not Exist Anywhere)	[26] 21.6.3			[26] 21.6.3		
53	606 (Not Acceptable)	[26] 21.6.4			[26] 21.6.4		
c1:	IF A.5/9 THEN m ELSE n/a - - INVITE response.						
c2:	IF A.5/9 THEN o ELSE n/a - - INVITE response.						
c3:	IF A.4/20 THEN m ELSE n/a - - SIP specific event notification extension.						
c4:	IF A.5/19 OR A.5/21 THEN m ELSE n/a - - REGISTER response or SUBSCRIBE response.						
c5:	IF A.4/37 AND A.4/2 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol and registrar.						
c6:	IF A.4/37 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol.						

A.2.1.4.2 ACK method

Prerequisite A.5/1 – ACK request

Table A.7: Supported headers within the ACK request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
2	Allow-Events	[28] 8.2.2	c1	c1	[28] 8.2.2	c2	c2
3	Authorization	[26] 20.7	c3	c3	[26] 20.7	c3	c3
4	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
6	Content-Disposition	[26] 20.11	o	o	[26] 20.11	m	m
7	Content-Encoding	[26] 20.12	o	o	[26] 20.12	m	m
8	Content-Language	[26] 20.13	o	o	[26] 20.13	m	m
9	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
10	Content-Type	[26] 20.15	o ^{rn}	m ^o	[26] 20.15	m	m
11	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
12	Date	[26] 20.17	c4	c4	[26] 20.17	m	m
13	From	[26] 20.20	m	m	[26] 20.20	m	m
14	Max-Forwards	[26] 20.22	e ^m	e ^m	[26] 20.22	n/a	n/a
15	MIME-Version	[26] 20.24	o	o	[26] 20.24	m	m
15A	Privacy	[33] 4.2	c6	n/a	[33] 4.2	c6	n/a
16	Proxy-Authorization	[26] 20.28	c5	c5	[26] 20.28	n/a	n/a
17	Proxy-Require	[26] 20.29	o	n/a	[26] 20.29	n/a	n/a
18	Require	[26] 20.32	o	o	[26] 20.32	m	m
19	Route	[26] 20.34	m	m	[26] 20.34	n/a	n/a
20	Timestamp	[26] 20.38	c7	c7	[26] 20.38	m	m
21	To	[26] 20.39	m	m	[26] 20.39	m	m
22	User-Agent	[26] 20.41	o	o	[26] 20.41	m	m
23	Via	[26] 20.42	m	m	[26] 20.42	m	m
c1:	IF A.4/20 THEN o ELSE n/a - - SIP specific event notification extension.						
c2:	IF A.4/20 THEN m ELSE n/a - - SIP specific event notification extension.						
c3:	IF A.4/7 THEN m ELSE n/a - - authentication between UA and UA.						
c4:	IF A.4/11 THEN o ELSE n/a - - insertion of date in requests and responses.						
c5:	IF A.4/8A THEN m ELSE n/a - - authentication between UA and proxy.						
c6:	IF A.4/26 THEN o ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).						
c7:	IF A.4/6 THEN o ELSE n/a - - timestamping of requests.						

Editor's note: Is the following table a suitable way of showing the contents of message bodies.

Prerequisite A.5/1 – ACK request

Table A.8: Supported message bodies within the ACK request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1							

A.2.1.4.3 BYE method

Prerequisite A.5/2 - - BYE request

Table A.9: Supported headers within the BYE request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Accept	[26] 20.1	o	o	[26] 20.1	m	m
2	Accept-Encoding	[26] 20.2	o	o	[26] 20.2	m	m
3	Accept-Language	[26] 20.3	o	o	[26] 20.3	m	m
3A	Allow	[26] 20.5	o	o	[26] 20.5	m	m
4	Allow-Events	[28] 8.2.2	c1	c1	[28] 8.2.2	c2	c2
5	Authorization	[26] 20.7	c3	c3	[26] 20.7	c3	c3
6	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
7	Content-Disposition	[26] 20.11	o	o	[26] 20.11	m	m
8	Content-Encoding	[26] 20.12	o	o	[26] 20.12	m	m
9	Content-Language	[26] 20.13	o	o	[26] 20.13	m	m
10	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
11	Content-Type	[26] 20.15	m	m	[26] 20.15	m	m
12	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
13	Date	[26] 20.17	c4	c4	[26] 20.17	m	m
14	From	[26] 20.20	m	m	[26] 20.20	m	m
15	Max-Forwards	[26] 20.22	em	em	[26] 20.22	n/a	n/a
16	MIME-Version	[26] 20.24	o	o	[26] 20.24	m	m
16A	P-Access-Network-Info	[52] 4.4	c9	c10	[52] 4.4	c9	c11
16B	P-Asserted-Identity	[34] 9.1	n/a	n/a	[34] 9.1	c6	c6
16C	P-Charging-Function-Addresses	[52] 4.5	c13	c14	[52] 4.5	c13	c14
16D	P-Charging-Vector	[52] 4.6	c12	n/a	[52] 4.6	c12	n/a
16E	P-Preferred-Identity	[34] 9.2	c6	x	[34] 9.2	n/a	n/a
16F	Privacy	[33] 4.2	c7	n/a	[33] 4.2	c7	c7
17	Proxy-Authorization	[26] 20.28	c5	c5	[26] 20.28	n/a	n/a
18	Proxy-Require	[26] 20.29	o	n/a	[26] 20.29	n/a	n/a
19	Record-Route	[26] 20.30	n/a	n/a	[26] 20.30	n/a	n/a
20	Require	[26] 20.32	o	o	[26] 20.32	m	m
21	Route	[26] 20.34	m	m	[26] 20.34	n/a	n/a
21A	Security-Client	[48] 2.3.1	c15	c15	[48] 2.3.1	n/a	n/a
21B	Security-Verify	[48] 2.3.1	c16	c16	[48] 2.3.1	n/a	n/a
22	Supported	[26] 20.37	o	o	[26] 20.37	m	m
23	Timestamp	[26] 20.38	c8	c8	[26] 20.38	m	m
24	To	[26] 20.39	m	m	[26] 20.39	m	m
25	User-Agent	[26] 20.41	o	o	[26] 20.41	o	o
26	Via	[26] 20.42	m	m	[20] 20.42	m	m
c1:	IF A.4/20 THEN o ELSE n/a - - SIP specific event notification extension.						
c2:	IF A.4/20 THEN m ELSE n/a - - SIP specific event notification extension.						
c3:	IF A.4/7 THEN m ELSE n/a - - authentication between UA and UA.						
c4:	IF A.4/11 THEN o ELSE n/a - - insertion of date in requests and responses.						
c5:	IF A.4/8A THEN m ELSE n/a - - authentication between UA and proxy.						
c6:	IF A.4/25 THEN o ELSE n/a - - private extensions to the Session Initiation Protocol (SIP) for asserted identity within trusted networks.						
c7:	IF A.4/26 THEN o ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).						
c8:	IF A.4/6 THEN o ELSE n/a - - timestamping of requests.						
c9:	IF A.4/34 THEN o ELSE n/a - - the P-Access-Network-Info header extension.						
c10:	IF A.4/34 AND A.3/1 THEN m ELSE n/a - - the P-Access-Network-Info header extension and UE.						
c11:	IF A.4/34 AND (A.3/7A OR A.3/7D) THEN m ELSE n/a - - the P-Access-Network-Info header extension and AS acting as terminating UA or AS acting as third-party call controller.						
c12:	IF A.4/36 THEN o ELSE n/a - - the P-Charging-Vector header extension.						
c13:	IF A.4/35 THEN o ELSE n/a - - the P-Charging-Function-Addresses header extension.						
c14:	IF A.4/35 THEN m ELSE n/a - - the P-Charging-Function-Addresses header extension.						
c15:	IF A.4/37 THEN o ELSE n/a - - security mechanism agreement for the session initiation protocol (note).						
c16:	IF A.4/37 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol.						
NOTE:	Support of this header in this method is dependent on the security mechanism and the security architecture which is implemented. Use of this header in this method is not appropriate to the security mechanism defined by 3GPP TS 33.203 [19].						

Prerequisite A.5/2 - - BYE request

Table A.10: Supported message bodies within the BYE request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1							

Prerequisite A.5/3 - - BYE response

Prerequisite: A.6/1 - - 100 (Trying)

Table A.11: Supported headers within the BYE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Call-ID	[26] 20.8	n/a	n/a	[26] 20.8	m	m
2	Content-Length	[26] 20.14	n/a	n/a	[26] 20.14	m	m
3	Cseq	[26] 20.16	n/a	n/a	[26] 20.16	m	m
4	Date	[26] 20.17	n/a	n/a	[26] 20.17	m	m
5	From	[26] 20.20	n/a	n/a	[26] 20.20	m	m
6	To	[26] 20.39	n/a	n/a	[26] 20.39	m	m
7	Via	[26] 20.42	n/a	n/a	[26] 20.42	m	m

Prerequisite A.5/3 - - BYE response

Table A.12: Supported headers within the BYE response - all remaining status-codes

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
2	Content-Disposition	[26] 20.11	o	o	[26] 20.11	m	m
3	Content-Encoding	[26] 20.12	o	o	[26] 20.12	m	m
4	Content-Language	[26] 20.13	o	o	[26] 20.13	m	m
5	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
6	Content-Type	[26] 20.15	m	m	[26] 20.15	m	m
7	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
8	Date	[26] 20.17	c1	c1	[26] 20.17	m	m
9	From	[26] 20.20	m	m	[26] 20.20	m	m
10	MIME-Version	[26] 20.24	o	o	[26] 20.24	m	m
10A	P-Access-Network-Info	[52] 4.4	c5	c6	[52] 4.4	c5	c6
10B	P-Asserted-Identity	[34] 9.1	n/a	n/a	[34] 9.1	c3	c3
10C	P-Charging-Function-Addresses	[52] 4.5	c9	c10	[52] 4.5	c9	c10
10D	P-Charging-Vector	[52] 4.6	c8	n/a	[52] 4.6	c8	n/a
10E	P-Preferred-Identity	[34] 9.2	c3	x	[34] 9.2	n/a	n/a
10F	Privacy	[33] 4.2	c4	n/a	[33] 4.2	c4	c4
10G	Require	[26] 20.32	m	m	[26] 20.32	m	m
10H	Server	[26] 20.35	o	o	[26] 20.35	o	o
11	Timestamp	[26] 20.38	m	m	[26] 20.38	c2	c2
12	To	[26] 20.39	m	m	[26] 20.39	m	m
12A	User-Agent	[26] 20.41	o	o	[26] 20.41	o	o
13	Via	[26] 20.42	m	m	[26] 20.42	m	m
14	Warning	[26] 20.43	o (note)	o	[26] 20.43	o	o

c1: IF A.4/11 THEN o ELSE n/a - - insertion of date in requests and responses.
c2: IF A.4/6 THEN m ELSE n/a - - timestamping of requests.
c3: IF A.4/25 THEN o ELSE n/a - - private extensions to the Session Initiation Protocol (SIP) for asserted identity within trusted networks.
c4: IF A.4/26 THEN o ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).
c5: IF A.4/34 THEN o ELSE n/a - - the P-Access-Network-Info header extension.
c6: IF A.4/34 AND A.3/1 THEN m ELSE n/a - - the P-Access-Network-Info header extension and UE.
c7: IF A.4/34 AND (A.3/7A OR A.3/7D) THEN m ELSE n/a - - the P-Access-Network-Info header extension and AS acting as terminating UA or AS acting as third-party call controller.
c8: IF A.4/36 THEN o ELSE n/a - - the P-Charging-Vector header extension.
c9: IF A.4/35 THEN o ELSE n/a - - the P-Charging-Function-Addresses header extension.
c10: IF A.4/35 THEN m ELSE n/a - - the P-Charging-Function-Addresses header extension.

NOTE: For a 606 (Not Acceptable Here) response, this status is RECOMMENDED rather than OPTIONAL.

Prerequisite A.5/3 - - BYE response

Prerequisite: A.6/6 - - 2xx

Table A.13: Supported headers within the BYE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	o	o	[26] 20.5	m	m
1	Authentication-Info	[26] 20.6	c1	c1	[26] 20.6	c2	c2
4	Supported	[26] 20.37	m	m	[26] 20.37	m	m

c1: IF A.4/7 THEN o ELSE n/a - - authentication between UA and UA.
c2: IF A.4/7 THEN m ELSE n/a - - authentication between UA and UA.

Prerequisite A.5/3 - - BYE response

Prerequisite: A.6/8 OR A.6/9 OR A.6/10 OR A.6/11 OR A.6/12 OR A.6/35 - - 3xx or 485 (Ambiguous)

Table A.14: Supported headers within the BYE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	o	o	[26] 20.5	m	m
0B	Contact	[26] 20.10	o (note)	o	[26] 20.10	m	m
1	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
4	Supported	[26] 20.37	m	m	[26] 20.37	m	m

NOTE: The strength of this requirement is RECOMMENDED rather than OPTIONAL.

Prerequisite A.5/3 - - BYE response

Prerequisite: A.6/14 - - 401 (Unauthorized)

Table A.15: Supported headers within the BYE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	o	o	[26] 20.5	m	m
1	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
2	Proxy-Authenticate	[26] 20.27	c1	c1	[26] 20.27	c1	c1
5	Supported	[26] 20.37	m	m	[26] 20.37	m	m
8	WWW-Authenticate	[26] 20.44	m	m	[26] 20.44	m	m
c1:	IF A.5/7 THEN m ELSE n/a - - support of authentication between UA and UA.						

Prerequisite A.5/3 - - BYE response

Prerequisite: A.6/17 OR A.6/23 OR A.6/30 OR A.6/36 OR A.6/42 OR A.6/45 OR A.6/50 OR A.6/51 - - 404, 413, 480, 486, 500, 503, 600, 603

Table A.16: Supported headers within the BYE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	o	o	[26] 20.5	m	m
1	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
3	Retry-After	[26] 20.33	o	o	[26] 20.33	o	o
5	Supported	[26] 20.37	m	m	[26] 20.37	m	m

Prerequisite A.5/3 - - BYE response

Prerequisite: A.6/18 - - 405 (Method Not Allowed)

Table A.17: Supported headers within the BYE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	m	m
2	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
5	Supported	[26] 20.37	m	m	[26] 20.37	m	m

Prerequisite A.5/3 - - BYE response

Prerequisite: A.6/19 - - 407 (Proxy Authentication Required)

Table A.18: Supported headers within the BYE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	o	o	[26] 20.5	m	m
1	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
2	Proxy-Authenticate	[26] 20.27	c1	c1	[26] 20.27	c1	c1
5	Supported	[26] 20.37	m	m	[26] 20.37	m	m
6	WWW-Authenticate	[26] 20.44	o	o	[26] 20.44	o	o
c1:	IF A.5/7 THEN m ELSE n/a - - support of authentication between UA and UA.						

Prerequisite A.5/3 - - BYE response

Prerequisite A.6/25 - - 415 (Unsupported Media Type)

Table A.19: Supported headers within the BYE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Accept	[26] 20.1	o.1	o.1	[26] 20.1	m	m
2	Accept-Encoding	[26] 20.2	o.1	o.1	[26] 20.2	m	m
3	Accept-Language	[26] 20.3	o.1	o.1	[26] 20.3	m	m
3A	Allow	[26] 20.5	o	o	[26] 20.5	m	m
4	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
7	Supported	[26] 20.37	m	m	[26] 20.37	m	m
o.1	At least one of these capabilities is supported.						

Prerequisite A.5/3 - - BYE response

Prerequisite: A.6/27 - - 420 (Bad Extension)

Table A.20: Supported headers within the BYE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	o	o	[26] 20.5	m	m
1	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
4	Supported	[26] 20.37	m	m	[26] 20.37	m	m
5	Unsupported	[26] 20.40	m	m	[26] 20.40	m	m

Prerequisite A.5/3 - - BYE response

Prerequisite: A.6/28 OR A.6/41A - - 421 (Extension Required), 494 (Security Agreement Required)

Table A.20A: Supported headers within the BYE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
2	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
3	Security-Server	[48] 2	x	x	[48] 2	c1	c1
3	Supported	[26] 20.37	m	m	[26] 20.37	m	m
c1:	IF A.4/37 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol.						

Prerequisite A.5/3 - - BYE response

Prerequisite: A.6/34 - - 484 (Address Incomplete)

Table A.21: Supported headers within the BYE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	o	o	[26] 20.5	m	m
1	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
4	Supported	[26] 20.37	m	m	[26] 20.37	m	m

Prerequisite A.5/3 - - BYE response

Table A.22: Supported message bodies within the BYE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1							

A.2.1.4.4 CANCEL method

Prerequisite A.5/4 - - CANCEL request

Table A.23: Supported headers within the CANCEL request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
4	Allow-Events	[28] 8.2.2	c1	c1	[28] 8.2.2	c2	c2
5	Authorization	[26] 20.7	c3	c3	[26] 20.7	c3	c3
6	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
8	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
9	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
10	Date	[26] 20.17	c4	c4	[26] 20.17	m	m
11	From	[26] 20.20	m	m	[26] 20.20	m	m
12	Max-Forwards	[26] 20.22	em	em	[26] 20.22	n/a	n/a
14	Privacy	[33] 4.2	c6	n/a	[33] 4.2	c6	n/a
16	Record-Route	[26] 20.30	n/a	n/a	[26] 20.30	n/a	n/a
18	Route	[26] 20.34	m	m	[26] 20.34	n/a	n/a
19	Supported	[26] 20.37	o	o	[26] 20.37	m	m
20	Timestamp	[26] 20.38	c8	c8	[26] 20.38	m	m
21	To	[26] 20.39	m	m	[26] 20.39	m	m
22	User-Agent	[26] 20.41	o		[26] 20.41	o	
23	Via	[26] 20.42	m	m	[26] 20.42	m	m

c1: IF A.4/20 THEN o ELSE n/a - - SIP specific event notification extension.
c2: IF A.4/20 THEN m ELSE n/a - - SIP specific event notification extension.
c3: IF A.4/7 THEN m ELSE n/a - - authentication between UA and UA.
c4: IF A.4/11 THEN o ELSE n/a - - insertion of date in requests and responses.
c6: IF A.4/26 THEN o ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).
c8: IF A.4/6 THEN o ELSE n/a - - timestamping of requests.

Prerequisite A.5/4 - - CANCEL request

Table A.24: Supported message bodies within the CANCEL request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1							

Prerequisite A.5/5 - - CANCEL response

Table A.25: Supported headers within the CANCEL response - all status-codes

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
2	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
3	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
4	Date	[26] 20.17	c1	c1	[26] 20.17	m	m
5	From	[26] 20.20	m	m	[26] 20.20	m	m
5A	Privacy	[33] 4.2	c3	n/a	[33] 4.2	c3	n/a
6	Timestamp	[26] 20.38	m	m	[26] 20.38	c2	c2
7	To	[26] 20.39	m	m	[26] 20.39	m	m
7A	User-Agent	[26] 20.41	o	o	[26] 20.41	o	o
8	Via	[26] 20.42	m	m	[26] 20.42	m	m
9	Warning	[26] 20.43	o (note)	o	[26] 20.43	o	o
c1:	IF A.4/11 THEN o ELSE n/a - - insertion of date in requests and responses.						
c2:	IF A.4/6 THEN m ELSE n/a - - timestamping of requests.						
c3:	IF A.4/26 THEN o ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).						
NOTE:	For a 606 (Not Acceptable Here) response, this status is RECOMMENDED rather than OPTIONAL.						

Prerequisite A.5/5 - - CANCEL response

Prerequisite: A.6/6 - - 200 (OK)

Table A.26: Supported headers within the CANCEL response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
2	Record-Route	[26] 20.30	n/a	n/a	[26] 20.30	n/a	n/a
4	Supported	[26] 20.37	m	m	[26] 20.37	m	m

Prerequisite A.5/5 - - CANCEL response

Prerequisite: A.6/14 - - 401 (Unauthorized)

Table A.27: Supported headers within the CANCEL response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
2	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
5	Supported	[26] 20.37	m	m	[26] 20.37	m	m

Prerequisite A.5/5 - - CANCEL response

Prerequisite: A.6/17 OR A.6/23 OR A.6/30 OR A.6/42 OR A.6/45 OR A.6/50 OR A.6/51 - - 404, 413, 480, 500, 503, 600, 603

Table A.28: Supported headers within the CANCEL response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
2	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
4	Retry-After	[26] 20.33	o	o	[26] 20.33	o	o
5	Supported	[26] 20.37	m	m	[26] 20.37	m	m

Prerequisite A.5/5 - - CANCEL response

Prerequisite: A.6/34 - - 484 (Address Incomplete)

Table A.30: Supported headers within the CANCEL response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
2	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
4	Supported	[26] 20.37	m	m	[26] 20.37	m	m

Prerequisite A.5/5 - - CANCEL response

Table A.31: Supported message bodies within the CANCEL response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1							

A.2.1.4.5 COMET method

Void

A.2.1.4.6 INFO method

Void

A.2.1.4.7 INVITE method

Prerequisite A.5/8 - - INVITE request

Table A.46: Supported headers within the INVITE request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Accept	[26] 20.1	o	o	[26] 20.1	m	m
2	Accept-Encoding	[26] 20.2	o	o	[26] 20.2	m	m
3	Accept-Language	[26] 20.3	o	o	[26] 20.3	m	m
4	Alert-Info	[26] 20.4	o	o	[26] 20.4	c1	c1
5	Allow	[26] 20.5, [26] 5.1	o (note 1)	o	[26] 20.5, [26] 5.1	m	m
6	Allow-Events	[28] 87.2.2	c2	c2	[28] 8.2.2	c2	c2
8	Authorization	[26] 20.7	c3	c3	[26] 20.7	c3	c3
9	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
10	Call-Info	[26] 20.9	o	o	[26] 20.9	o	o
11	Contact	[26] 20.10	m	m	[26] 20.10	m	m
12	Content-Disposition	[26] 20.11	o	o	[26] 20.11	m	m
13	Content-Encoding	[26] 20.12	o	o	[26] 20.12	m	m
14	Content-Language	[26] 20.13	o	o	[26] 20.13	m	m
15	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
16	Content-Type	[26] 20.15	m	m	[26] 20.15	m	m
17	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
18	Date	[26] 20.17	c4	c4	[26] 20.17	m	m
19	Expires	[26] 20.19	o	o	[26] 20.19	o	o
20	From	[26] 20.20	m	m	[26] 20.20	m	m
21	In-Reply-To	[26] 20.21	o	o	[26] 20.21	o	o
22	Max-Forwards	[26] 20.22	em	em	[26] 20.22	n/a	n/a
23	MIME-Version	[26] 20.24	o	o	[26] 20.24	m	m
24	Organization	[26] 20.25	o	o	[26] 20.25	o	o
24A	P-Access-Network-Info	[52] 4.4	c15	c16	[52] 4.4	c15	c17
24B	P-Asserted-Identity	[34] 9.1	n/a	n/a	[34] 9.1	c7	c7
24C	P-Called-Party-ID	[52] 4.2	x	x	[52] 4.2	c13	c13
24D	P-Charging-Function-Addresses	[52] 4.5	c20	c21	[52] 4.5	c20	c21
24E	P-Charging-Vector	[52] 4.6	c18	c19	[52] 4.6	c18	c19
25	P-Media-Authorization	[31] 6.1	n/a	n/a	[31] 6.1	c11	c12
25A	P-Preferred-Identity	[34] 9.2	c7	c5	[34] 9.2	n/a	n/a
25B	P-Visited-Network-ID	[52] 4.3	x (note 3)	x	[52] 4.3	c14	n/a
26	Priority	[26] 20.26	o	o	[26] 20.26	o	o
26A	Privacy	[33] 4.2	c9	c9	[33] 4.2	c9	c9
27	Proxy-Authorization	[26] 20.28	c6	c6	[26] 20.28	n/a	n/a
28	Proxy-Require	[26] 20.29	o (note 2)	o (note 2)	[26] 20.29	n/a	n/a
29	Record-Route	[26] 20.30	n/a	n/a	[26] 20.30	m	m
31	Reply-To	[26] 20.31	o	o	[26] 20.31	o	o
32	Require	[26] 20.32	e8o	me	[26] 20.32	m	m
33	Route	[26] 20.34	m	m	[26] 20.34	n/a	n/a
33A	Security-Client	[48] 2.3.1	c22	c22	[48] 2.3.1	n/a	n/a
33B	Security-Verify	[48] 2.3.1	c23	c23	[48] 2.3.1	n/a	n/a
34	Subject	[26] 20.36	o	o	[26] 20.36	o	o
35	Supported	[26] 20.37	c8	m	[26] 20.37	m	m
36	Timestamp	[26] 20.38	c10	c10	[26] 20.38	m	m

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
37	To	[26] 20.39	m	m	[26] 20.39	m	m
38	User-Agent	[26] 20.41	o	o	[26] 20.41	o	o
39	Via	[26] 20.42	m	m	[26] 20.42	m	m
c1:	IF A.4/12 THEN m ELSE n/a - - downloading of alerting information.						
c2:	IF A.4/20 THEN m ELSE n/a - - SIP specific event notification extension.						
c3:	IF A.4/7 THEN m ELSE n/a - - authentication between UA and UA.						
c4:	IF A.4/11 THEN o ELSE n/a - - insertion of date in requests and responses.						
c5:	IF A.3/1 AND A.4/25 THEN o ELSE n/a - - UE and private extensions to the Session Initiation Protocol (SIP) for asserted identity within trusted networks.						
c6:	IF A.4/8A THEN m ELSE n/a - - authentication between UA and proxy.						
c7:	IF A.4/25 THEN o ELSE n/a - - private extensions to the Session Initiation Protocol (SIP) for asserted identity within trusted networks.						
c8:	IF A.4/14 THEN o.1 ELSE o - Reliability of provisional responses in SIP.						
c9:	IF A.4/26 THEN o ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).						
c10:	IF A.4/6 THEN o ELSE n/a - - timestamping of requests.						
c11:	IF A.4/19 THEN m ELSE n/a - - SIP extensions for media authorization.						
c12:	IF A.3/1 THEN m ELSE n/a - - UE.						
c13:	IF A.4/32 THEN o ELSE n/a - - the P-Called-Party-ID extension.						
c14:	IF A.4/33 THEN o ELSE n/a - - the P-Visited-Network-ID extension.						
c15:	IF A.4/34 THEN o ELSE n/a - - the P-Access-Network-Info header extension.						
c16:	IF A.4/34 AND A.3/1 THEN m ELSE n/a - - the P-Access-Network-Info header extension and UE.						
c17:	IF A.4/34 AND (A.3/7A OR A.3/7D) THEN m ELSE n/a - - the P-Access-Network-Info header extension and AS acting as terminating UA or AS acting as third-party call controller.						
c18:	IF A.4/36 THEN o ELSE n/a - - the P-Charging-Vector header extension.						
c19:	IF A.4/36 THEN m ELSE n/a - - the P-Charging-Vector header extension.						
c20:	IF A.4/35 THEN o ELSE n/a - - the P-Charging-Function-Addresses header extension.						
c21:	IF A.4/35 THEN m ELSE n/a - - the P-Charging-Function-Addresses header extension.						
c22:	IF A.4/37 THEN o ELSE n/a - - security mechanism agreement for the session initiation protocol (note 4).						
c23:	IF A.4/37 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol.						
o.1:	At least one of these shall be supported.						
NOTE 1: The strength of this requirement in RFC 3261 [26] is RECOMMENDED, rather than OPTIONAL.							
NOTE 2: No distinction has been made in these tables between first use of a request on a From/To/Call-ID combination, and the usage in a subsequent one. Therefore the use of "o" etc. above has been included from a viewpoint of first usage.							
NOTE 3: The strength of this requirement in RFC 3455 [52] is SHOULD NOT, rather than MUST NOT.							
NOTE 4: Support of this header in this method is dependent on the security mechanism and the security architecture which is implemented. Use of this header in this method is not appropriate to the security mechanism defined by 3GPP TS 33.203 [19].							

Prerequisite A.5/8 - - INVITE request

Table A.47: Supported message bodies within the INVITE request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1							

Prerequisite A.5/9 - - INVITE response

Prerequisite: A.6/1 - - 100 (Trying)

Table A.48: Supported headers within the INVITE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Call-ID	[26] 20.8	n/a	n/a	[26] 20.8	m	m
2	Content-Length	[26] 20.14	n/a	n/a	[26] 20.14	m	m
3	Cseq	[26] 20.16	n/a	n/a	[26] 20.16	m	m
4	Date	[26] 20.17	n/a	n/a	[26] 20.17	m	m
5	From	[26] 20.20	n/a	n/a	[26] 20.20	m	m
6	To	[26] 20.39	n/a	n/a	[26] 20.39	m	m
7	Via	[26] 20.42	n/a	n/a	[26] 20.42	m	m

Prerequisite A.5/9 - - INVITE response

Table A.49: Supported headers within the INVITE response - all remaining status-codes

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
1A	Call-Info	[26] 20.9	o	o	[26] 20.9	o	o
2	Content-Disposition	[26] 20.11	o	o	[26] 20.11	m	m
3	Content-Encoding	[26] 20.12	o	o	[26] 20.12	m	m
4	Content-Language	[26] 20.13	o	o	[26] 20.13	m	m
5	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
6	Content-Type	[26] 20.15	m	m	[26] 20.15	m	m
7	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
8	Date	[26] 20.17	c1	c1	[26] 20.17	m	m
9	From	[26] 20.20	m	m	[26] 20.20	m	m
10	MIME-Version	[26] 20.24	o	o	[26] 20.24	m	m
11	Organization	[26] 20.25	o	o	[26] 20.25	o	o
11A	P-Access-Network-Info	[52] 4.4	c5	c6	[52] 4.4	c5	c7
11B	P-Asserted-Identity	[34] 9.1	n/a	n/a	[34] 9.1	c3	c3
11C	P-Charging-Function-Addresses	[52] 4.5	c10	c11	[52] 4.5	c11	c11
11D	P-Charging-Vector	[52] 4.6	c8	c9	[52] 4.6	c8	c9
11E	P-Preferred-Identity	[34] 9.2	c3	x	[34] 9.2	n/a	n/a
11F	Privacy	[33] 4.2	c4	c4	[33] 4.2	c4	c4
11G	Require	[26] 20.32	m	m	[26] 20.32	m	m
11H	Server	[26] 20.35	o	o	[26] 20.35	o	o
12	Timestamp	[26] 20.38	m	m	[26] 20.38	c2	c2
13	To	[26] 20.39	m	m	[26] 20.39	m	m
13A	User-Agent	[26] 20.41	o	o	[26] 20.41	o	o
14	Via	[26] 20.42	m	m	[26] 20.42	m	m
15	Warning	[26] 20.43	o (note)	o	[26] 20.43	o	o

c1: IF A.4/11 THEN o ELSE n/a - - insertion of date in requests and responses.
c2: IF A.4/6 THEN m ELSE n/a - - timestamping of requests.
c3: IF A.4/25 THEN o ELSE n/a - - private extensions to the Session Initiation Protocol (SIP) for asserted identity within trusted networks.
c4: IF A.4/26 THEN o ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).
c5: IF A.4/34 THEN o ELSE n/a - - the P-Access-Network-Info header extension.
c6: IF A.4/34 AND A.3/1 THEN m ELSE n/a - - the P-Access-Network-Info header extension and UE.
c7: IF A.4/34 AND (A.3/7A OR A.3/7D) THEN m ELSE n/a - - the P-Access-Network-Info header extension and AS acting as terminating UA or AS acting as third-party call controller.
c8: IF A.4/36 THEN o ELSE n/a - - the P-Charging-Vector header extension.
c9: IF A.4/36 THEN m ELSE n/a - - the P-Charging-Vector header extension.
c10: IF A.4/35 THEN o ELSE n/a - - the P-Charging-Function-Addresses header extension.
c11: IF A.4/35 THEN m ELSE n/a - - the P-Charging-Function-Addresses header extension.

NOTE: For a 606 (Not Acceptable Here) response, this status is RECOMMENDED rather than OPTIONAL.

Prerequisite A.5/9 - - INVITE response

Prerequisite: A.6/2 OR A.6/3 OR A.6/4 OR A.6/5 - - 1xx

Table A.50: Supported headers within the INVITE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
4	Contact	[26] 20.10	o	m	[26] 20.10	e/m	m
6	P-Media-Authorization	[31] 6.1	n/a	n/a	[31] 6.1	c11	c12
9	Rseq	[27] 7.1	c2	m	[27] 7.1	c3	m
11	Supported	[26] 20.37	mo	mo	[26] 20.37	m	m
c2: IF A.4/14 THEN o ELSE n/a - - reliability of provisional responses in SIP. c3: IF A.4/14 THEN m ELSE n/a - - reliability of provisional responses in SIP. c11: IF A.4/19 THEN m ELSE n/a - - SIP extensions for media authorization. c12: IF A.3/1 THEN m ELSE n/a - - UE.							

Prerequisite A.5/9 - - INVITE response

Prerequisite: A.6/6 - - 2xx

Table A.51: Supported headers within the INVITE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Accept	[26] 20.1	o	o	[26] 20.1	m	m
1A	Accept-Encoding	[26] 20.2	o	o	[26] 20.2	m	m
1B	Accept-Language	[26] 20.3	o	o	[26] 20.3	m	m
2	Allow	[26] 20.5	o (note 1)	o	[26] 20.5	m	m
4	Authentication-Info	[26] 20.6	c1	c1	[26] 20.6	c2	c2
6	Contact	[26] 20.10	m	m	[26] 20.10	m	m
8	P-Media-Authorization	[31] 6.1	n/a	n/a	[31] 6.1	c11	c12
9	Record-Route	[26] 20.30	m	m	[26] 20.30	m	m
13	Supported	[26] 20.37	m	m	[26] 20.37	m	m
c1: IF A.4/7 THEN o ELSE n/a - - authentication between UA and UA. c2: IF A.4/7 THEN m ELSE n/a - - authentication between UA and UA. c11: IF A.4/19 THEN m ELSE n/a - - SIP extensions for media authorization. c12: IF A.3/1 THEN m ELSE n/a - - UE.							
NOTE 1: The strength of this requirement in RFC 3261 [26] is RECOMMENDED, rather than OPTIONAL.							

Prerequisite A.5/9 - - INVITE response

Prerequisite: A.6/8 OR A.6/9 OR A.6/10 OR A.6/11 OR A.6/12 OR A.6/3⁴⁵ - - 3xx or 485 (Ambiguous)**Table A.52: Supported headers within the INVITE response**

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
4	Contact	[26] 20.10	o (note 1)	o	[26] 20.10	m	m
5	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
10	Supported	[26] 20.37	m	m	[26] 20.37	m	m
NOTE: The strength of this requirement is RECOMMENDED rather than OPTIONAL.							

Prerequisite A.5/9 - - INVITE response

Prerequisite: A.6/14 - - 401 (Unauthorized)

Table A.53: Supported headers within the INVITE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
4	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
6	Proxy-Authenticate	[26] 20.27	c3	c3	[26] 20.27	c3	c3
10	Supported	[26] 20.37	m	m	[26] 20.37	m	m
13	WWW-Authenticate	[26] 20.44	m	m	[26] 20.44	m	m
c1:	IF A.4/11 THEN o ELSE n/a - - insertion of date in requests and responses.						
c2:	IF A.4/6 THEN m ELSE n/a - - timestamping of requests.						
c3:	IF A.5/7 THEN m ELSE n/a - - support of authentication between UA and UA.						

Prerequisite A.5/9 - - INVITE response

Prerequisite: A.6/17 OR A.6/23 OR A.6/30 OR A.6/36 OR A.6/50 OR A.6/51 - - 404, 413, 480, 486, 600, 603

Table A.54: Supported headers within the INVITE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
4	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
8	Retry-After	[26] 20.33	o	o	[26] 20.33	o	o
10	Supported	[26] 20.37	m	m	[26] 20.37	m	m

Prerequisite A.5/9 - - INVITE response

Prerequisite: A.6/18 - - 405 (Method Not Allowed)

Table A.55: Supported headers within the INVITE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
2	Allow	[26] 20.5	m	m	[26] 20.5	m	m
5	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
10	Supported	[26] 20.37	m	m	[26] 20.37	m	m

Prerequisite A.5/9 - - INVITE response

Prerequisite: A.6/20 - - 407 (Proxy Authentication Required)

Table A.56: Supported headers within the INVITE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
4	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
6	Proxy-Authenticate	[26] 20.27	o		[26] 20.27	o	
10	Supported	[26] 20.37	m	m	[26] 20.37	m	m
11	WWW-Authenticate	[26] 20.44	o	o	[26] 20.44	o	o
c1:	IF A.5/7 THEN m ELSE n/a - - support of authentication between UA and UA.						

Prerequisite A.5/9 - - INVITE response

Prerequisite: A.6/25 - - 415 (Unsupported Media Type)

Table A.57: Supported headers within the INVITE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Accept	[26] 20.1	o.1	o.1	[26] 20.1	m	m
2	Accept-Encoding	[26] 20.2	o.1	o.1	[26] 20.2	m	m
3	Accept-Language	[26] 20.3	o.1	o.1	[26] 20.3	m	m
3A	Allow	[26] 20.5	o	o	[26] 20.5	m	m
6	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
11	Supported	[26] 20.37	m	m	[26] 20.37	m	m
o.1	At least one of these capabilities is supported.						

Prerequisite A.5/9 - - INVITE response

Prerequisite: A.6/27 - - 420 (Bad Extension)

Table A.58: Supported headers within the INVITE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
4	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
9	Supported	[26] 20.37	m	m	[26] 20.37	m	m
10	Unsupported	[26] 20.40	m	m	[26] 20.40	m	m

Prerequisite A.5/9 - - INVITE response

Prerequisite: A.6/28 OR A.6/41A - - 421 (Extension Required), 494 (Security Agreement Required)

Table A.58A: Supported headers within the INVITE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
2	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
3	Security-Server	[48] 2	x	x	[48] 2	c1	c1
3	Supported	[26] 20.37	m	m	[26] 20.37	m	m
c1:	IF A.4/37 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol.						

Prerequisite A.5/9 - - INVITE response

Prerequisite: A.6/34 - - 484 (Address Incomplete)

Table A.59: Supported headers within the INVITE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
4	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
9	Supported	[26] 20.37	m	m	[26] 20.37	m	m

Prerequisite A.5/9 - - INVITE response

Prerequisite: A.6/42 - - 500 (Server Internal Error)

Table A.60: Supported headers within the INVITE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
4	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
8	Retry-After	[26] 20.33	m	m	[26] 20.33	o	o
10	Supported	[26] 20.37	m	m	[26] 20.37	m	m

Prerequisite A.5/9 - - INVITE response

Prerequisite: A.6/45 - - 503 (Service Unavailable)

Table A.61: Supported headers within the INVITE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
4	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
8	Retry-After	[26] 20.33	o	o	[26] 20.33	o	m
10	Supported	[26] 20.37	m	m	[26] 20.37	m	m

Prerequisite A.5/9 - - INVITE response

Table A.62: Supported message bodies within the INVITE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1							

A.2.1.4.7A MESSAGE method

Prerequisite A.5/9A - - MESSAGE request

Table A.62A: Supported headers within the MESSAGE request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
2	Allow-Events	[28] 8.2.2	c1	c1	[28] 8.2.2	c2	c2
3	Authorization	[26] 20.7	c3	c3	[26] 20.7	c3	c3
4	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
5	Call-Info	[26] 20.9	o	o	[26] 20.9	o	o
6	Content-Disposition	[26] 20.11	o	o	[26] 20.11	m	m
7	Content-Encoding	[26] 20.12	o	o	[26] 20.12	m	m
8	Content-Language	[26] 20.13	o	o	[26] 20.13	m	m
9	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
10	Content-Type	[26] 20.15	m	m	[26] 29.15	m	m
11	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
12	Date	[26] 20.17	c4	c4	[26] 20.17	m	m
13	Expires	[26] 20.19	o	o	[26] 20.19	o	o
14	From	[26] 20.20	m	m	[26] 20.20	m	m
15	In-Reply-To	[26] 20.21	o	o	[26] 20.21	o	o
16	Max-Forwards	[26] 20.22	em	em	[26] 20.22	n/a	en/a
17	MIME-Version	[26] 20.24	o	o	[26] 20.24	m	m
18	Organization	[26] 20.25	o	o	[26] 20.25	o	o
18A	P-Access-Network-Info	[52] 4.4	c15	c16	[52] 4.4	c15	c16
18B	P-Asserted-Identity	[34] 9.1	n/a	n/a	[34] 9.1	c11	c11
18C	P-Called-Party-ID	[52] 4.2	x	x	[52] 4.2	c13	c13
18D	P-Charging-Function-Addresses	[52] 4.5	c20	c21	[52] 4.5	c20	c21
18E	P-Charging-Vector	[52] 4.6	c18	c19	[52] 4.6	c18	c19
18F	P-Preferred-Identity	[34] 9.2	c11	c7	[34] 9.2	n/a	n/a
18G	P-Visited-Network-ID	[52] 4.3	x (note 1)	x	[52] 4.3	c14	n/a
19	Priority	[26] 20.26	o	o	[26] 20.26	o	o
19A	Privacy	[33] 4.2	c12	c12	[33] 4.2	c12	c12
20	Proxy-Authorization	[26] 20.28	c5	c5	[26] 20.28	n/a	n/a
21	Proxy-Require	[26] 20.29	o	n/a	[26] 20.29	n/a	n/a
22	Record-Route	[26] 20.30	n/a	n/a	[26] 20.30	n/a	n/a
23	Reply-To	[26] 20.31	o	o	[26] 20.31	o	o
24	Require	[26] 20.32	c8	o	[26] 20.32	m	m
25	Route	[26] 20.34	m	m	[26] 20.34	n/a	n/a
25A	Security-Client	[48] 2.3.1	c22	c22	[48] 2.3.1	n/a	n/a
25B	Security-Verify	[48] 2.3.1	c23	c23	[48] 2.3.1	n/a	n/a
26	Subject	[26] 20.35	o	o	[26] 20.36	o	o
27	Supported	[26] 20.37	c9	m	[26] 20.37	m	m
28	Timestamp	[26] 20.38	c10	c10	[26] 20.38	m	m
29	To	[26] 20.39	m	m	[26] 20.39	m	m
30	User-Agent	[26] 20.41	o	o	[26] 20.41	o	o
31	Via	[26] 20.42	m	m	[26] 20.42	m	m

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
c1:	IF A.4/20 THEN o ELSE n/a - - SIP specific event notification extension.						
c2:	IF A.4/20 THEN m ELSE n/a - - SIP specific event notification extension.						
c3:	IF A.4/7 THEN m ELSE n/a - - authentication between UA and UA.						
c4:	IF A.4/11 THEN o ELSE n/a - - insertion of date in requests and responses.						
c5:	IF A.162/8A THEN m ELSE i - - authentication between UA and proxy.						
c7:	IF A.3/1 AND A.4/25 THEN o ELSE n/a - - UE and private extensions to the Session Initiation Protocol (SIP) for asserted identity within trusted networks.						
c8:	IF A.4/14 THEN o.1 ELSE o - - Reliable transport.						
c9:	IF IF A.4/14 THEN o.1 ELSE o - - support of reliable transport.						
c10:	IF A.4/6 THEN o ELSE n/a - - timestamping of requests.						
c11:	IF A.4/25 THEN o ELSE n/a - - private extensions to the Session Initiation Protocol (SIP) for asserted identity within trusted networks.						
c12:	IF A.4/26 THEN o ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).						
c13:	IF A.4/32 THEN o ELSE n/a - - the P-Called-Party-ID extension.						
c14:	IF A.4/33 THEN o ELSE n/a - - the P-Visited-Network-ID extension.						
c15:	IF A.4/34 THEN o ELSE n/a - - the P-Access-Network-Info header extension.						
c16:	IF A.4/34 AND A.3/1 THEN m ELSE n/a - - the P-Access-Network-Info header extension and UE.						
c17:	IF A.4/34 AND (A.3/7A OR A.3/7D) THEN m ELSE n/a - - the P-Access-Network-Info header extension and AS acting as terminating UA or AS acting as third-party call controller.						
c18:	IF A.4/36 THEN o ELSE n/a - - the P-Charging-Vector header extension.						
c19:	IF A.4/36 THEN m ELSE n/a - - the P-Charging-Vector header extension.						
c20:	IF A.4/35 THEN o ELSE n/a - - the P-Charging-Function-Addresses header extension.						
c21:	IF A.4/35 THEN m ELSE n/a - - the P-Charging-Function-Addresses header extension.						
c22:	IF A.4/37 THEN o ELSE n/a - - security mechanism agreement for the session initiation protocol (note 2).						
c23:	IF A.4/37 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol.						
NOTE 1: The strength of this requirement in RFC 3455 [52] is SHOULD NOT, rather than MUST NOT.							
NOTE 2: Support of this header in this method is dependent on the security mechanism and the security architecture which is implemented. Use of this header in this method is not appropriate to the security mechanism defined by 3GPP TS 33.203 [19].							

Prerequisite A.5/9A - - MESSAGE request

Table A.62B: Supported message bodies within the MESSAGE request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1							

Prerequisite A.5/9B - - MESSAGE response

Table A.62C: Supported headers within the MESSAGE response - all remaining status-codes

Item	Header	Sending			Receiving									
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status							
1	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m							
2	Call-Info	[26] 20.9	o	o	[26] 20.9	o	o							
3	Content-Disposition	[26] 20.11	o (Note 2)e	o (Note 2)e	[26] 20.11	m (Note 2)m	m (Note 2)m							
4	Content-Encoding	[26] 20.12	o (Note 2)e	o (Note 2)e	[26] 20.12	m (Note 2)m	m (Note 2)m							
5	Content-Language	[26] 20.13	o (Note 2)e	o (Note 2)e	[26] 20.13	m (Note 2)m	m (Note 2)m							
6	Content-Length	[26] 20.14	m (Note 2)m	m (Note 2)m	[26] 20.14	m (Note 2)m	m (Note 2)m							
7	Content-Type	[26] 20.15	m (Note 2)m	m (Note 2)m	[26] 20.15	m (Note 2)m	m (Note 2)m							
8	Cseq	[26] 20.16	m	m	[26] 20.16	m	m							
9	Date	[26] 20.17	c1	c1	[26] 20.17	m	m							
10	From	[26] 20.20	m	m	[26] 20.20	m	m							
11	MIME-Version	[26] 20.24	o	o	[26] 20.24	m	m							
12	Organization	[26] 20.25	o	o	[26] 20.25	o	o							
12A	P-Access-Network-Info	[52] 4.4	c5	c6	[52] 4.4	c5	c7							
12B	P-Asserted-Identity	[34] 9.1	n/a	n/a	[34] 9.1	c3	c3							
12C	P-Charging-Function-Addresses	[52] 4.5	c10	c11	[52] 4.5	c10	c11							
12D	P-Charging-Vector	[52] 4.6	c8	c9	[52] 4.6	c8	c9							
12E	P-Preferred-Identity	[34] 9.2	c3	x	[34] 9.2	n/a	n/a							
12F	Privacy	[33] 4.2	c4	c4	[33] 4.2	c4	c4							
12G	Require	[26] 20.32	oA	m o	[26] 20.32	m	m							
13	Server	[26] 20.35	o	o	[26] 20.35	o	o							
14	Timestamp	[26] 20.38	m	m	[26] 20.38	c2	c2							
15	To	[26] 20.39	m	m	[26] 20.39	m	m							
16	User-Agent	[26] 20.41	o	o	[26] 20.41	o	o							
17	Via	[26] 20.42	m	m	[26] 20.42	m	m							
18	Warning	[26] 20.43	o	o	[26] 20.43	o	o							
c1:	IF A.4/11 THEN o ELSE n/a - - insertion of date in requests and responses.													
c2:	IF A.4/6 THEN m ELSE n/a - - timestamping of requests.													
c3:	IF A.4/25 THEN o ELSE n/a - - private extensions to the Session Initiation Protocol (SIP) for asserted identity within trusted networks.													
c4:	IF A.4/26 THEN o ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).													
c5:	IF A.4/34 THEN o ELSE n/a - - the P-Access-Network-Info header extension.													
c6:	IF A.4/34 AND A.3/1 THEN m ELSE n/a - - the P-Access-Network-Info header extension and UE.													
c7:	IF A.4/34 AND (A.3/7A OR A.3/7D) THEN m ELSE n/a - - the P-Access-Network-Info header extension and AS acting as terminating UA or AS acting as third-party call controller.													
c8:	IF A.4/36 THEN o ELSE n/a - - the P-Charging-Vector header extension.													
c9:	IF A.4/36 THEN m ELSE n/a - - the P-Charging-Vector header extension.													
c10:	IF A.4/35 THEN o ELSE n/a - - the P-Charging-Function-Addresses header extension.													
c11:	IF A.4/35 THEN m ELSE n/a - - the P-Charging-Function-Addresses header extension.													
NOTE 1: For a 606 (Not Acceptable Here) response, this status is RECOMMENDED rather than OPTIONAL.														
NOTE 2: RFC 3428 [50] clause 7 states that all 2xx class responses to a MESSAGE request must not include any body, therefore for 2xx responses to the MESSAGE request the values on Sending side for "RFC status" and "Profile status" are "x", the values for Receiving side for "RFC status" and "Profile Status" are "n/a". RFC 3261 [26] clause 7.4 states that all responses may contain bodies, therefore for all responses to the MESSAGE request other than 2xx responses, the values on Sending side for "RFC status" and "Profile status" are "o", the values for Receiving side for "RFC status" and "Profile Status" are "m".														

Prerequisite A.5/9B - - MESSAGE response

Prerequisite: A.6/6 - - 2xx

Table A.62D: Supported headers within the MESSAGE response

Item	Header	Sending	Receiving
------	--------	---------	-----------

		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
2	Authentication-Info	[26] 20.6	c1	c1	[26] 20.6	c2	c2
4	Supported	[26] 20.37	mo	mo	[26] 20.37	m	m
c1:	IF A.4/7 THEN o ELSE n/a - - authentication between UA and UA.						
c2:	IF A.4/7 THEN m ELSE n/a - - authentication between UA and UA.						

Prerequisite A.5/9B - - MESSAGE response

Prerequisite: A.6/8 OR A.6/9 OR A.6/10 OR A.6/11 OR A.6/12 OR A.6/35 - - 3xx or 485 (Ambiguous)

Table A.62E: Supported headers within the MESSAGE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
2	Contact	[26] 20.10	o (note)	o	[26] 20.10	m	m
3	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
5	Supported	[26] 20.37	m	m	[26] 20.37	m	m

NOTE: The strength of this requirement is RECOMMENDED rather than OPTIONAL.

Prerequisite A.5/9B - - MESSAGE response

Prerequisite: A.6/14 - - 401 (Unauthorized)

Table A.62F: Supported headers within the MESSAGE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
2	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
3	Proxy-Authenticate	[26] 20.27	c1	c1	[26] 20.27	c1	c1
5	Supported	[26] 20.37	m	m	[26] 20.37	m	m
6	WWW-Authenticate	[26] 20.44	m	m	[26] 20.44	m	m
c1:	IF A.5/7 THEN m ELSE n/a - - support of authentication between UA and UA.						

Prerequisite A.5/9B - - MESSAGE response

Prerequisite: A.6/17 OR A.6/23 OR A.6/30 OR A.6/36 OR A.6/42 OR A.6/45 OR A.6/50 OR A.6/51 - - 404, 413, 480, 486, 500, 503, 600, 603

Table A.62G: Supported headers within the MESSAGE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
2	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
4	Retry-After	[26] 20.33	o	o	[26] 20.33	o	o
5	Supported	[26] 20.37	m	m	[26] 20.37	m	m

Prerequisite A.5/9B - - MESSAGE response

Prerequisite: A.6/18 - - 405 (Method Not Allowed)

Table A.62H: Supported headers within the MESSAGE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	m	m
2	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
4	Supported	[26] 20.37	m	m	[26] 20.37	m	m

Prerequisite A.5/9B - - MESSAGE response

Prerequisite: A.6/20 - - 407 (Proxy Authentication Required)

Table A.62I: Supported headers within the MESSAGE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
2	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
3	Proxy-Authenticate	[26] 20.27	c1	c1	[26] 20.27	c1	c1
5	Supported	[26] 20.37	m	m	[26] 20.37	m	m
6	WWW-Authenticate	[26] 20.44	o	o	[26] 20.44	o	o
c1:	IF A.5/7 THEN m ELSE n/a -- support of authentication between UA and UA.						

Prerequisite A.5/9B - - MESSAGE response

Prerequisite: A.6/25 - - 415 (Unsupported Media Type)

Table A.62J: Supported headers within the MESSAGE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Accept	[26] 20.1	o.1	o.1	[26] 20.1	m	m
2	Accept-Encoding	[26] 20.2	o.1	o.1	[26] 20.2	m	m
3	Accept-Language	[26] 20.3	o.1	o.1	[26] 20.3	m	m
4	Allow	[26] 20.5	o	o	[26] 20.5	m	m
5	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
7	Supported	[26] 20.37	m	m	[26] 20.37	m	m
o.1	At least one of these capabilities is supported.						

Prerequisite A.5/9B - - MESSAGE response

Prerequisite: A.6/27 - - 420 (Bad Extension)

Table A.62K: Supported headers within the MESSAGE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
2	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
4	Supported	[26] 20.37	m	m	[26] 20.37	m	m
5	Unsupported	[26] 20.40	m	m	[26] 20.40	m	m

Prerequisite A.5/9B - - MESSAGE response

Prerequisite: A.6/28 OR A.6/41A - - 421 (Extension Required), 494 (Security Agreement Required)

Table A.62L: Supported headers within the MESSAGE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
2	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
3	Security-Server	[48] 2	x	x	[48] 2	c1	c1
4	Supported	[26] 20.37	m	m	[26] 20.37	m	m
c1:	IF A.4/37 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol.						

Prerequisite A.5/9B - - MESSAGE response

Prerequisite: A.6/34 - - 484 (Address Incomplete)

Table A.62M: Supported headers within the MESSAGE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
2	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
4	Supported	[26] 20.37	m	m	[26] 20.37	m	m

Prerequisite A.5/9B - - MESSAGE response

Table A.62N: Supported message bodies within the MESSAGE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1							

A.2.1.4.8 NOTIFY method

Prerequisite A.5/10 - - NOTIFY request

Table A.63: Supported headers within the NOTIFY request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Accept	[26] 20.1	o	o	[26] 20.1	m	m
2	Accept-Encoding	[26] 20.2	o	o	[26] 20.2	m	m
3	Accept-Language	[26] 20.3	o	o	[26] 20.3	m	m
3A	Allow	[26] 20.5	o	o	[26] 20.5	m	m
4	Allow-Events	[28] 8.2.2	c1	c1	[28] 8.2.2	c2	c2
5	Authorization	[26] 20.7	c3	c3	[26] 20.7	c3	c3
6	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
6A	Contact	[26] 20.10	m	m	[26] 20.10	m	m
7	Content-Disposition	[26] 20.11	o	o	[26] 20.11	m	m
8	Content-Encoding	[26] 20.12	o	o	[26] 20.12	m	m
9	Content-Language	[26] 20.13	o	o	[26] 20.13	m	m
10	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
11	Content-Type	[26] 20.15	m	m	[26] 20.15	m	m
12	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
13	Date	[26] 20.17	c4	c4	[26] 20.17	m	m
14	Event	[28] 8.2.1	m	m	[28] 8.2.1	m	m
15	From	[26] 20.20	m	m	[26] 20.20	m	m
16	Max-Forwards	[26] 20.22	em	em	[26] 20.22	n/a	n/a
17	MIME-Version	[26] 20.24	o	o	[26] 20.24	m	m
17A	P-Access-Network-Info	[52] 4.4	c10	c11	[52] 4.4	c10	c12
17B	P-Asserted-Identity	[34] 9.1	n/a	n/a	[34] 9.1	c6	c6
17C	P-Charging-Function-Addresses	[52] 4.5	c14	c15	[52] 4.5	c14	c15
17D	P-Charging-Vector	[52] 4.6	c13	n/a	[52] 4.6	c13	n/a
17E	P-Preferred-Identity	[34] 9.2	c6	x	[34] 9.2	n/a	n/a
17F	Privacy	[33] 4.2	c7	n/a	[33] 4.2	c7	c7
18	Proxy-Authorization	[26] 20.28	c5	c5	[26] 20.28	n/a	n/a
19	Proxy-Require	[26] 20.29	o	n/a	[26] 20.29	n/a	n/a
20	Record-Route	[26] 20.30	n/a	n/a	[26] 20.30	c9	c9
21	Require	[26] 20.32	o	o	[26] 20.32	m	m
22A	Security-Client	[48] 2.3.1	c16	c16	[48] 2.3.1	n/a	n/a
22B	Security-Verify	[48] 2.3.1	c17	c17	[48] 2.3.1	n/a	n/a
22	Route	[26] 20.34	m	m	[26] 20.34	n/a	n/a
23	Subscription-State	[28] 8.2.3	m	m	[28] 8.2.3	m	m
24	Supported	[26] 20.37	o	o	[26] 20.37	m	m
25	Timestamp	[26] 20.38	c8	c8	[26] 20.38	m	m
26	To	[26] 20.39	m	m	[26] 20.39	m	m
27	User-Agent	[26] 20.41	o	o	[26] 20.41	o	o
28	Via	[26] 20.42	m	m	[26] 20.42	m	m

c1:	IF A.4/20 THEN o ELSE n/a - - SIP specific event notification extension.
c2:	IF A.4/20 THEN m ELSE n/a - - SIP specific event notification extension.
c3:	IF A.4/7 THEN m ELSE n/a - - authentication between UA and UA.
c4:	IF A.4/11 THEN o ELSE n/a - - insertion of date in requests and responses.
c5:	IF A.4/8A THEN m ELSE n/a - - authentication between UA and proxy.
c6:	IF A.4/25 THEN o ELSE n/a - - private extensions to the Session Initiation Protocol (SIP) for asserted identity within trusted networks.
c7:	IF A.4/26 THEN o ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).
c8:	IF A.4/6 THEN o ELSE n/a - - timestamping of requests.
c9:	IF A.4/15 OR A.4/20 THEN m ELSE n/a - - the REFER method extension or SIP specific event notification extension.
c10:	IF A.4/34 THEN o ELSE n/a - - the P-Access-Network-Info header extension.
c11:	IF A.4/34 AND A.3/1 THEN m ELSE n/a - - the P-Access-Network-Info header extension and UE.
c12:	IF A.4/34 AND (A.3/7A OR A.3/7D) THEN m ELSE n/a - - the P-Access-Network-Info header extension and AS acting as terminating UA or AS acting as third-party call controller.
c13:	IF A.4/36 THEN o ELSE n/a - - the P-Charging-Vector header extension.
c14:	IF A.4/35 THEN o ELSE n/a - - the P-Charging-Function-Addresses header extension.
c15:	IF A.4/35 THEN m ELSE n/a - - the P-Charging-Function-Addresses header extension.
c16:	IF A.4/37 THEN o ELSE n/a - - security mechanism agreement for the session initiation protocol (note).
c17:	IF A.4/37 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol.
NOTE:	Support of this header in this method is dependent on the security mechanism and the security architecture which is implemented. Use of this header in this method is not appropriate to the security mechanism defined by 3GPP TS 33.203 [19].

Prerequisite A.5/10 - - NOTIFY request

Table A.64: Supported message bodies within the NOTIFY request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	sipfrag	[37] 2	c1	c1	[37]	c1	c1
c1:	IF A.4/15 THEN m ELSE o - - the REFER method extension						

Prerequisite A.5/11 - - NOTIFY response

Table A.65: Supported headers within the NOTIFY response - all status-codes

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
2	Content-Disposition	[26] 20.11	o	o	[26] 20.11	m	m
3	Content-Encoding	[26] 20.12	o	o	[26] 20.12	m	m
4	Content-Language	[26] 20.13	o	o	[26] 20.13	m	m
5	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
6	Content-Type	[26] 20.15	m	m	[26] 20.15	m	m
7	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
8	Date	[26] 20.17	c1	c1	[26] 20.17	m	m
9	From	[26] 20.20	m	m	[26] 20.20	m	m
10	MIME-Version	[26] 20.24	o	o	[26] 20.24	m	m
10A	P-Access-Network-Info	[52] 4.4	c5	c6	[52] 4.4	c5	c7
10B	P-Asserted-Identity	[34] 9.1	n/a	n/a	[34] 9.1	c3	c3
10C	P-Charging-Function-Addresses	[52] 4.5	c9	c10	[52] 4.5	c9	c10
10D	P-Charging-Vector	[52] 4.6	c8	n/a	[52] 4.6	c8	n/a
10E	P-Preferred-Identity	[34] 9.2	c3	x	[34] 9.2	n/a	n/a
10F	Privacy	[33] 4.2	c4	n/a	[33] 4.2	c4	c4
10G	Require	[26] 20.32	m	m	[26] 20.32	m	m
10H	Server	[26] 20.35	o	o	[26] 20.35	o	o
11	Timestamp	[26] 20.38	m	m	[26] 20.38	c2	c2
12	To	[26] 20.39	m	m	[26] 20.39	m	m
12A	User-Agent	[26] 20.41	o	o	[26] 20.41	o	o
13	Via	[26] 20.42	m	m	[26] 20.42	m	m
14	Warning	[26] 20.43	o (note)	o	[26] 20.43	o	o
<p>c1: IF A.4/11 THEN o ELSE n/a - - insertion of date in requests and responses.</p> <p>c2: IF A.4/6 THEN m ELSE n/a - - timestamping of requests.</p> <p>c3: IF A.4/25 THEN o ELSE n/a - - private extensions to the Session Initiation Protocol (SIP) for asserted identity within trusted networks.</p> <p>c4: IF A.4/26 THEN o ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).</p> <p>c5: IF A.4/34 THEN o ELSE n/a - - the P-Access-Network-Info header extension.</p> <p>c6: IF A.4/34 AND A.3/1 THEN m ELSE n/a - - the P-Access-Network-Info header extension and UE.</p> <p>c7: IF A.4/34 AND (A.3/7A OR A.3/7D) THEN m ELSE n/a - - the P-Access-Network-Info header extension and AS acting as terminating UA or AS acting as third-party call controller.</p> <p>c8: IF A.4/36 THEN o ELSE n/a - - the P-Charging-Vector header extension.</p> <p>c9: IF A.4/35 THEN o ELSE n/a - - the P-Charging-Function-Addresses header extension.</p> <p>c10: IF A.4/35 THEN m ELSE n/a - - the P-Charging-Function-Addresses header extension.</p>							
NOTE: For a 606 (Not Acceptable Here) response, this status is RECOMMENDED rather than OPTIONAL.							

Prerequisite A.5/11 - - NOTIFY response

Prerequisite: A.6/6 and A.6/7 - - 2xx

Table A.66: Supported headers within the NOTIFY response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	o	o	[26] 20.5	m	m
1	Authentication-Info	[26] 20.6	c1	c1	[26] 20.6	c2	c2
1A	Contact	[26] 20.10	m	m	[26] 20.10	m	m
2	Record-Route	[26] 20.30	c3	c3	[26] 20.30	c3	c3
5	Supported	[26] 20.37	m	m	[26] 20.37	m	m
<p>c1: IF A.4/7 THEN o ELSE n/a - - authentication between UA and UA.</p> <p>c2: IF A.4/7 THEN m ELSE n/a - - authentication between UA and UA.</p> <p>c3: IF A.4/15 OR A.4/20 THEN m ELSE n/a - - the REFER method extension or SIP specific event notification extension.</p>							

Prerequisite A.5/11 - - NOTIFY response

Prerequisite: A.6/8 OR A.6/9 OR A.6/10 OR A.6/11 OR A.6/12 OR A.6/35 - - 3xx or 485 (Ambiguous)

Table A.67: Supported headers within the NOTIFY response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	o	o	[26] 20.5	m	m
1	Contact	[26] 20.10	m (note)	m	[26] 20.10	m	m
2	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
5	Supported	[26] 20.37	m	m	[26] 20.37	m	m

NOTE: The strength of this requirement is RECOMMENDED rather than MANDATORY for a 485 response.

Prerequisite A.5/11 - - NOTIFY response

Prerequisite: A.6/14 - - 401 (Unauthorized)

Table A.68: Supported headers within the NOTIFY response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	o	o	[26] 20.5	m	m
1	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
2	Proxy-Authenticate	[26] 20.27	c1	c1	[26] 20.27	c1	c1
5	Supported	[26] 20.37	m	m	[26] 20.37	m	m
8	WWW-Authenticate	[26] 20.44	m	m	[26] 20.44	m	m
c1:	IF A.5/7 THEN m ELSE n/a - - support of authentication between UA and UA.						

Prerequisite A.5/11 - - NOTIFY response

Prerequisite: A.6/17 OR A.6/23 OR A.6/30 OR A.6/36 OR A.6/42 OR A.6/45 OR A.6/50 OR A.6/51 - - 404, 413, 480, 486, 500, 503, 600, 603

Table A.69: Supported headers within the NOTIFY response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	o	o	[26] 20.5	m	m
1	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
3	Retry-After	[26] 20.33	o	o	[26] 20.33	o	o
5	Supported	[26] 20.37	m	m	[26] 20.37	m	m

Prerequisite A.5/11 - - NOTIFY response

Prerequisite: A.6/18 -- 405 (Method Not Allowed)

Table A.70: Supported headers within the NOTIFY response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	m	m
2	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
5	Supported	[26] 20.37	m	m	[26] 20.37	m	m

Prerequisite A.5/11 - - NOTIFY response

Prerequisite: A.6/20 - - 407 (Proxy Authentication Required)

Table A.71: Supported headers within the NOTIFY response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	o	o	[26] 20.5	m	m
1	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
2	Proxy-Authenticate	[26] 20.27	c3	c3	[26] 20.27	c3	c3
5	Supported	[26] 20.37	m	m	[26] 20.37	m	m
6	WWW-Authenticate	[26] 20.44	o	o	[26] 20.44	o	o
c3:	IF A.5/7 THEN m ELSE n/a - - support of authentication between UA and UA.						

Prerequisite A.5/11 - - NOTIFY response

Prerequisite A.6/25 - - 415 (Unsupported Media Type)

Table A.72: Supported headers within the NOTIFY response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Accept	[26] 20.1	o.1	o.1	[26] 20.1	m	m
2	Accept-Encoding	[26] 20.2	o.1	o.1	[26] 20.2	m	m
3	Accept-Language	[26] 20.3	o.1	o.1	[26] 20.3	m	m
3A	Allow	[26] 20.5	o	o	[26] 20.5	m	m
4	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
7	Supported	[26] 20.37	m	m	[26] 20.37	m	m

Prerequisite A.5/11 - - NOTIFY response

Prerequisite: A.6/27 - - 420 (Bad Extension)

Table A.73: Supported headers within the NOTIFY response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	o	o	[26] 20.5	m	m
1	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
4	Supported	[26] 20.37	m	m	[26] 20.37	m	m
5	Unsupported	[26] 20.40	m	m	[26] 20.40	m	m

Prerequisite A.5/11 - - NOTIFY response

Prerequisite: A.6/28 OR A.6/41A - - 421 (Extension Required), 494 (Security Agreement Required)

Table A.73A: Supported headers within the NOTIFY response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
2	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
3	Security-Server	[48] 2	x	x	[48] 2	c1	c1
4	Supported	[26] 20.37	m	m	[26] 20.37	m	m
c1:	IF A.4/37 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol.						

Prerequisite A.5/11 - - NOTIFY response

Prerequisite: A.6/34 - - 484 (Address Incomplete)

Table A.74: Supported headers within the NOTIFY response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	o	o	[26] 20.5	m	m
1	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
4	Supported	[26] 20.37	m	m	[26] 20.37	m	m

Prerequisite A.5/11 - - NOTIFY response

Prerequisite: A.6/39 - - 489 (Bad Event)

Table A.75: Supported headers within the NOTIFY response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	o	o	[26] 20.5	m	m
1	Allow-Events	[28] 8.2.2	m	m	[28] 8.2.2	m	m
3	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o

Prerequisite A.5/11 - - NOTIFY response

Table A.76: Supported message bodies within the NOTIFY response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1							

A.2.1.4.9 OPTIONS method

Prerequisite A.5/12 - - OPTIONS request

Table A.77: Supported headers within the OPTIONS request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Accept	[26] 20.1	m	m	[26] 20.1	m	m
2	Accept-Encoding	[26] 20.2	m	m	[26] 20.2	m	m
3	Accept-Language	[26] 20.3	m	m	[26] 20.3	m	m
3A	Allow	[26] 20.5	o	o	[26] 20.5	m	m
4	Allow-Events	[28] 8.2.2	c1	c1	[28] 8.2.2	c1	c1
5	Authorization	[26] 20.7	c2	c2	[26] 20.7	c2	c2
6	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
7	Call-Info	[26] 20.9	o	o	[26] 20.9	o	o
8	Contact	[26] 20.10	o	o	[26] 20.10	o	o
9	Content-Disposition	[26] 20.11	o	o	[26] 20.11	m	m
10	Content-Encoding	[26] 20.12	o	o	[26] 20.12	m	m
11	Content-Language	[26] 20.13	o	o	[26] 20.13	m	m
12	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
13	Content-Type	[26] 20.15	m	m	[26] 20.15	m	m
14	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
15	Date	[26] 20.17	c3	c3	[26] 20.17	m	m
16	From	[26] 20.20	m	m	[26] 20.20	m	m
17	Max-Forwards	[26] 20.22	em	em	[26] 20.22	n/a	n/a
18	MIME-Version	[26] 20.24	o	o	[26] 20.24	m	m
19	Organization	[26] 20.25	o	o	[26] 20.25	o	o
19A	P-Access-Network-Info	[52] 4.4	c11	c12	[52] 4.4	c11	c13
19B	P-Asserted-Identity	[34] 9.1	n/a	n/a	[34] 9.1	c6	c6
19C	P-Called-Party-ID	[52] 4.2	x	x	[52] 4.2	c9	c9
19D	P-Charging-Function-Addresses	[52] 4.5	c16	c17	[52] 4.5	c16	c17
19E	P-Charging-Vector	[52] 4.6	c14	c15	[52] 4.6	c14	c15
19F	P-Preferred-Identity	[34] 9.2	c6	c4	[34] 9.2	n/a	n/a
19G	P-Visited-Network-ID	[52] 4.3	x (note 2)	x	[52] 4.3	c10	n/a
19H	Privacy	[33] 4.2	c8	c8	[33] 4.2	c8	c8
20	Proxy-Authorization	[26] 20.28	c5	c5	[26] 20.28	n/a	n/a
21	Proxy-Require	[26] 20.29	o	o (note 1)	[26] 20.29	n/a	n/a
22	Record-Route	[26] 20.30	n/a	n/a	[26] 20.30	n/a	n/a
23	Require	[26] 20.32	o	o	[26] 20.32	m	m
24	Route	[26] 20.34	m	m	[26] 20.34	n/a	n/a
24A	Security-Client	[48] 2.3.1	c18	c18	[48] 2.3.1	n/a	n/a
24B	Security-Verify	[48] 2.3.1	c19	c19	[48] 2.3.1	n/a	n/a
25	Supported	[26] 20.37	c6	c6	[26] 20.37	m	m
26	Timestamp	[26] 20.38	c7	c7	[26] 20.38	m	m
27	To	[26] 20.39	m	m	[26] 20.39	m	m
28	User-Agent	[26] 20.41	o	o	[26] 20.41	o	o
29	Via	[26] 20.42	m	m	[26] 20.42	m	m

c1:	IF A.4/20 THEN m ELSE n/a - - SIP specific event notification extension.
c2:	IF A.4/7 THEN m ELSE n/a - - authentication between UA and UA.
c3:	IF A.4/11 THEN o ELSE n/a - - insertion of date in requests and responses.
c4:	IF A.3/1 AND A.4/25 THEN o ELSE n/a - - UE and private extensions to the Session Initiation Protocol (SIP) for asserted identity within trusted networks.
c5:	IF A.4/8A THEN m ELSE n/a - - authentication between UA and proxy.
c6:	IF A.4/25 THEN o ELSE n/a - - private extensions to the Session Initiation Protocol (SIP) for asserted identity within trusted networks.
c7:	IF A.4/6 THEN o ELSE n/a - - timestamping of requests.
c8:	IF A.4/26 THEN o ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).
c9:	IF A.4/32 THEN o ELSE n/a - - the P-Called-Party-ID extension.
c10:	IF A.4/33 THEN o ELSE n/a - - the P-Visited-Network-ID extension.
c11:	IF A.4/34 THEN o ELSE n/a - - the P-Access-Network-Info header extension.
c12:	IF A.4/34 AND A.3/1 THEN m ELSE n/a - - the P-Access-Network-Info header extension and UE.
c13:	IF A.4/34 AND (A.3/7A OR A.3/7D) THEN m ELSE n/a - - the P-Access-Network-Info header extension and AS acting as terminating UA or AS acting as third-party call controller.
c14:	IF A.4/36 THEN o ELSE n/a - - the P-Charging-Vector header extension.
c15:	IF A.4/36 THEN m ELSE n/a - - the P-Charging-Vector header extension.
c16:	IF A.4/35 THEN o ELSE n/a - - the P-Charging-Function-Addresses header extension.
c17:	IF A.4/35 THEN m ELSE n/a - - the P-Charging-Function-Addresses header extension.
c18:	IF A.4/37 THEN o ELSE n/a - - security mechanism agreement for the session initiation protocol (note 3).
c19:	IF A.4/37 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol.
NOTE 1: No distinction has been made in these tables between first use of a request on a From/To/Call-ID combination, and the usage in a subsequent one. Therefore the use of "o" etc. above has been included from a viewpoint of first usage.	
NOTE 2: The strength of this requirement in RFC 3455 [52] is SHOULD NOT, rather than MUST NOT.	
NOTE 3: Support of this header in this method is dependent on the security mechanism and the security architecture which is implemented. Use of this header in this method is not appropriate to the security mechanism defined by 3GPP TS 33.203 [19].	

Prerequisite A.5/12 - - OPTIONS request

Table A.78: Supported message bodies within the OPTIONS request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1							

Prerequisite A.5/13 - - OPTIONS response

Prerequisite: A.6/1 - - 100 (Trying)

Table A.79: Supported headers within the OPTIONS response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Call-ID	[26] 20.8	n/a	n/a	[26] 20.8	m	m
2	Content-Length	[26] 20.14	n/a	n/a	[26] 20.14	m	m
3	Cseq	[26] 20.16	n/a	n/a	[26] 20.16	m	m
4	Date	[26] 20.17	n/a	n/a	[26] 20.17	m	m
5	From	[26] 20.20	n/a	n/a	[26] 20.20	m	m
6	To	[26] 20.39	n/a	n/a	[26] 20.39	m	m
7	Via	[26] 20.42	n/a	n/a	[26] 20.42	m	m

Prerequisite A.5/13 - - OPTIONS response

Table A.80: Supported headers within the OPTIONS response - all remaining status-codes

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
1A	Call-Info	[26] 20.9	o	o	[26] 20.9	o	o
2	Content-Disposition	[26] 20.11	o	o	[26] 20.11	m	m
3	Content-Encoding	[26] 20.12	o	o	[26] 20.12	m	m
4	Content-Language	[26] 20.13	o	o	[26] 20.13	m	m
5	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
6	Content-Type	[26] 20.15	m	m	[26] 20.15	m	m
7	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
8	Date	[26] 20.17	c1	c1	[26] 20.17	m	m
9	From	[26] 20.20	m	m	[26] 20.20	m	m
10	MIME-Version	[26] 20.24	o	o	[26] 20.24	m	m
11	Organization	[26] 20.25	o	o	[26] 20.25	o	o
11A	P-Access-Network-Info	[52] 4.4	c5	c6	[52] 4.4	c5	c7
11B	P-Asserted-Identity	[34] 9.1	n/a	n/a	[34] 9.1	c3	c3
11C	P-Charging-Function-Addresses	[52] 4.5	c10	c11	[52] 4.5	c10	c11
11D	P-Charging-Vector	[52] 4.6	c8	c9	[52] 4.6	c8	c9
11E	P-Preferred-Identity	[34] 9.2	c3	x	[34] 9.2	n/a	n/a
11F	Privacy	[33] 4.2	c4	c4	[33] 4.2	c4	c4
11G	Require	[26] 20.32	m	m	[26] 20.32	m	m
12	Timestamp	[26] 20.38	m	m	[26] 20.38	c2	c2
13	To	[26] 20.39	m	m	[26] 20.39	m	m
13A	User-Agent	[26] 20.41	o	o	[26] 20.41	o	o
14	Via	[26] 20.42	m	m	[26] 20.42	m	m
15	Warning	[26] 20.43	o (note)	o	[26] 20.43	o	o
c1:	IF A.4/11 THEN o ELSE n/a - - insertion of date in requests and responses.						
c2:	IF A.4/6 THEN m ELSE n/a - - timestamping of requests.						
c3:	IF A.4/25 THEN o ELSE n/a - - private extensions to the Session Initiation Protocol (SIP) for asserted identity within trusted networks.						
c4:	IF A.4/26 THEN o ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).						
c5:	IF A.4/34 THEN o ELSE n/a - - the P-Access-Network-Info header extension.						
c6:	IF A.4/34 AND A.3/1 THEN m ELSE n/a - - the P-Access-Network-Info header extension and UE.						
c7:	IF A.4/34 AND (A.3/7A OR A.3/7D) THEN m ELSE n/a - - the P-Access-Network-Info header extension and AS acting as terminating UA or AS acting as third-party call controller.						
c8:	IF A.4/36 THEN o ELSE n/a - - the P-Charging-Vector header extension.						
c9:	IF A.4/36 THEN m ELSE n/a - - the P-Charging-Vector header extension.						
c10:	IF A.4/35 THEN o ELSE n/a - - the P-Charging-Function-Addresses header extension.						
c11:	IF A.4/35 THEN m ELSE n/a - - the P-Charging-Function-Addresses header extension.						
NOTE:	For a 606 (Not Acceptable Here) response, this status is RECOMMENDED rather than OPTIONAL.						

Prerequisite A.5/13 - - OPTIONS response

Prerequisite: A.6/6 - - 2xx

Table A.81: Supported headers within the OPTIONS response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Accept	[26] 20.1	m	m	[26] 20.1	m	m
2	Allow	[26] 20.5	o (note 1)	o	[26] 20.5	m	m
3	Authentication-Info	[26] 20.6	c1	c1	[26] 20.6	c2	c2
5	Contact	[26] 20.10	o		[26] 20.10	o	
8	Supported	[26] 20.37	m	m	[26] 20.37	m	m
c1:	IF A.4/7 THEN o ELSE n/a - - authentication between UA and UA.						
c2:	IF A.4/7 THEN m ELSE n/a - - authentication between UA and UA.						
NOTE 1:	The strength of this requirement in RFC 3261 [26] is RECOMMENDED, rather than OPTIONAL.						

Prerequisite A.5/13 - - OPTIONS response

Prerequisite: A.6/8 OR A.6/9 OR A.6/10 OR A.6/11 OR A.6/12 OR A.6/35 - - 3xx or 485 (Ambiguous)

Table A.82: Supported headers within the OPTIONS response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
3	Contact	[26] 20.10	o (note)	o	[26] 20.10	m	m
4	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
7	Supported	[26] 20.37	m	m	[26] 20.37	m	m

NOTE: The strength of this requirement is RECOMMENDED rather than OPTIONAL.

Prerequisite A.5/13 - - OPTIONS response

Prerequisite: A.6/14 - - 401 (Unauthorized)

Table A.83: Supported headers within the OPTIONS response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
3	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
4	Proxy-Authenticate	[26] 20.27	c1	c1	[26] 20.27	c1	c1
7	Supported	[26] 20.37	m	m	[26] 20.37	m	m
10	WWW-Authenticate	[26] 20.44	o		[26] 20.44	o	
c1: IF A.5/7 THEN m ELSE n/a - - support of authentication between UA and UA.							

Prerequisite A.5/13 - - OPTIONS response

Prerequisite: A.6/17 OR A.6/23 OR A.6/30 OR A.6/36 OR A.6/42 OR A.6/45 OR A.6/50 OR A.6/51 - - 404, 413, 480, 486, 500, 503, 600, 603

Table A.84: Supported headers within the OPTIONS response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
3	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
5	Retry-After	[26] 20.33	o	o	[26] 20.33	o	o
7	Supported	[26] 20.37	m	m	[26] 20.37	m	m

Prerequisite A.5/13 - - OPTIONS response

Prerequisite: A.6/18 - - 405 (Method Not Allowed)

Table A.85: Supported headers within the OPTIONS response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
2	Allow	[26] 20.5	m	m	[26] 20.5	m	m
4	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
7	Supported	[26] 20.37	m	m	[26] 20.37	m	m

Prerequisite A.5/13 - - OPTIONS response

Prerequisite: A.6/20 - - 407 (Proxy Authentication Required)

Table A.86: Supported headers within the OPTIONS response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
3	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
4	Proxy-Authenticate	[26] 20.27	c1	c1	[26] 20.27	c1	c1
7	Supported	[26] 20.37	m	m	[26] 20.37	m	m
8	WWW-Authenticate	[26] 20.44	o	o	[26] 20.44	o	o
c1:	IF A.5/7 THEN m ELSE n/a - - support of authentication between UA and UA.						

Prerequisite A.5/13 - - OPTIONS response

Prerequisite: A.6/25 - - 415 (Unsupported Media Type)

Table A.87: Supported headers within the OPTIONS response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Accept	[26] 20.1	o.1	o.1	[26] 20.1	m	m
2	Accept-Encoding	[26] 20.2	o.1	o.1	[26] 20.2	m	m
3	Accept-Language	[26] 20.3	o.1	o.1	[26] 20.3	m	m
4	Allow	[26] 20.5	o	o	[26] 20.5	m	m
5	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
8	Supported	[26] 20.37	m	m	[26] 20.37	m	m
o.1	At least one of these capabilities is supported.						

Prerequisite A.5/13 - - OPTIONS response

Prerequisite: A.6/27 - - 420 (Bad Extension)

Table A.88: Supported headers within the OPTIONS response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
3	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
6	Supported	[26] 20.37	m	m	[26] 20.37	m	m
7	Unsupported	[26] 20.40	m	m	[26] 20.40	m	m

Prerequisite A.5/13 - - OPTIONS response

Prerequisite: A.6/28 OR A.6/41A - - 421 (Extension Required), 494 (Security Agreement Required)

Table A.88A: Supported headers within the OPTIONS response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
2	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
3	Security-Server	[48] 2	x	x	[48] 2	c1	c1
4	Supported	[26] 20.37	m	m	[26] 20.37	m	m
c1:	IF A.4/37 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol.						

Prerequisite A.5/13 - - OPTIONS response

Prerequisite: A.6/34 - - 484 (Address Incomplete)

Table A.89: Supported headers within the OPTIONS response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
4	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
7	Supported	[26] 20.37	m	m	[26] 20.37	m	m

Prerequisite A.5/13 - - OPTIONS response

Table A.90: Supported message bodies within the OPTIONS response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1							

A.2.1.3.10 PRACK method

Prerequisite A.5/14 -- PRACK request

Table A.91: Supported headers within the PRACK request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Accept	[26] 20.1	o	o	[26] 20.1	m	m
2	Accept-Encoding	[26] 20.2	o	o	[26] 20.2	m	m
3	Accept-Language	[26] 20.3	o	o	[26] 20.3	m	m
3A	Allow	[26] 20.5	o	o	[26] 20.5	m	m
4	Allow-Events	[28] 8.2.2	c1	c1	[28] 8.2.2	c2	c2
5	Authorization	[26] 20.7	c3	c3	[26] 20.7	c3	c3
6	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
7	Content-Disposition	[26] 20.11	o	o	[26] 20.11	m	m
8	Content-Encoding	[26] 20.12	o	o	[26] 20.12	m	m
9	Content-Language	[26] 20.13	o	o	[26] 20.13	m	m
10	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
11	Content-Type	[26] 20.15	m	m	[26] 20.15	m	m
12	CSeq	[26] 20.16	m	m	[26] 20.16	m	m
13	Date	[26] 20.17	c4	c4	[26] 20.17	m	m
14	From	[26] 20.20	m	m	[26] 20.20	m	m
15	Max-Forwards	[26] 20.22	em	em	[26] 20.22	n/a	n/a
16	MIME-Version	[26] 20.24	o	o	[26] 20.24	m	m
16A	P-Access-Network-Info	[52] 4.4	c9	c10	[52] 4.4	c9	c11
16B	P-Charging-Function-Addresses	[52] 4.5	c13	c14	[52] 4.5	c13	c14
16C	P-Charging-Vector	[52] 4.6	c12	n/a	[52] 4.6	c12	n/a
16D	Privacy	[33] 4.2	c6	n/a	[33] 4.2	c6	n/a
17	Proxy-Authorization	[26] 20.28	c5	c5	[26] 20.28	n/a	n/a
18	Proxy-Require	[26] 20.29	o	n/a	[26] 20.29	n/a	n/a
19	RAck	[27] 7.2	m	m	[27] 7.2	m	m
20	Record-Route	[26] 20.30	n/a	n/a	[26] 20.30	n/a	n/a
21	Require	[26] 20.32	o	o	[26] 20.32	m	m
22	Route	[26] 20.34	m	m	[26] 20.34	n/a	n/a
23	Supported	[26] 20.37	o	o	[26] 20.37	m	m
24	Timestamp	[26] 20.38	c8	c8	[26] 20.38	m	m
25	To	[26] 20.39	m	m	[26] 20.39	m	m
26	User-Agent	[26] 20.41	o	o	[26] 20.41	o	o
27	Via	[26] 20.42	m	m	[26] 20.42	m	m

c1: IF A.4/20 THEN o ELSE n/a - - SIP specific event notification extension.
 c2: IF A.4/20 THEN m ELSE n/a - - SIP specific event notification extension.
 c3: IF A.4/7 THEN m ELSE n/a - - authentication between UA and UA.
 c4: IF A.4/11 THEN o ELSE n/a - - insertion of date in requests and responses.
 c5: IF A.4/8A THEN m ELSE n/a - - authentication between UA and proxy.
 c6: IF A.4/26 THEN o ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).
 c8: IF A.4/6 THEN o ELSE n/a - - timestamping of requests.
 c9: IF A.4/34 THEN o ELSE n/a - - the P-Access-Network-Info header extension.
 c10: IF A.4/34 AND A.3/1 THEN m ELSE n/a - - the P-Access-Network-Info header extension and UE.
 c11: IF A.4/34 AND (A.3/7A OR A.3/7D) THEN m ELSE n/a - - the P-Access-Network-Info header extension and AS acting as terminating UA or AS acting as third-party call controller.
 c12: IF A.4/36 THEN o ELSE n/a - - the P-Charging-Vector header extension.
 c13: IF A.4/35 THEN o ELSE n/a - - the P-Charging-Function-Addresses header extension.
 c14: IF A.4/35 THEN m ELSE n/a - - the P-Charging-Function-Addresses header extension.

Prerequisite A.5/14 - - PRACK request

Table A.92: Supported message bodies within the PRACK request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1							

Prerequisite A.5/15 - - PRACK response

Prerequisite: A.6/1 - - 100 (Trying)

Table A.93: Supported headers within the PRACK response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Call-ID	[26] 20.8	n/a	n/a	[26] 20.8	m	m
2	Content-Length	[26] 20.14	n/a	n/a	[26] 20.14	m	m
3	Cseq	[26] 20.16	n/a	n/a	[26] 20.16	m	m
4	Date	[26] 20.17	n/a	n/a	[26] 20.17	m	m
5	From	[26] 20.20	n/a	n/a	[26] 20.20	m	m
6	To	[26] 20.39	n/a	n/a	[26] 20.39	m	m
7	Via	[26] 20.42	n/a	n/a	[26] 20.42	m	m

Prerequisite A.5/15 - - PRACK response

Table A.94: Supported headers within the PRACK response - all remaining status-codes

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
2	Content-Disposition	[26] 20.11	o	o	[26] 20.11	m	m
3	Content-Encoding	[26] 20.12	o	o	[26] 20.12	m	m
4	Content-Language	[26] 20.13	o	o	[26] 20.13	m	m
5	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
6	Content-Type	[26] 20.15	m	m	[26] 20.15	m	m
7	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
8	Date	[26] 20.17	c1	c1	[26] 20.17	m	m
9	From	[26] 20.20	m	m	[26] 20.20	m	m
10	MIME-Version	[26] 20.24	o	o	[26] 20.24	m	m
10A	P-Access-Network-Info	[52] 4.4	c3	c4	[52] 4.4	c3	c5
10B	P-Charging-Function-Addresses	[52] 4.5	c7	c8	[52] 4.5	c7	c8
10C	P-Charging-Vector	[52] 4.6	c6	n/a	[52] 4.6	c6	n/a
10D	Privacy	[33] 4.2	c2	n/a	[33] 4.2	c2	n/a
10E	Require	[26] 20.32	mo	mo	[26] 20.32	m	m
10F	Server	[26] 20.35	o	o	[26] 20.35	o	o
11	Timestamp	[26] 20.38	m	m	[26] 20.38	c2	c2
12	To	[26] 20.39	m	m	[26] 20.39	m	m
12A	User-Agent	[26] 20.41	o	o	[26] 20.41	o	o
13	Via	[26] 20.42	m	m	[26] 20.42	m	m
14	Warning	[26] 20.43	o (note)	o	[26] 20.43	o	o
c1: IF A.4/11 THEN o ELSE n/a - - insertion of date in requests and responses. c2: IF A.4/26 THEN o ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP). c3: IF A.4/34 THEN o ELSE n/a - - the P-Access-Network-Info header extension. c4: IF A.4/34 AND A.3/1 THEN m ELSE n/a - - the P-Access-Network-Info header extension and UE. c5: IF A.4/34 AND (A.3/7A OR A.3/7D) THEN m ELSE n/a - - the P-Access-Network-Info header extension and AS acting as terminating UA or AS acting as third-party call controller. c6: IF A.4/36 THEN o ELSE n/a - - the P-Charging-Vector header extension. c7: IF A.4/35 THEN o ELSE n/a - - the P-Charging-Function-Addresses header extension. c8: IF A.4/35 THEN m ELSE n/a - - the P-Charging-Function-Addresses header extension.							
NOTE: For a 606 (Not Acceptable Here) response, this status is RECOMMENDED rather than OPTIONAL.							

Prerequisite A.5/15 - - PRACK response

Prerequisite: A.6/6 - - 2xx

Table A.95: Supported headers within the PRACK response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	o	o	[26] 20.5	m	m
0B	Authentication-Info	[26] 20.6	c1	c1	[26] 20.6	c2	c2
3	Supported	[26] 20.37	mo	mo	[26] 20.37	m	m
c1: IF A.4/7 THEN o ELSE n/a - - authentication between UA and UA. c2: IF A.4/7 THEN m ELSE n/a - - authentication between UA and UA.							

Prerequisite A.5/15 - - PRACK response

Prerequisite: A.6/8 OR A.6/9 OR A.6/10 OR A.6/11 OR A.6/12 OR A.6/35 - - 3xx or 485 (Ambiguous)

Table A.96: Supported headers within the PRACK response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	o	o	[26] 20.5	m	m
1	Contact	[26] 20.10	o (note)	o	[26] 20.10	m	m
2	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
5	Supported	[26] 20.37	m	m	[26] 20.37	m	m

NOTE: The strength of this requirement is RECOMMENDED rather than OPTIONAL.

Prerequisite A.5/15 - - PRACK response

Prerequisite: A.6/14 - - 401 (Unauthorized)

Table A.97: Supported headers within the PRACK response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	o	o	[26] 20.5	m	m
1	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
2	Proxy-Authenticate	[26] 20.27	c1	c1	[26] 20.27	c1	c1
5	Supported	[26] 20.37	m	m	[26] 20.37	m	m
8	WWW-Authenticate	[26] 20.44	m	m	[26] 20.44	m	m
c1:	IF A.5/7 THEN m ELSE n/a - - support of authentication between UA and UA.						

Prerequisite A.5/15 - - PRACK response

Prerequisite: A.6/17 OR A.6/23 OR A.6/30 OR A.6/36 OR A.6/42 OR A.6/45 OR A.6/50 OR A.6/51 - - 404, 413, 480, 486, 500, 503, 600, 603

Table A.98: Supported headers within the PRACK response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	o	o	[26] 20.5	m	m
1	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
3	Retry-After	[26] 20.33	o	o	[26] 20.33	o	o
5	Supported	[26] 20.37	m	m	[26] 20.37	m	m

Prerequisite A.5/15 - - PRACK response

Prerequisite: A.6/18 - - 405 (Method Not Allowed)

Table A.99: Supported headers within the PRACK response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	m	m
2	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
5	Supported	[26] 20.37	m	m	[26] 20.37	m	m

Prerequisite A.5/15 - - PRACK response

Prerequisite: A.6/20 - - 407 (Proxy Authentication Required)

Table A.100: Supported headers within the PRACK response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	o	o	[26] 20.5	m	m
1	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
2	Proxy-Authenticate	[26] 20.27	c1	c1	[26] 20.27	c1	c1
5	Supported	[26] 20.37	m	m	[26] 20.37	m	m
6	WWW-Authenticate	[26] 20.44	o	o	[26] 20.44	o	o
c1: IF A.5/7 THEN m ELSE n/a - - support of authentication between UA and UA.							

Prerequisite A.5/15 - - PRACK response

Prerequisite: A.6/25 - - 415 (Unsupported Media Type)

Table A.101: Supported headers within the PRACK response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Accept	[26] 20.1	o.1	o.1	[26] 20.1	m	m
2	Accept-Encoding	[26] 20.2	o.1	o.1	[26] 20.2	m	m
3	Accept-Language	[26] 20.3	o.1	o.1	[26] 20.3	m	m
3A	Allow	[26] 20.5	o	o	[26] 20.5	m	m
4	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
7	Supported	[26] 20.37	m	m	[26] 20.37	m	m

Prerequisite A.5/15 - - PRACK response

Prerequisite: A.6/27 - - 420 (Bad Extension)

Table A.102: Supported headers within the PRACK response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	o	o	[26] 20.5	m	m
1	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
4	Supported	[26] 20.37	m	m	[26] 20.37	m	m

Prerequisite A.5/15 - - PRACK response

Prerequisite: A.6/28 OR A.6/41A - - 421 (Extension Required), 494 (Security Agreement Required)

Table A.102A: Supported headers within the PRACK response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
2	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
3	Security-Server	[48] 2	x	x	[48] 2	c1	c1
4	Supported	[26] 20.37	m	m	[26] 20.37	m	m
c1: IF A.4/37 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol.							

Prerequisite A.5/15 - - PRACK response

Prerequisite: A.6/34 - - 484 (Address Incomplete)

Table A.103: Supported headers within the PRACK response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	o	o	[26] 20.5	m	m
1	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
4	Supported	[26] 20.37	m	m	[26] 20.37	m	m

Prerequisite A.5/15 - - PRACK response

Table A.104: Supported message bodies within the PRACK response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1							

A.2.1.4.11 REFER method

Prerequisite A.5/16 - - REFER request

Table A.105: Supported headers within the REFER request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Accept	[26] 20.1	o	o	[26] 20.1	m	m
0B	Accept-Encoding	[26] 20.2	o	o	[26] 20.2	m	m
1	Accept-Language	[26] 20.3	o	o	[26] 20.3	m	m
1A	Allow	[26] 20.5	o	o	[26] 20.5	m	m
2	Allow-Events	[28] 8.2.2	c1	c1	[28] 8.2.2	c2	c2
3	Authorization	[26] 20.7	c3	c3	[26] 20.7	c3	c3
4	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
5	Contact	[26] 20.10	m	m	[26] 20.10	m	m
5A	Content-Disposition	[26] 20.11	o	o	[26] 20.11	m	m
5B	Content-Encoding	[26] 20.12	o	o	[26] 20.12	m	m
5C	Content-Language	[26] 20.13	o	o	[26] 20.13	m	m
6	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
7	Content-Type	[26] 20.15	m	m	[26] 20.15	m	m
8	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
9	Date	[26] 20.17	c4	c4	[26] 20.17	m	m
10	Expires	[26] 20.19	o	o	[26] 20.19	o	o
11	From	[26] 20.20	m	m	[26] 20.20	m	m
12	Max-Forwards	[26] 20.22	em	em	[26] 20.22	n/a	n/a
13	MIME-Version	[26] 20.24	o	o	[26] 20.24	m	m
14	Organization	[26] 20.25	o	o	[26] 20.25	o	o
14A	P-Access-Network-Info	[52] 4.4	c12	c13	[52] 4.4	c12	c14
14B	P-Asserted-Identity	[34] 9.1	n/a	n/a	[34] 9.1	c8	c8
14C	P-Called-Party-ID	[52] 4.2	x	x	[52] 4.2	c10	c10
14D	P-Charging-Function-Addresses	[52] 4.5	c17	c18	[52] 4.5	c17	c18
14E	P-Charging-Vector	[52] 4.6	c15	c16	[52] 4.6	c15	c16
14F	P-Preferred-Identity	[34] 9.2	c8	c7	[34] 9.2	n/a	n/a
14G	P-Visited-Network-ID	[52] 4.3	x (note 1)	x	[52] 4.3	c11	n/a
14H	Privacy	[33] 4.2	c9	c9	[33] 4.2	c9	c9
15	Proxy-Authorization	[26] 20.28	c5	c5	[26] 20.28	n/a	n/a
16	Proxy-Require	[26] 20.29	o	n/a	[26] 20.29	n/a	n/a
17	Record-Route	[26] 20.30	n/a	n/a	[26] 20.30	m	m
18	Refer-To	[36] 3	m	m	[36] 3	m	m
19	Require	[26] 20.32	o	o	[26] 20.32	m	m
20	Route	[26] 20.34	m	m	[26] 20.34	n/a	n/a
20A	Security-Client	[48] 2.3.1	c19	c19	[48] 2.3.1	n/a	n/a
20B	Security-Verify	[48] 2.3.1	c20	c20	[48] 2.3.1	n/a	n/a
20C	Subject	[26] 20.36	o	o	[26] 20.36	o	o
21	Supported	[26] 20.37, [26] 7.1	o	o	[26] 20.37, [26] 7.1	m	m
22	Timestamp	[26] 20.38	c6	c6	[26] 20.38	m	m
23	To	[26] 20.39	m	m	[26] 20.39	m	m
24	User-Agent	[26] 20.41	o	o	[26] 20.41	o	o
25	Via	[26] 20.42	m	m	[26] 20.42	m	m

c1:	IF A.4/20 THEN o ELSE n/a - - SIP specific event notification extension.
c2:	IF A.4/20 THEN m ELSE n/a - - SIP specific event notification extension.
c3:	IF A.4/7 THEN m ELSE n/a - - authentication between UA and UA.
c4:	IF A.4/11 THEN o ELSE n/a - - insertion of date in requests and responses.
c5:	IF A.4/8A THEN m ELSE n/a - - authentication between UA and proxy.
c6:	IF A.4/6 THEN o ELSE n/a - - timestamping of requests.
c7:	IF A.3/1 AND A.4/25 THEN o ELSE n/a - - UE and private extensions to the Session Initiation Protocol (SIP) for asserted identity within trusted networks.
c8:	IF A.4/25 THEN o ELSE n/a - - private extensions to the Session Initiation Protocol (SIP) for asserted identity within trusted networks.
c9:	IF A.4/26 THEN o ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).
c10:	IF A.4/32 THEN o ELSE n/a - - the P-Called-Party-ID extension.
c11:	IF A.4/33 THEN o ELSE n/a - - the P-Visited-Network-ID extension.
c12:	IF A.4/34 THEN o ELSE n/a - - the P-Access-Network-Info header extension.
c13:	IF A.4/34 AND A.3/1 THEN m ELSE n/a - - the P-Access-Network-Info header extension and UE.
c14:	IF A.4/34 AND (A.3/7A OR A.3/7D) THEN m ELSE n/a - - the P-Access-Network-Info header extension and AS acting as terminating UA or AS acting as third-party call controller.
c15:	IF A.4/36 THEN o ELSE n/a - - the P-Charging-Vector header extension.
c16:	IF A.4/36 THEN m ELSE n/a - - the P-Charging-Vector header extension.
c17:	IF A.4/35 THEN o ELSE n/a - - the P-Charging-Function-Addresses header extension.
c18:	IF A.4/35 THEN m ELSE n/a - - the P-Charging-Function-Addresses header extension.
c19:	IF A.4/37 THEN o ELSE n/a - - security mechanism agreement for the session initiation protocol (note 2).
c20:	IF A.4/37 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol.

NOTE 1: The strength of this requirement in RFC 3455 [52] is SHOULD NOT, rather than MUST NOT.
 NOTE 2: Support of this header in this method is dependent on the security mechanism and the security architecture which is implemented. Use of this header in this method is not appropriate to the security mechanism defined by 3GPP TS 33.203 [19].

Prerequisite A.5/16 - - REFER request

Table A.106: Supported message bodies within the REFER request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1							

Prerequisite A.5/17 - - REFER response

Prerequisite: A.6/1 - - 100 (Trying)

Table A.107: Supported headers within the REFER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Call-ID	[26] 20.8	n/a	n/a	[26] 20.8	m	m
2	Content-Length	[26] 20.14	n/a	n/a	[26] 20.14	m	m
3	Cseq	[26] 20.16	n/a	n/a	[26] 20.16	m	m
4	Date	[26] 20.17	n/a	n/a	[26] 20.17	m	m
5	From	[26] 20.20	n/a	n/a	[26] 20.20	m	m
6	To	[26] 20.39	n/a	n/a	[26] 20.39	m	m
7	Via	[26] 20.42	n/a	n/a	[26] 20.42	m	m

Prerequisite A.5/17 - - REFER response

Table A.108: Supported headers within the REFER response - all remaining status-codes

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
1A	Content-Disposition	[26] 20.11	o	o	[26] 20.11	m	m
2	Content-Encoding	[26] 20.12	o	o	[26] 20.12	m	m
3	Content-Language	[26] 20.13	o	o	[26] 20.13	m	m
4	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
5	Content-Type	[26] 20.15	m	m	[26] 20.15	m	m
6	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
7	Date	[26] 20.17	c1	c1	[26] 20.17	m	m
8	From	[26] 20.20	m	m	[26] 20.20	m	m
9	MIME-Version	[26] 20.24	o	o	[26] 20.24	m	m
10	Organization	[26] 20.25	o	o	[26] 20.25	o	o
10A	P-Access-Network-Info	[52] 4.4	c5	c6	[52] 4.4	c5	c7
10B	P-Asserted-Identity	[34] 9.1	n/a	n/a	[34] 9.1	c3	c3
10C	P-Charging-Function-Addresses	[52] 4.5	c10	c11	[52] 4.5	c10	c11
10D	P-Charging-Vector	[52] 4.6	c8	c9	[52] 4.6	c8	c9
10E	P-Preferred-Identity	[34] 9.2	c3	x	[34] 9.2	n/a	n/a
10F	Privacy	[33] 4.2	c4	c4	[33] 4.2	c4	c4
10G	Require	[26] 20.32	m	m	[26] 20.32	m	m
10H	Server	[26] 20.35	o	o	[26] 20.35	o	o
11	Timestamp	[26] 20.38	m	m	[26] 20.38	c2	c2
12	To	[26] 20.39	m	m	[26] 20.39	m	m
12A	User-Agent	[26] 20.41	o	o	[26] 20.41	o	o
13	Via	[26] 20.42	m	m	[26] 20.42	m	m
14	Warning	[26] 20.43	o (note)	o	[26] 20.43	o	o
c1:	IF A.4/11 THEN o ELSE n/a - - insertion of date in requests and responses.						
c2:	IF A.4/6 THEN m ELSE n/a - - timestamping of requests.						
c3:	IF A.4/25 THEN o ELSE n/a - - private extensions to the Session Initiation Protocol (SIP) for asserted identity within trusted networks.						
c4:	IF A.4/26 THEN o ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).						
c5:	IF A.4/34 THEN o ELSE n/a - - the P-Access-Network-Info header extension.						
c6:	IF A.4/34 AND A.3/1 THEN m ELSE n/a - - the P-Access-Network-Info header extension and UE.						
c7:	IF A.4/34 AND (A.3/7A OR A.3/7D) THEN m ELSE n/a - - the P-Access-Network-Info header extension and AS acting as terminating UA or AS acting as third-party call controller.						
c8:	IF A.4/36 THEN o ELSE n/a - - the P-Charging-Vector header extension.						
c9:	IF A.4/36 THEN m ELSE n/a - - the P-Charging-Vector header extension.						
c10:	IF A.4/35 THEN o ELSE n/a - - the P-Charging-Function-Addresses header extension.						
c11:	IF A.4/35 THEN m ELSE n/a - - the P-Charging-Function-Addresses header extension.						
NOTE:	For a 606 (Not Acceptable Here) response, this status is RECOMMENDED rather than OPTIONAL.						

Prerequisite A.5/17 - - REFER response

Prerequisite: A.6/7 - - 202 (Accepted)

Table A.109: Supported headers within the REFER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
2	Authentication-Info	[26] 20.6	c1	c1	[26] 20.6	c2	c2
3	Contact	[26] 20.10	m	m	[26] 20.10	m	m
5	Record-Route	[26] 20.30	m	m	[26] 20.30	m	m
8	Supported	[26] 20.37	m	m	[26] 20.37	m	m
c1:	IF A.4/7 THEN o ELSE n/a - - authentication between UA and UA.						
c2:	IF A.4/7 THEN m ELSE n/a - - authentication between UA and UA.						

Prerequisite A.5/17 - - REFER response

Prerequisite: A.6/8 OR A.6/9 OR A.6/10 OR A.6/11 OR A.6/12 OR A.6/35 - - 3xx or 485 (Ambiguous)

Table A.110: Supported headers within the REFER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
2	Contact	[26] 20.10	o (note)	o	[26] 20.10	m	m
3	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
7	Supported	[26] 20.37	m	m	[26] 20.37	m	m

NOTE: The strength of this requirement is RECOMMENDED rather than OPTIONAL.

Prerequisite A.5/17 - - REFER response

Prerequisite: A.6/14 - - 401 (Unauthorized)

Table A.111: Supported headers within the REFER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
2	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
4	Proxy-Authenticate	[26] 20.27	c1	c1	[26] 20.27	c1	c1
7	Supported	[26] 20.37	m	m	[26] 20.37	m	m
10	WWW-Authenticate	[26] 20.44	m	m	[26] 20.44	m	m
c1: IF A.5/7 THEN m ELSE n/a - - support of authentication between UA and UA.							

Prerequisite A.5/17 - - REFER response

Prerequisite: A.6/17 OR A.6/23 OR A.6/30 OR A.6/36 OR A.6/42 OR A.6/45 OR A.6/50 OR A.6/51 - - 404, 413, 480, 486, 500, 503, 600, 603

Table A.112: Supported headers within the REFER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
3	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
6	Retry-After	[26] 20.33	o	o	[26] 20.33	o	o
8	Supported	[26] 20.37	m	m	[26] 20.37	m	m

Prerequisite A.5/17 - - REFER response

Prerequisite: A.6/18 - - 405 (Method Not Allowed)

Table A.113: Supported headers within the REFER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
2	Allow	[26] 20.5	m	m	[26] 20.5	m	m
3	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
6	Supported	[26] 20.37	m	m	[26] 20.37	m	m

Prerequisite A.5/17 - - REFER response

Prerequisite: A.6/20 - - 407 (Proxy Authentication Required)

Table A.114: Supported headers within the REFER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
2	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
4	Proxy-Authenticate	[26] 20.27	c1	c1	[26] 20.27	c1	c1
7	Supported	[26] 20.37	m	m	[26] 20.37	m	m
8	WWW-Authenticate	[26] 20.44	o	o	[26] 20.44	o	o
c1:	IF A.5/7 THEN m ELSE n/a - - support of authentication between UA and UA.						

Prerequisite A.5/17 - - REFER response

Prerequisite: A.6/25 - - 415 (Unsupported Media Type)

Table A.115: Supported headers within the REFER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Accept	[26] 20.1	o.1	o.1	[26] 20.1	m	m
2	Accept-Encoding	[26] 20.2	o.1	o.1	[26] 20.2	m	m
3	Accept-Language	[26] 20.3	o.1	o.1	[26] 20.3	m	m
3A	Allow	[26] 20.5	o	o	[26] 20.5	m	m
4	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
8	Supported	[26] 20.37	m	m	[26] 20.37	m	m
o.1	At least one of these capabilities is supported.						

Prerequisite A.5/17 - - REFER response

Prerequisite: A.6/27 - - 420 (Bad Extension)

Table A.116: Supported headers within the REFER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
3	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
7	Supported	[26] 20.37	m	m	[26] 20.37	m	m
8	Unsupported	[26] 20.40	m	m	[26] 20.40	m	m

Prerequisite A.5/17 - - REFER response

Prerequisite: A.6/28 OR A.6/41A - - 421 (Extension Required), 494 (Security Agreement Required)

Table A.116A: Supported headers within the REFER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
2	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
3	Security-Server	[48] 2	x	x	[48] 2	c1	c1
4	Supported	[26] 20.37	m	m	[26] 20.37	m	m
c1:	IF A.4/37 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol.						

Prerequisite A.5/17 - - REFER response

Prerequisite: A.6/34 - - 484 (Address Incomplete)

Table A.117: Supported headers within the REFER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
3	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
7	Supported	[26] 20.37	m	m	[26] 20.37	m	m

Prerequisite A.5/17 - - REFER response

Table A.118: Supported message bodies within the REFER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1							

A.2.1.4.12 REGISTER method

Prerequisite A.5/18 - - REGISTER request

Table A.119: Supported headers within the REGISTER request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Accept	[26] 20.1	o	o	[26] 20.1	m	m
2	Accept-Encoding	[26] 20.2	o	o	[26] 20.2	m	m
3	Accept-Language	[26] 20.3	o	o	[26] 20.3	m	m
3A	Allow	[26] 20.5	o	o	[26] 20.5	m	m
4	Allow-Events	[28] 8.2.2	c1	c1	[28] 8.2.2	c1	c1
5	Authorization	[26] 20.7 [49]	c2	n/a o	[26] 20.7 [49]	m	c22
6	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
7	Call-Info	[26] 20.9	o	o	[26] 20.9	o	o
8	Contact	[26] 20.10	o	o	[26] 20.10	m	m
9	Content-Disposition	[26] 20.11	o	o	[26] 20.11	m	m
10	Content-Encoding	[26] 20.12	o	o	[26] 20.12	m	m
11	Content-Language	[26] 20.13	o	o	[26] 20.13	m	m
12	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
13	Content-Type	[26] 20.15	m	m	[26] 20.15	m	m
14	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
15	Date	[26] 20.17	c3	c3	[26] 20.17	m	m
16	Expires	[26] 20.19	o	o	[26] 20.19	m	m
17	From	[26] 20.20	m	m	[26] 20.20	m	m
18	Max-Forwards	[26] 20.22	em	em	[26] 20.22	n/a	n/a
19	MIME-Version	[26] 20.24	o	o	[26] 20.24	m	m
20	Organization	[26] 20.25	o	o	[26] 20.25	o	o
20A	P-Access-Network-Info	[52] 4.4	c12	c13	[52] 4.4	c12	c14
20B	P-Charging-Function-Addresses	[52] 4.5	c17	c18	[52] 4.5	c17	c18
20C	P-Charging-Vector	[52] 4.6	c15	c16	[52] 4.6	c15	c16
20D	P-Visited-Network-ID	[52] 4.3	x (note 2)	x	[52] 4.3	c10	c11
20E	Path	[35] 4	c4	c5	[35] 4	m	c6
20F	Privacy	[33] 4.2	c9	n/a	[33] 4.2	c9	n/a
21	Proxy-Authorization	[26] 20.28	c8	c8	[26] 20.28	n/a	n/a
22	Proxy-Require	[26] 20.29	o	o (note 1)	[26] 20.29	n/a	n/a
23	Require	[26] 20.32	o	o	[26] 20.32	m	m
24	Route	[26] 20.34	o	n/a	[26] 20.34	n/a	n/a
24A	Security-Client	[48] 2.3.1	c19	c20	[48] 2.3.1	n/a	n/a
24B	Security-Verify	[48] 2.3.1	c20	c20	[48] 2.3.1	c21	n/a
25	Supported	[26] 20.37	o	o	[26] 20.37	m	m
26	Timestamp	[26] 20.38	m	m	[26] 20.38	c7	c7
27	To	[26] 20.39	m	m	[26] 20.39	m	m
28	User-Agent	[26] 20.41	o	o	[26] 20.41	o	o
29	Via	[26] 20.42	m	m	[26] 20.42	m	m

c1:	IF A.4/20 THEN m ELSE n/a - - SIP specific event notification extension.
c2:	IF A.4/8 THEN m ELSE n/a - - authentication between UA and registrar.
c3:	IF A.4/11 THEN o ELSE n/a - - insertion of date in requests and responses.
c4:	IF A.4/24 THEN o ELSE n/a - - session initiation protocol extension header field for registering non-adjacent contacts.
c5:	IF A.4/24 THEN x ELSE n/a - - session initiation protocol extension header field for registering non-adjacent contacts.
c6:	IF (A.3/4) OR A.3/4 THEN m ELSE n/a - - S-CSCF or UE.
c7:	IF A.4/6 THEN m ELSE n/a - - timestamping of requests.
c8:	IF A.4/8A THEN m ELSE n/a - - authentication between UA and proxy.
c9:	IF A.4/26 THEN o ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).
c10:	IF A.4/33 THEN o ELSE n/a - - the P-Visited-Network-ID extension.
c11:	IF A.4/33 THEN m ELSE n/a - - the P-Visited-Network-ID extension.
c12:	IF A.4/34 THEN o ELSE n/a - - the P-Access-Network-Info header extension.
c13:	IF A.4/34 AND (A.3/1 OR A.3/4) THEN m ELSE n/a - - the P-Access-Network-Info header extension and UE or S-CSCF. (NOTE 4)
c14:	IF A.4/34 AND (A.3/4 OR A.3/7A) THEN m ELSE n/a - - the P-Access-Network-Info header extension and S-CSCF or AS acting as terminating UA.
c15:	IF A.4/36 THEN o ELSE n/a - - the P-Charging-Vector header extension.
c16:	IF A.4/36 OR A.3/4 THEN m ELSE n/a - - the P-Charging-Vector header extension (including S-CSCF as registrar).
c17:	IF A.4/35 THEN o ELSE n/a - - the P-Charging-Function-Addresses header extension.
c18:	IF A.4/35 OR A.3/4 THEN m ELSE n/a - - the P-Charging-Function-Addresses header extension (including S-CSCF as registrar).
c19:	IF A.4/37 THEN o ELSE n/a - - security mechanism agreement for the session initiation protocol (note 3).
c20:	IF A.4/37 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol.
c21:	IF A.4/37 AND A.4/2 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol and registrar.
c22:	IF A.3/4 THEN m ELSE A4/8n/a - - S-CSCF UE .

NOTE 1: No distinction has been made in these tables between first use of a request on a From/To/Call-ID combination, and the usage in a subsequent one. Therefore the use of "o" etc. above has been included from a viewpoint of first usage.

NOTE 2: The strength of this requirement in RFC 3455 [52] is SHOULD NOT, rather than MUST NOT.

NOTE 3: Support of this header in this method is dependent on the security mechanism and the security architecture which is implemented.

[NOTE 4: Refere to clause 5.1.1.2 for information on when the UE sets the P-Access-Network-Info header.](#)

Prerequisite A.5/18 - - REGISTER request

Table A.120: Supported message bodies within the REGISTER request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1							

Prerequisite A.5/19 - - REGISTER response

Prerequisite: A.6/1 - - 100 (Trying)

Table A.121: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Call-ID	[26] 20.8	n/a	n/a	[26] 20.8	m	m
2	Content-Length	[26] 20.14	n/a	n/a	[26] 20.14	m	m
3	Cseq	[26] 20.16	n/a	n/a	[26] 20.16	m	m
4	Date	[26] 20.17	n/a	n/a	[26] 20.17	m	m
5	From	[26] 20.20	n/a	n/a	[26] 20.20	m	m
6	To	[26] 20.39	n/a	n/a	[26] 20.39	m	m
7	Via	[26] 20.42	n/a	n/a	[26] 20.42	m	m

Prerequisite A.5/19 - - REGISTER response

Table A.122: Supported headers within the REGISTER response - all status-codes

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
1A	Call-Info	[26] 20.9	o	o	[26] 20.9	o	o
2	Content-Disposition	[26] 20.11	o	o	[26] 20.11	m	m
3	Content-Encoding	[26] 20.12	o	o	[26] 20.12	m	m
4	Content-Language	[26] 20.13	o	o	[26] 20.13	m	m
5	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
6	Content-Type	[26] 20.15	m	m	[26] 20.15	m	m
7	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
8	Date	[26] 20.17	c1	c1	[26] 20.17	m	m
9	From	[26] 20.20	m	m	[26] 20.20	m	m
10	MIME-Version	[26] 20.24	o	o	[26] 20.24	m	m
11	Organization	[26] 20.25	o	o	[26] 20.25	o	o
11A	P-Access-Network-Info	[52] 4.4	c3	n/a	[52] 4.4	c3	n/a
11B	P-Charging-Function-Addresses	[52] 4.5	c6	c7	[52] 4.5	c6	c7
11C	P-Charging-Vector	[52] 4.6	c4	c5	[52] 4.6	c4	c5
11D	Privacy	[33] 4.2	c2	n/a	[33] 4.2	c2	n/a
11E	Require	[26] 20.32	m	m	[26] 20.32	m	m
11F	Server	[26] 20.35	o	o	[26] 20.35	o	o
12	Timestamp	[26] 20.38	c2	c2	[26] 20.38	m	m
13	To	[26] 20.39	m	m	[26] 20.39	m	m
13A	User-Agent	[26] 20.41	o	o	[26] 20.41	o	o
14	Via	[26] 20.42	m	m	[26] 20.42	m	m
15	Warning	[26] 20.43	o (note)	o	[26] 20.43	o	o

c1: IF A.4/11 THEN o ELSE n/a - - insertion of date in requests and responses.
 c2: IF A.4/26 THEN o ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).
 c3: IF A.4/34 THEN o ELSE n/a - - the P-Access-Network-Info header extension.
 c4: IF A.4/36 THEN o ELSE n/a - - the P-Charging-Vector header extension.
 c5: IF A.4/36 OR A.3/4 THEN m ELSE n/a - - the P-Charging-Vector header extension (including S-CSCF as registrar).
 c6: IF A.4/35 THEN o ELSE n/a - - the P-Charging-Function-Addresses header extension.
 c7: IF A.4/35 OR A.3/4 THEN m ELSE n/a - - the P-Charging-Function-Addresses header extension (including S-CSCF as registrar).

NOTE: For a 606 (Not Acceptable Here) response, this status is RECOMMENDED rather than OPTIONAL.

Prerequisite A.5/19 - - REGISTER response

Prerequisite: A.6/6 - - 2xx

Table A.123: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Accept	[26] 20.1	o		[26] 20.1	o	
1A	Accept-Encoding	[26] 20.2	o	o	[26] 20.2	m	m
1B	Accept-Language	[26] 20.3	o	o	[26] 20.3	m	m
2	Allow	[26] 20.5	o	o	[26] 20.5	m	m
3	Authentication-Info	[26] 20.6	c6	c6	[26] 20.6	c7	c7
5	Contact	[26] 20.10	o	o	[26] 20.10	m	m
5A	P-Associated-URI	[52] 4.1	c8	c9	[52] 4.1	c10	c11
6	Path	[35] 4	c3	c3	[35] 4	c4	c4
8	Service-Route	[38] 6	c5	c5	[38] 6	c5	c5
9	Supported	[26] 20.37	m	m	[26] 20.37	m	m
c1:	IF (A.3/4 AND A.4/2) THEN m ELSE n/a - - S-CSCF acting as registrar.						
c2:	IF A.3/4 OR A.3/1 THEN m ELSE n/a - - S-CSCF or UE.						
c3:	IF A.4/24 THEN m ELSE n/a - - session initiation protocol extension header field for registering non-adjacent contacts.						
c4:	IF A.4/24 THEN o ELSE n/a - - session initiation protocol extension header field for registering non-adjacent contacts.						
c5:	IF A.4/28 THEN m ELSE n/a - - session initiation protocol extension header field for service route discovery during registration.						
c6:	IF A.4/8 THEN o ELSE n/a - - authentication between UA and registrar.						
c7:	IF A.4/8 THEN m ELSE n/a - - authentication between UA and registrar.						
c8:	IF A.4/2 AND A.4/31 THEN m ELSE n/a - - P-Associated-URI header extension and registrar.						
c9:	IF A.3/1 AND A.4/31 THEN m ELSE n/a - - P-Associated-URI header extension and S-CSCF.						
c10:	IF A.4/31 THEN o ELSE n/a - - P-Associated-URI header extension.						
c11:	IF A.4/31 AND A.3/1 THEN m ELSE n/a - - P-Associated-URI header extension and UE.						

Prerequisite A.5/19 - - REGISTER response

Prerequisite: A.6/8 OR A.6/9 OR A.6/10 OR A.6/11 OR A.6/12 OR A.6/35 - - 3xx or 485 (Ambiguous)

Table A.124: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
3	Contact	[26] 20.10	o (note)	o	[26] 20.10	m	m
4	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
8	Supported	[26] 20.37	m	m	[26] 20.37	m	m
NOTE: The strength of this requirement is RECOMMENDED rather than OPTIONAL.							

Prerequisite A.5/19 - - REGISTER response

Prerequisite: A.6/14 - - 401 (Unauthorized)

Table A.125: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
3	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
4	Proxy-Authenticate	[26] 20.27	c1	x	[26] 20.27	c1	x
6	Security-Server	[48] 2	x	x	[48] 2	n/a	c2
7	Supported	[26] 20.37	m	m	[26] 20.37	m	m
10	WWW-Authenticate	[26] 20.44	m	m	[26] 20.44	m	m
c1: IF A.5/8 THEN m ELSE n/a - - support of authentication between UA and UA.							
c2: IF A.4/37 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol.							

Prerequisite A.5/19 - - REGISTER response

Prerequisite: A.6/17 OR A.6/23 OR A.6/30 OR A.6/36 OR A.6/42 OR A.6/45 OR A.6/50 OR A.6/51 - - 404, 413, 480, 486, 500, 503, 600, 603

Table A.126: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
3	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
6	Retry-After	[26] 20.33	o	o	[26] 20.33	o	o
8	Supported	[26] 20.37	m	m	[26] 20.37	m	m

Prerequisite A.5/19 - - REGISTER response

Prerequisite: A.6/18 - - 405 (Method Not Allowed)

Table A.127: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
2	Allow	[26] 20.5	m	m	[26] 20.5	m	m
4	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
8	Supported	[26] 20.37	m	m	[26] 20.37	m	m

Prerequisite A.5/19 - - REGISTER response

Prerequisite: A.6/20 - - 407 (Proxy Authentication Required)

Table A.128: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
3	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
5	Proxy-Authenticate	[26] 20.27	c1	x	[26] 20.27	c1	x
8	Supported	[26] 20.37	m	m	[26] 20.37	m	m
9	WWW-Authenticate	[26] 20.44	o	o	[26] 20.44	o	o
c1: IF A.5/8 THEN m ELSE n/a - - support of authentication between UA and UA.							

Prerequisite A.5/19 - - REGISTER response

Prerequisite: A.6/25 - - 415 (Unsupported Media Type)

Table A.129: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Accept	[26] 20.1	o.1	o.1	[26] 20.1	m	m
2	Accept-Encoding	[26] 20.2	o.1	o.1	[26] 20.2	m	m
3	Accept-Language	[26] 20.3	o.1	o.1	[26] 20.3	m	m
4	Allow	[26] 20.5	o	o	[26] 20.5	m	m
5	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
9	Supported	[26] 20.37	m	m	[26] 20.37	m	m
o.1	At least one of these capabilities is supported.						

Prerequisite A.5/19 - - REGISTER response

Prerequisite: A.6/27 - - 420 (Bad Extension)

Table A.130: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
3	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
7	Supported	[26] 20.37	m	m	[26] 20.37	m	m
8	Unsupported	[26] 20.40	m	m	[26] 20.40	m	m

Prerequisite A.5/19 - - REGISTER response

Prerequisite: A.6/28 OR A.6/41A - - 421 (Extension Required), 494 (Security Agreement Required)

Table A.130A: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
2	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
3	Security-Server	[48] 2	c2	c2	[48] 2	c1	c1
4	Supported	[26] 20.37	m	m	[26] 20.37	m	m
c1:	IF A.4/37 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol.						
c2:	IF A.4/37 AND A.4/2 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol and registrar.						

Prerequisite A.5/19 - - REGISTER response

Prerequisite: A.6/29 - - 423 (Interval Too Brief)

Table A.131: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
3	Error-Info	[26] 20.18	o		[26] 20.18	o	
5	Min-Expires	[26] 20.23	m	m	[26] 20.23	m	m
8	Supported	[26] 20.37	m	m	[26] 20.37	m	m

Prerequisite A.5/19 - - REGISTER response

Prerequisite: A.6/34 - - 484 (Address Incomplete)

Table A.132: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
3	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
7	Supported	[26] 20.37	m	m	[26] 20.37	m	m

Prerequisite A.5/19 - - REGISTER response

Table A.133: Supported message bodies within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1							

A.2.1.4.13 SUBSCRIBE method

Prerequisite A.5/20 - - SUBSCRIBE request

Table A.134: Supported headers within the SUBSCRIBE request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Accept	[26] 20.1	o	o	[26] 20.1	m	m
2	Accept-Encoding	[26] 20.2	o	o	[26] 20.2	m	m
3	Accept-Language	[26] 20.3	o	o	[26] 20.3	m	m
3A	Allow	[26] 20.5	o	o	[26] 20.5	m	m
4	Allow-Events	[28] 8.2.2	c1	c1	[28] 8.2.2	c2	c2
5	Authorization	[26] 20.7	c3	c3	[26] 20.7	c3	c3
6	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
6A	Contact	[26] 20.10	m	m	[26] 20.10	m	m
7	Content-Disposition	[26] 20.11	o	o	[26] 20.11	m	m
8	Content-Encoding	[26] 20.12	o	o	[26] 20.12	m	m
9	Content-Language	[26] 20.13	o	o	[26] 20.13	m	m
10	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
11	Content-Type	[26] 20.15	m	m	[26] 20.15	m	m
12	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
13	Date	[26] 20.17	c4	c4	[26] 20.17	m	m
14	Event	[28] 78.2.1	m	m	[28] 8.2.1	m	m
15	Expires	[26] 20.19	o (note 1)	o (note 1)	[26] 20.19	m	m
16	From	[26] 20.20	m	m	[26] 20.20	m	m
17	Max-Forwards	[26] 20.22	em	em	[26] 20.22	n/a	n/a
18	MIME-Version	[26] 20.24	o	o	[26] 20.24	m	m
18A	Organization	[26] 20.25	o	o	[26] 20.25	o	o
18B	P-Access-Network-Info	[52] 4.4	c12	c13	[52] 4.4	c12	c14
18C	P-Asserted-Identity	[34] 9.1	n/a	n/a	[34] 9.1	c6	c6
18D	P-Called-Party-ID	[52] 4.2	x	x	[52] 4.2	c10	c10
18E	P-Charging-Function-Addresses	[52] 4.5	c17	c18	[52] 4.5	c17	c18
18F	P-Charging-Vector	[52] 4.6	c15	c16	[52] 4.6	c15	c16
18G	P-Preferred-Identity	[34] 9.2	c6	c7	[34] 9.2	n/a	n/a
18H	P-Visited-Network-ID	[52] 4.3	x (note 2)	x	[52] 4.3	c11	n/a
18I	Privacy	[33] 4.2	c9	c9	[33] 4.2	c9	c9
19	Proxy-Authorization	[26] 20.28	c5	c5	[26] 20.28	n/a	n/a
20	Proxy-Require	[26] 20.29	o	n/a	[26] 20.29	n/a	n/a
21	Record-Route	[26] 20.30	n/a	n/a	[26] 20.30	m	m
22	Require	[26] 20.32	o	o	[26] 20.32	m	m
23	Route	[26] 20.34	m	m	[26] 20.34	n/a	n/a
23A	Security-Client	[48] 2.3.1	c19	c19	[48] 2.3.1	n/a	n/a
23B	Security-Verify	[48] 2.3.1	c20	c20	[48] 2.3.1	n/a	n/a
24	Supported	[26] 20.37	o	o	[26] 20.37	m	m
25	Timestamp	[26] 20.38	c8	c8	[26] 20.38	m	m
26	To	[26] 20.39	m	m	[26] 20.39	m	m
27	User-Agent	[26] 20.41	o	o	[26] 20.41	o	o
28	Via	[26] 20.42	m	m	[26] 20.42	m	m

c1:	IF A.4/20 THEN o ELSE n/a - - SIP specific event notification extension.
c2:	IF A.4/20 THEN m ELSE n/a - - SIP specific event notification extension.
c3:	IF A.4/7 THEN m ELSE n/a - - authentication between UA and UA.
c4:	IF A.4/11 THEN o ELSE n/a - - insertion of date in requests and responses.
c5:	IF A.4/8A THEN m ELSE n/a - - authentication between UA and proxy.
c6:	IF A.4/25 THEN o ELSE n/a - - private extensions to the Session Initiation Protocol (SIP) for asserted identity within trusted networks.
c7:	IF A.3/1 AND A.4/25 THEN o ELSE n/a - - UE and private extensions to the Session Initiation Protocol (SIP) for asserted identity within trusted networks.
c8:	IF A.4/6 THEN o ELSE n/a - - timestamping of requests.
c9:	IF A.4/26 THEN o ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).
c10:	IF A.4/32 THEN o ELSE n/a - - the P-Called-Party-ID extension.
c11:	IF A.4/33 THEN o ELSE n/a - - the P-Visited-Network-ID extension.
c12:	IF A.4/34 THEN o ELSE n/a - - the P-Access-Network-Info header extension.
c13:	IF A.4/34 AND A.3/1 THEN m ELSE n/a - - the P-Access-Network-Info header extension and UE.
c14:	IF A.4/34 AND (A.3/7A OR A.3/7D) THEN m ELSE n/a - - the P-Access-Network-Info header extension and AS acting as terminating UA or AS acting as third-party call controller.
c15:	IF A.4/36 THEN o ELSE n/a - - the P-Charging-Vector header extension.
c16:	IF A.4/36 THEN m ELSE n/a - - the P-Charging-Vector header extension.
c17:	IF A.4/35 THEN o ELSE n/a - - the P-Charging-Function-Addresses header extension.
c18:	IF A.4/35 THEN m ELSE n/a - - the P-Charging-Function-Addresses header extension.
c19:	IF A.4/37 THEN o ELSE n/a - - security mechanism agreement for the session initiation protocol (note 3).
c20:	IF A.4/37 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol.

NOTE 1: The strength of this requirement is RECOMMENDED rather than OPTIONAL.
 NOTE 2: The strength of this requirement in RFC 3455 [52] is SHOULD NOT, rather than MUST NOT.
 NOTE 3: Support of this header in this method is dependent on the security mechanism and the security architecture which is implemented. Use of this header in this method is not appropriate to the security mechanism defined by 3GPP TS 33.203 [19].

Prerequisite A.5/20 - - SUBSCRIBE request

Table A.135: Supported message bodies within the SUBSCRIBE request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1							

Prerequisite A.5/21 - - SUBSCRIBE response

Table A.136: Supported headers within the SUBSCRIBE response - all status-codes

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
2	Content-Disposition	[26] 20.11	o	o	[26] 20.11	m	m
3	Content-Encoding	[26] 20.12	o	o	[26] 20.12	m	m
4	Content-Language	[26] 20.13	o	o	[26] 20.13	m	m
5	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
6	Content-Type	[26] 20.15	m	m	[26] 20.15	m	m
7	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
8	Date	[26] 20.17	c1	c1	[26] 20.17	m	m
9	From	[26] 20.20	m	m	[26] 20.20	m	m
10	MIME-Version	[26] 20.24	o	o	[26] 20.24	m	m
10A	Organization	[26] 20.25	o	o	[26] 20.25	o	o
10B	P-Access-Network-Info	[52] 4.4	c5	c6	[52] 4.4	c5	c7
10C	P-Asserted-Identity	[34] 9.1	n/a	n/a	[34] 9.1	c3	c3
10D	P-Charging-Function-Addresses	[52] 4.5	c10	c11	[52] 4.5	c10	c11
10E	P-Charging-Vector	[52] 4.6	c8	c9	[52] 4.6	c8	c9
10F	P-Preferred-Identity	[34] 9.2	c3	x	[34] 9.2	n/a	n/a
10G	Privacy	[33] 4.2	c4	c4	[33] 4.2	c4	c4
10H	Require	[26] 20.32	m	m	[26] 20.32	m	m
10I	Server	[26] 20.35	o	o	[26] 20.35	o	o
11	Timestamp	[26] 20.38	m	m	[26] 20.38	c2	c2
12	To	[26] 20.39	m	m	[26] 20.39	m	m
12A	User-Agent	[26] 20.41	o	o	[26] 20.41	o	o
13	Via	[26] 20.42	m	m	[26] 20.42	m	m
14	Warning	[26] 20.43	o (note)	o	[26] 20.43	o	o
c1:	IF A.4/11 THEN o ELSE n/a - - insertion of date in requests and responses.						
c2:	IF A.4/6 THEN m ELSE n/a - - timestamping of requests.						
c3:	IF A.4/25 THEN o ELSE n/a - - private extensions to the Session Initiation Protocol (SIP) for asserted identity within trusted networks.						
c4:	IF A.4/26 THEN o ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).						
c5:	IF A.4/34 THEN o ELSE n/a - - the P-Access-Network-Info header extension.						
c6:	IF A.4/34 AND A.3/1 THEN m ELSE n/a - - the P-Access-Network-Info header extension and UE.						
c7:	IF A.4/34 AND (A.3/7A OR A.3/7D) THEN m ELSE n/a - - the P-Access-Network-Info header extension and AS acting as terminating UA or AS acting as third-party call controller.						
c8:	IF A.4/36 THEN o ELSE n/a - - the P-Charging-Vector header extension.						
c9:	IF A.4/36 THEN m ELSE n/a - - the P-Charging-Vector header extension.						
c10:	IF A.4/35 THEN o ELSE n/a - - the P-Charging-Function-Addresses header extension.						
c11:	IF A.4/35 THEN m ELSE n/a - - the P-Charging-Function-Addresses header extension.						
NOTE:	For a 606 (Not Acceptable Here) response, this status is RECOMMENDED rather than OPTIONAL.						

Prerequisite A.5/21 - - SUBSCRIBE response

Prerequisite: A.6/6 and A.6/7 - - 2xx

Table A.137: Supported headers within the SUBSCRIBE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	o	o	[26] 20.5	m	m
1	Authentication-Info	[26] 20.6	c1	c1	[26] 20.6	c2	c2
1A	Contact	[26] 20.10	m	m	[26] 20.10	m	m
2	Expires	[26] 20.19	m	m	[26] 20.19	m	m
4	Require	[26] 20.32	m	m	[26] 20.32	m	m
6	Supported	[26] 20.37	m	m	[26] 20.37	m	m
c1:	IF A.4/7 THEN o ELSE n/a - - authentication between UA and UA.						
c2:	IF A.4/7 THEN m ELSE n/a - - authentication between UA and UA.						

Prerequisite A.5/21 - - SUBSCRIBE response

Prerequisite: A.6/8 OR A.6/9 OR A.6/10 OR A.6/11 OR A.6/12 OR A.6/35 - - 3xx or 485 (Ambiguous)

Table A.138: Supported headers within the SUBSCRIBE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	o	o	[26] 20.5	m	m
1	Contact	[26] 20.10	m (note)	m	[26] 20.10	m	m
2	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
5	Supported	[26] 20.37	m	m	[26] 20.37	m	m

NOTE: The strength of this requirement is RECOMMENDED rather than MANDATORY for a 485 response.

Prerequisite A.5/21 - - SUBSCRIBE response

Prerequisite: A.6/14 - - 401 (Unauthorized)

Table A.139: Supported headers within the SUBSCRIBE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	o	o	[26] 20.5	m	m
1	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
2	Proxy-Authenticate	[26] 20.27	c1	c1	[26] 20.27	c1	c1
5	Supported	[26] 20.37	m	m	[26] 20.37	m	m
8	WWW-Authenticate	[26] 20.44	m	m	[26] 20.44	m	m
c1:	IF A.5/7 THEN m ELSE n/a - - support of authentication between UA and UA.						

Prerequisite A.5/21 - - SUBSCRIBE response

Prerequisite: A.6/17 OR A.6/23 OR A.6/30 OR A.6/36 OR A.6/42 OR A.6/50 OR A.6/51 - - 404, 413, 480, 486, 500, 600, 603

Table A.140: Supported headers within the SUBSCRIBE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	o	o	[26] 20.5	m	m
1	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
3	Retry-After	[26] 20.33	o		[26] 20.33	o	
5	Supported	[26] 20.37	m	m	[26] 20.37	m	m

Prerequisite A.5/21 - - SUBSCRIBE response

Prerequisite: A.6/18 - - 405 (Method Not Allowed)

Table A.141: Supported headers within the SUBSCRIBE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	m	m
2	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
5	Supported	[26] 20.37	m	m	[26] 20.37	m	m

Prerequisite A.5/21 - - SUBSCRIBE response

Prerequisite: A.6/20 - - 407 (Proxy Authentication Required)

Table A.142: Supported headers within the SUBSCRIBE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	o	o	[26] 20.5	m	m
1	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
2	Proxy-Authenticate	[26] 20.27	c1	c1	[26] 20.27	c1	c1
5	Supported	[26] 20.37	m	m	[26] 20.37	m	m
6	WWW-Authenticate	[26] 20.44	o	o	[26] 20.44	o	o
c1:	IF A.5/7 THEN m ELSE n/a - - support of authentication between UA and UA.						

Prerequisite A.5/21 - - SUBSCRIBE response

Prerequisite A.6/25 - - 415 (Unsupported Media Type)

Table A.143: Supported headers within the SUBSCRIBE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Accept	[26] 20.1	o.1	o.1	[26] 20.1	m	m
2	Accept-Encoding	[26] 20.2	o.1	o.1	[26] 20.2	m	m
3	Accept-Language	[26] 20.3	o.1	o.1	[26] 20.3	m	m
4	Allow	[26] 20.5	o	o	[26] 20.5	m	m
6	Server	[26] 20.35	o	o	[26] 20.35	o	o
7	Supported	[26] 20.37	m	m	[26] 20.37	m	m
o.1	At least one of these capabilities is supported.						

Prerequisite A.5/21 - - SUBSCRIBE response

Prerequisite: A.6/27 - - 420 (Bad Extension)

Table A.144: Supported headers within the SUBSCRIBE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	o	o	[26] 20.5	m	m
1	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
4	Supported	[26] 20.37	m	m	[26] 20.37	m	m
5	Unsupported	[26] 20.40	m	m	[26] 20.40	m	m

Prerequisite A.5/21 - - SUBSCRIBE response

Prerequisite: A.6/28 OR A.6/41A - - 421 (Extension Required), 494 (Security Agreement Required)

Table A.144A: Supported headers within the SUBSCRIBE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
2	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
3	Security-Server	[48] 2	x	x	[48] 2	c1	c1
4	Supported	[26] 20.37	m	m	[26] 20.37	m	m
c1:	IF A.4/37 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol.						

Prerequisite A.5/21 - - SUBSCRIBE response

Prerequisite: A.6/29 - - 423 (Interval Too Brief)

Table A.145: Supported headers within the SUBSCRIBE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	o	o	[26] 20.5	m	m
1	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
2	Min-Expires	[26] 20.23	m	m	[26] 20.23	m	m
5	Supported	[26] 20.37	m	m	[26] 20.37	m	m

Prerequisite A.5/21 - - SUBSCRIBE response

Prerequisite: A.6/34 - - 484 (Address Incomplete)

Table A.146: Supported headers within the SUBSCRIBE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	o	o	[26] 20.5	m	m
1	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
4	Supported	[26] 20.37	m	m	[26] 20.37	m	m

Prerequisite A.5/21 - - SUBSCRIBE response

Prerequisite: A.6/39 - - 489 (Bad Event)

Table A.147: Supported headers within the SUBSCRIBE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	o	o	[26] 20.5	m	m
1	Allow-Events	[28] 8.2.2	m	m	[28] 8.2.2	m	m
3	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o

Prerequisite A.5/21 - - SUBSCRIBE response

Prerequisite: A.6/45 - - 503 (Service Unavailable)

Table A.148: Supported headers within the SUBSCRIBE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	o	o	[26] 20.5	m	m
1	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
3	Retry-After	[26] 20.33	o	o	[26] 20.33	o	m
5	Supported	[26] 20.37	m	m	[26] 20.37	m	m

Prerequisite A.5/21 - - SUBSCRIBE response

Table A.149: Supported message bodies within the SUBSCRIBE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1							

A.2.1.4.14 UPDATE method

Prerequisite A.5/22 - - UPDATE request

Table A.150: Supported headers within the UPDATE request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Accept	[26] 20.1	o	o	[26] 20.1	m	m
2	Accept-Encoding	[26] 20.2	o	o	[26] 20.2	m	m
3	Accept-Language	[26] 20.3	o	o	[26] 20.3	m	m
4	Allow	[26] 20.5	o	o	[26] 20.5	m	m
5	Allow-Events	[28] 8.2.2	c2	c2	[28] 8.2.2	c3	c3
6	Authorization	[26] 20.7	c4	c4	[26] 20.7	c4	c4
7	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
8	Call-Info	[26] 20.9	o	o	[26] 20.9	o	o
9	Contact	[26] 20.10	m	m	[26] 20.10	m	m
10	Content-Disposition	[26] 20.11	o	o	[26] 20.11	m	m
11	Content-Encoding	[26] 20.12	o	o	[26] 20.12	m	m
12	Content-Language	[26] 20.13	o	o	[26] 20.13	m	m
13	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
14	Content-Type	[26] 20.15	m	m	[26] 20.15	m	m
15	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
16	Date	[26] 20.17	c5	c5	[26] 20.17	m	m
17	From	[26] 20.20	m	m	[26] 20.20	m	m
18	Max-Forwards	[26] 20.22	em	em	[26] 20.22	n/a	n/a
19	MIME-Version	[26] 20.24	o	o	[26] 20.24	m	m
20	Organization	[26] 20.25	o	o	[26] 20.25	o	o
20A	P-Access-Network-Info	[52] 4.4	c11	c12	[52] 4.4	c11	c13
20B	P-Charging-Function-Addresses	[52] 4.5	c16	c17	[52] 4.5	c16	c17
20C	P-Charging-Vector	[52] 4.6	c14	c15	[52] 4.6	c14	c15
20D	Privacy	[33] 4.2	c6	n/a	[33] 4.2	c6	n/a
21	Proxy-Authorization	[26] 20.28	c10	c10	[26] 20.28	n/a	n/a
22	Proxy-Require	[26] 20.29	o	n/a	[26] 20.29	n/a	n/a
23	Record-Route	[26] 20.30	n/a	n/a	[26] 20.30	n/a	n/a
24	Require	[26] 20.32	o	o	[26] 20.32	m	m
25	Route	[26] 20.34	m	m	[26] 20.34	n/a	n/a
25A	Security-Client	[48] 2.3.1	c18	c18	[48] 2.3.1	n/a	n/a
25B	Security-Verify	[48] 2.3.1	c19	c19	[48] 2.3.1	n/a	n/a
26	Supported	[26] 20.37	o	o	[26] 20.37	m	m
27	Timestamp	[26] 20.38	c9	c9	[26] 20.38	m	m
28	To	[26] 20.39	m	m	[26] 20.39	m	m
29	User-Agent	[26] 20.41	o	o	[26] 20.41	o	o
30	Via	[26] 20.42	m	m	[26] 20.42	m	m
c2:	IF A.4/20 THEN o ELSE n/a - - SIP specific event notification extension.						
c3:	IF A.4/20 THEN m ELSE n/a - - SIP specific event notification extension.						
c4:	IF A.4/7 THEN m ELSE n/a - - authentication between UA and UA.						
c5:	IF A.4/11 THEN o ELSE n/a - - insertion of date in requests and responses.						
c6:	IF A.4/26 THEN o ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).						
c9:	IF A.4/6 THEN o ELSE n/a - - timestamping of requests.						
c10:	IF A.4/8A THEN m ELSE n/a - - authentication between UA and proxy.						
c11:	IF A.4/34 THEN o ELSE n/a - - the P-Access-Network-Info header extension.						
c12:	IF A.4/34 AND A.3/1 THEN m ELSE n/a - - the P-Access-Network-Info header extension and UE.						
c13:	IF A.4/34 AND (A.3/7A OR A.3/7D) THEN m ELSE n/a - - the P-Access-Network-Info header extension and AS acting as terminating UA or AS acting as third-party call controller.						
c14:	IF A.4/36 THEN o ELSE n/a - - the P-Charging-Vector header extension.						
c15:	IF A.4/36 THEN m ELSE n/a - - the P-Charging-Vector header extension.						
c16:	IF A.4/35 THEN o ELSE n/a - - the P-Charging-Function-Addresses header extension.						
c17:	IF A.4/35 THEN m ELSE n/a - - the P-Charging-Function-Addresses header extension.						
c18:	IF A.4/37 THEN o ELSE n/a - - security mechanism agreement for the session initiation protocol (note).						
c19:	IF A.4/37 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol.						
NOTE:	Support of this header in this method is dependent on the security mechanism and the security architecture which is implemented. Use of this header in this method is not appropriate to the security mechanism defined by 3GPP TS 33.203 [19].						

Prerequisite A.5/22 - - UPDATE request

Table A.151: Supported message bodies within the UPDATE request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1							

Prerequisite A.5/23 - - UPDATE response

Table A.152: Supported headers within the UPDATE response - all remaining status-codes

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
1A	Call-Info	[26] 20.9	o	o	[26] 20.9	o	o
2	Content-Disposition	[26] 20.11	o	o	[26] 20.11	m	m
3	Content-Encoding	[26] 20.12	o	o	[26] 20.12	m	m
4	Content-Language	[26] 20.13	o	o	[26] 20.13	m	m
5	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
6	Content-Type	[26] 20.15	m	m	[26] 20.15	m	m
7	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
8	Date	[26] 20.17	c1	c1	[26] 20.17	m	m
9	From	[26] 20.20	m	m	[26] 20.20	m	m
10	MIME-Version	[26] 20.24	o	o	[26] 20.24	m	m
10A	Organization	[26] 20.25	o	o	[26] 20.25	o	o
10B	P-Access-Network-Info	[52] 4.4	c4	c5	[52] 4.4	c4	c6
10C	P-Charging-Function-Addresses	[52] 4.5	c9	c10	[52] 4.5	c9	c10
10D	P-Charging-Vector	[52] 4.6	c7	c8	[52] 4.6	c7	c8
10E	Privacy	[33] 4.2	c3	n/a	[33] 4.2	c3	n/a
10F	Require	[26] 20.31	m	m	[26] 20.31	m	m
10G	Server	[26] 20.35	o	o	[26] 20.35	o	o
11	Timestamp	[26] 20.38	m	m	[26] 20.38	c2	c2
12	To	[26] 20.39	m	m	[26] 20.39	m	m
12A	User-Agent	[26] 20.41	o	o	[26] 20.41	o	o
13	Via	[26] 20.42	m	m	[26] 20.42	m	m
14	Warning	[26] 20.43	o (note)	o	[26] 20.43	o	o
c1:	IF A.4/11 THEN o ELSE n/a - - insertion of date in requests and responses.						
c2:	IF A.4/6 THEN m ELSE n/a - - timestamping of requests.						
c3:	IF A.4/26 THEN o ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).						
c4:	IF A.4/34 THEN o ELSE n/a - - the P-Access-Network-Info header extension.						
c5:	IF A.4/34 AND A.3/1 THEN m ELSE n/a - - the P-Access-Network-Info header extension and UE.						
c6:	IF A.4/34 AND (A.3/7A OR A.3/7D) THEN m ELSE n/a - - the P-Access-Network-Info header extension and AS acting as terminating UA or AS acting as third-party call controller.						
c7:	IF A.4/36 THEN o ELSE n/a - - the P-Charging-Vector header extension.						
c8:	IF A.4/36 THEN m ELSE n/a - - the P-Charging-Vector header extension.						
c9:	IF A.4/35 THEN o ELSE n/a - - the P-Charging-Function-Addresses header extension.						
c10:	IF A.4/35 THEN m ELSE n/a - - the P-Charging-Function-Addresses header extension.						
NOTE:	For a 606 (Not Acceptable Here) response, this status is RECOMMENDED rather than OPTIONAL.						

Prerequisite A.5/23 - - UPDATE response

Prerequisite: A.6/6 - - 2xx

Table A.153: Supported headers within the UPDATE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Accept	[26] 20.1	o	o	[26] 20.1	m	m
0B	Accept-Encoding	[26] 20.2	o	o	[26] 20.2	m	m
0C	Accept-Language	[26] 20.3	o	o	[26] 20.3	m	m
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
2	Authentication-Info	[26] 20.6	c1	c1	[26] 20.6	c2	c2
3	Contact	[26] 20.10	m	m	[26] 20.10	m	m
6	Supported	[26] 20.37	m	m	[26] 20.37	m	m
c1:	IF A.4/7 THEN o ELSE n/a - - authentication between UA and UA.						
c2:	IF A.4/7 THEN m ELSE n/a - - authentication between UA and UA.						

Prerequisite A.5/23 - - UPDATE response

Prerequisite: A.6/8 OR A.6/9 OR A.6/10 OR A.6/11 OR A.6/12 - - 3xx

Table A.154: Supported headers within the UPDATE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
2	Contact	[26] 20.10	o	o	[26] 20.10	o	o
3	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
7	Supported	[26] 20.37	m	m	[26] 20.37	m	m

Prerequisite A.5/23 - - UPDATE response

Prerequisite: A.6/14 - - 401 (Unauthorized)

Table A.154A: Supported headers within the UPDATE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
2	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
3	Proxy-Authenticate	[26] 20.27	o		[26] 20.27	o	
5	Supported	[26] 20.37	m	m	[26] 20.37	m	m
6	WWW-Authenticate	[26] 20.44	m	m	[26] 20.44	m	m
c1:	IF A.5/7 THEN m ELSE n/a - - support of authentication between UA and UA.						

Prerequisite A.5/23 - - UPDATE response

Prerequisite: A.6/17 OR A.6/23 OR A.6/30 OR A.6/36 OR A.6/42 OR A.6/45 OR A.6/50 OR A.6/51 - - 404, 413, 480, 486, 500, 503, 600, 603

Table A.155: Supported headers within the UPDATE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
2	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
5	Retry-After	[26] 20.33	o	o	[26] 20.33	o	o
7	Supported	[26] 20.37	m	m	[26] 20.37	m	m

Prerequisite A.5/23 - - UPDATE response

Prerequisite: A.6/18 - - 405 (Method Not Allowed)

Table A.156: Supported headers within the UPDATE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	m	m
3	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
7	Supported	[26] 20.37	m	m	[26] 20.37	m	m

Prerequisite A.5/23 - - UPDATE response

Prerequisite: A.6/20 - - 407 (Proxy Authentication Required)

Table A.157: Supported headers within the UPDATE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
2	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
4	Proxy-Authenticate	[26] 20.27	c1	c1	[26] 20.27	c1	c1
7	Supported	[26] 20.37	m	m	[26] 20.37	m	m
8	WWW-Authenticate	[26] 20.44	o	o	[26] 20.44	o	o
c1:	IF A.5/7 THEN m ELSE n/a - - support of authentication between UA and UA.						

Prerequisite A.5/23 - - UPDATE response

Prerequisite: A.6/25 - - 415 (Unsupported Media Type)

Table A.158: Supported headers within the UPDATE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Accept	[26] 20.1	o.1	o.1	[26] 20.1	m	m
2	Accept-Encoding	[26] 20.2	o.1	o.1	[26] 20.2	m	m
3	Accept-Language	[26] 20.3	o.1	o.1	[26] 20.3	m	m
4	Allow	[26] 20.5	o	o	[26] 20.5	m	m
6	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
10	Supported	[26] 20.37	m	m	[26] 20.37	m	m
o.1	At least one of these capabilities is supported.						

Prerequisite A.5/23 - - UPDATE response

Prerequisite: A.6/27 - - 420 (Bad Extension)

Table A.159: Supported headers within the UPDATE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
2	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
6	Supported	[26] 20.37	m	m	[26] 20.37	m	m
7	Unsupported	[26] 20.40	m	m	[26] 20.40	m	m

Prerequisite A.5/23 - - UPDATE response

Prerequisite: A.6/28 OR A.6/41A - - 421 (Extension Required), 494 (Security Agreement Required)

Table A.159A: Supported headers within the UPDATE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
2	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
3	Security-Server	[48] 2	x	x	[48] 2	c1	c1
4	Supported	[26] 20.37	m	m	[26] 20.37	m	m
c1:	IF A.4/37 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol.						

Prerequisite A.5/23 - - UPDATE response

Prerequisite: A.6/35 - - 485 (Ambiguous)

Table A.160: Supported headers within the UPDATE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
2	Contact	[26] 20.10	o (note)	o	[26] 20.10	m	m
3	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
7	Supported	[26] 20.37	m	m	[26] 20.37	m	m

NOTE: The strength of this requirement is RECOMMENDED rather than OPTIONAL.

Prerequisite A.5/23 - - UPDATE response

Table A.161: Supported message bodies within the UPDATE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1							

A.2.2 Proxy role

A.2.2.1 Introduction

This subclause contains the ICS proforma tables related to the proxy role. They need to be completed only for proxy implementations.

Prerequisite: A.2/2 - - proxy role

A.2.2.2 Major capabilities

Table A.162: Major capabilities

Item	Does the implementation support Capabilities within main protocol	Reference	RFC status	Profile status
3	initiate session release?	[26] 16	x	c27
4	stateless proxy behaviour?	[26] 16.11	o.1	c28
5	stateful proxy behaviour?	[26] 16.2	o.1	c29
6	forking of initial requests?	[26] 16.1	c1	x
7	support of TLS connections on the upstream side?	[26] 16.7	o	n/a
8	support of TLS connections on the downstream side?	[26] 16.7	o	n/a
8A	authentication between UA and proxy?	[26] 20.28, 22.3	o	x
9	insertion of date in requests and responses?	[26] 20.17	o	o
10	suppression or modification of alerting information data?	[26] 20.4	o	o
11	reading the contents of the Require header before proxying the request or response?	[26] 20.32	o	o
12	adding or modifying the contents of the Require header before proxying the REGISTER request or response	[26] 20.32	o	m
13	adding or modifying the contents of the Require header before proxying the request or response for methods other than REGISTER?	[26] 20.32	o	o
14	being able to insert itself in the subsequent transactions in a dialog (record-routing)?	[26] 16.6	o	c2
15	the requirement to be able to use separate URIs in the upstream direction and downstream direction when record routeing?	[26] 16.7	c3	c3
16	reading the contents of the Supported header before proxying the response?	[26] 20.37	o	o
17	reading the contents of the Unsupported header before proxying the 420 response to a REGISTER?	[26] 20.40	o	m
18	reading the contents of the Unsupported header before proxying the 420 response to a method other than REGISTER?	[26] 20.40	o	o
19	the inclusion of the Error-Info header in 3xx - 6xx responses?	[26] 20.18	o	o
19A	reading the contents of the Organization header before proxying the request or response?	[26] 20.25	o	o
19B	adding or concatenating the Organization header before proxying the request or response?	[26] 20.25	o	o
19C	reading the contents of the Call-Info header before proxying the request or response?	[26] 20.25	o	o
19D	adding or concatenating the Call-Info header before proxying the request or response?	[26] 20.25	o	o
19E	delete Contact headers from 3xx responses prior to relaying the response?	[26] 20	o	o
	Extensions			
20	the SIP INFO method?	[25]	o	o
21	reliability of provisional responses in	[27]	o	i

	SIP?			
22	the REFER method?	[36]	o	o
23	integration of resource management and SIP?	[30]	o	i
24	the SIP UPDATE method?	[29]	c4	i
26	SIP extensions for media authorization?	[31]	o	c7
27	SIP specific event notification	[28]	o	i
28	the use of NOTIFY to establish a dialog	[28] 4.2	o	n/a
29	Session Initiation Protocol Extension Header Field for Registering Non-Adjacent Contacts	[35]	o	c6
30	extensions to the Session Initiation Protocol (SIP) for asserted identity within trusted networks	[34]	o	m
30A	act as first entity within the trust domain for asserted identity	[34]	c5	c8
30B	act as subsequent entity within trust network that can route outside the trust network	[34]	c5	c9
31	a privacy mechanism for the Session Initiation Protocol (SIP)	[33]	o	m
31A	request of privacy by the inclusion of a Privacy header	[33]	n/a	
31B	application of privacy based on the received Privacy header	[33]	c10	
31C	passing on of the Privacy header transparently	[33]	c10	
31D	application of the privacy option "header" such that those headers which cannot be completely expunged of identifying information without the assistance of intermediaries are obscured?	[33] 5.1	x	
31E	application of the privacy option "session" such that anonymization for the session(s) initiated by this message occurs?	[33] 5.2	n/a	n/a
31F	application of the privacy option "user" such that user level privacy functions are provided by the network?	[33] 5.3	n/a	n/a
31G	application of the privacy option "id" such that privacy of the network asserted identity is provided by the network?	[34] 7	c11	c12
32	Session Initiation Protocol Extension Header Field for Service Route Discovery During Registration	[38]	o	c30
33	a messaging mechanism for the Session Initiation Protocol (SIP)	[50]	o	m
34	Compressing the Session Initiation Protocol	[55]	o	c7
35	private header extensions to the session initiation protocol for the 3rd-Generation Partnership Project (3GPP)?	[52]	o	m
36	the P-Associated-URI header extension?	[52] 4.1	c14	c15
37	the P-Called-Party-ID header extension?	[52] 4.2	c14	c16
38	the P-Visited-Network-ID header extension?	[52] 4.3	c14	c17
39	reading, or deleting the P-Visited-Network-ID header before proxying the request or response?	[52] 4.3	c18	n/a
41	the P-Access-Network-Info header extension?	[52] 4.4	c14	c19
42	act as first entity within the trust domain	[52] 4.4	c20	c21

	for access network information?			
43	act as subsequent entity within trust network for access network information that can route outside the trust network?	[52] 4.4	c20	c22
44	the P-Charging-Function-Addresses header extension?	[52] 4.5	c14	m
44A	adding, deleting or reading the P-Charging-Function-Addresses header before proxying the request or response?	[52] 4.6	c25	c26
45	the P-Charging-Vector header extension?	[52] 4.6	c14	m
46	adding, deleting, reading or modifying the P-Charging-Vector header before proxying the request or response?	[52] 4.6	c23	c24
47	security mechanism agreement for the session initiation protocol?	[48]	o	c7

c1:	IF A.162/5 THEN o ELSE n/a - - stateful proxy behaviour.
c2:	IF A.3/2 OR A.3/3A OR A.3/4 THEN m ELSE o - - P-CSCF, I-CSCF(THIG) or S-CSCF.
c3:	IF (A.162/7 AND NOT A.162/8) OR (NOT A.162/7 AND A.162/8) THEN m ELSE IF A.162/14 THEN o ELSE n/a - - TLS interworking with non-TLS else proxy insertion.
c4:	IF A.162/23 THEN m ELSE o - - integration of resource management and SIP.
c5:	IF A.162/30 THEN o ELSE n/a - - extensions to the Session Initiation Protocol (SIP) for asserted identity within trusted networks.
c6:	IF A.3/2 OR A.3/3A THEN m ELSE n/a - - P-CSCF or I-CSCF (THIG).
c7:	IF A.3/2 THEN m ELSE n/a - - P-CSCF.
c8:	IF A.3/2 AND A.162/30 THEN m ELSE n/a - - P-CSCF and extensions to the Session Initiation Protocol (SIP) for asserted identity within trusted networks.
c9:	
c10:	IF A.162/31 THEN o.2 ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).
c11:	IF A.162/31B THEN o ELSE x - - application of privacy based on the received Privacy header.
c12:	
c13:	
c14:	IF A.162/35 THEN o.3 ELSE n/a - - private header extensions to the session initiation protocol for the 3rd-Generation Partnership Project (3GPP).
c15:	IF A.162/35 AND (A.3/2 OR A.3/3) THEN m THEN o ELSE n/a - - private header extensions to the session initiation protocol for the 3rd-Generation Partnership Project (3GPP) and P-CSCF or I-CSCF.
c16:	IF A.162/35 AND (A.3/2 OR A.3/3 OR A.3/4) THEN m ELSE n/a - - private header extensions to the session initiation protocol for the 3rd-Generation Partnership Project (3GPP) and P-CSCF or I-CSCF or S-CSCF.
c17:	IF A.162/35 AND (A.3/2 OR A.3/3) THEN m ELSE n/a - - private header extensions to the session initiation protocol for the 3rd-Generation Partnership Project (3GPP) and P-CSCF or I-CSCF.
c18:	IF A.162/38 THEN o ELSE n/a - - the P-Visited-Network-ID header extension.
c19:	IF A.162/35 AND (A.3/2 OR A.3.3 OR A.3/4 OR A.3/7 THEN m ELSE n/a - - private header extensions to the session initiation protocol for the 3rd-Generation Partnership Project (3GPP) and P-CSCF, I-CSCF, S-CSCF, AS acting as a proxy.
c20:	IF A.162/41 THEN o ELSE n/a - - the P-Access-Network-Info header extension.
c21:	IF A.162/41 AND A.3/2 THEN m ELSE n/a - - the P-Access-Network-Info header extension and P-CSCF.
c22:	IF A.162/41 AND A.3/4 THEN m ELSE n/a - - the P-Access-Network-Info header extension and S-CSCF.
c23:	IF A.162/45 THEN o ELSE n/a - - the P-Charging-Vector header extension.
c24:	IF A.162/45 THEN m ELSE n/a - - the P-Charging-Vector header extension.
c25:	IF A.162/44 THEN o ELSE n/a - - the P-Charging-Function-Addresses header extension.
c26:	IF A.162/44 THEN m ELSE n/a - - the P-Charging-Function Addresses header extension.
c27:	IF A.3/2 OR A.3/4 THEN m ELSE x - - P-CSCF or S-CSCF.
c28:	IF A.3/2 OR A.3/4 OR A.3/6 then m ELSE o - - P-CSCF or S-CSCF of MGCF.
c29:	IF A.3/2 OR A.3/4 OR A.3/6 then o ELSE m - - P-CSCF or S-CSCF of MGCF.
c30:	IF A.3/2 o ELSE i - - P-CSCF.
o.1:	It is mandatory to support at least one of these items.
o.2:	It is mandatory to support at least one of these items.
o.3:	It is mandatory to support at least one of these items.
NOTE:	An AS acting as a proxy may be outside the trust domain, and therefore not able to support the capability for that reason; in this case it is perfectly reasonable for the header to be passed on transparently, as specified in the PDU parts of the profile.

A.2.2.3 PDUs

Table A.163: Supported methods

Item	PDU	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	ACK request	[26] 13	m	m	[26] 13	m	m
2	BYE request	[26] 16	o	m	[26] 16	o	m
3	BYE response	[26] 16	o	m	[26] 16	o	m
4	CANCEL request	[26] 16.10	o	m	[26] 16.10	o	m
5	CANCEL response	[26] 16.10	o	m	[26] 16.10	o	m
8	INVITE request	[26] 16	m	m	[26] 16	m	m
9	INVITE response	[26] 16	m	m	[26] 16	m	m
9A	MESSAGE request	[50] 4	c5	c5	[50] 7	c5	c5
9B	MESSAGE response	[50] 4	c5	c5	[50] 7	c5	c5
10	NOTIFY request	[28] 8.1.2	c3	c3	[28] 8.1.2	c3	c3
11	NOTIFY response	[28] 8.1.2	c3	c3	[28] 8.1.2	c3	c3
12	OPTIONS request	[26] 16	m	m	[26] 16	m	m
13	OPTIONS response	[26] 16	m	m	[26] 16	m	m
14	PRACK request	[27] 6	c6	c6	[27] 6	c6	c6
15	PRACK response	[27] 6	c6	c6	[27] 6	c6	c6
16	REFER request	[36] 3	c1	c1	[36] 3	c1	c1
17	REFER response	[36] 3	c1	c1	[36] 3	c1	c1
18	REGISTER request	[26] 16	m	m	[26] 16	m	m
19	REGISTER response	[26] 16	m	m	[26] 16	m	m
20	SUBSCRIBE request	[28] 8.1.1	c3	c3	[28] 8.1.1	c3	c3
21	SUBSCRIBE response	[28] 8.1.1	c3	c3	[28] 8.1.1	c3	c3
22	UPDATE request	[30] 7	c4	c4	[30] 7	c4	c4
23	UPDATE response	[30] 7	c4	c4	[30] 7	c4	c4

c1: IF A.162/22 THEN m ELSE n/a - - the REFER method.
 c3: IF A.162/27 THEN m ELSE n/a - - SIP specific event notification.
 c4: IF A.162/24 THEN m ELSE n/a - - the SIP UPDATE method.
 c5: IF A.162/33 THEN m ELSE n/a - - the SIP MESSAGE method.
 c6: IF A.162/21 THEN m ELSE n/a - - reliability of provisional responses.

A.2.2.4 PDU parameters

A.2.2.4.1 Status-codes

Table A.164: Supported-status codes

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	100 (Trying)	[26] 21.1.1	c1	c1	[26] 21.1.1	c2	c2
2	180 (Ringing)	[26] 21.1.2	c3	c3	[26] 21.1.2	c3	c3
3	181 (Call Is Being Forwarded)	[26] 21.1.3	c3	c3	[26] 21.1.3	c3	c3
4	182 (Queued)	[26] 21.1.4	c3	c3	[26] 21.1.4	c3	c3
5	183 (Session Progress)	[26] 21.1.5	c3	c3	[26] 21.1.5	c3	c3
6	200 (OK)	[26] 21.2.1			[26] 21.2.1		
7	202 (Accepted)	[28] 8.3.1	c4	c4	[28] 8.3.1	c4	c4
8	300 (Multiple Choices)	[26] 21.3.1			[26] 21.3.1		
9	301 (Moved Permanently)	[26] 21.3.2			[26] 21.3.2		
10	302 (Moved Temporarily)	[26] 21.3.3			[26] 21.3.3		
11	305 (Use Proxy)	[26] 21.3.4			[26] 21.3.4		
12	380 (Alternative Service)	[26] 21.3.5			[26] 21.3.5		
13	400 (Bad Request)	[26] 21.4.1			[26] 21.4.1		
14	401 (Unauthorized)	[26] 21.4.2			[26] 21.4.2		
15	402 (Payment Required)	[26] 21.4.3			[26] 21.4.3		
16	403 (Forbidden)	[26] 21.4.4			[26] 21.4.4		
17	404 (Not Found)	[26] 21.4.5			[26] 21.4.5		
18	405 (Method Not Allowed)	[26] 21.4.6			[26] 21.4.6		
19	406 (Not Acceptable)	[26] 21.4.7			[26] 21.4.7		
20	407 (Proxy Authentication Required)	[26] 21.4.8			[26] 21.4.8		
21	408 (Request Timeout)	[26] 21.4.9			[26] 21.4.9		
22	410 (Gone)	[26] 21.4.10			[26] 21.4.10		
23	413 (Request Entity Too Large)	[26] 21.4.11			[26] 21.4.11		
24	414 (Request-URI Too Large)	[26] 21.4.12			[26] 21.4.12		
25	415 (Unsupported Media Type)	[26] 21.4.13			[26] 21.4.13		
26	416 (Unsupported URI Scheme)	[26] 21.4.14			[26] 21.4.14		
27	420 (Bad Extension)	[26] 21.4.15			[26] 21.4.15		
28	421 (Extension Required)	[26] 21.4.16			[26] 21.4.16		
29	423 (Interval Too Brief)	[26] 21.4.17	c5	c5	[26] 21.4.17	c6	c6

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
30	480 (Temporarily not available)	[26] 21.4.18			[26] 21.4.18		
31	481 (Call /Transaction Does Not Exist)	[26] 21.4.19			[26] 21.4.19		
32	482 (Loop Detected)	[26] 21.4.20			[26] 21.4.20		
33	483 (Too Many Hops)	[26] 21.4.21			[26] 21.4.21		
34	484 (Address Incomplete)	[26] 21.4.22			[26] 21.4.22		
35	485 (Ambiguous)	[26] 21.4.23			[26] 21.4.23		
36	486 (Busy Here)	[26] 21.4.24			[26] 21.4.24		
37	487 (Request Terminated)	[26] 21.4.25			[26] 21.4.25		
38	488 (Not Acceptable Here)	[26] 21.4.26			[26] 21.4.26		
39	489 (Bad Event)	[28] 7.3.2	c4	c4	[28] 7.3.2	c4	c4
40	491 (Request Pending)	[26] 21.4.27			[26] 21.4.27		
41	493 (Undecipherable)	[26] 21.4.28			[26] 21.4.28		
41A	494 (Security Agreement Required)	[48] 2	c7	c7	[48] 2	n/a	n/a
42	500 (Internal Server Error)	[26] 21.5.1			[26] 21.5.1		
43	501 (Not Implemented)	[26] 21.5.2			[26] 21.5.2		
44	502 (Bad Gateway)	[26] 21.5.3			[26] 21.5.3		
45	503 (Service Unavailable)	[26] 21.5.4			[26] 21.5.4		
46	504 (Server Time-out)	[26] 21.5.5			[26] 21.5.5		
47	505 (Version not supported)	[26] 21.5.6			[26] 21.5.6		
48	513 (Message Too Large)	[26] 21.5.7			[26] 21.5.7		
49	580 (Precondition Failure)	[30] 8			[30] 8		
50	600 (Busy Everywhere)	[26] 21.6.1			[26] 21.6.1		
51	603 (Decline)	[26] 21.6.2			[26] 21.6.2		
52	604 (Does Not Exist Anywhere)	[26] 21.6.3			[26] 21.6.3		
53	606 (Not Acceptable)	[26] 21.6.4			[26] 21.6.4		
c1:	IF A.162/15 THEN m ELSE n/a - - stateful proxy.						
c2:	IF A.162/15 THEN m ELSE i - - the requirement to be able to use separate URIs in the upstream direction and downstream direction when record routeing.						
c3:	IF A.163/9 THEN m ELSE n/a - - INVITE response.						
c4:	IF A.162/27 THEN m ELSE n/a - - SIP specific event notification.						
c5:	IF A.163/19 OR A.163/21 THEN m ELSE n/a - - REGISTER response or SUBSCRIBE response.						
c6:	IF A.163/19 OR A.163/21 THEN i ELSE n/a - - REGISTER response or SUBSCRIBE response.						
c7:	IF A.162/47 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol.						

A.2.2.4.2 ACK method

Prerequisite A.163/1 -- ACK request

Table A.165: Supported headers within the ACK request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
2	Allow-Events	[28]	8.2.2	m	[28]	8.2.2	c1
3	Authorization	[26]	20.7	m	[26]	20.7	i
4	Call-ID	[26]	20.8	m	[26]	20.8	m
6	Content-Disposition	[26]	20.11	m	[26]	20.11	i
7	Content-Encoding	[26]	20.12	m	[26]	20.12	i
8	Content-Language	[26]	20.13	m	[26]	20.13	i
9	Content-Length	[26]	20.14	m	[26]	20.14	m
10	Content-Type	[26]	20.15	m	[26]	20.15	i
11	Cseq	[26]	20.16	m	[26]	20.16	m
12	Date	[26]	20.17	m	[26]	20.17	c2
13	From	[26]	20.20	m	[26]	20.20	m
14	Max-Forwards	[26]	20.22	m	[26]	20.22	m
15	MIME-Version	[26]	20.24	m	[26]	20.24	i
16	Proxy-Authorization	[26]	20.28	m	[26]	20.28	c4
17	Proxy-Require	[26]	20.29	m	[26]	20.29	m
17A	Privacy	[33]	4.2	c6	[33]	4.2	c7
18	Require	[26]	20.32	m	[26]	20.32	c5
19	Route	[26]	20.34	m	[26]	20.34	m
20	Timestamp	[26]	20.38	m	[26]	20.38	i
21	To	[26]	20.39	m	[26]	20.39	m
22	User-Agent	[26]	20.41	m	[26]	20.41	i
23	Via	[26]	20.42	m	[26]	20.42	m
c1:	IF A.4/20 THEN m ELSE i -- SIP specific event notification extension.						
c2:	IF A.162/9 THEN m ELSE i -- insertion of date in requests and responses.						
c3:	IF A.3/2 OR A.3/4 THEN m ELSE i -- P-CSCF or S-CSCF.						
c4:	IF A.162/8A THEN m ELSE i -- authentication between UA and proxy.						
c5:	IF A.162/11 OR A.162/13 THEN m ELSE i -- reading the contents of the Require header before proxying the request or response or adding or modifying the contents of the Require header before proxying the request or response for methods other than REGISTER.						
c6:	IF A.162/31 THEN m ELSE n/a -- a privacy mechanism for the Session Initiation Protocol (SIP).						
c7:	IF A.162/31D OR A.162/31G THEN m ELSE IF A.162/31C THEN i ELSE n/a -- application of the privacy option "header" or application of the privacy option "id" or passing on of the Privacy header transparently.						
NOTE:	c1 refers to the UA role major capability as this is the case of a proxy that also acts as a UA specifically for SUBSCRIBE and NOTIFY.						

Editor's note: Is the following table a suitable way of showing the contents of message bodies.

Prerequisite A.163/1 -- ACK request

Table A.166: Supported message bodies within the ACK request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1							

A.2.2.4.3 BYE method

Prerequisite A.163/2 - - BYE request

Table A.167: Supported headers within the BYE request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Accept	[26] 20.1	m	m	[26] 20.1	i	i
2	Accept-Encoding	[26] 20.2	m	m	[26] 20.2	i	i
3	Accept-Language	[26] 20.3	m	m	[26] 20.3	i	i
3A	Allow	[26] 20.5	m	m	[26] 20.5	i	i
4	Allow-Events	[28] 8.2.2	m	m	[28] 8.2.2	c1	c1
5	Authorization	[26] 20.7	m	m	[26] 20.7	i	i
6	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
7	Content-Disposition	[26] 20.11	m	m	[26] 20.11	i	c3
8	Content-Encoding	[26] 20.12	m	m	[26] 20.12	i	c3
9	Content-Language	[26] 20.13	m	m	[26] 20.13	i	c3
10	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
11	Content-Type	[26] 20.15	m	m	[26] 20.15	i	c3
12	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
13	Date	[26] 20.17	m	m	[26] 20.17	c2	c2
14	From	[26] 20.20	m	m	[26] 20.20	m	m
15	Max-Forwards	[26] 20.22	m	m	[26] 20.22	m	m
16	MIME-Version	[26] 20.24	m	m	[26] 20.24	i	c3
16A	P-Access-Network-Info	[52] 4.4	c13	c13	[52] 4.4	c14	c14
16B	P-Asserted-Identity	[34] 9.1	c9	c9	[34] 9.1	c10	c10
16C	P-Charging-Function-Addresses	[52] 4.5	c17	c17	[52] 4.5	c18	c18
16D	P-Charging-Vector	[52] 4.6	c15	n/a	[52] 4.6	c16	n/a
16E	P-Preferred-Identity	[34] 9.2	x	x	[34] 9.2	c8	n/a
16F	Privacy	[33] 4.2	c11	c11	[33] 4.2	c12	c12
17	Proxy-Authorization	[26] 20.28	m	m	[26] 20.28	c4	c4
18	Proxy-Require	[26] 20.29	m	m	[26] 20.29	m	m
19	Record-Route	[26] 20.30	m	m	[26] 20.30	c7	c7
20	Require	[26] 20.32	m	m	[26] 20.32	c5	c5
21	Route	[26] 20.34	m	m	[26] 20.34	m	m
21A	Security-Client	[48] 2.3.1	x	x	[48] 2.3.1	c19	c19
21B	Security-Verify	[48] 2.3.1	x	x	[48] 2.3.1	c19	c19
22	Supported	[26] 20.37	m	m	[26] 20.37	c6	c6
23	Timestamp	[26] 20.38	m	m	[26] 20.38	i	i
24	To	[26] 20.39	m	m	[26] 20.39	m	m
25	User-Agent	[26] 20.41	m	m	[26] 20.41	i	i
26	Via	[26] 20.42	m	m	[26] 20.42	m	m

c1:	IF A.4/20 THEN m ELSE i - - SIP specific event notification extension.
c2:	IF A.162/9 THEN m ELSE i - - insertion of date in requests and responses.
c3:	IF A.3/2 OR A.3/4 THEN m ELSE i - - P-CSCF or S-CSCF.
c4:	IF A.162/8A THEN m ELSE i - - authentication between UA and proxy.
c5:	IF A.162/11 OR A.162/13 THEN m ELSE i - - reading the contents of the Require header before proxying the request or response or adding or modifying the contents of the Require header before proxying the request or response for methods other than REGISTER.
c6:	IF A.162/16 THEN m ELSE i - - reading the contents of the Supported header before proxying the response.
c7:	IF A.162/14 THEN o ELSE i - - the requirement to be able to insert itself in the subsequent transactions in a dialog.
c8:	IF A.162/30A THEN m ELSE n/a - - act as first entity within the trust domain for asserted identity.
c9:	IF A.162/30 THEN m ELSE n/a - - extensions to the Session Initiation Protocol (SIP) for asserted identity within trusted networks.
c10:	IF A.162/30A or A.162/30B THEN m ELSE i - - extensions to the Session Initiation Protocol (SIP) for asserted identity within trusted networks or subsequent entity within trust network that can route outside the trust network.
c11:	IF A.162/31 THEN m ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).
c12:	IF A.162/31D OR A.162/31G THEN m ELSE IF A.162/31C THEN i ELSE n/a - - application of the privacy option "header" or application of the privacy option "id" or passing on of the Privacy header transparently.
c13:	IF A.162/43 THEN x ELSE IF A.162/41 THEN m ELSE n/a - - act as subsequent entity within trust network for access network information that can route outside the trust network, the P-Access-Network-Info header extension.
c14:	IF A.162/43 THEN m ELSE IF A.162/41 THEN i ELSE n/a - - act as subsequent entity within trust network for access network information that can route outside the trust network, the P-Access-Network-Info header extension.
c15:	IF A.162/45 THEN m ELSE n/a - - the P-Charging-Vector header extension.
c16:	IF A.162/46 THEN m ELSE IF A.162/45 THEN i ELSE n/a - - adding, deleting, reading or modifying the P-Charging-Vector header before proxying the request or response or the P-Charging-Vector header extension.
c17:	IF A.162/44 THEN m ELSE n/a - - the P-Charging-Function-Addresses header extension.
c18:	IF A.162/44A THEN m ELSE IF A.162/44 THEN i ELSE n/a - - adding, deleting or reading the P-Charging-Function-Addresses header before proxying the request or response, or the P-Charging-Function-Addresses header extension.
c19:	IF A.4/37 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol.
NOTE:	c1 refers to the UA role major capability as this is the case of a proxy that also acts as a UA specifically for SUBSCRIBE and NOTIFY.

Prerequisite A.163/2 - - BYE request

Table A.168: Supported message bodies within the BYE request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1							

Prerequisite A.163/3 - - BYE response

Prerequisite: A.164/1 - - 100 (Trying)

Table A.169: Supported headers within the BYE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
2	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
3	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
4	Date	[26] 20.17	m	m	[26] 20.17	c1	c1
5	From	[26] 20.20	m	m	[26] 20.20	m	m
6	To	[26] 20.39	m	m	[26] 20.39	m	m
7	Via	[26] 20.42	m	m	[26] 20.42	m	m
c1:	IF A.162/9 THEN m ELSE i - - insertion of date in requests and responses.						

Prerequisite A.163/3 - - BYE response

Table A.170: Supported headers within the BYE response - all remaining status-codes

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
2	Content-Disposition	[26] 20.11	m	m	[26] 20.11	i	c2
3	Content-Encoding	[26] 20.12	m	m	[26] 20.12	i	c2
4	Content-Language	[26] 20.13	m	m	[26] 20.13	i	c2
5	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
6	Content-Type	[26] 20.15	m	m	[26] 20.15	i	c2
7	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
8	Date	[26] 20.17	m	m	[26] 20.17	c1	c1
9	From	[26] 20.20	m	m	[26] 20.20	m	m
10	MIME-Version	[26] 20.24	m	m	[26] 20.24	i	c2
10A	P-Access-Network-Info	[52] 4.4	c12	c12	[52] 4.4	c13	c13
10B	P-Asserted-Identity	[34] 9.1	c4	c4	[34] 9.1	c5	c5
10C	P-Charging-Function-Addresses	[52] 4.5	c10	c10	[52] 4.5	c11	c11
10D	P-Charging-Vector	[52] 4.6	c8	n/a	[52] 4.6	c9	n/a
10E	P-Preferred-Identity	[34] 9.2	x	x	[34] 9.2	c3	n/a
10F	Privacy	[33] 4.2	c6	c6	[33] 4.2	c7	c7
10G	Require	[26] 20.32	m	m	[26] 20.32	c14	c14
10H	Server	[26] 20.35	m	m	[26] 20.35	i	i
11	Timestamp	[26] 20.38	m	m	[26] 20.38	i	i
12	To	[26] 20.39	m	m	[26] 20.39	m	m
12A	User-Agent	[26] 20.41	m	m	[26] 20.41	i	i
13	Via	[26] 20.42	m	m	[26] 20.42	m	m
14	Warning	[26] 20.43	m	m	[26] 20.43	i	i
c1:	IF A.162/9 THEN m ELSE i - - insertion of date in requests and responses.						
c2:	IF A.3/2 OR A.3/4 THEN m ELSE i - - P-CSCF or S-CSCF.						
c3:	IF A.162/30A THEN m ELSE n/a - - act as first entity within the trust domain for asserted identity.						
c4:	IF A.162/30 THEN m ELSE n/a - - extensions to the Session Initiation Protocol (SIP) for asserted identity within trusted networks.						
c5:	IF A.162/30A or A.162/30B THEN m ELSE i - - extensions to the Session Initiation Protocol (SIP) for asserted identity within trusted networks or subsequent entity within trust network that can route outside the trust network.						
c6:	IF A.162/31 THEN m ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).						
c7:	IF A.162/31D OR A.162/31G THEN m ELSE IF A.162/31C THEN i ELSE n/a - - application of the privacy option "header" or application of the privacy option "id" or passing on of the Privacy header transparently.						
c8:	IF A.162/45 THEN m ELSE n/a - - the P-Charging-Vector header extension.						
c9:	IF A.162/46 THEN m ELSE IF A.162/45 THEN i ELSE n/a - - adding, deleting, reading or modifying the P-Charging-Vector header before proxying the request or response or the P-Charging-Vector header extension.						
c10:	IF A.162/44 THEN m ELSE n/a - - the P-Charging-Function-Addresses header extension.						
c11:	IF A.162/44A THEN m ELSE IF A.162/44 THEN i ELSE n/a - - adding, deleting or reading the P-Charging-Function-Addresses header before proxying the request or response, or the P-Charging-Function-Addresses header extension.						
c12:	IF A.162/43 THEN x ELSE IF A.162/41 THEN m ELSE n/a - - act as subsequent entity within trust network for access network information that can route outside the trust network, the P-Access-Network-Info header extension.						
c13:	IF A.162/43 THEN m ELSE IF A.162/41 THEN i ELSE n/a - - act as subsequent entity within trust network for access network information that can route outside the trust network, the P-Access-Network-Info header extension.						
c14:	IF A.162/11 OR A.162/13 THEN m ELSE i - - reading the contents of the Require header before proxying the request or response or adding or modifying the contents of the Require header before proxying the request or response for methods other than REGISTER.						

Prerequisite A.163/3 - - BYE response

Prerequisite: A.164/6 - - 2xx

Table A.171: Supported headers within the BYE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	m	m	[26] 20.5	i	i
1	Authentication-Info	[26] 20.6	m	m	[26] 20.6	i	i
2	Record-Route	[26] 20.30	m	m	[26] 20.30	c3	c3
5	Supported	[26] 20.37	m	m	[26] 20.37	i	i
c3:	IF A.162/15 THEN o ELSE i - - the requirement to be able to use separate URIs in the upstream direction and downstream direction when record routeing.						

Prerequisite A.163/3 - BYE response

Prerequisite: A.164/8 OR A.164/9 OR A.164/10 OR A.164/11 OR A.164/12 OR A.164/35 - - 3xx or 485 (Ambiguous)

Table A.172: Supported headers within the BYE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	m	m	[26] 20.5	i	i
1	Contact	[26] 20.10	m	m	[26] 20.10	c1	c1
2	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
4	Supported	[26] 20.37	m	m	[26] 20.37	i	i
c1:	IF A.162/19E THEN m ELSE i - - deleting Contact headers.						

Prerequisite A.163/3 - - BYE response

Prerequisite: A.164/14 - - 401 (Unauthorized)

Table A.173: Supported headers within the BYE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	m	m	[26] 20.5	i	i
1	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
2	Proxy-Authenticate	[26] 20.27	m	m	[26] 20.27	m	m
5	Supported	[26] 20.37	m	m	[26] 20.37	i	i
8	WWW-Authenticate	[26] 20.44	m	m	[26] 20.44	i	i

Prerequisite A.163/3 - - BYE response

Prerequisite: A.164/17 OR A.164/23 OR A.164/30 OR A.164/36 OR A.164/42 OR A.164/45 OR A.164/50 OR A.164/51 - - 404, 413, 480, 486, 500, 503, 600, 603

Table A.174: Supported headers within the BYE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	m	m	[26] 20.5	i	i
1	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
3	Retry-After	[26] 20.33	m	m	[26] 20.33	i	i
5	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/3 - - BYE response

Prerequisite: A.164/18 - - 405 (Method Not Allowed)

Table A.175: Supported headers within the BYE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
2	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
5	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/3 - - BYE response

Prerequisite: A.164/20 - - 407 (Proxy Authentication Required)

Table A.176: Supported headers within the BYE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	m	m	[26] 20.5	i	i
1	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
2	Proxy-Authenticate	[26] 20.27	m	m	[26] 20.27	m	m
5	Supported	[26] 20.37	m	m	[26] 20.37	i	i
6	WWW-Authenticate	[26] 20.44	m	m	[26] 20.44	i	i

Prerequisite A.163/3 - - BYE response

Prerequisite: A.164/25 - - 415 (Unsupported Media Type)

Table A.177: Supported headers within the BYE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Accept	[26] 20.1	m	m	[26] 20.1	i	i
2	Accept-Encoding	[26] 20.2	m	m	[26] 20.2	i	i
3	Accept-Language	[26] 20.3	m	m	[26] 20.3	i	i
3A	Allow	[26] 20.5	m	m	[26] 20.5	i	i
4	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
7	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/3 - - BYE response

Prerequisite: A.164/27 - - 420 (Bad Extension)

Table A.178: Supported headers within the BYE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	m	m	[26] 20.5	i	i
1	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
4	Supported	[26] 20.37	m	m	[26] 20.37	i	i
5	Unsupported	[26] 20.40	m	m	[26] 20.40	c3	c3
c3:	IF A.162/18 THEN m ELSE i - - reading the contents of the Unsupported header before proxying the 420 response to a method other than REGISTER.						

Prerequisite A.163/3 - - BYE response

Prerequisite: A.164/28 OR A.164/41A - - 421 (Extension Required), 494 (Security Agreement Required)

Table A.178A: Supported headers within the BYE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
2	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
3	Security-Server	[48] 2	c1	c1	[48] 2	n/a	n/a
4	Supported	[26] 20.37	m	m	[26] 20.37	m	m
c1: IF A.162/47 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol.							

Prerequisite A.163/3 - - BYE response

Prerequisite: A.164/34 - - 484 (Address Incomplete)

Table A.179: Supported headers within the BYE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	m	m	[26] 20.5	i	i
1	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
4	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/3 - - BYE response

Table A.180: Supported message bodies within the BYE response

Item	Header	Sending			Receiving		
		Ref.	RFC Status	Profile status	Ref.	RFC status	Profile status
1							

A.2.2.4.4 CANCEL method

Prerequisite A.163/4 -- CANCEL request

Table A.181: Supported headers within the CANCEL request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
4	Allow-Events	[28]	8.2.2	m	[28]	8.2.2	c1
5	Authorization	[26]	20.7	m	[26]	20.7	i
6	Call-ID	[26]	20.8	m	[26]	20.8	m
8	Content-Length	[26]	20.14	m	[26]	20.14	m
9	Cseq	[26]	20.16	m	[26]	20.16	m
10	Date	[26]	20.17	m	[26]	20.17	c2
11	From	[26]	20.20	m	[26]	20.20	m
12	Max-Forwards	[26]	20.22	m	[26]	20.22	m
13	Privacy	[33]	4.2	c3	[33]	4.2	c4
16	Record-Route	[26]	20.30	m	[26]	20.30	c7
18	Route	[26]	20.34	m	[26]	20.34	m
19	Supported	[26]	20.37	m	[26]	20.37	c6
20	Timestamp	[26]	20.38	m	[26]	20.38	i
21	To	[26]	20.39	m	[26]	20.39	m
22	User-Agent	[26]	20.41	m	[26]	20.41	i
23	Via	[26]	20.42	m	[26]	20.42	m
c1:	IF A.4/20 THEN m ELSE i -- SIP specific event notification extension.						
c2:	IF A.162/9 THEN m ELSE i -- insertion of date in requests and responses.						
c3:	IF A.162/31 THEN m ELSE n/a -- a privacy mechanism for the Session Initiation Protocol (SIP).						
c4:	IF A.162/31D OR A.162/31G THEN m ELSE IF A.162/31C THEN i ELSE n/a -- application of the privacy option "header" or application of the privacy option "id" or passing on of the Privacy header transparently.						
c6:	IF A.162/16 THEN m ELSE i -- reading the contents of the Supported header before proxying the response.						
c7:	IF A.162/14 THEN o ELSE i -- the requirement to be able to insert itself in the subsequent transactions in a dialog.						
NOTE:	c1 refers to the UA role major capability as this is the case of a proxy that also acts as a UA specifically for SUBSCRIBE and NOTIFY.						

Prerequisite A.163/4 -- CANCEL request

Table A.182: Supported message bodies within the CANCEL request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1							

Prerequisite A.163/5 - - CANCEL response

Table A.183: Supported headers within the CANCEL response - all status-codes

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
2	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
3	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
4	Date	[26] 20.17	m	m	[26] 20.17	c1	c1
5	From	[26] 20.20	m	m	[26] 20.20	m	m
5A	Privacy	[33] 4.2	c2	c2	[33] 4.2	c3	c3
6	Timestamp	[26] 20.38	m	m	[26] 20.38	i	i
7	To	[26] 20.39	m	m	[26] 20.39	m	m
7A	User-Agent	[26] 20.41	o		[26] 20.41	o	
8	Via	[26] 20.42	m	m	[26] 20.42	m	m
9	Warning	[26] 20.43	m	m	[26] 20.43	i	i

c1: IF A.162/9 THEN m ELSE i - - insertion of date in requests and responses.
 c2: IF A.162/31 THEN m ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).
 c3: IF A.162/31D OR A.162/31G THEN m ELSE IF A.162/31C THEN i ELSE n/a - - application of the privacy option "header" or application of the privacy option "id" or passing on of the Privacy header transparently.

Prerequisite A.163/5 - - CANCEL response

Prerequisite: A.164/6 - - 200 (OK)

Table A.184: Supported headers within the CANCEL response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
2	Record-Route	[26] 20.30	m	m	[26] 20.30	c3	c3
4	Supported	[26] 20.37	m	m	[26] 20.37	i	i

c3: IF A.162/15 THEN o ELSE i - - the requirement to be able to use separate URLs in the upstream direction and downstream direction when record routeing.

Prerequisite A.163/5 - - CANCEL response

Prerequisite: A.164/14 - - 401 (Unauthorized)

Table A.185: Supported headers within the CANCEL response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
2	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
5	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/5 - - CANCEL response

Prerequisite: A.164/17 OR A.164/23 OR A.164/30 OR A.164/42 OR A.164/45 OR A.164/50 OR A.164/51 - - 404, 413, 480, 500, 503, 600, 603

Table A.186: Supported headers within the CANCEL response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
2	Error-Info	[26] 2418	m	m	[26] 20.18	i	i
4	Retry-After	[26] 20.33	m	m	[26] 20.33	i	i
5	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/5 - - CANCEL response

Prerequisite: A.164/34 - - 484 (Address Incomplete)

Table A.188: Supported headers within the CANCEL response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
2	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
4	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/5 - - CANCEL response

Table A.189: Supported message bodies within the CANCEL response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1							

A.2.2.4.5 COMET method

Void

A.2.2.4.6 INFO method

Void

A.2.2.4.7 INVITE method

Prerequisite A.163/8 -- INVITE request

Table A.204: Supported headers within the INVITE request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Accept	[26] 20.1	m	m	[26] 20.1	i	i
2	Accept-Encoding	[26] 20.2	m	m	[26] 20.2	i	i
3	Accept-Language	[26] 20.3	m	m	[26] 20.3	i	i
4	Alert-Info	[26] 20.4	c2	c2	[26] 20.4	c3	c3
5	Allow	[26] 20.5	m	m	[26] 20.5	i	i
6	Allow-Events	[28] 8.2.2	m	m	[28] 8.2.2	c1	c1
8	Authorization	[26] 20.7	m	m	[26] 20.7	i	i
9	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
10	Call-Info	[26] 20.9	m	m	[26] 20.9	c12	c12
11	Contact	[26] 20.10	m	m	[26] 20.10	i	i
12	Content-Disposition	[26] 20.11	m	m	[26] 20.11	i	c6
13	Content-Encoding	[26] 20.12	m	m	[26] 20.12	i	c6
14	Content-Language	[26] 20.13	m	m	[26] 20.13	i	c6
15	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
16	Content-Type	[26] 20.15	m	m	[26] 20.15	i	c6
17	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
18	Date	[26] 20.17	m	m	[26] 20.17	c4	c4
19	Expires	[26] 20.19	m	m	[26] 20.19	i	i
20	From	[26] 20.20	m	m	[26] 20.20	m	m
21	In-Reply-To	[26] 20.21	m	m	[26] 20.21	i	i
22	Max-Forwards	[26] 20.22	m	m	[26] 20.22	m	m
23	MIME-Version	[26] 20.24	m	m	[26] 20.24	i	c6
24	Organization	[26] 20.25	m	m	[26] 20.25	c5	c5
24A	P-Access-Network-Info	[52] 4.4	c28	c28	[52] 4.4	c29	c30
24B	P-Asserted-Identity	[34] 9.1	c15	c15	[34] 9.1	c16	c16
24C	P-Called-Party-ID	[52] 4.2	c19	c19	[52] 4.2	c20	c21
24D	P-Charging-Function-Addresses	[52] 4.5	c26	c27	[52] 4.5	c26	c27
24E	P-Charging-Vector	[52] 4.6	c24	c24	[52] 4.6	c25	c25
25	P-Media-Authorization	[31] 6.1	c9	c10	[31] 6.1	n/a	n/a
25A	P-Preferred-Identity	[34] 9.2	x	x	[34] 9.2	c14	c14
25B	P-Visited-Network-ID	[52] 4.3	c22	n/a	[52] 4.3	c23	n/a
26	Priority	[26] 20.26	m	m	[26] 20.26	i	i
26A	Privacy	[33] 4.2	c17	c17	[33] 4.2	c18	c18
27	Proxy-Authorization	[26] 20.28	m	m	[26] 20.28	c13	c13
28	Proxy-Require	[26] 20.29, [34] 4	m	m	[26] 20.29, [34] 4	m	m
29	Record-Route	[26] 20.30	m	m	[26] 20.30	c11	c11
31	Reply-To	[26] 20.31	m	m	[26] 20.31	i	i
32	Require	[26] 20.32	m	m	[26] 20.32	c7	c7
33	Route	[26] 20.34	m	m	[26] 20.34	m	m
33A	Security-Client	[48] 2.3.1	x	x	[48] 2.3.1	c31	c31
33B	Security-Verify	[48] 2.3.1	x	x	[48] 2.3.1	c31	c31
34	Subject	[26] 20.36	m	m	[26] 20.36	i	i
35	Supported	[26] 20.37	m	m	[26] 20.37	c8	c8
36	Timestamp	[26] 20.38	m	m	[26] 20.38	i	i

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
37	To	[26] 20.39	m	m	[26] 20.39	m	m
38	User-Agent	[26] 20.41	m	m	[26] 20.41	i	i
39	Via	[26] 20.42	m	m	[26] 20.42	m	m
c1:	IF A.4/20 THEN m ELSE i - - SIP specific event notification extension.						
c2:	IF A.162/10 THEN n/a ELSE m - - suppression or modification of alerting information data.						
c3:	IF A.162/10 THEN m ELSE i - - suppression or modification of alerting information data.						
c4:	IF A.162/9 THEN m ELSE i - - insertion of date in requests and responses.						
c5:	IF A.162/19A OR A.162/19B THEN m ELSE i - - reading, adding or concatenating the Organization header.						
c6:	IF A.3/2 OR A.3/4 THEN m ELSE i - - P-CSCF or S-CSCF.						
c7:	IF A.162/11 OR A.162/13 THEN m ELSE i - - reading the contents of the Require header before proxying the request or response or adding or modifying the contents of the Require header before proxying the request or response for methods other than REGISTER.						
c8:	IF A.162/16 THEN m ELSE i - - reading the contents of the Supported header before proxying the response.						
c9:	IF A.162/26 THEN m ELSE n/a - - SIP extensions for media authorization.						
c10:	IF A.3/2 THEN m ELSE n/a - - P-CSCF.						
c11:	IF A.162/14 THEN m ELSE i - - the requirement to be able to insert itself in the subsequent transactions in a dialog.						
c12:	IF A.162/19C OR A.162/19D THEN m ELSE i - - reading, adding or concatenating the Call-Info header.						
c13:	IF A.162/8A THEN m ELSE i - - authentication between UA and proxy.						
c14:	IF A.162/30A THEN m ELSE n/a - - act as first entity within the trust domain for asserted identity.						
c15:	IF A.162/30 THEN m ELSE n/a - - extensions to the Session Initiation Protocol (SIP) for asserted identity within trusted networks.						
c16:	IF A.162/30A or A.162/30B THEN m ELSE i - - extensions to the Session Initiation Protocol (SIP) for asserted identity within trusted networks or subsequent entity within trust network that can route outside the trust network.						
c17:	IF A.162/31 THEN m ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).						
c18:	IF A.162/31D OR A.162/31G THEN m ELSE IF A.162/31C THEN i ELSE n/a - - application of the privacy option "header" or application of the privacy option "id" or passing on of the Privacy header transparently.						
c19:	IF A.162/37 THEN m ELSE n/a - - the P-Called-Party-ID header extension.						
c20:	IF A.162/37 THEN i ELSE n/a - - the P-Called-Party-ID header extension.						
c21:	IF A.162/37 AND A.3/2 THEN m ELSE IF A.162/37 AND A.3/3 THEN i ELSE n/a - - the P-Called-Party-ID header extension and P-CSCF or I-CSCF.						
c22:	IF A.162/38 THEN m ELSE n/a - - the P-Visited-Network-ID header extension.						
c23:	IF A.162/39 THEN m ELSE i - - reading, or deleting the P-Visited-Network-ID header before proxying the request or response.						
c24:	IF A.162/45 THEN m ELSE n/a - - the P-Charging-Vector header extension.						
c25:	IF A.162/46 THEN m ELSE IF A.162/45 THEN i ELSE n/a - - adding, deleting, reading or modifying the P-Charging-Vector header before proxying the request or response or the P-Charging-Vector header extension.						
c26:	IF A.162/44 THEN m ELSE n/a - - the P-Charging-Function-Addresses header extension.						
c27:	IF A.162/44A THEN m ELSE IF A.162/44 THEN i ELSE n/a - - adding, deleting or reading the P-Charging-Function-Addresses header before proxying the request or response, or the P-Charging-Function-Addresses header extension.						
c28:	IF A.162/43 THEN x ELSE IF A.162/41 THEN m ELSE n/a - - act as subsequent entity within trust network for access network information that can route outside the trust network, the P-Access-Network-Info header extension.						
c29:	IF A.162/43 THEN m ELSE IF A.162/41 THEN i ELSE n/a - - act as subsequent entity within trust network for access network information that can route outside the trust network, the P-Access-Network-Info header extension.						
c30:	IF A.162/43 OR (A.162/41 AND A.3/2) THEN m ELSE IF A.162/41 THEN i ELSE n/a - - act as subsequent entity within trust network for access network information that can route outside the trust network, the P-Access-Network-Info header extension (with or without P-CSCF).						
c31:	IF A.4/37 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol.						
NOTE:	c1 refers to the UA role major capability as this is the case of a proxy that also acts as a UA specifically for SUBSCRIBE and NOTIFY.						

Prerequisite A.163/8 - - INVITE request

Table A.205: Supported message bodies within the INVITE request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1							

Prerequisite A.163/9 - - INVITE response

Prerequisite: A.164/1 - - 100 (Trying)

Table A.206: Supported headers within the INVITE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
2	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
3	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
4	Date	[26] 20.17	c1	c1	[26] 20.17	c2	c2
5	From	[26] 20.20	m	m	[26] 20.20	m	m
6	To	[26] 20.39	m	m	[26] 20.39	m	m
7	Via	[26] 20.42	m	m	[26] 20.42	m	m
c1: IF (A.162/9 AND A.162/5) OR A.162/4 THEN m ELSE n/a - - stateful proxy behaviour that inserts date, or stateless proxies.							
c2: IF A.162/4 THEN i ELSE m - - Stateless proxy passes on.							

Prerequisite A.163/9 - - INVITE response

Table A.207: Supported headers within the INVITE response - all remaining status-codes

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
1A	Call-Info	[26] 20.9	m	m	[26] 20.9	c4	c4
2	Content-Disposition	[26] 20.11	m	m	[26] 20.11	i	c3
3	Content-Encoding	[26] 20.12	m	m	[26] 20.12	i	c3
4	Content-Language	[26] 20.13	m	m	[26] 20.13	i	c3
5	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
6	Content-Type	[26] 20.15	m	m	[26] 20.15	i	c3
7	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
8	Date	[26] 20.17	m	m	[26] 20.17	c1	c1
9	From	[26] 20.20	m	m	[26] 20.20	m	m
10	MIME-Version	[26] 20.24	m	m	[26] 20.24	i	c3
11	Organization	[26] 20.25	m	m	[26] 20.25	c2	c2
11A	P-Access-Network-Info	[52] 4.4	c14	c14	[52] 4.4	c15	c15
11B	P-Asserted-Identity	[34] 9.1	c6	c6	[34] 9.1	c7	c7
11C	P-Charging-Function-Addresses	[52] 4.5	c12	c12	[52] 4.5	c13	c13
11D	P-Charging-Vector	[52] 4.6	c10	c10	[52] 4.6	c11	c11
11E	P-Preferred-Identity	[34] 9.2	x	x	[34] 9.2	c5	n/a
11F	Privacy	[33] 4.2	c8	c8	[33] 4.2	c9	c9
11G	Require	[26] 20.32	m	m	[26] 20.32	c16	c16
11H	Server	[26] 20.35	m	m	[26] 20.35	i	i
12	Timestamp	[26] 20.38	m	m	[26] 20.38	i	i
13	To	[26] 20.39	m	m	[26] 20.39	m	m
13A	User-Agent	[26] 20.41	m	m	[26] 20.41	i	i
14	Via	[26] 20.42	m	m	[26] 20.42	m	m
15	Warning	[26] 20.43	m	m	[26] 20.43	i	i
c1:	IF A.162/9 THEN m ELSE i - - insertion of date in requests and responses.						
c2:	IF A.162/19A OR A.162/19B THEN m ELSE i - - reading, adding or concatenating the Organization header.						
c3:	IF A.3/2 OR A.3/4 THEN m ELSE i - - P-CSCF or S-CSCF.						
c4:	IF A.162/19C OR A.162/19D THEN m ELSE i - - reading, adding or concatenating the Call-Info header.						
c5:	IF A.162/30A THEN m ELSE n/a - - act as first entity within the trust domain for asserted identity.						
c6:	IF A.162/30 THEN m ELSE n/a - - extensions to the Session Initiation Protocol (SIP) for asserted identity within trusted networks.						
c7:	IF A.162/30A or A.162/30B THEN m ELSE i - - extensions to the Session Initiation Protocol (SIP) for asserted identity within trusted networks or subsequent entity within trust network that can route outside the trust network.						
c8:	IF A.162/31 THEN m ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).						
c9:	IF A.162/31D OR A.162/31G THEN m ELSE IF A.162/31C THEN i ELSE n/a - - application of the privacy option "header" or application of the privacy option "id" or passing on of the Privacy header transparently.						
c10:	IF A.162/45 THEN m ELSE n/a - - the P-Charging-Vector header extension.						
c11:	IF A.162/46 THEN m ELSE IF A.162/45 THEN i ELSE n/a - - adding, deleting, reading or modifying the P-Charging-Vector header before proxying the request or response or the P-Charging-Vector header extension.						
c12:	IF A.162/44 THEN m ELSE n/a - - the P-Charging-Function-Addresses header extension.						
c13:	IF A.162/44A THEN m ELSE IF A.162/44 THEN i ELSE n/a - - adding, deleting or reading the P-Charging-Function-Addresses header before proxying the request or response, or the P-Charging-Function-Addresses header extension.						
c14:	IF A.162/43 THEN x ELSE IF A.162/41 THEN m ELSE n/a - - act as subsequent entity within trust network for access network information that can route outside the trust network, the P-Access-Network-Info header extension.						
c15:	IF A.162/43 THEN m ELSE IF A.162/41 THEN i ELSE n/a - - act as subsequent entity within trust network for access network information that can route outside the trust network, the P-Access-Network-Info header extension.						
c16:	IF A.162/11 OR A.162/13 THEN m ELSE i - - reading the contents of the Require header before proxying the request or response or adding or modifying the contents of the Require header before proxying the request or response for methods other than REGISTER.						

Prerequisite A.163/9 - - INVITE response

Prerequisite: A.164/2 OR A.164/3 OR A.164/4 OR A.164/5 - - 1xx

Table A.208: Supported headers within the INVITE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
4	Contact	[26] 20.10	m	m	[26] 20.10	i	i
6	P-Media-Authorization	[31] 6.1	c9	c10	[31] 6.1	n/a	n/a
9	Rseq	[27] 7.1	m	m	[27] 7.1	i	i
11	Supported	[26] 20.37	m	m	[26] 20.37	i	i
c9: IF A.162/26 THEN m ELSE n/a - - SIP extensions for media authorization.							
c10: IF A.3/2 THEN m ELSE n/a - - P-CSCF.							

Prerequisite A.163/9 - - INVITE response

Prerequisite: A.164/6 - - 2xx

Table A.209: Supported headers within the INVITE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Accept	[26] 20.1	m	m	[26] 20.1	i	i
1A	Accept-Encoding	[26] 20.2	m	m	[26] 20.2	i	i
1B	Accept-Language	[26] 20.3	m	m	[26] 20.3	i	i
2	Allow	[26] 20.5	m	m	[26] 20.5	i	i
4	Authentication-Info	[26] 20.6	m	m	[26] 20.6	i	i
6	Contact	[26] 20.10	m	m	[26] 20.10	i	i
8	P-Media-Authorization	[31] 6.1	c9	c10	[31] 6.1	n/a	n/a
9	Record-Route	[26] 20.30	m	m	[26] 20.30	c3	c3
13	Supported	[26] 20.37	m	m	[26] 20.37	i	i
c3: IF A.162/14 THEN m ELSE i - - the requirement to be able to insert itself in the subsequent transactions in a dialog.							
c9: IF A.162/26 THEN m ELSE n/a - - SIP extensions for media authorization.							
c10: IF A.3/2 THEN m ELSE n/a - - P-CSCF.							

Prerequisite A.163/9 - - INVITE response

Prerequisite: A.164/8 OR A.164/9 OR A.164/10 OR A.164/11 OR A.164/12 OR A.164/35 - - 3xx or 485 (Ambiguous)

Table A.210: Supported headers within the INVITE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
4	Contact	[26] 20.10	m	m	[26] 20.10	c1	c1
5	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
10	Supported	[26] 20.37	m	m	[26] 20.37	i	i
c1: IF A.162/19E THEN m ELSE i - - deleting Contact headers.							

Prerequisite A.163/9 - - INVITE response

Prerequisite: A.164/14 - - 401 (Unauthorized)

Table A.211: Supported headers within the INVITE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
4	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
6	Proxy-Authenticate	[26] 20.27	m	m	[26] 20.27	m	m
10	Supported	[26] 20.37	m	m	[26] 20.37	i	i
15	WWW-Authenticate	[26] 20.44	o		[26] 20.44	o	

Prerequisite A.163/9 - - INVITE response

Prerequisite: A.164/17 OR A.164/23 OR A.164/30 OR A.164/36 OR A.164/50 OR A.164/51 - - 404, 413, 480, 486, 600, 603

Table A.212: Supported headers within the INVITE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
4	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
8	Retry-After	[26] 20.33	m	m	[26] 20.33	i	i
10	Supported	[26] 20.37	m	m	[26] 20.37	i	i
12	Via	[26] 20.42	m	m	[26] 20.42	m	m

Prerequisite A.163/9 - - INVITE response

Prerequisite: A.164/18 - - 405 (Method Not Allowed)

Table A.213: Supported headers within the INVITE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
2	Allow	[26] 20.5	m		[26] 20.5	m/o	
5	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
13	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/9 - - INVITE response

Prerequisite: A.164/20 - - 407 (Proxy Authentication Required)

Table A.214: Supported headers within the INVITE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
4	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
6	Proxy-Authenticate	[26] 20.27	m	m	[26] 20.27	m	m
10	Supported	[26] 20.37	m	m	[26] 20.37	i	i
11	WWW-Authenticate	[26] 20.44	m	m	[26] 20.44	i	i

Prerequisite A.163/9 - - INVITE response

Prerequisite: A.164/25 - - 415 (Unsupported Media Type)

Table A.215: Supported headers within the INVITE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Accept	[26] 20.1	m	m	[26] 20.1	i	i
2	Accept-Encoding	[26] 20.2	m	m	[26] 20.2	i	i
3	Accept-Language	[26] 20.3	m	m	[26] 20.3	i	i
3A	Allow	[26] 20.5	m	m	[26] 20.5	i	i
6	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
11	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/9 - - INVITE response

Prerequisite: A.164/27 - - 420 (Bad Extension)

Table A.216: Supported headers within the INVITE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
4	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
9	Supported	[26] 20.37	m	m	[26] 20.37	i	i
10	Unsupported	[26] 20.40	m	m	[26] 20.40	c3	c3
c3:	IF A.162/18 THEN m ELSE i - - reading the contents of the Unsupported header before proxying the 420 response to a method other than REGISTER.						

Prerequisite A.163/9 - - INVITE response

Prerequisite: A.164/28 OR A.164/41A - - 421 (Extension Required), 494 (Security Agreement Required)

Table A.216A: Supported headers within the INVITE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
2	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
3	Security-Server	[48] 2	c1	c1	[48] 2	n/a	n/a
4	Supported	[26] 20.37	m	m	[26] 20.37	m	m
c1:	IF A.162/47 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol.						

Prerequisite A.163/9 - - INVITE response

Prerequisite: A.164/34 - - 484 (Address Incomplete)

Table A.217: Supported headers within the INVITE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
4	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
9	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/9 - - INVITE response

Prerequisite: A.164/42 - - 500 (Server Internal Error)

Table A.217A: Supported headers within the INVITE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
4	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
8	Retry-After	[26] 20.33	m	m	[26] 20.33	i	i
10	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/9 - - INVITE response

Prerequisite: A.164/45 - - 503 (Service Unavailable)

Table A.217B: Supported headers within the INVITE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
4	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
8	Retry-After	[26] 20.33	m	m	[26] 20.33	i	i
10	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/9 - - INVITE response

Table A.218: Supported message bodies within the INVITE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1							

A.2.2.4.7A MESSAGE method

Prerequisite A.163/9A - - MESSAGE request

Table A.218A: Supported headers within the MESSAGE request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[50] 10	i	i
2	Allow-Events	[28] 8.2.2	m	m	[28] 8.2.2	c1	c1
3	Authorization	[26] 20.7	m	m	[26] 20.7	i	i
4	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
5	Call-Info	[26] 20.9	m	m	[26] 20.9	c4	c4
6	Content-Disposition	[26] 20.11	m	m	[26] 20.11	i	i
7	Content-Encoding	[26] 20.12	m	m	[26] 20.12	i	i
8	Content-Language	[26] 20.13	m	m	[26] 20.13	i	i
9	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
10	Content-Type	[26] 20.15	m	m	[26] 20.15	i	i
11	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
12	Date	[26] 20.17	m	m	[26] 20.17	c2	c2
13	Expires	[26] 20.19	m	m	[26] 20.19	i	i
14	From	[26] 20.20	m	m	[26] 20.20	m	m
15	In-Reply-To	[26] 20.21	m	m	[50] 10	i	i
16	Max-Forwards	[26] 20.22	m	m	[26] 20.22	m	m
17	MIME-Version	[26] 20.24	m	m	[26] 20.24	i	i
18	Organization	[26] 20.25	m	m	[26] 20.25	c3	c3
18A	P-Access-Network-Info	[52] 4.4	c23	c23	[52] 4.4	c24	c24
18B	P-Asserted-Identity	[34] 9.1	c10	c10	[34] 9.1	c11	c11
18C	P-Called-Party-ID	[52] 4.2	c14	c14	[52] 4.2	c15	c16
18D	P-Charging-Function-Addresses	[52] 4.5	c21	c21	[52] 4.5	c22	c22
18E	P-Charging-Vector	[52] 4.6	c19	c19	[52] 4.6	c20	c20
18F	P-Preferred-Identity	[34] 9.2	x	x	[34] 9.2	c9	c9
18G	P-Visited-Network-ID	[52] 4.3	c17	n/a	[52] 4.3	c18	n/a
19	Priority	[26] 20.26	m	m	[26] 20.26	i	i
19A	Privacy	[33] 4.2	c12	c12	[33] 4.2	c13	c13
20	Proxy-Authorization	[26] 20.28	m	m	[26] 20.28	c8	c8
21	Proxy-Require	[26] 20.29	m	m	[26] 20.29	m	m
22	Record-Route	[26] 20.30	m	m	[26] 20.30	c7	c7
23	Reply-To	[26] 20.31	m	m	[26] 20.31	i	i
24	Require	[26] 20.32	m	m	[26] 20.32	c5	c5
25	Route	[26] 20.34	m	m	[26] 20.34	m	m
25A	Security-Client	[48] 2.3.1	x	x	[48] 2.3.1	c25	c25
25B	Security-Verify	[48] 2.3.1	x	x	[48] 2.3.1	c25	c25
26	Subject	[26] 20.36	m	m	[26] 20.36	i	i
27	Supported	[26] 20.37	m	m	[26] 20.37	c6	c6
28	Timestamp	[26] 20.38	m	m	[26] 20.38	i	i
29	To	[26] 20.39	m	m	[26] 20.39	m	m
30	User-Agent	[26] 20.41	m	m	[26] 20.41	i	i
31	Via	[26] 20.42	m	m	[26] 20.42	m	m

c1:	IF A.4/20 THEN m ELSE i - - SIP specific event notification extension.
c2:	IF A.162/9 THEN m ELSE i - - insertion of date in requests and responses.
c3:	IF A.162/19A OR A.162/19B THEN m ELSE i - - reading, adding or concatenating the Organization header.
c4:	IF A.162/19C OR A.162/19D THEN m ELSE i - - reading, adding or concatenating the Call-Info header.
c5:	IF A.162/11 OR A.162/13 THEN m ELSE i - - reading the contents of the Require header before proxying the request or response or adding or modifying the contents of the Require header before proxying the request or response for methods other than REGISTER.
c6:	IF A.162/16 THEN m ELSE i - - reading the contents of the Supported header before proxying the response.
c7:	IF A.162/14 THEN o ELSE i - - the requirement to be able to insert itself in the subsequent transactions in a dialog.
c8:	IF A.162/8A THEN m ELSE i - - authentication between UA and proxy.
c9:	IF A.162/30A THEN m ELSE n/a - - act as first entity within the trust domain for asserted identity.
c10:	IF A.162/30 THEN m ELSE n/a - - extensions to the Session Initiation Protocol (SIP) for asserted identity within trusted networks.
c11:	IF A.162/30A or A.162/30B THEN m ELSE i - - extensions to the Session Initiation Protocol (SIP) for asserted identity within trusted networks or subsequent entity within trust network that can route outside the trust network.
c12:	IF A.162/31 THEN m ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).
c13:	IF A.162/31D OR A.162/31G THEN m ELSE IF A.162/31C THEN i ELSE n/a - - application of the privacy option "header" or application of the privacy option "id" or passing on of the Privacy header transparently.
c14:	IF A.162/37 THEN m ELSE n/a - - the P-Called-Party-ID header extension.
c15:	IF A.162/37 THEN i ELSE n/a - - the P-Called-Party-ID header extension.
c16:	IF A.162/37 AND A.3/2 THEN m ELSE IF A.162/37 AND A.3/3 THEN i ELSE n/a - - the P-Called-Party-ID header extension and P-CSCF or I-CSCF.
c17:	IF A.162/38 THEN m ELSE n/a - - the P-Visited-Network-ID header extension.
c18:	IF A.162/39 THEN m ELSE i - - reading, or deleting the P-Visited-Network-ID header before proxying the request or response.
c19:	IF A.162/45 THEN m ELSE n/a - - the P-Charging-Vector header extension.
c20:	IF A.162/46 THEN m ELSE IF A.162/45 THEN i ELSE n/a - - adding, deleting, reading or modifying the P-Charging-Vector header before proxying the request or response or the P-Charging-Vector header extension.
c21:	IF A.162/44 THEN m ELSE n/a - - the P-Charging-Function-Addresses header extension.
c22:	IF A.162/44A THEN m ELSE IF A.162/44 THEN i ELSE n/a - - adding, deleting or reading the P-Charging-Function-Addresses header before proxying the request or response, or the P-Charging-Function-Addresses header extension.
c23:	IF A.162/43 THEN x ELSE IF A.162/41 THEN m ELSE n/a - - act as subsequent entity within trust network for access network information that can route outside the trust network, the P-Access-Network-Info header extension.
c24:	IF A.162/43 THEN m ELSE IF A.162/41 THEN i ELSE n/a - - act as subsequent entity within trust network for access network information that can route outside the trust network, the P-Access-Network-Info header extension.
c25:	IF A.4/37 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol.
NOTE:	c1 refers to the UA role major capability as this is the case of a proxy that also acts as a UA specifically for SUBSCRIBE and NOTIFY.

Prerequisite A.163/9A - - MESSAGE request

Table A.218B: Supported message bodies within the MESSAGE request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1							

Prerequisite A.163/9B - - MESSAGE response

Table A.218C: Supported headers within the MESSAGE response - all remaining status-codes

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
2	Call-Info	[26] 20.9	m	m	[26] 20.9	c3	c3
3	Content-Disposition	[26] 20.11	m	m	[26] 20.11	i	i
4	Content-Encoding	[26] 20.12	m	m	[26] 20.12	i	i
5	Content-Language	[26] 20.13	m	m	[26] 20.13	i	i
6	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
7	Content-Type	[26] 20.15	m	m	[26] 20.15	i	i
8	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
9	Date	[26] 20.17	m	m	[26] 20.17	c1	c1
10	From	[26] 20.20	m	m	[26] 20.20	m	m
11	MIME-Version	[26] 20.24	m	m	[26] 20.24	i	i
12	Organization	[26] 20.25	m	m	[26] 20.25	c2	c2
12A	P-Access-Network-Info	[52] 4.4	c13	c13	[52] 4.4	c14	c14
12B	P-Asserted-Identity	[34] 9.1	c5	c5	[34] 9.1	c6	c6
12C	P-Charging-Function-Addresses	[52] 4.5	c11	c11	[52] 4.5	c12	c12
12D	P-Charging-Vector	[52] 4.6	c9	n/a	[52] 4.6	c10	n/a
12E	P-Preferred-Identity	[34] 9.2	x	x	[34] 9.2	c4	n/a
12F	Privacy	[33] 4.2	c7	c7	[33] 4.2	c8	c8
12G	Require	[26] 20.32	m	m	[26] 20.32	c15	c15
13	Server	[26] 20.35	m	m	[26] 20.35	i	i
14	Timestamp	[26] 20.38	i	i	[26] 20.38	i	i
15	To	[26] 20.39	m	m	[26] 20.39	m	m
16	User-Agent	[26] 20.41	m	m	[26] 20.41	i	i
17	Via	[26] 20.42	m	m	[26] 20.42	m	m
18	Warning	[26] 20.43	m	m	[26] 20.43	i	i
c1:	IF A.162/9 THEN m ELSE i - - insertion of date in requests and responses.						
c2:	IF A.162/19A OR A.162/19B THEN m ELSE i - - reading, adding or concatenating the Organization header.						
c3:	IF A.162/19C OR A.162/19D THEN m ELSE i - - reading, adding or concatenating the Call-Info header.						
c4:	IF A.162/30A THEN m ELSE n/a - - act as first entity within the trust domain for asserted identity.						
c5:	IF A.162/30 THEN m ELSE n/a - - extensions to the Session Initiation Protocol (SIP) for asserted identity within trusted networks.						
c6:	IF A.162/30A or A.162/30B THEN m ELSE i - - extensions to the Session Initiation Protocol (SIP) for asserted identity within trusted networks or subsequent entity within trust network that can route outside the trust network.						
c7:	IF A.162/31 THEN m ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).						
c8:	IF A.162/31D OR A.162/31G THEN m ELSE IF A.162/31C THEN i ELSE n/a - - application of the privacy option "header" or application of the privacy option "id" or passing on of the Privacy header transparently.						
c9:	IF A.162/45 THEN m ELSE n/a - - the P-Charging-Vector header extension.						
c10:	IF A.162/46 THEN m ELSE IF A.162/45 THEN i ELSE n/a - - adding, deleting, reading or modifying the P-Charging-Vector header before proxying the request or response or the P-Charging-Vector header extension.						
c11:	IF A.162/44 THEN m ELSE n/a - - the P-Charging-Function-Addresses header extension.						
c12:	IF A.162/44A THEN m ELSE IF A.162/44 THEN i ELSE n/a - - adding, deleting or reading the P-Charging-Function-Addresses header before proxying the request or response, or the P-Charging-Function-Addresses header extension.						
c13:	IF A.162/43 THEN x ELSE IF A.162/41 THEN m ELSE n/a - - act as subsequent entity within trust network for access network information that can route outside the trust network, the P-Access-Network-Info header extension.						
c14:	IF A.162/43 THEN m ELSE IF A.162/41 THEN i ELSE n/a - - act as subsequent entity within trust network for access network information that can route outside the trust network, the P-Access-Network-Info header extension.						
c15:	IF A.162/11 OR A.162/13 THEN m ELSE i - - reading the contents of the Require header before proxying the request or response or adding or modifying the contents of the Require header before proxying the request or response for methods other than REGISTER.						

Prerequisite A.163/9B - - MESSAGE response

Prerequisite: A.164/6 - - 2xx

Table A.218D: Supported headers within the MESSAGE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
2	Authentication-Info	[26] 20.6	m	m	[26] 20.6	i	i
4	Record-Route	[26] 20.30	m	m	[26] 20.30	c3	c3
6	Supported	[26] 20.37	m	m	[26] 20.37	i	i
c3:	IF A.162/15 THEN o ELSE i - - the requirement to be able to use separate URIs in the upstream direction and downstream direction when record routeing.						

Prerequisite A.163/9B - - MESSAGE response

Prerequisite: A.164/8 OR A.164/9 OR A.164/10 OR A.164/11 OR A.164/12 OR A.164/35 - - 3xx or 485 (Ambiguous)

Table A.218E: Supported headers within the MESSAGE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[50] 10	i	i
2	Contact	[26] 20.10	m	m	[26] 20.10	c1	c1
3	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
5	Supported	[26] 20.37	m	m	[26] 20.37	i	i
c1:	IF A.162/19E THEN m ELSE i - - deleting Contact headers.						

Prerequisite A.163/9B - - MESSAGE response

Prerequisite: A.164/14 - - 401 (Unauthorized)

Table A.218F: Supported headers within the MESSAGE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[50] 10	i	i
2	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
3	Proxy-Authenticate	[26] 20.27	m	m	[26] 20.27	m	m
5	Supported	[26] 20.37	m	m	[26] 20.37	i	i
6	WWW-Authenticate	[26] 20.44	m	m	[26] 20.44	i	i

Prerequisite A.163/9B - - MESSAGE response

Prerequisite: A.164/17 OR A.164/23 OR A.164/30 OR A.164/36 OR A.164/42 OR A.164/45 OR A.164/50 OR A.164/51 - - 404, 413, 480, 486, 500, 503, 600, 603

Table A.218G: Supported headers within the MESSAGE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[50] 10	i	i
2	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
4	Retry-After	[26] 20.33	m	m	[26] 20.33	i	i
5	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/9B - - MESSAGE response

Prerequisite: A.164/18 - - 405 (Method Not Allowed)

Table A.218H: Supported headers within the MESSAGE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
2	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
4	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/9B - - MESSAGE response

Prerequisite: A.164/20 - - 407 (Proxy Authentication Required)

Table A.218I: Supported headers within the MESSAGE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[50] 10	i	i
2	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
3	Proxy-Authenticate	[26] 20.27	m	m	[26] 20.27	m	m
5	Supported	[26] 20.37	m	m	[26] 20.37	i	i
6	WWW-Authenticate	[26] 20.44	m	m	[26] 20.44	i	i

Prerequisite A.163/9B - - MESSAGE response

Prerequisite: A.164/25 - - 415 (Unsupported Media Type)

Table A.218J: Supported headers within the MESSAGE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Accept	[26] 20.1	m	m	[26] 20.1	i	i
2	Accept-Encoding	[26] 20.2	m	m	[26] 20.2	i	i
3	Accept-Language	[26] 20.3	m	m	[26] 20.3	i	i
4	Allow	[26] 20.5	m	m	[50] 10	i	i
5	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
7	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/9B - - MESSAGE response

Prerequisite: A.164/27 - - 420 (Bad Extension)

Table A.218K: Supported headers within the MESSAGE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[50] 10	i	i
2	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
4	Supported	[26] 20.37	m	m	[26] 20.37	i	i
5	Unsupported	[26] 20.40	m	m	[26] 20.40	c3	c3
c3:	IF A.162/18 THEN m ELSE i - - reading the contents of the Unsupported header before proxying the 420 response to a method other than REGISTER.						

Prerequisite A.163/9B - - MESSAGE response

Prerequisite: A.164/28 OR A.164/41A - - 421 (Extension Required), 494 (Security Agreement Required)

Table A.218L: Supported headers within the MESSAGE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
2	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
3	Security-Server	[48] 2	c1	c1	[48] 2	n/a	n/a
4	Supported	[26] 20.37	m	m	[26] 20.37	m	m
c1:	IF A.162/47 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol.						

Prerequisite A.163/9B - - MESSAGE response

Prerequisite: A.164/34 - - 484 (Address Incomplete)

Table A.218M: Supported headers within the MESSAGE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[50] 10	i	i
3	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
5	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/9B - - MESSAGE response

Table A.218N: Supported message bodies within the MESSAGE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1							

A.2.2.4.8 NOTIFY method

Prerequisite A.163/10 - - NOTIFY request

Table A.219: Supported headers within the NOTIFY request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Accept	[26] 20.1	m	m	[26] 20.1	i	i
2	Accept-Encoding	[26] 20.2	m	m	[26] 20.2	i	i
3	Accept-Language	[26] 20.3	m	m	[26] 20.3	i	i
3A	Allow	[26] 20.5	m	m	[26] 20.5	i	i
4	Allow-Events	[28] 8.2.2	m	m	[28] 8.2.2	c1	c1
5	Authorization	[26] 20.7	m	m	[26] 20.7	i	i
6	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
6A	Contact	[26] 20.10	m	m	[26] 20.10	i	i
7	Content-Disposition	[26] 20.11	m	m	[26] 20.11	i	i
8	Content-Encoding	[26] 20.12	m	m	[26] 20.12	i	i
9	Content-Language	[26] 20.13	m	m	[26] 20.13	i	i
10	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
11	Content-Type	[26] 20.15	m	m	[26] 20.15	i	i
12	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
13	Date	[26] 20.17	m	m	[26] 20.17	c2	c2
14	Event	[28] 8.2.1	m	m	[28] 8.2.1	m	m
15	From	[26] 20.20	m	m	[26] 20.20	m	m
16	Max-Forwards	[26] 20.22	m	m	[26] 20.22	m	m
17	MIME-Version	[26] 20.24	m	m	[26] 20.24	i	i
17A	P-Access-Network-Info	[52] 4.4	c16	c16	[52] 4.4	c17	c17
17B	P-Asserted-Identity	[34] 9.1	c8	c8	[34] 9.1	c9	c9
17C	P-Charging-Function-Addresses	[52] 4.5	c14	c14	[52] 4.5	c15	c15
17D	P-Charging-Vector	[52] 4.6	c12	n/a	[52] 4.6	c13	n/a
17E	P-Preferred-Identity	[34] 9.2	x	x	[34] 9.2	c3	n/a
17F	Privacy	[33] 4.2	c10	c10	[33] 4.2	c11	c11
18	Proxy-Authorization	[26] 20.28	m	m	[26] 20.28	c4	c4
19	Proxy-Require	[26] 20.29	m	m	[26] 20.29	m	m
20	Record-Route	[26] 20.30	m	m	[26] 20.30	c7	c7
21	Require	[26] 20.32	m	m	[26] 20.32	c5	c5
22	Route	[26] 20.34	m	m	[26] 20.34	m	m
22A	Security-Client	[48] 2.3.1	x	x	[48] 2.3.1	c18	c18
22B	Security-Verify	[48] 2.3.1	x	x	[48] 2.3.1	c18	c18
23	Subscription-State	[28] 8.2.3	m	m	[28] 8.2.3	i	i
24	Supported	[26] 20.37	m	m	[26] 20.37	c6	c6
25	Timestamp	[26] 20.38	m	m	[26] 20.38	i	i
26	To	[26] 20.39	m	m	[26] 20.39	m	m
27	User-Agent	[26] 20.41	m	m	[26] 20.41	i	i
28	Via	[26] 20.42	m	m	[26] 20.42	m	m

c1:	IF A.4/20 THEN m ELSE i - - SIP specific event notification extension.
c2:	IF A.162/9 THEN m ELSE i - - insertion of date in requests and responses.
c3:	IF A.162/30A THEN m ELSE n/a - - act as first entity within the trust domain for asserted identity.
c4:	IF A.162/8A THEN m ELSE i - - authentication between UA and proxy.
c5:	IF A.162/11 OR A.162/13 THEN m ELSE i - - reading the contents of the Require header before proxying the request or response or adding or modifying the contents of the Require header before proxying the request or response for methods other than REGISTER.
c6:	IF A.162/16 THEN m ELSE i - - reading the contents of the Supported header before proxying the response.
c7:	IF A.162/14 THEN (IF A.162/22 OR A.162/27 THEN m ELSE o) ELSE i - - the requirement to be able to insert itself in the subsequent transactions in a dialog or (the REFER method or SIP specific event notification).
c8:	IF A.162/30 THEN m ELSE n/a - - extensions to the Session Initiation Protocol (SIP) for asserted identity within trusted networks.
c9:	IF A.162/30A or A.162/30B THEN m ELSE i - - extensions to the Session Initiation Protocol (SIP) for asserted identity within trusted networks or subsequent entity within trust network that can route outside the trust network.
c10:	IF A.162/31 THEN m ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).
c11:	IF A.162/31D OR A.162/31G THEN m ELSE IF A.162/31C THEN i ELSE n/a - - application of the privacy option "header" or application of the privacy option "id" or passing on of the Privacy header transparently.
c12:	IF A.162/45 THEN m ELSE n/a - - the P-Charging-Vector header extension.
c13:	IF A.162/46 THEN m ELSE IF A.162/45 THEN i ELSE n/a - - adding, deleting, reading or modifying the P-Charging-Vector header before proxying the request or response or the P-Charging-Vector header extension.
c14:	IF A.162/44 THEN m ELSE n/a - - the P-Charging-Function-Addresses header extension.
c15:	IF A.162/44A THEN m ELSE IF A.162/44 THEN i ELSE n/a - - adding, deleting or reading the P-Charging-Function-Addresses header before proxying the request or response, or the P-Charging-Function-Addresses header extension.
c16:	IF A.162/43 THEN x ELSE IF A.162/41 THEN m ELSE n/a - - act as subsequent entity within trust network for access network information that can route outside the trust network, the P-Access-Network-Info header extension.
c17:	IF A.162/43 THEN m ELSE IF A.162/41 THEN i ELSE n/a - - act as subsequent entity within trust network for access network information that can route outside the trust network, the P-Access-Network-Info header extension.
c18:	IF A.4/37 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol.
NOTE:	c1 refers to the UA role major capability as this is the case of a proxy that also acts as a UA specifically for SUBSCRIBE and NOTIFY.

Prerequisite A.163/10 - - NOTIFY request

Table A.220: Supported message bodies within the NOTIFY request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	sipfrag	[37] 2	m	m	[37] 2	i	i

Prerequisite A.163/11 - - NOTIFY response

Table A.221: Supported headers within the NOTIFY response - all status-codes

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
2	Content-Disposition	[26] 20.11	m	m	[26] 20.11	i	i
3	Content-Encoding	[26] 20.12	m	m	[26] 20.12	i	i
4	Content-Language	[26] 20.13	m	m	[26] 20.13	i	i
5	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
6	Content-Type	[26] 20.15	m	m	[26] 20.15	i	i
7	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
8	Date	[26] 20.17	m	m	[26] 20.17	c1	c1
9	From	[26] 20.20	m	m	[26] 20.20	m	m
10	MIME-Version	[26] 20.24	m	m	[26] 20.24	i	i
10A	P-Access-Network-Info	[52] 4.4	c11	c11	[52] 4.4	c12	c12
10B	P-Asserted-Identity	[34] 9.1	c3	c3	[34] 9.1	c4	c4
10C	P-Charging-Function-Addresses	[52] 4.5	c9	c9	[52] 4.5	c10	c10
10D	P-Charging-Vector	[52] 4.6	c7	n/a	[52] 4.6	c8	n/a
10E	P-Preferred-Identity	[34] 9.2	x	x	[34] 9.2	c2	n/a
10F	Privacy	[33] 4.2	c5	c5	[33] 4.2	c6	c6
10G	Require	[26] 20.32	m	m	[26] 20.32	c13	c13
10H	Server	[26] 20.35	m	m	[26] 20.35	i	i
11	Timestamp	[26] 20.38	m	m	[26] 20.38	i	i
12	To	[26] 20.39	m	m	[26] 20.39	m	m
12A	User-Agent	[26] 20.41	m	m	[26] 20.41	i	i
13	Via	[26] 20.42	m	m	[26] 20.42	m	m
14	Warning	[26] 20.43	m	m	[26] 20.43	i	i
c1:	IF A.162/9 THEN m ELSE i - - insertion of date in requests and responses.						
c2:	IF A.162/30A THEN m ELSE n/a - - act as first entity within the trust domain for asserted identity.						
c3:	IF A.162/30 THEN m ELSE n/a - - extensions to the Session Initiation Protocol (SIP) for asserted identity within trusted networks.						
c4:	IF A.162/30A or A.162/30B THEN m ELSE i - - extensions to the Session Initiation Protocol (SIP) for asserted identity within trusted networks or subsequent entity within trust network that can route outside the trust network.						
c5:	IF A.162/31 THEN m ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).						
c6:	IF A.162/31D OR A.162/31G THEN m ELSE IF A.162/31C THEN i ELSE n/a - - application of the privacy option "header" or application of the privacy option "id" or passing on of the Privacy header transparently.						
c7:	IF A.162/45 THEN m ELSE n/a - - the P-Charging-Vector header extension.						
c8:	IF A.162/46 THEN m ELSE IF A.162/45 THEN i ELSE n/a - - adding, deleting, reading or modifying the P-Charging-Vector header before proxying the request or response or the P-Charging-Vector header extension.						
c9:	IF A.162/44 THEN m ELSE n/a - - the P-Charging-Function-Addresses header extension.						
c10:	IF A.162/44A THEN m ELSE IF A.162/44 THEN i ELSE n/a - - adding, deleting or reading the P-Charging-Function-Addresses header before proxying the request or response, or the P-Charging-Function-Addresses header extension.						
c11:	IF A.162/43 THEN x ELSE IF A.162/41 THEN m ELSE n/a - - act as subsequent entity within trust network for access network information that can route outside the trust network, the P-Access-Network-Info header extension.						
c12:	IF A.162/43 THEN m ELSE IF A.162/41 THEN i ELSE n/a - - act as subsequent entity within trust network for access network information that can route outside the trust network, the P-Access-Network-Info header extension.						
c13:	IF A.162/11 OR A.162/13 THEN m ELSE i - - reading the contents of the Require header before proxying the request or response or adding or modifying the contents of the Require header before proxying the request or response for methods other than REGISTER.						

Prerequisite A.163/11 - - NOTIFY response

Prerequisite: A.164/6 AND A.164/7 - - 2xx

Table A.222: Supported headers within the NOTIFY response

Item	Header	Sending	Receiving
------	--------	---------	-----------

		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	m	m	[26] 20.5	i	i
1	Authentication-Info	[26] 20.6	m	m	[26] 20.6	i	i
1A	Contact	[26] 20.10	m	m	[26] 20.10	i	i
2	Record-Route	[26] 20.30	m	m	[26] 20.30	c3	c3
5	Supported	[26] 20.37	m	m	[26] 20.37	i	i
c3: IF A.162/15 THEN m ELSE i - - the requirement to be able to use separate URIs in the upstream direction and downstream direction when record routeing.							

Prerequisite A.163/11 - - NOTIFY response

Prerequisite: A.164/8 OR A.164/9 OR A.164/10 OR A.164/11 OR A.164/12 OR A.164/35 - - 3xx or 485 (Ambiguous)

Table A.223: Supported headers within the NOTIFY response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	m	m	[26] 20.5	i	i
1	Contact	[26] 20.10	m	m	[26] 20.10	c1	c1
2	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
5	Supported	[26] 20.37	m	m	[26] 20.37	i	i
c1: IF A.162/19E THEN m ELSE i - - deleting Contact headers.							

Prerequisite A.163/11 - - NOTIFY response

Prerequisite: A.164/14 - - 401 (Unauthorized)

Table A.224: Supported headers within the NOTIFY response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	m	m	[26] 20.5	i	i
1	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
2	Proxy-Authenticate	[26] 20.27	m	m	[26] 20.27	m	m
5	Supported	[26] 20.37	m	m	[26] 20.37	i	i
8	WWW-Authenticate	[26] 20.44	m	m	[26] 20.44	i	i

Prerequisite A.163/11 - - NOTIFY response

Prerequisite: A.164/17 OR A.164/23 OR A.164/30 OR A.164/36 OR A.164/42 OR A.164/45 OR A.164/50 OR A.164/51 - - 404, 413, 480, 486, 500, 503, 600, 603

Table A.225: Supported headers within the NOTIFY response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	m	m	[26] 20.5	i	i
1	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
3	Retry-After	[26] 20.33	m	m	[26] 20.33	i	i
5	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/11 - - NOTIFY response

Prerequisite: A.164/18 - - 405 (Method Not Allowed)

Table A.226: Supported headers within the NOTIFY response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
2	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
5	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/11 - - NOTIFY response

Prerequisite: A.164/20 - - 407 (Proxy Authentication Required)

Table A.227: Supported headers within the NOTIFY response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	m	m	[26] 20.5	i	i
1	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
2	Proxy-Authenticate	[26] 20.27	m	m	[26] 20.27	m	m
5	Supported	[26] 20.37	m	m	[26] 20.37	i	i
6	WWW-Authenticate	[26] 20.44	m	m	[26] 20.44	i	i

Prerequisite A.163/11 - - NOTIFY response

Prerequisite: A.164/25 - - 415 (Unsupported Media Type)

Table A.228: Supported headers within the NOTIFY response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Accept	[26] 20.1	m	m	[26] 20.1	i	i
2	Accept-Encoding	[26] 20.2	m	m	[26] 20.2	i	i
3	Accept-Language	[26] 20.3	m	m	[26] 20.3	i	i
3A	Allow	[26] 20.5	m	m	[26] 20.5	i	i
4	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
7	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/11 - - NOTIFY response

Prerequisite: A.164/27 - - 420 (Bad Extension)

Table A.229: Supported headers within the NOTIFY response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	m	m	[26] 20.5	i	i
1	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
4	Supported	[26] 20.37	m	m	[26] 20.37	i	i
5	Unsupported	[26] 20.40	m	m	[26] 20.40	c3	c3
c3:	IF A.162/18 THEN m ELSE i - - reading the contents of the Unsupported header before proxying the 420 response to a method other than REGISTER.						

Prerequisite A.163/11 -- NOTIFY response

Prerequisite: A.164/28 OR A.164/41A -- 421 (Extension Required), 494 (Security Agreement Required)

Table A.229A: Supported headers within the NOTIFY response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
2	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
3	Security-Server	[48] 2	c1	c1	[48] 2	n/a	n/a
4	Supported	[26] 20.37	m	m	[26] 20.37	m	m
c1: IF A.162/47 THEN m ELSE n/a -- security mechanism agreement for the session initiation protocol.							

Prerequisite A.163/11 -- NOTIFY response

Prerequisite: A.164/34 -- 484 (Address Incomplete)

Table A.230: Supported headers within the NOTIFY response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	m	m	[26] 20.5	i	i
1	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
4	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/11 -- NOTIFY response

Prerequisite: A.164/39 -- 489 (Bad Event)

Table A.231: Supported headers within the NOTIFY response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	m	m	[26] 20.5	i	i
1	Allow-Events	[28] 8.2.2	m	m	[28] 8.2.2	c1	c1
3	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
c1: IF A.4/20 THEN m ELSE i -- SIP specific event notification extension.							
NOTE: c1 refers to the UA role major capability as this is the case of a proxy that also acts as a UA specifically for SUBSCRIBE and NOTIFY.							

Prerequisite A.163/11 -- NOTIFY response

Table A.232: Supported message bodies within the NOTIFY response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1							

A.2.2.4.9 OPTIONS method

Prerequisite A.163/12 - - OPTIONS request

Table A.233: Supported headers within the OPTIONS request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Accept	[26] 20.1	m	m	[26] 20.1	i	i
2	Accept-Encoding	[26] 20.2	m	m	[26] 20.2	i	i
3	Accept-Language	[26] 20.3	m	m	[26] 20.3	i	i
3A	Allow	[26] 20.5	m	m	[26] 20.5	i	i
4	Allow-Events	[28] 8.2.2	m	m	[28] 8.2.2	c1	c1
5	Authorization	[26] 20.7	m	m	[26] 20.7	i	i
6	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
7	Call-Info	[26] 20.9	m	m	[26] 20.9	c4	c4
8	Contact	[26] 20.10	m	m	[26] 20.10	i	i
9	Content-Disposition	[26] 20.11	m	m	[26] 20.11	i	i
10	Content-Encoding	[26] 20.12	m	m	[26] 20.12	i	i
11	Content-Language	[26] 20.13	m	m	[26] 20.13	i	i
12	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
13	Content-Type	[26] 20.15	m	m	[26] 20.15	i	i
14	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
15	Date	[26] 20.17	m	m	[26] 20.17	c2	c2
16	From	[26] 20.20	m	m	[26] 20.20	m	m
17	Max-Forwards	[26] 20.22	m	m	[26] 20.22	m	m
18	MIME-Version	[26] 20.24	m	m	[26] 20.24	i	i
19	Organization	[26] 20.25	m	m	[26] 20.25	c3	c3
19A	P-Access-Network-Info	[52] 4.4	c23	c23	[52] 4.4	c24	c24
19B	P-Asserted-Identity	[34] 9.1	c10	c10	[34] 9.1	c11	c11
19C	P-Called-Party-ID	[52] 4.2	c14	c14	[52] 4.2	c15	c16
19D	P-Charging-Function-Addresses	[52] 4.5	c21	c21	[52] 4.5	c22	c22
19E	P-Charging-Vector	[52] 4.6	c19	c19	[52] 4.6	c20	c20
19F	P-Preferred-Identity	[34] 9.2	x	x	[34] 9.2	c9	c9
19G	P-Visited-Network-ID	[52] 4.3	c17	n/a	[52] 4.3	c18	n/a
19H	Privacy	[33] 4.2	c12	c12	[33] 4.2	c13	c13
20	Proxy-Authorization	[26] 20.28	m	m	[26] 20.28	c8	c8
21	Proxy-Require	[26] 20.29	m	m	[26] 20.29	m	m
22	Record-Route	[26] 20.30	m	m	[26] 20.30	c7	c7
23	Require	[26] 20.32	m	m	[26] 20.32	c5	c5
24	Route	[26] 20.34	m	m	[26] 20.34	m	m
24A	Security-Client	[48] 2.3.1	x	x	[48] 2.3.1	c25	c25
24B	Security-Verify	[48] 2.3.1	x	x	[48] 2.3.1	c25	c25
25	Supported	[26] 20.37	m	m	[26] 20.37	c6	c6
26	Timestamp	[26] 20.38	m	m	[26] 20.38	i	i
27	To	[26] 20.39	m	m	[26] 20.39	m	m
28	User-Agent	[26] 20.41	m	m	[26] 20.41	i	i
29	Via	[26] 20.42	m	m	[26] 20.42	m	m

c1:	IF A.4/20 THEN m ELSE i - - SIP specific event notification extension.
c2:	IF A.162/9 THEN m ELSE i - - insertion of date in requests and responses.
c3:	IF A.162/19A OR A.162/19B THEN m ELSE i - - reading, adding or concatenating the Organization header.
c4:	IF A.162/19C OR A.162/19D THEN m ELSE i - - reading, adding or concatenating the Call-Info header.
c5:	IF A.162/11 OR A.162/13 THEN m ELSE i - - reading the contents of the Require header before proxying the request or response or adding or modifying the contents of the Require header before proxying the request or response for methods other than REGISTER.
c6:	IF A.162/16 THEN m ELSE i - - reading the contents of the Supported header before proxying the response.
c7:	IF A.162/14 THEN o ELSE i - - the requirement to be able to insert itself in the subsequent transactions in a dialog.
c8:	IF A.162/8A THEN m ELSE i - - authentication between UA and proxy.
c9:	IF A.162/30A THEN m ELSE n/a - - act as first entity within the trust domain for asserted identity.
c10:	IF A.162/30 THEN m ELSE n/a - - extensions to the Session Initiation Protocol (SIP) for asserted identity within trusted networks.
c11:	IF A.162/30A or A.162/30B THEN m ELSE i - - extensions to the Session Initiation Protocol (SIP) for asserted identity within trusted networks or subsequent entity within trust network that can route outside the trust network.
c12:	IF A.162/31 THEN m ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).
c13:	IF A.162/31D OR A.162/31G THEN m ELSE IF A.162/31C THEN i ELSE n/a - - application of the privacy option "header" or application of the privacy option "id" or passing on of the Privacy header transparently.
c14:	IF A.162/37 THEN m ELSE n/a - - the P-Called-Party-ID header extension.
c15:	IF A.162/37 THEN i ELSE n/a - - the P-Called-Party-ID header extension.
c16:	IF A.162/37 AND A.3/2 THEN m ELSE IF A.162/37 AND A.3/3 THEN i ELSE n/a - - the P-Called-Party-ID header extension and P-CSCF or I-CSCF.
c17:	IF A.162/38 THEN m ELSE n/a - - the P-Visited-Network-ID header extension.
c18:	IF A.162/39 THEN m ELSE i - - reading, or deleting the P-Visited-Network-ID header before proxying the request or response.
c19:	IF A.162/45 THEN m ELSE n/a - - the P-Charging-Vector header extension.
c20:	IF A.162/46 THEN m ELSE IF A.162/45 THEN i ELSE n/a - - adding, deleting, reading or modifying the P-Charging-Vector header before proxying the request or response or the P-Charging-Vector header extension.
c21:	IF A.162/44 THEN m ELSE n/a - - the P-Charging-Function-Addresses header extension.
c22:	IF A.162/44A THEN m ELSE IF A.162/44 THEN i ELSE n/a - - adding, deleting or reading the P-Charging-Function-Addresses header before proxying the request or response, or the P-Charging-Function-Addresses header extension.
c23:	IF A.162/43 THEN x ELSE IF A.162/41 THEN m ELSE n/a - - act as subsequent entity within trust network for access network information that can route outside the trust network, the P-Access-Network-Info header extension.
c24:	IF A.162/43 THEN m ELSE IF A.162/41 THEN i ELSE n/a - - act as subsequent entity within trust network for access network information that can route outside the trust network, the P-Access-Network-Info header extension.
c25:	IF A.4/37 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol.
NOTE:	c1 refers to the UA role major capability as this is the case of a proxy that also acts as a UA specifically for SUBSCRIBE and NOTIFY.

Prerequisite A.163/12 - - OPTIONS request

Table A.234: Supported message bodies within the OPTIONS request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1							

Prerequisite A.163/13 - - OPTIONS response

Prerequisite: A.164/1 - - 100 (Trying)

Table A.235: Supported headers within the OPTIONS response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
2	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
3	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
4	Date	[26] 20.17	m	m	[26] 20.17	c1	c1
5	From	[26] 20.20	m	m	[26] 20.20	m	m
6	To	[26] 20.39	m	m	[26] 20.39	m	m
7	Via	[26] 20.42	m	m	[26] 20.42	m	m
c1: IF A.162/9 THEN m ELSE i - - insertion of date in requests and responses.							

Prerequisite A.163/13 - - OPTIONS response

Table A.236: Supported headers within the OPTIONS response - all remaining status-codes

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
1A	Call-Info	[26] 20.9	m	m	[26] 20.9	c3	c3
2	Content-Disposition	[26] 20.11	m	m	[26] 20.11	i	i
3	Content-Encoding	[26] 20.12	m	m	[26] 20.12	i	i
4	Content-Language	[26] 20.13	m	m	[26] 20.13	i	i
5	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
6	Content-Type	[26] 20.15	m	m	[26] 20.15	i	i
7	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
8	Date	[26] 20.17	m	m	[26] 20.17	c1	c1
9	From	[26] 20.20	m	m	[26] 20.20	m	m
10	MIME-Version	[26] 20.24	m	m	[26] 20.24	i	i
11	Organization	[26] 20.25	m	m	[26] 20.25	c2	c2
11A	P-Access-Network-Info	[52] 4.4	c13	c13	[52] 4.4	c14	c14
11B	P-Asserted-Identity	[34] 9.1	c5	c5	[34] 9.1	c6	c6
11C	P-Charging-Function-Addresses	[52] 4.5	c11	c11	[52] 4.5	c12	c12
11D	P-Charging-Vector	[52] 4.6	c9	c9	[52] 4.6	c10	c10
11E	P-Preferred-Identity	[34] 9.2	x	x	[34] 9.2	c4	n/a
11F	Privacy	[33] 4.2	c7	c7	[33] 4.2	c8	c8
11G	Require	[26] 20.32	m	m	[26] 20.32	c15	c15
11H	Server	[26] 20.35	m	m	[26] 20.35	i	i
12	Timestamp	[26] 20.38	m	m	[26] 20.38	i	i
13	To	[26] 20.39	m	m	[26] 20.39	m	m
13A	User-Agent	[26] 20.41	m	m	[26] 20.41	i	i
14	Via	[26] 20.42	m	m	[26] 20.42	m	m
15	Warning	[26] 20.43	m	m	[26] 20.43	i	i
c1:	IF A.162/9 THEN m ELSE i - - insertion of date in requests and responses.						
c2:	IF A.162/19A OR A.162/19B THEN m ELSE i - - reading, adding or concatenating the Organization header.						
c3:	IF A.162/19C OR A.162/19D THEN m ELSE i - - reading, adding or concatenating the Call-Info header.						
c4:	IF A.162/30A THEN m ELSE n/a - - act as first entity within the trust domain for asserted identity.						
c5:	IF A.162/30 THEN m ELSE n/a - - extensions to the Session Initiation Protocol (SIP) for asserted identity within trusted networks.						
c6:	IF A.162/30A or A.162/30B THEN m ELSE i - - extensions to the Session Initiation Protocol (SIP) for asserted identity within trusted networks or subsequent entity within trust network that can route outside the trust network.						
c7:	IF A.162/31 THEN m ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).						
c8:	IF A.162/31D OR A.162/31G THEN m ELSE IF A.162/31C THEN i ELSE n/a - - application of the privacy option "header" or application of the privacy option "id" or passing on of the Privacy header transparently.						
c9:	IF A.162/45 THEN m ELSE n/a - - the P-Charging-Vector header extension.						
c10:	IF A.162/46 THEN m ELSE IF A.162/45 THEN i ELSE n/a - - adding, deleting, reading or modifying the P-Charging-Vector header before proxying the request or response or the P-Charging-Vector header extension.						
c11:	IF A.162/44 THEN m ELSE n/a - - the P-Charging-Function-Addresses header extension.						
c12:	IF A.162/44A THEN m ELSE IF A.162/44 THEN i ELSE n/a - - adding, deleting or reading the P-Charging-Function-Addresses header before proxying the request or response, or the P-Charging-Function-Addresses header extension.						
c13:	IF A.162/43 THEN x ELSE IF A.162/41 THEN m ELSE n/a - - act as subsequent entity within trust network for access network information that can route outside the trust network, the P-Access-Network-Info header extension.						
c14:	IF A.162/43 THEN m ELSE IF A.162/41 THEN i ELSE n/a - - act as subsequent entity within trust network for access network information that can route outside the trust network, the P-Access-Network-Info header extension.						
c15:	IF A.162/11 OR A.162/13 THEN m ELSE i - - reading the contents of the Require header before proxying the request or response or adding or modifying the contents of the Require header before proxying the request or response for methods other than REGISTER.						

Prerequisite A.163/13 - - OPTIONS response

Prerequisite: A.164/6 - - 2xx

Table A.237: Supported headers within the OPTIONS response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Accept	[26] 20.1	m	m	[26] 20.1	i	i
2	Allow	[26] 20.5	m	m	[26] 20.5	i	i
3	Authentication-Info	[26] 20.6	m	m	[26] 20.6	i	i
5	Contact	[26] 20.10	m	m	[26] 20.10	i	i
9	Record-Route	[26] 20.30	m	m	[26] 20.30	c3	c3
12	Supported	[26] 20.37	m	m	[26] 20.37	i	i
c3:	IF A.162/15 THEN o ELSE i - - the requirement to be able to use separate URIs in the upstream direction and downstream direction when record routeing.						

Prerequisite A.163/13 - - OPTIONS response

Prerequisite: A.164/8 OR A.164/9 OR A.164/10 OR A.164/11 OR A.164/12 OR A.164/35 - - 3xx or 485 (Ambiguous)

Table A.238: Supported headers within the OPTIONS response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
3	Contact	[26] 20.10	m	m	[26] 20.10	c1	c1
4	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
7	Supported	[26] 20.37	m	m	[26] 20.37	i	i
c1:	IF A.162/19E THEN m ELSE i - - deleting Contact headers.						

Prerequisite A.163/13 - - OPTIONS response

Prerequisite: A.164/14 - - 401 (Unauthorized)

Table A.239: Supported headers within the OPTIONS response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
3	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
4	Proxy-Authenticate	[26] 20.27	m	m	[26] 20.27	m	m
7	Supported	[26] 20.37	m	m	[26] 20.37	i	i
10	WWW-Authenticate	[26] 20.44	m	m	[26] 20.44	i	i

Prerequisite A.163/13 - - OPTIONS response

Prerequisite: A.164/17 OR A.164/23 OR A.164/30 OR A.164/36 OR A.164/42 OR A.164/45 OR A.164/50 OR A.164/51 - - 404, 413, 480, 486, 500, 503, 600, 603

Table A.240: Supported headers within the OPTIONS response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
3	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
5	Retry-After	[26] 20.33	m	m	[26] 20.33	i	i
7	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/13 - - OPTIONS response

Prerequisite: A.164/18 - - 405 (Method Not Allowed)

Table A.241: Supported headers within the OPTIONS response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
2	Allow	[26] 20.5	m	m	[26] 20.5	i	i
4	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
7	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/13 - - OPTIONS response

Prerequisite: A.164/20 - - 407 (Proxy Authentication Required)

Table A.242: Supported headers within the OPTIONS response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
3	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
4	Proxy-Authenticate	[26] 20.27	m	m	[26] 20.27	m	m
7	Supported	[26] 20.37	m	m	[26] 20.37	i	i
8	WWW-Authenticate	[26] 20.44	m	m	[26] 20.44	i	i

Prerequisite A.163/13 - - OPTIONS response

Prerequisite: A.164/25 - - 415 (Unsupported Media Type)

Table A.243: Supported headers within the OPTIONS response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Accept	[26] 20.1	m	m	[26] 20.1	i	i
2	Accept-Encoding	[26] 20.2	m	m	[26] 20.2	i	i
3	Accept-Language	[26] 20.3	m	m	[26] 20.3	i	i
4	Allow	[26] 20.5	m	m	[26] 20.5	i	i
5	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
8	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/13 - - OPTIONS response

Prerequisite: A.164/27 - - 420 (Bad Extension)

Table A.244: Supported headers within the OPTIONS response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
3	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
6	Supported	[26] 20.37	m	m	[26] 20.37	i	i
7	Unsupported	[26] 20.40	m	m	[26] 20.40	c3	c3
c3:	IF A.162/18 THEN m ELSE i - - reading the contents of the Unsupported header before proxying the 420 response to a method other than REGISTER.						

Prerequisite A.163/13 - - OPTIONS response

Prerequisite: A.164/28 OR A.164/41A - - 421 (Extension Required), 494 (Security Agreement Required)

Table A.244A: Supported headers within the OPTIONS response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
2	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
3	Security-Server	[48] 2	c1	c1	[48] 2	n/a	n/a
4	Supported	[26] 20.37	m	m	[26] 20.37	m	m
c1: IF A.162/47 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol.							

Prerequisite A.163/13 - - OPTIONS response

Prerequisite: A.164/34 - - 484 (Address Incomplete)

Table A.245: Supported headers within the OPTIONS response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
4	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
7	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/13 - - OPTIONS response

Table A.246: Supported message bodies within the OPTIONS response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1							

A.2.2.4.10 PRACK method

Prerequisite A.163/14 - - PRACK request

Table A.247: Supported headers within the PRACK request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Accept	[26] 20.1	m	m	[26] 20.1	i	i
2	Accept-Encoding	[26] 20.2	m	m	[26] 20.2	i	i
3	Accept-Language	[26] 20.3	m	m	[26] 20.3	i	i
3A	Allow	[26] 20.5	m	m	[26] 20.5	i	i
4	Allow-Events	[28] 8.2.2	m	m	[28] 8.2.2	c1	c1
5	Authorization	[26] 20.7	m	m	[26] 20.7	i	i
6	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
7	Content-Disposition	[26] 20.11	m	m	[26] 20.11	i	c3
8	Content-Encoding	[26] 20.12	m	m	[26] 20.12	i	c3
9	Content-Language	[26] 20.13	m	m	[26] 20.13	i	c3
10	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
11	Content-Type	[26] 20.15	m	m	[26] 20.15	i	c3
12	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
13	Date	[26] 20.17	m	m	[26] 20.17	c2	c2
14	From	[26] 20.20	m	m	[26] 20.20	m	m
15	Max-Forwards	[26] 20.22	em	em	[26] 20.22	n/a	n/a
16	MIME-Version	[26] 20.24	m	m	[26] 20.24	i	c3
16A	P-Access-Network-Info	[52] 4.4	c14	c14	[52] 4.4	c15	c15
16B	P-Charging-Function-Addresses	[52] 4.5	c12	c12	[52] 4.5	c13	c13
16C	P-Charging-Vector	[52] 4.6	c10	n/a	[52] 4.6	c11	n/a
16D	Privacy	[33] 4.2	c8	c8	[33] 4.2	c9	c9
17	Proxy-Authorization	[26] 20.28	m	m	[26] 20.28	c4	c4
18	Proxy-Require	[26] 20.29	m	m	[26] 20.29	m	m
19	RAck	[27] 7.2	m	m	[27] 7.2	i	i
20	Record-Route	[26] 20.30	m	m	[26] 20.30	c7	c7
21	Require	[26] 20.32	m	m	[26] 20.32	c5	c5
22	Route	[26] 20.34	m	m	[26] 20.34	m	m
23	Supported	[26] 20.37	m	m	[26] 20.37	c6	c6
24	Timestamp	[26] 20.38	m	m	[26] 20.38	i	i
25	To	[26] 20.39	m	m	[26] 20.39	m	m
26	User-Agent	[26] 20.41	m	m	[26] 20.41	i	i
27	Via	[26] 20.42	m	m	[26] 20.42	m	m

c1:	IF A.4/20 THEN m ELSE i - - SIP specific event notification extension.
c2:	IF A.162/9 THEN m ELSE i - - insertion of date in requests and responses.
c3:	IF A.3/2 OR A.3/4 THEN m ELSE i - - P-CSCF or S-CSCF.
c4:	IF A.162/8A THEN m ELSE i - - authentication between UA and proxy.
c5:	IF A.162/11 OR A.162/13 THEN m ELSE i - - reading the contents of the Require header before proxying the request or response or adding or modifying the contents of the Require header before proxying the request or response for methods other than REGISTER.
c6:	IF A.162/16 THEN m ELSE i - - reading the contents of the Supported header before proxying the response.
c7:	IF A.162/14 THEN 0 ELSE i - - the requirement to be able to insert itself in the subsequent transactions in a dialog.
c8:	IF A.162/31 THEN m ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).
c9:	IF A.162/31D OR A.162/31G THEN m ELSE IF A.162/31C THEN i ELSE n/a - - application of the privacy option "header" or application of the privacy option "id" or passing on of the Privacy header transparently.
c10:	IF A.162/45 THEN m ELSE n/a - - the P-Charging-Vector header extension.
c11:	IF A.162/46 THEN m ELSE IF A.162/45 THEN i ELSE n/a - - adding, deleting, reading or modifying the P-Charging-Vector header before proxying the request or response or the P-Charging-Vector header extension.
c12:	IF A.162/44 THEN m ELSE n/a - - the P-Charging-Function-Addresses header extension.
c13:	IF A.162/44A THEN m ELSE IF A.162/44 THEN i ELSE n/a - - adding, deleting or reading the P-Charging-Function-Addresses header before proxying the request or response, or the P-Charging-Function-Addresses header extension.
c14:	IF A.162/43 THEN x ELSE IF A.162/41 THEN m ELSE n/a - - act as subsequent entity within trust network for access network information that can route outside the trust network, the P-Access-Network-Info header extension.
c15:	IF A.162/43 THEN m ELSE IF A.162/41 THEN i ELSE n/a - - act as subsequent entity within trust network for access network information that can route outside the trust network, the P-Access-Network-Info header extension.
NOTE:	c1 refers to the UA role major capability as this is the case of a proxy that also acts as a UA specifically for SUBSCRIBE and NOTIFY.

Prerequisite A.163/14 - - PRACK request

Table A.248: Supported message bodies within the PRACK request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1							

Prerequisite A.163/15 - - PRACK response

Prerequisite: A.164/1 - - 100 (Trying)

Table A.249: Supported headers within the PRACK response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
2	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
3	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
4	Date	[26] 20.17	m	m	[26] 20.17	c1	c1
5	From	[26] 20.20	m	m	[26] 20.20	m	m
6	To	[26] 20.39	m	m	[26] 20.39	m	m
7	Via	[26] 20.42	m	m	[26] 20.42	m	m
c1:	IF A.162/9 THEN m ELSE i - - insertion of date in requests and responses.						

Prerequisite A.163/15 - - PRACK response

Table A.250: Supported headers within the PRACK response - all remaining status-codes

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
2	Content-Disposition	[26] 20.11	m	m	[26] 20.11	i	c2
3	Content-Encoding	[26] 20.12	m	m	[26] 20.12	i	c2
4	Content-Language	[26] 20.13	m	m	[26] 20.13	i	c2
5	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
6	Content-Type	[26] 20.15	m	m	[26] 20.15	i	c2
7	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
8	Date	[26] 20.17	m	m	[26] 20.17	c1	c1
9	From	[26] 20.20	m	m	[26] 20.20	m	m
10	MIME-Version	[26] 20.24	m	m	[26] 20.24	i	c2
10A	P-Access-Network-Info	[52] 4.4	c9	c9	[52] 4.4	c10	c10
10B	P-Charging-Function-Addresses	[52] 4.5	c7	c7	[52] 4.5	c8	c8
10C	P-Charging-Vector	[52] 4.6	c5	n/a	[52] 4.6	c6	n/a
10D	Privacy	[33] 4.2	c3	c3	[33] 4.2	c4	c4
10E	Require	[26] 20.32	m	m	[26] 20.32	c11	c11
10F	Server	[26] 20.35	m	m	[26] 20.35	i	i
11	Timestamp	[26] 20.38	m	m	[26] 20.38	i	i
12	To	[26] 20.39	m	m	[26] 20.39	m	m
12A	User-Agent	[26] 20.41	m	m	[26] 20.41	i	i
13	Via	[26] 20.42	m	m	[26] 20.42	m	m
14	Warning	[26] 20.43	m	m	[26] 20.43	i	i
c1:	IF A.162/9 THEN m ELSE i - - insertion of date in requests and responses.						
c2:	IF A.3/2 OR A.3/4 THEN m ELSE i - - P-CSCF or S-CSCF.						
c3:	IF A.162/31 THEN m ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).						
c4:	IF A.162/31D OR A.162/31G THEN m ELSE IF A.162/31C THEN i ELSE n/a - - application of the privacy option "header" or application of the privacy option "id" or passing on of the Privacy header transparently.						
c5:	IF A.162/45 THEN m ELSE n/a - - the P-Charging-Vector header extension.						
c6:	IF A.162/46 THEN m ELSE IF A.162/45 THEN n/a - - adding, deleting, reading or modifying the P-Charging-Vector header before proxying the request or response or the P-Charging-Vector header extension.						
c7:	IF A.162/44 THEN m ELSE n/a - - the P-Charging-Function-Addresses header extension.						
c8:	IF A.162/44A THEN m ELSE IF A.162/44 THEN i ELSE n/a - - adding, deleting or reading the P-Charging-Function-Addresses header before proxying the request or response, or the P-Charging-Function-Addresses header extension.						
c9:	IF A.162/43 THEN x ELSE IF A.162/41 THEN m ELSE n/a - - act as subsequent entity within trust network for access network information that can route outside the trust network, the P-Access-Network-Info header extension.						
c10:	IF A.162/43 THEN m ELSE IF A.162/41 THEN i ELSE n/a - - act as subsequent entity within trust network for access network information that can route outside the trust network, the P-Access-Network-Info header extension.						
c11:	IF A.162/11 OR A.162/13 THEN m ELSE i - - reading the contents of the Require header before proxying the request or response or adding or modifying the contents of the Require header before proxying the request or response for methods other than REGISTER.						

Prerequisite A.163/15 - - PRACK response

Prerequisite: A.164/6 - - 2xx

Table A.251: Supported headers within the PRACK response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	m	m	[26] 20.5	i	i
0B	Authentication-Info	[26] 20.6	m	m	[26] 20.6	i	i
1	Record-Route	[26] 20.30	m	m	[26] 20.30	c3	c3
4	Supported	[26] 20.37	m	m	[26] 20.37	i	i

c3:	IF A.162/15 THEN o ELSE i -- the requirement to be able to use separate URIs in the upstream direction and downstream direction when record routeing.
-----	---

Prerequisite A.163/15 -- PRACK response

Prerequisite: A.164/8 OR A.164/9 OR A.164/10 OR A.164/11 OR A.164/12 OR A.164/35 -- 3xx or 485 (Ambiguous)

Table A.252: Supported headers within the PRACK response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	m	m	[26] 20.5	i	i
1	Contact	[26] 20.10	m	m	[26] 20.10	c1	c1
2	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
5	Supported	[26] 20.37	m	m	[26] 20.37	i	i
c1:	IF A.162/19E THEN m ELSE i -- deleting Contact headers.						

Prerequisite A.163/15 -- PRACK response

Prerequisite: A.164/14 -- 401 (Unauthorized)

Table A.253: Supported headers within the PRACK response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	m	m	[26] 20.5	i	i
1	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
2	Proxy-Authenticate	[26] 20.27	m	m	[26] 20.27	m	m
5	Supported	[26] 20.37	m	m	[26] 20.37	i	i
8	WWW-Authenticate	[26] 20.44	m	m	[26] 20.44	i	i

Prerequisite A.163/15 -- PRACK response

Prerequisite: A.164/17 OR A.164/23 OR A.164/30 OR A.164/36 OR A.164/42 OR A.164/45 OR A.164/50 OR A.164/51 -- 404, 413, 480, 486, 500, 503, 600, 603

Table A.254: Supported headers within the PRACK response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	m	m	[26] 20.5	i	i
1	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
3	Retry-After	[26] 20.33	m	m	[26] 20.33	i	i
5	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/15 -- PRACK response

Prerequisite: A.164/18 -- 405 (Method Not Allowed)

Table A.255: Supported headers within the PRACK response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
2	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
5	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/15 - - PRACK response

Prerequisite: A.164/20 - - 407 (Proxy Authentication Required)

Table A.256: Supported headers within the PRACK response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	m	m	[26] 20.5	i	i
1	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
2	Proxy-Authenticate	[26] 20.27	m	m	[26] 20.27	m	m
5	Supported	[26] 20.37	m	m	[26] 20.37	i	i
6	WWW-Authenticate	[26] 20.44	m	m	[26] 20.44	i	i

Prerequisite A.163/15 - - PRACK response

Prerequisite: A.164/25 - - 415 (Unsupported Media Type)

Table A.257: Supported headers within the PRACK response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Accept	[26] 20.1	m	m	[26] 20.1	i	i
2	Accept-Encoding	[26] 20.2	m	m	[26] 20.2	i	i
3	Accept-Language	[26] 20.3	m	m	[26] 20.3	i	i
3A	Allow	[26] 20.5	m	m	[26] 20.5	i	i
4	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
7	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/15 - - PRACK response

Prerequisite: A.164/27 - - 420 (Bad Extension)

Table A.258: Supported headers within the PRACK response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	m	m	[26] 20.5	i	i
1	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
4	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/15 - - PRACK response

Prerequisite: A.164/28 OR A.164/41A - - 421 (Extension Required), 494 (Security Agreement Required)

Table A.258A: Supported headers within the PRACK response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
2	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
3	Security-Server	[48] 2	c1	c1	[48] 2	n/a	n/a
4	Supported	[26] 20.37	m	m	[26] 20.37	m	m
c1:	IF A.162/47 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol.						

Prerequisite A.163/15 - - PRACK response

Prerequisite: A.164/34 - - 484 (Address Incomplete)

Table A.259: Supported headers within the PRACK response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	m	m	[26] 20.5	i	i
1	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
4	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/15 - - PRACK response

Table A.260: Supported message bodies within the PRACK response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1							

A.2.2.4.11 REFER method

Prerequisite A.163/16 - - REFER request

Table A.261: Supported headers within the REFER request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Accept	[26] 20.1	m	m	[26] 20.1	i	i
0B	Accept-Encoding	[26] 20.2	m	m	[26] 20.2	i	i
1	Accept-Language	[26] 20.3	m	m	[26] 20.3	i	i
1A	Allow	[26] 20.5	m	m	[26] 20.5	i	i
2	Allow-Events	[28] 8.2.2	m	m	[28] 8.2.2	c1	c1
3	Authorization	[26] 20.7	m	m	[26] 20.7	i	i
4	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
5	Contact	[26] 20.10	m	m	[26] 20.10	i	i
5A	Content-Disposition	[26] 20.11	m	m	[26] 20.11	i	i
5B	Content-Encoding	[26] 20.12	m	m	[26] 20.12	i	i
5C	Content-Language	[26] 20.13	m	m	[26] 20.13	i	i
6	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
7	Content-Type	[26] 20.15	m	m	[26] 20.15	i	i
8	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
9	Date	[26] 20.17	m	m	[26] 20.17	c2	c2
10	Expires	[26] 20.19	m	m	[26] 20.19	i	i
11	From	[26] 20.20	m	m	[26] 20.20	m	m
12	Max-Forwards	[26] 20.22	m	m	[26] 20.22	m	m
13	MIME-Version	[26] 20.24	m	m	[26] 20.24	i	i
14	Organization	[26] 20.25	m	m	[26] 20.25	c3	c3
14A	P-Access-Network-Info	[52] 4.4	c22	c22	[52] 4.4	c23	c23
14B	P-Asserted-Identity	[34] 9.1	c9	c9	[34] 9.1	c10	c10
14C	P-Called-Party-ID	[52] 4.2	c13	c13	[52] 4.2	c14	c15
14D	P-Charging-Function-Addresses	[52] 4.5	c20	c20	[52] 4.5	c21	c21
14E	P-Charging-Vector	[52] 4.6	c18	c18	[52] 4.6	c19	c19
14F	P-Preferred-Identity	[34] 9.2	x	x	[34] 9.2	c8	c8
14G	P-Visited-Network-ID	[52] 4.3	c16	n/a	[52] 4.3	c17	n/a
14H	Privacy	[33] 4.2	c11	c11	[33] 4.2	c12	c12
15	Proxy-Authorization	[26] 20.28	m	m	[26] 20.28	c4	c4
16	Proxy-Require	[26] 20.29	m	m	[26] 20.29	m	m
17	Record-Route	[26] 20.30	m	m	[26] 20.30	c7	c7
18	Refer-To	[36] 3	c3	c3	[36] 3	c4	c4
19	Require	[26] 20.32	m	m	[26] 20.32	c5	c5
20	Route	[26] 20.34	m	m	[26] 20.34	m	m
20A	Security-Client	[48] 2.3.1	x	x	[48] 2.3.1	c24	c24
20B	Security-Verify	[48] 2.3.1	x	x	[48] 2.3.1	c24	c24
20C	Subject	[26] 20.36	m	m	[26] 20.36	i	i
21	Supported	[26] 20.37	m	m	[26] 20.37	c6	c6
22	Timestamp	[26] 20.38	m	m	[26] 20.38	i	i
23	To	[26] 20.39	m	m	[26] 20.39	m	m
24	User-Agent	[26] 20.41	m	m	[26] 20.41	i	i
25	Via	[26] 20.42	m	m	[26] 20.42	m	m

c1:	IF A.4/20 THEN m ELSE i - - SIP specific event notification extension.
c2:	IF A.162/9 THEN m ELSE i - - insertion of date in requests and responses.
c3:	IF A.162/19A OR A.162/19B THEN m ELSE i - - reading, adding or concatenating the Organization header.
c4:	IF A.162/8A THEN m ELSE i - - authentication between UA and proxy.
c5:	IF A.162/11 OR A.162/13 THEN m ELSE i - - reading the contents of the Require header before proxying the request or response or adding or modifying the contents of the Require header before proxying the request or response for methods other than REGISTER.
c6:	IF A.162/16 THEN m ELSE i - - reading the contents of the Supported header before proxying the response.
c7:	IF A.162/14 THEN m ELSE i - - the requirement to be able to insert itself in the subsequent transactions in a dialog.
c8:	IF A.162/30A THEN m ELSE n/a - - act as first entity within the trust domain for asserted identity.
c9:	IF A.162/30 THEN m ELSE n/a - - extensions to the Session Initiation Protocol (SIP) for asserted identity within trusted networks.
c10:	IF A.162/30A or A.162/30B THEN m ELSE i - - extensions to the Session Initiation Protocol (SIP) for asserted identity within trusted networks or subsequent entity within trust network that can route outside the trust network.
c11:	IF A.162/31 THEN m ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).
c12:	IF A.162/31D OR A.162/31G THEN m ELSE IF A.162/31C THEN i ELSE n/a - - application of the privacy option "header" or application of the privacy option "id" or passing on of the Privacy header transparently.
c13:	IF A.162/37 THEN m ELSE n/a - - the P-Called-Party-ID header extension.
c14:	IF A.162/37 THEN i ELSE n/a - - the P-Called-Party-ID header extension.
c15:	IF A.162/37 AND A.3/2 THEN m ELSE IF A.162/37 AND A.3/3 THEN i ELSE n/a - - the P-Called-Party-ID header extension and P-CSCF or I-CSCF.
c16:	IF A.162/38 THEN m ELSE n/a - - the P-Visited-Network-ID header extension.
c17:	IF A.162/39 THEN m ELSE i - - reading, or deleting the P-Visited-Network-ID header before proxying the request or response.
c18:	IF A.162/45 THEN m ELSE n/a - - the P-Charging-Vector header extension.
c19:	IF A.162/46 THEN m ELSE IF A.162/45 THEN i ELSE n/a - - adding, deleting, reading or modifying the P-Charging-Vector header before proxying the request or response or the P-Charging-Vector header extension.
c20:	IF A.162/44 THEN m ELSE n/a - - the P-Charging-Function-Addresses header extension.
c21:	IF A.162/44A THEN m ELSE IF A.162/44 THEN i ELSE n/a - - adding, deleting or reading the P-Charging-Function-Addresses header before proxying the request or response, or the P-Charging-Function-Addresses header extension.
c22:	IF A.162/43 THEN x ELSE IF A.162/41 THEN m ELSE n/a - - act as subsequent entity within trust network for access network information that can route outside the trust network, the P-Access-Network-Info header extension.
c23:	IF A.162/43 THEN m ELSE IF A.162/41 THEN i ELSE n/a - - act as subsequent entity within trust network for access network information that can route outside the trust network, the P-Access-Network-Info header extension.
c24:	IF A.4/37 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol.
NOTE:	c1 refers to the UA role major capability as this is the case of a proxy that also acts as a UA specifically for SUBSCRIBE and NOTIFY.

Prerequisite A.163/16 - - REFER request

Table A.262: Supported message bodies within the REFER request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1							

Prerequisite A.163/17 - - REFER response

Prerequisite: A.164/1 - - 100 (Trying)

Table A.263: Supported headers within the REFER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
2	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
3	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
4	Date	[26] 20.17	m	m	[26] 20.17	c1	c1
5	From	[26] 20.20	m	m	[26] 20.20	m	m
6	To	[26] 20.39	m	m	[26] 20.39	m	m
7	Via	[26] 20.42	m	m	[26] 20.42	m	m

c1: IF A.162/9 THEN m ELSE i - - insertion of date in requests and responses.

Prerequisite A.163/17 - - REFER response

Table A.264: Supported headers within the REFER response - all remaining status-codes

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
1A	Content-Disposition	[26] 20.11	m	m	[26] 20.11	i	i
2	Content-Encoding	[26] 20.12	m	m	[26] 20.12	i	i
3	Content-Language	[26] 20.13	m	m	[26] 20.13	i	i
4	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
5	Content-Type	[26] 20.15	m	m	[26] 20.15	i	i
6	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
7	Date	[26] 20.17	m	m	[26] 20.17	c1	c1
8	From	[26] 20.20	m	m	[26] 20.20	m	m
9	MIME-Version	[26] 20.24	m	m	[26] 20.24	i	i
10	Organization	[26] 20.25	m	m	[26] 20.25	c2	c2
10A	P-Access-Network-Info	[52] 4.4	c12	c12	[52] 4.4	c13	c13
10B	P-Asserted-Identity	[34] 9.1	c4	c4	[34] 9.1	c5	c5
10C	P-Charging-Function-Addresses	[52] 4.5	c10	c10	[52] 4.5	c11	c11
10D	P-Charging-Vector	[52] 4.6	c8	c8	[52] 4.6	c9	c9
10E	P-Preferred-Identity	[34] 9.2	x	x	[34] 9.2	c3	n/a
10F	Privacy	[33] 4.2	c6	c6	[33] 4.2	c7	c7
10G	Require	[26] 20.32	m	m	[26] 20.32	c14	c14
10H	Server	[26] 20.35	m	m	[26] 20.35	i	i
11	Timestamp	[26] 20.38	m	m	[26] 20.38	i	i
12	To	[26] 20.39	m	m	[26] 20.39	m	m
12A	User-Agent	[26] 20.41	m	m	[26] 20.41	i	i
13	Via	[26] 20.42	m	m	[26] 20.42	m	m
14	Warning	[26] 20.43	m	m	[26] 20.43	i	i
c1:	IF A.162/9 THEN m ELSE i - - insertion of date in requests and responses.						
c2:	IF A.162/19A OR A.162/19B THEN m ELSE i - - reading, adding or concatenating the Organization header.						
c3:	IF A.162/30A THEN m ELSE n/a - - act as first entity within the trust domain for asserted identity.						
c4:	IF A.162/30 THEN m ELSE n/a - - extensions to the Session Initiation Protocol (SIP) for asserted identity within trusted networks.						
c5:	IF A.162/30A or A.162/30B THEN m ELSE i - - extensions to the Session Initiation Protocol (SIP) for asserted identity within trusted networks or subsequent entity within trust network that can route outside the trust network.						
c6:	IF A.162/31 THEN m ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).						
c7:	IF A.162/31D OR A.162/31G THEN m ELSE IF A.162/31C THEN i ELSE n/a - - application of the privacy option "header" or application of the privacy option "id" or passing on of the Privacy header transparently.						
c8:	IF A.162/45 THEN m ELSE n/a - - the P-Charging-Vector header extension.						
c9:	IF A.162/46 THEN m ELSE IF A.162/45 THEN i ELSE n/a - - adding, deleting, reading or modifying the P-Charging-Vector header before proxying the request or response or the P-Charging-Vector header extension.						
c10:	IF A.162/44 THEN m ELSE n/a - - the P-Charging-Function-Addresses header extension.						
c11:	IF A.162/44A THEN m ELSE IF A.162/44 THEN i ELSE n/a - - adding, deleting or reading the P-Charging-Function-Addresses header before proxying the request or response, or the P-Charging-Function-Addresses header extension.						
c12:	IF A.162/43 THEN x ELSE IF A.162/41 THEN m ELSE n/a - - act as subsequent entity within trust network for access network information that can route outside the trust network, the P-Access-Network-Info header extension.						
c13:	IF A.162/43 THEN m ELSE IF A.162/41 THEN i ELSE n/a - - act as subsequent entity within trust network for access network information that can route outside the trust network, the P-Access-Network-Info header extension.						
c14:	IF A.162/11 OR A.162/13 THEN m ELSE i - - reading the contents of the Require header before proxying the request or response or adding or modifying the contents of the Require header before proxying the request or response for methods other than REGISTER.						

Prerequisite A.163/17 - - REFER response

Prerequisite: A.164/7 - - 202 (Accepted)

Table A.265: Supported headers within the REFER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
2	Authentication-Info	[26] 20.6	m	m	[26] 20.6	i	i
3	Contact	[26] 20.10	m	m	[26] 20.10	i	i
5	Record-Route	[26] 20.30	m	m	[26] 20.30	c3	c3
8	Supported	[26] 20.37	m	m	[26] 20.37	i	i
c3:	IF A.162/15 THEN m ELSE i - - the requirement to be able to use separate URIs in the upstream direction and downstream direction when record routeing.						

Prerequisite A.163/17 - - REFER response

Prerequisite: A.164/8 OR A.164/9 OR A.164/10 OR A.164/11 OR A.164/12 OR A.164/35 - - 3xx or 485 (Ambiguous)

Table A.266: Supported headers within the REFER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
2	Contact	[26] 20.10	m	m	[26] 20.10	c1	c1
3	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
7	Supported	[26] 20.37	m	m	[26] 20.37	i	i
c1:	IF A.162/19E THEN m ELSE i - - deleting Contact headers.						

Prerequisite A.163/17 - - REFER response

Prerequisite: A.164/8 OR A.164/9 OR A.164/10 OR A.164/11 OR A.164/12 - - 401 (Unauthorized)

Table A.267: Supported headers within the REFER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
2	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
4	Proxy-Authenticate	[26] 20.27	m	m	[26] 20.27	m	m
7	Supported	[26] 20.37	m	m	[26] 20.37	i	i
10	WWW-Authenticate	[26] 20.44	m	m	[26] 20.44	i	i

Prerequisite A.163/17 - - REFER response

Prerequisite: A.164/17 OR A.164/23 OR A.164/30 OR A.164/36 OR A.164/42 OR A.164/45 OR A.164/50 OR A.164/51 - - 404, 413, 480, 486, 500, 503, 600, 603

Table A.268: Supported headers within the REFER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
3	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
6	Retry-After	[26] 20.33	m	m	[26] 20.33	i	i
8	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/17 - - REFER response

Prerequisite: A.164/18 - - 405 (Method Not Allowed)

Table A.269: Supported headers within the REFER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
2	Allow	[26] 20.5	m	m	[26] 20.5	i	i
3	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
7	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/17 - - REFER response

Prerequisite: A.164/20 - - 407 (Proxy Authentication Required)

Table A.270: Supported headers within the REFER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
2	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
4	Proxy-Authenticate	[26] 20.27	o		[26] 20.27	o	
7	Supported	[26] 20.37	m	m	[26] 20.37	i	i
8	WWW-Authenticate	[26] 20.44	m	m	[26] 20.44	i	i

Prerequisite A.163/17 - - REFER response

Prerequisite: A.164/25 - - 415 (Unsupported Media Type)

Table A.271: Supported headers within the REFER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Accept	[26] 20.1	m	m	[26] 20.1	i	i
2	Accept-Encoding	[26] 20.2	m	m	[26] 20.2	i	i
3	Accept-Language	[26] 20.3	m	m	[26] 20.3	i	i
3A	Allow	[26] 20.5	m	m	[26] 20.5	i	i
4	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
8	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/17 - - REFER response

Prerequisite: A.164/27 - - 420 (Bad Extension)

Table A.272: Supported headers within the REFER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
3	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
7	Supported	[26] 20.37	m	m	[26] 20.37	i	i
8	Unsupported	[26] 20.40	m	m	[26] 20.40	c3	c3
c3:	IF A.162/18 THEN m ELSE i - - reading the contents of the Unsupported header before proxying the 420 response to a method other than REGISTER.						

Prerequisite A.163/17 - - REFER response

Prerequisite: A.164/28 OR A.164/41A - - 421 (Extension Required), 494 (Security Agreement Required)

Table A.272A: Supported headers within the REFER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
2	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
3	Security-Server	[48] 2	c1	c1	[48] 2	n/a	n/a
4	Supported	[26] 20.37	m	m	[26] 20.37	m	m
c1: IF A.162/47 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol.							

Prerequisite A.163/17 - - REFER response

Prerequisite: A.164/34 - - 484 (Address Incomplete)

Table A.273: Supported headers within the REFER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
3	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
7	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/17 - - REFER response

Table A.274: Supported message bodies within the REFER response

Item	Header	Sending			Receiving		
		Ref.	RFC Status	Profile status	Ref.	RFC status	Profile status
1							

A.2.2.4.12 REGISTER method

Prerequisite A.163/18 - - REGISTER request

Table A.275: Supported headers within the REGISTER request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Accept	[26] 20.1	m	m	[26] 20.1	i	i
2	Accept-Encoding	[26] 20.2	m	m	[26] 20.2	i	i
3	Accept-Language	[26] 20.3	m	m	[26] 20.3	i	i
3A	Allow	[26] 20.5	m	m	[26] 20.5	i	i
4	Allow-Events	[28] 8.2.2	m	m	[28] 8.2.2	c1	c1
5	Authorization	[26] 20.7 [49]	m	m	[26] 20.7 [49]	i	i
6	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
7	Call-Info	[26] 20.9	m	m	[26] 20.9	c2	c2
8	Contact	[26] 20.10	m	m	[26] 20.10	i	i
9	Content-Disposition	[26] 20.11	m	m	[26] 20.11	i	i
10	Content-Encoding	[26] 20.12	m	m	[26] 20.12	i	i
11	Content-Language	[26] 20.13	m	m	[26] 20.13	i	i
12	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
13	Content-Type	[26] 20.15	m	m	[26] 20.15	i	i
14	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
15	Date	[26] 20.17	m	m	[26] 20.17	m	m
16	Expires	[26] 20.19	m	m	[26] 20.19	i	i
17	From	[26] 20.20	m	m	[26] 20.20	m	m
18	Max-Forwards	[26] 20.22	m	m	[26] 20.22	m	m
19	MIME-Version	[26] 20.24	m	m	[26] 20.24	i	i
20	Organization	[26] 20.25	m	m	[26] 20.25	c3	c3
20A	P-Access-Network-Info	[52] 4.4	c16	c16	[52] 4.4	c17	c17
20B	P-Charging-Function-Addresses	[52] 4.5	c14	c14	[52] 4.5	c15	c15
20C	P-Charging-Vector	[52] 4.6	c12	c12	[52] 4.6	c13	c13
20D	P-Visited-Network-ID	[52] 4.3	c10	c10	[52] 4.3	c11	c11
20E	Path	[35] 4.2	c6	c6	[35] 4.2	c6	c6
20F	Privacy	[33] 4.2	c8	c8	[33] 4.2	c9	c9
21	Proxy-Authorization	[26] 20.28	m	m	[26] 20.28	c7	c7
22	Proxy-Require	[26] 20.29	m	m	[26] 20.29	m	m
23	Require	[26] 20.32	m	m	[26] 20.32	c4	c4
24	Route	[26] 20.34	m	m	[26] 20.34	m	m
24A	Security-Client	[48] 2.3.1	x	x	[48] 2.3.1	c18	c18
24B	Security-Verify	[48] 2.3.1	x	x	[48] 2.3.1	c18	c18
25	Supported	[26] 20.37	m	m	[26] 20.37	c5	c5
26	Timestamp	[26] 20.38	m	m	[26] 20.38	i	i
27	To	[26] 20.39	m	m	[26] 20.39	m	m
28	User-Agent	[26] 20.41	m	m	[26] 20.41	i	i
29	Via	[26] 20.42	m	m	[26] 20.42	m	m

c1:	IF A.4/20 THEN m ELSE i - - SIP specific event notification extension.
c2:	IF A.162/19C OR A.162/19D THEN m ELSE i - - reading, adding or concatenating the Call-Info header.
c3:	IF A.162/19A OR A.162/19B THEN m ELSE i - - reading, adding or concatenating the Organization header.
c4:	IF A.162/11 OR A.162/12 THEN m ELSE i - - reading the contents of the Require header before proxying the request or response or adding or modifying the contents of the Require header before proxying the request or response for methods other than REGISTER.
c5:	IF A.162/16 THEN m ELSE i - - reading the contents of the Supported header before proxying the response.
c6:	IF A.162/29 THEN m ELSE n/a - - PATH header support.
c7:	IF A.162/8A THEN m ELSE i - - authentication between UA and proxy.
c8:	IF A.162/31 THEN m ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).
c9:	IF A.162/31D OR A.162/31G THEN m ELSE IF A.162/31C THEN i ELSE n/a - - application of the privacy option "header" or application of the privacy option "id" or passing on of the Privacy header transparently.
c10:	IF A.162/38 THEN m ELSE n/a - - the P-Visited-Network-ID header extension.
c11:	IF A.162/39 THEN m ELSE i - - reading, or deleting the P-Visited-Network-ID header before proxying the request or response.
c12:	IF A.162/45 THEN m ELSE n/a - - the P-Charging-Vector header extension.
c13:	IF A.162/46 THEN m ELSE IF A.162/45 THEN i ELSE n/a - - adding, deleting, reading or modifying the P-Charging-Vector header before proxying the request or response or the P-Charging-Vector header extension.
c14:	IF A.162/44 THEN m ELSE n/a - - the P-Charging-Function-Addresses header extension.
c15:	IF A.162/44A THEN m ELSE IF A.162/44 THEN i ELSE n/a - - adding, deleting or reading the P-Charging-Function-Addresses header before proxying the request or response, or the P-Charging-Function-Addresses header extension.
c16:	IF A.162/43 THEN x ELSE IF A.162/41 THEN m ELSE n/a - - act as subsequent entity within trust network for access network information that can route outside the trust network, the P-Access-Network-Info header extension.
c17:	IF A.162/43 THEN m ELSE IF A.162/41 THEN i ELSE n/a - - act as subsequent entity within trust network for access network information that can route outside the trust network, the P-Access-Network-Info header extension.
c18:	IF A.4/37 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol.
NOTE:	c1 refers to the UA role major capability as this is the case of a proxy that also acts as a UA specifically for SUBSCRIBE and NOTIFY.

Prerequisite A.163/18 - - REGISTER request

Table A.276: Supported message bodies within the REGISTER request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1							

Prerequisite A.163/19 - - REGISTER response

Prerequisite: A.164/1 - - 100 (Trying)

Table A.277: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
2	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
3	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
4	Date	[26] 20.17	m	m	[26] 20.17	m	m
5	From	[26] 20.20	m	m	[26] 20.20	m	m
6	To	[26] 20.39	m	m	[26] 20.39	m	m
7	Via	[26] 20.42	m	m	[26] 20.42	m	m

Prerequisite A.163/19 - - REGISTER response

Table A.278: Supported headers within the REGISTER response - all remaining status-codes

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
1A	Call-Info	[26] 20.9	m	m	[26] 20.9	c2	c2
2	Content-Disposition	[26] 20.11	m	m	[26] 20.11	i	i
3	Content-Encoding	[26] 20.12	m	m	[26] 20.12	i	i
4	Content-Language	[26] 20.13	m	m	[26] 20.13	i	i
5	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
6	Content-Type	[26] 20.15	m	m	[26] 20.15	i	i
7	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
8	Date	[26] 20.17	m	m	[26] 20.17	m	m
9	From	[26] 20.20	m	m	[26] 20.20	m	m
10	MIME-Version	[26] 20.24	m	m	[26] 20.24	i	i
11	Organization	[26] 20.25	m	m	[26] 20.25	c1	c1
11A	P-Access-Network-Info	[52] 4.4	c9	c9	[52] 4.4	c10	c10
11B	P-Charging-Function-Addresses	[52] 4.5	c7	c7	[52] 4.5	c8	c8
11C	P-Charging-Vector	[52] 4.6	c5	c5	[52] 4.6	c6	c6
11D	Privacy	[33] 4.2	c3	c3	[33] 4.2	c4	c4
11E	Require	[26] 20.32	m	m	[26] 20.32	c11	c11
11F	Server	[26] 20.35	m	m	[26] 20.35	i	i
12	Timestamp	[26] 20.38	m	m	[26] 20.38	i	i
13	To	[26] 20.39	m	m	[26] 20.39	m	m
13A	User-Agent	[26] 20.41	m	m	[26] 20.41	i	i
14	Via	[26] 20.42	m	m	[26] 20.42	m	m
15	Warning	[26] 20.43	m	m	[26] 20.43	i	i

c1: IF A.162/19A OR A.162/19B THEN m ELSE i - - reading, adding or concatenating the Organization header.
c2: IF A.162/19C OR A.162/19D THEN m ELSE i - - reading, adding or concatenating the Call-Info header.
c3: IF A.162/31 THEN m ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).
c4: IF A.162/31D OR A.162/31G THEN m ELSE IF A.162/31C THEN i ELSE n/a - - application of the privacy option "header" or application of the privacy option "id" or passing on of the Privacy header transparently.
c5: IF A.162/45 THEN m ELSE n/a - - the P-Charging-Vector header extension.
c6: IF A.162/46 THEN m ELSE IF A.162/45 THEN i ELSE n/a - - adding, deleting, reading or modifying the P-Charging-Vector header before proxying the request or response or the P-Charging-Vector header extension.
c7: IF A.162/44 THEN m ELSE n/a - - the P-Charging-Function-Addresses header extension.
c8: IF A.162/44A THEN m ELSE IF A.162/44 THEN i ELSE n/a - - adding, deleting or reading the P-Charging-Function-Addresses header before proxying the request or response, or the P-Charging-Function-Addresses header extension.
c9: IF A.162/43 THEN x ELSE IF A.162/41 THEN m ELSE n/a - - act as subsequent entity within trust network for access network information that can route outside the trust network, the P-Access-Network-Info header extension.
c10: IF A.162/43 THEN m ELSE IF A.162/41 THEN i ELSE n/a - - act as subsequent entity within trust network for access network information that can route outside the trust network, the P-Access-Network-Info header extension.
c11: IF A.162/11 OR A.162/12 THEN m ELSE i - - reading the contents of the Require header before proxying the request or response or adding or modifying the contents of the Require header before proxying the request or response for methods other than REGISTER.

Prerequisite A.163/19 - - REGISTER response

Prerequisite: A.164/6 - - 2xx

Table A.279: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Accept	[26] 20.1	m	m	[26] 20.1	i	i
1A	Accept-Encoding	[26] 20.2	m	m	[26] 20.2	i	i
1B	Accept-Language	[26] 20.3	m	m	[26] 20.3	i	i
2	Allow	[26] 20.5	m	m	[26] 20.5	i	i
3	Authentication-Info	[26] 20.6	m	m	[26] 20.6	i	i
5	Contact	[26] 20.10	m	m	[26] 20.10	i	i
5A	P-Associated-URI	[52] 4.1	c8	c8	[52] 4.1	c9	c10
6	Path	[35] 4.2	c3	c3	[35] 4.2	c4	c4
8	Service-Route	[38] 6	c5	c5	[38] 6	c6	c7
9	Supported	[26] 20.37	m	m	[26] 20.37	i	i
c2:	IF A.3/2 OR A.3/3A THEN m ELSE n/a - - P-CSCF or I-CSCF (THIG).						
c3:	IF A.162/29 THEN m ELSE n/a - - Path extension support.						
c4:	IF A.162/29 THEN i ELSE n/a - - Path extension support.						
c5:	IF A.162/32 THEN m ELSE n/a - - Service-Route extension support.						
c6:	IF A.162/32 THEN i ELSE n/a - - Service-Route extension support.						
c7:	IF A.162/32 THEN (IF A.3/2 THEN m ELSE i) ELSE n/a - - Service-Route extension and P-CSCF.						
c8:	IF A.162/36 THEN m ELSE n/a - - the P-Associated-URI extension.						
c9:	IF A.162/36 THEN i ELSE n/a - - the P-Associated-URI extension.						
c10:	IF A.162/36 AND A.3/2 THEN m ELSE IF A.162/36 AND A.3/3 THEN i ELSE n/a - - the P-Associated-URI extension and P-CSCF or I-CSCF.						

Prerequisite A.163/19 - - REGISTER response

Prerequisite: A.164/8 OR A.164/9 OR A.164/10 OR A.164/11 OR A.164/12 OR A.164/35 - - 3xx or 485 (Ambiguous)

Table A.280: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
3	Contact	[26] 20.10	m	m	[26] 20.10	c2	c2
4	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
8	Supported	[26] 20.37	m	m	[26] 20.37	i	i
c2:	IF A.162/19E THEN m ELSE i - - deleting Contact headers.						

Prerequisite A.163/19 - - REGISTER response

Prerequisite: A.164/14 - - 401 (Unauthorized)

Table A.281: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
3	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
4	Proxy-Authenticate	[26] 20.27	m	m	[26] 20.27	m	m
6	Security-Server	[48] 2	x	c1	[48] 2	n/a	n/a
7	Supported	[26] 20.37	m	m	[26] 20.37	i	i
10	WWW-Authenticate	[26] 20.44	m	m	[26] 20.44	i	i
c1:	IF A.162/47 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol.						

Prerequisite A.163/19 - - REGISTER response

Prerequisite: A.164/17 OR A.164/23 OR A.164/30 OR A.164/36 OR A.164/42 OR A.164/45 OR A.164/50 OR A.164/51 - - 404, 413, 480, 486, 500, 503, 600, 603

Table A.282: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
3	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
6	Retry-After	[26] 20.33	m	m	[26] 20.33	i	i
8	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/19 - - REGISTER response

Prerequisite: A.164/18 - - 405 (Method Not Allowed)

Table A.283: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
2	Allow	[26] 20.5	m	m	[26] 20.5	i	i
4	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
8	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/19 - - REGISTER response

Prerequisite: A.164/20 - - 407 (Proxy Authentication Required)

Table A.284: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
3	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
5	Proxy-Authenticate	[26] 20.27	m	m	[26] 20.27	m	m
8	Supported	[26] 20.37	m	m	[26] 20.37	i	i
9	WWW-Authenticate	[26] 20.44	m	m	[26] 20.44	i	i

Prerequisite A.163/19 - - REGISTER response

Prerequisite: A.164/25 - - 415 (Unsupported Media Type)

Table A.285: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Accept	[26] 20.1	m	m	[26] 20.1	i	i
2	Accept-Encoding	[26] 20.2	m	m	[26] 20.2	i	i
3	Accept-Language	[26] 20.3	m	m	[26] 20.3	i	i
4	Allow	[26] 20.5	m	m	[26] 20.5	i	i
5	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
9	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/19 - - REGISTER response

Prerequisite: A.164/27 - - 420 (Bad Extension)

Table A.286: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
3	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
7	Supported	[26] 20.37	m	m	[26] 20.37	i	i
8	Unsupported	[26] 20.40	m	m	[26] 20.40	c3	c3
c3:	IF A.162/17 THEN m ELSE.i						

Prerequisite A.163/19 - - REGISTER response

Prerequisite: A.164/28 OR A.164/41A - - 421 (Extension Required), 494 (Security Agreement Required)

Table A.286A: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
2	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
3	Security-Server	[48] 2	c1	c1	[48] 2	n/a	n/a
4	Supported	[26] 20.37	m	m	[26] 20.37	m	m
c1:	IF A.162/47 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol.						

Prerequisite A.163/19 - - REGISTER response

Prerequisite: A.164/29 - - 423 (Interval Too Brief)

Table A.287: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC Status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
3	Error-Info	[26] 20.18	o		[26] 20.18	o	
5	Min-Expires	[26] 20.23	m	m	[26] 20.23	i	i
8	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/19 - - REGISTER response

Prerequisite: A.164/34 - - 484 (Address Incomplete)

Table A.288: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
3	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
7	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/19 - - REGISTER response

Table A.289: Supported message bodies within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1							

A.2.2.4.13 SUBSCRIBE method

Prerequisite A.163/20 - - SUBSCRIBE request

Table A.290: Supported headers within the SUBSCRIBE request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Accept	[26] 20.1	m	m	[26] 20.1	i	i
2	Accept-Encoding	[26] 20.2	m	m	[26] 20.2	i	i
3	Accept-Language	[26] 20.3	m	m	[26] 20.3	i	i
3A	Allow	[26] 20.5	m	m	[26] 20.5	i	i
4	Allow-Events	[28] 8.2.2	m	m	[28] 8.2.2	c1	c1
5	Authorization	[26] 20.7	m	m	[26] 20.7	i	i
6	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
6A	Contact	[26] 20.10	m	m	[26] 20.10	i	i
7	Content-Disposition	[26] 20.11	m	m	[26] 20.11	i	i
8	Content-Encoding	[26] 20.12	m	m	[26] 20.12	i	i
9	Content-Language	[26] 20.13	m	m	[26] 20.13	i	i
10	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
11	Content-Type	[26] 20.15	m	m	[26] 20.15	i	i
12	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
13	Date	[26] 20.17	m	m	[26] 20.17	c2	c2
14	Event	[28] 8.2.1	m	m	[28] 8.2.1	m	m
15	Expires	[26] 20.19	m	m	[26] 20.19	i	i
16	From	[26] 20.20	m	m	[26] 20.20	m	m
17	Max-Forwards	[26] 20.22	m	m	[26] 20.22	m	m
18	MIME-Version	[26] 20.24	m	m	[26] 20.24	i	i
18A	Organization	[26] 20.25	m	m	[26] 20.25	c3	c3
18B	P-Access-Network-Info	[52] 4.4	c22	c22	[52] 4.4	c23	c23
18C	P-Asserted-Identity	[34] 9.1	c9	c9	[34] 9.1	c10	c10
18D	P-Called-Party-ID	[52] 4.2	c13	c13	[52] 4.2	c14	c15
18E	P-Charging-Function-Addresses	[52] 4.5	c20	c20	[52] 4.5	c21	c21
18F	P-Charging-Vector	[52] 4.6	c18	c18	[52] 4.6	c19	c19
18G	P-Preferred-Identity	[34] 9.2	x	x	[34] 9.2	c8	c8
18H	P-Visited-Network-ID	[52] 4.3	c16	n/a	[52] 4.3	c17	n/a
18I	Privacy	[33] 4.2	c11	c11	[33] 4.2	c12	c12
19	Proxy-Authorization	[26] 20.28	m	m	[26] 20.28	c4	c4
20	Proxy-Require	[26] 20.29	m	m	[26] 20.29	m	m
21	Record-Route	[26] 20.30	m	m	[26] 20.30	c7	c7
22	Require	[26] 20.32	m	m	[26] 20.32	c5	c5
23	Route	[26] 20.34	m	m	[26] 20.34	m	m
23A	Security-Client	[48] 2.3.1	x	x	[48] 2.3.1	c24	c24
23B	Security-Verify	[48] 2.3.1	x	x	[48] 2.3.1	c24	c24
24	Supported	[26] 20.37	m	m	[26] 20.37	c6	c6
25	Timestamp	[26] 20.38	m	m	[26] 20.38	i	i
26	To	[26] 20.39	m	m	[26] 20.39	m	m
27	User-Agent	[26] 20.41	m	m	[26] 20.41	i	i
28	Via	[26] 20.42	m	m	[26] 20.42	m	m

c1:	IF A.4/20 THEN m ELSE i - - SIP specific event notification extension.
c2:	IF A.162/9 THEN m ELSE i - - insertion of date in requests and responses.
c3:	IF A.162/19A OR A.162/19B THEN m ELSE i - - reading, adding or concatenating the Organization header.
c4:	IF A.162/8A THEN m ELSE i - - authentication between UA and proxy.
c5:	IF A.162/11 OR A.162/13 THEN m ELSE i - - reading the contents of the Require header before proxying the request or response or adding or modifying the contents of the Require header before proxying the request or response for methods other than REGISTER.
c6:	IF A.162/16 THEN m ELSE i - - reading the contents of the Supported header before proxying the response.
c7:	IF A.162/14 THEN m ELSE i - - the requirement to be able to insert itself in the subsequent transactions in a dialog.
c8:	IF A.162/30A THEN m ELSE n/a - - act as first entity within the trust domain for asserted identity.
c9:	IF A.162/30 THEN m ELSE n/a - - extensions to the Session Initiation Protocol (SIP) for asserted identity within trusted networks.
c10:	IF A.162/30A or A.162/30B THEN m ELSE i - - extensions to the Session Initiation Protocol (SIP) for asserted identity within trusted networks or subsequent entity within trust network that can route outside the trust network.
c11:	IF A.162/31 THEN m ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).
c12:	IF A.162/31D OR A.162/31G THEN m ELSE IF A.162/31C THEN i ELSE n/a - - application of the privacy option "header" or application of the privacy option "id" or passing on of the Privacy header transparently.
c13:	IF A.162/37 THEN m ELSE n/a - - the P-Called-Party-ID header extension.
c14:	IF A.162/37 THEN i ELSE n/a - - the P-Called-Party-ID header extension.
c15:	IF A.162/37 AND A.3/2 THEN m ELSE IF A.162/37 AND A.3/3 THEN i ELSE n/a - - the P-Called-Party-ID header extension and P-CSCF or I-CSCF.
c16:	IF A.162/38 THEN m ELSE n/a - - the P-Visited-Network-ID header extension.
c17:	IF A.162/39 THEN m ELSE i - - reading, or deleting the P-Visited-Network-ID header before proxying the request or response.
c18:	IF A.162/45 THEN m ELSE n/a - - the P-Charging-Vector header extension.
c19:	IF A.162/46 THEN m ELSE IF A.162/45 THEN i ELSE n/a - - adding, deleting, reading or modifying the P-Charging-Vector header before proxying the request or response or the P-Charging-Vector header extension.
c20:	IF A.162/44 THEN m ELSE n/a - - the P-Charging-Function-Addresses header extension.
c21:	IF A.162/44A THEN m ELSE IF A.162/44 THEN i ELSE n/a - - adding, deleting or reading the P-Charging-Function-Addresses header before proxying the request or response, or the P-Charging-Function-Addresses header extension.
c22:	IF A.162/43 THEN x ELSE IF A.162/41 THEN m ELSE n/a - - act as subsequent entity within trust network for access network information that can route outside the trust network, the P-Access-Network-Info header extension.
c23:	IF A.162/43 THEN m ELSE IF A.162/41 THEN i ELSE n/a - - act as subsequent entity within trust network for access network information that can route outside the trust network, the P-Access-Network-Info header extension.
c24:	IF A.4/37 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol.
NOTE:	c1 refers to the UA role major capability as this is the case of a proxy that also acts as a UA specifically for SUBSCRIBE and NOTIFY.

Prerequisite A.163/20 - - SUBSCRIBE request

Table A.291: Supported message bodies within the SUBSCRIBE request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1							

Prerequisite A.163/21 - - SUBSCRIBE response

Table A.292: Supported headers within the SUBSCRIBE response - all status-codes

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
2	Content-Disposition	[26] 20.11	m	m	[26] 20.11	i	i
3	Content-Encoding	[26] 20.12	m	m	[26] 20.12	i	i
4	Content-Language	[26] 20.13	m	m	[26] 20.13	i	i
5	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
6	Content-Type	[26] 20.15	m	m	[26] 20.15	i	i
7	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
8	Date	[26] 20.17	m	m	[26] 20.17	c1	c1
9	From	[26] 20.20	m	m	[26] 20.20	m	m
10	MIME-Version	[26] 20.24	m	m	[26] 20.24	i	i
10A	Organization	[26] 20.25	m	m	[26] 20.25	c2	c2
10B	P-Access-Network-Info	[52] 4.4	c12	c12	[52] 4.4	c13	c13
10C	P-Asserted-Identity	[34] 9.1	c4	c4	[34] 9.1	c5	c5
10D	P-Charging-Function-Addresses	[52] 4.5	c10	c10	[52] 4.5	c11	c11
10E	P-Charging-Vector	[52] 4.6	c8	c8	[52] 4.6	c9	c9
10F	P-Preferred-Identity	[34] 9.2	x	x	[34] 9.2	c3	n/a
10G	Privacy	[33] 4.2	c6	c6	[33] 4.2	c7	c7
10H	Require	[26] 20.32	m	m	[26] 20.32	c14	c14
10I	Server	[26] 20.35	m	m	[26] 20.35	i	i
11	Timestamp	[26] 20.38	m	m	[26] 20.38	i	i
12	To	[26] 20.39	m	m	[26] 20.39	m	m
12A	User-Agent	[26] 20.41	m	m	[26] 20.41	i	i
13	Via	[26] 20.42	m	m	[26] 20.42	m	m
14	Warning	[26] 20.43	m	m	[26] 20.43	i	i
c1:	IF A.162/9 THEN m ELSE i - - insertion of date in requests and responses.						
c2:	IF A.162/19A OR A.162/19B THEN m ELSE i - - reading, adding or concatenating the Organization header.						
c3:	IF A.162/30A THEN m ELSE n/a - - act as first entity within the trust domain for asserted identity.						
c4:	IF A.162/30 THEN m ELSE n/a - - extensions to the Session Initiation Protocol (SIP) for asserted identity within trusted networks.						
c5:	IF A.162/30A or A.162/30B THEN m ELSE i - - extensions to the Session Initiation Protocol (SIP) for asserted identity within trusted networks or subsequent entity within trust network that can route outside the trust network.						
c6:	IF A.162/31 THEN m ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).						
c7:	IF A.162/31D OR A.162/31G THEN m ELSE IF A.162/31C THEN i ELSE n/a - - application of the privacy option "header" or application of the privacy option "id" or passing on of the Privacy header transparently.						
c8:	IF A.162/45 THEN m ELSE n/a - - the P-Charging-Vector header extension.						
c9:	IF A.162/46 THEN m ELSE IF A.162/45 THEN i ELSE n/a - - adding, deleting, reading or modifying the P-Charging-Vector header before proxying the request or response or the P-Charging-Vector header extension.						
c10:	IF A.162/44 THEN m ELSE n/a - - the P-Charging-Function-Addresses header extension.						
c11:	IF A.162/44A THEN m ELSE IF A.162/44 THEN i ELSE n/a - - adding, deleting or reading the P-Charging-Function-Addresses header before proxying the request or response, or the P-Charging-Function-Addresses header extension.						
c12:	IF A.162/43 THEN x ELSE IF A.162/41 THEN m ELSE n/a - - act as subsequent entity within trust network for access network information that can route outside the trust network, the P-Access-Network-Info header extension.						
c13:	IF A.162/43 THEN m ELSE IF A.162/41 THEN i ELSE n/a - - act as subsequent entity within trust network for access network information that can route outside the trust network, the P-Access-Network-Info header extension.						
c14:	IF A.162/11 OR A.162/13 THEN m ELSE i - - reading the contents of the Require header before proxying the request or response or adding or modifying the contents of the Require header before proxying the request or response for methods other than REGISTER.						

Prerequisite A.163/21 - - SUBSCRIBE response

Prerequisite: A.164/6 AND A.164/7 - - 2xx

Table A.293: Supported headers within the SUBSCRIBE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	m	m	[26] 20.5	i	i
1	Authentication-Info	[26] 20.6	m	m	[26] 20.6	i	i
1A	Contact	[26] 20.10	m	m	[26] 20.10	i	i
2	Expires	[26] 20.19	m	m	[26] 20.19	i	i
3	Record-Route	[26] 20.30	m	m	[26] 20.30	c3	c3
6	Supported	[26] 20.37	m	m	[26] 20.37	i	i
c3:	IF A.162/15 THEN m ELSE i - - the requirement to be able to use separate URIs in the upstream direction and downstream direction when record routeing.						

Prerequisite A.163/21 - - SUBSCRIBE response

Prerequisite: A.164/8 OR A.164/9 OR A.164/10 OR A.164/11 OR A.164/12 OR A.164/35 - - 3xx or 485 (Ambiguous)

Table A.294: Supported headers within the SUBSCRIBE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	m	m	[26] 20.5	i	i
1	Contact	[26] 20.10	m	m	[26] 20.10	c1	c1
2	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
5	Supported	[26] 20.37	m	m	[26] 20.37	i	i
c1:	IF A.162/19E THEN m ELSE i - - deleting Contact headers.						

Prerequisite A.163/21 - - SUBSCRIBE response

Prerequisite: A.164/14 - - 401 (Unauthorized)

Table A.295: Supported headers within the SUBSCRIBE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	m	m	[26] 20.5	i	i
1	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
2	Proxy-Authenticate	[26] 20.27	m	m	[26] 20.27	m	m
5	Supported	[26] 20.37	m	m	[26] 20.37	i	i
8	WWW-Authenticate	[26] 20.44	m	m	[26] 20.44	i	i

Prerequisite A.163/21 - - SUBSCRIBE response

Prerequisite: A.164/17 OR A.164/23 OR A.164/30 OR A.164/36 OR A.164/42 OR A.164/50 OR A.164/51 - - 404, 413, 480, 486, 500, 600, 603

Table A.296: Supported headers within the SUBSCRIBE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	m	m	[26] 20.5	i	i
1	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
3	Retry-After	[26] 20.33	m	m	[26] 20.33	i	i
5	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/21 -- SUBSCRIBE response

Prerequisite: A.164/18 -- 405 (Method Not Allowed)

Table A.297: Supported headers within the SUBSCRIBE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
2	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
5	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/21 -- SUBSCRIBE response

Prerequisite: A.164/20 -- 407 (Proxy Authentication Required)

Table A.298: Supported headers within the SUBSCRIBE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	m	m	[26] 20.5	i	i
1	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
2	Proxy-Authenticate	[26] 20.27	m	m	[26] 20.27	m	m
5	Supported	[26] 20.37	m	m	[26] 20.37	i	i
6	WWW-Authenticate	[26] 20.44	m	m	[26] 20.44	i	i

Prerequisite A.163/21 -- SUBSCRIBE response

Prerequisite: A.164/25 -- 415 (Unsupported Media Type)

Table A.299: Supported headers within the SUBSCRIBE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Accept	[26] 20.1	m	m	[26] 20.1	i	i
2	Accept-Encoding	[26] 20.2	m	m	[26] 20.2	i	i
3	Accept-Language	[26] 20.3	m	m	[26] 20.3	i	i
4	Allow	[26] 20.5	m	m	[26] 20.5	i	i
5	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
7	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/21 -- SUBSCRIBE response

Prerequisite: A.164/27 -- 420 (Bad Extension)

Table A.300: Supported headers within the SUBSCRIBE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	m	m	[26] 20.5	i	i
1	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
4	Supported	[26] 20.37	m	m	[26] 20.37	i	i
5	Unsupported	[26] 20.40	m	m	[26] 20.40	c3	c3
c3:	IF A.162/18 THEN m ELSE i -- reading the contents of the Unsupported header before proxying the 420 response to a method other than REGISTER.						

Prerequisite A.163/21 -- SUBSCRIBE response

Prerequisite: A.164/28 OR A.164/41A -- 421 (Extension Required), 494 (Security Agreement Required)

Table A.300A: Supported headers within the SUBSCRIBE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
2	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
3	Security-Server	[48] 2	c1	c1	[48] 2	n/a	n/a
4	Supported	[26] 20.37	m	m	[26] 20.37	m	m
c1: IF A.162/47 THEN m ELSE n/a -- security mechanism agreement for the session initiation protocol.							

Prerequisite A.163/21 -- SUBSCRIBE response

Prerequisite: A.164/29 -- 423 (Interval Too Brief)

Table A.301: Supported headers within the SUBSCRIBE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	m	m	[26] 20.5	i	i
1	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
2	Min-Expires	[26] 20.23	m	m	[26] 20.23	i	i
5	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/21 -- SUBSCRIBE response

Prerequisite: A.164/34 -- 484 (Address Incomplete)

Table A.302: Supported headers within the SUBSCRIBE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	m	m	[26] 20.5	i	i
1	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
4	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/21 -- SUBSCRIBE response

Prerequisite: A.164/39 -- 489 (Bad Event)

Table A.303: Supported headers within the SUBSCRIBE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	m	m	[26] 20.5	i	i
1	Allow-Events	[28] 8.2.2	m	m	[28] 8.2.2	c1	c1
3	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
c1: IF A.4/20 THEN m ELSE i -- SIP specific event notification extension.							
NOTE: c1 refers to the UA role major capability as this is the case of a proxy that also acts as a UA specifically for SUBSCRIBE and NOTIFY.							

Prerequisite A.163/21 -- SUBSCRIBE response

Prerequisite: A.164/45 -- 503 (Service Unavailable)

Table A.303A: Supported headers within the SUBSCRIBE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Allow	[26] 20.5	m	m	[26] 20.5	i	i
1	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
3	Retry-After	[26] 20.33	m	m	[26] 20.33	i	i
5	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/21 -- SUBSCRIBE response

Table A.304: Supported message bodies within the SUBSCRIBE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1							

A.2.2.4.14 UPDATE method

Prerequisite A.163/22 - - UPDATE request

Table A.305: Supported headers within the UPDATE request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Accept	[26] 20.1	m	m	[26] 20.1	i	i
2	Accept-Encoding	[26] 20.2	m	m	[26] 20.2	i	i
3	Accept-Language	[26] 20.3	m	m	[26] 20.3	i	i
4	Allow	[26] 20.5	m	m	[26] 20.5	i	i
5	Allow-Events	[28] 8.2.2	m	m	[28] 8.2.2	c1	c1
6	Authorization	[26] 20.7	m	m	[26] 20.7	i	i
7	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
8	Call-Info	[26] 20.9	m	m	[26] 20.9	c8	c8
9	Contact	[26] 20.10	m	m	[26] 20.10	i	i
10	Content-Disposition	[26] 20.11	m	m	[26] 20.11	c4	c4
11	Content-Encoding	[26] 20.12	m	m	[26] 20.12	c4	c4
12	Content-Language	[26] 20.13	m	m	[26] 20.13	c4	c4
13	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
14	Content-Type	[26] 20.15	m	m	[26] 20.15	c4	c4
15	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
16	Date	[26] 20.17	m	m	[26] 20.17	c2	c2
17	From	[26] 20.20	m	m	[26] 20.20	m	m
18	Max-Forwards	[26] 20.22	m	m	[26] 20.22	m	m
19	MIME-Version	[26] 20.24	m	m	[26] 20.24	i	c4
20	Organization	[26] 20.25	m	m	[26] 20.25	c3	c3
20A	P-Access-Network-Info	[52] 4.4	c16	c16	[52] 4.4	c17	c17
20B	P-Charging-Function-Addresses	[52] 4.5	c14	c14	[52] 4.5	c15	c15
20C	P-Charging-Vector	[52] 4.6	c12	c12	[52] 4.6	c13	c13
20D	Privacy	[33] 4.2	c10	c10	[33] 4.2	c11	c11
21	Proxy-Authorization	[26] 20.28	m	m	[26] 20.28	c9	c9
22	Proxy-Require	[26] 20.29	m	m	[26] 20.29	m	m
23	Record-Route	[26] 20.30	m	m	[26] 20.30	c7	c7
24	Require	[26] 20.32	m	m	[26] 20.32	c5	c5
25A	Security-Client	[48] 2.3.1	x	x	[48] 2.3.1	c18	c18
25B	Security-Verify	[48] 2.3.1	x	x	[48] 2.3.1	c18	c18
25	Route	[26] 20.34	m	m	[26] 20.34	m	m
26	Supported	[26] 20.37	m	m	[26] 20.37	c6	c6
27	Timestamp	[26] 20.38	m	m	[26] 20.38	i	i
28	To	[26] 20.39	m	m	[26] 20.39	m	m
29	User-Agent	[26] 20.41	m	m	[26] 20.41	i	i
30	Via	[26] 20.42	m	m	[26] 20.42	m	m

c1:	IF A.4/20 THEN m ELSE i - - SIP specific event notification extension.
c2:	IF A.162/9 THEN m ELSE i - - insertion of date in requests and responses.
c3:	IF A.162/19A OR A.162/19B THEN m ELSE i - - reading, adding or concatenating the Organization header.
c4:	IF A.3/2 OR A.3/4 THEN m ELSE i - - P-CSCF or S-CSCF.
c5:	IF A.162/11 OR A.162/13 THEN m ELSE i - - reading the contents of the Require header before proxying the request or response or adding or modifying the contents of the Require header before proxying the request or response for methods other than REGISTER.
c6:	IF A.162/16 THEN m ELSE i - - reading the contents of the Supported header before proxying the response.
c7:	IF A.162/14 THEN o ELSE i - - the requirement to be able to insert itself in the subsequent transactions in a dialog.
c8:	IF A.162/19C OR A.162/19D THEN m ELSE i - - reading, adding or concatenating the Call-Info header.
c9:	IF A.162/8A THEN m ELSE i - - authentication between UA and proxy.
c10:	IF A.162/31 THEN m ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).
c11:	IF A.162/31D OR A.162/31G THEN m ELSE IF A.162/31C THEN i ELSE n/a - - application of the privacy option "header" or application of the privacy option "id" or passing on of the Privacy header transparently.
c12:	IF A.162/45 THEN m ELSE n/a - - the P-Charging-Vector header extension.
c13:	IF A.162/46 THEN m ELSE IF A.162/45 THEN i ELSE n/a - - adding, deleting, reading or modifying the P-Charging-Vector header before proxying the request or response or the P-Charging-Vector header extension.
c14:	IF A.162/44 THEN m ELSE n/a - - the P-Charging-Function-Addresses header extension.
c15:	IF A.162/44A THEN m ELSE IF A.162/44 THEN i ELSE n/a - - adding, deleting or reading the P-Charging-Function-Addresses header before proxying the request or response, or the P-Charging-Function-Addresses header extension.
c16:	IF A.162/43 THEN x ELSE IF A.162/41 THEN m ELSE n/a - - act as subsequent entity within trust network for access network information that can route outside the trust network, the P-Access-Network-Info header extension.
c17:	IF A.162/43 THEN m ELSE IF A.162/41 THEN i ELSE n/a - - act as subsequent entity within trust network for access network information that can route outside the trust network, the P-Access-Network-Info header extension.
c18:	IF A.4/37 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol.
NOTE:	c1 refers to the UA role major capability as this is the case of a proxy that also acts as a UA specifically for SUBSCRIBE and NOTIFY.

Prerequisite A.163/22 - - UPDATE request

Table A.306: Supported message bodies within the UPDATE request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1							

Prerequisite A.163/22 - - UPDATE response

Table A.307: Supported headers within the UPDATE response - all remaining status-codes

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
1A	Call-Info	[26] 20.9	m	m	[26] 20.9	c4	c4
2	Content-Disposition	[26] 20.11	m	m	[26] 20.11	i	c3
3	Content-Encoding	[26] 20.12	m	m	[26] 20.12	i	c3
4	Content-Language	[26] 20.13	m	m	[26] 20.13	i	c3
5	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
6	Content-Type	[26] 20.15	m	m	[26] 20.15	i	c3
7	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
8	Date	[26] 20.17	m	m	[26] 20.17	c1	c1
9	From	[26] 20.20	m	m	[26] 20.20	m	m
10	MIME-Version	[26] 20.24	m	m	[26] 20.24	i	c3
10A	Organization	[26] 20.25	m	m	[26] 20.25	c2	c2
10B	P-Access-Network-Info	[52] 4.4	c11	c11	[52] 4.4	c12	c12
10C	P-Charging-Function-Addresses	[52] 4.5	c9	c9	[52] 4.5	c10	c10
10D	P-Charging-Vector	[52] 4.6	c7	n/a	[52] 4.6	c8	n/a
10E	Privacy	[33] 4.2	c5	c5	[33] 4.2	c6	c6
10F	Require	[26] 20.32	m	m	[26] 20.32	c13	c13
10G	Server	[26] 20.35	m	m	[26] 20.35	i	i
11	Timestamp	[26] 20.38	m	m	[26] 20.38	i	i
12	To	[26] 20.39	m	m	[26] 20.39	m	m
12A	User-Agent	[26] 20.41	m	m	[26] 20.41	i	i
13	Via	[26] 20.42	m	m	[26] 20.42	m	m
14	Warning	[26] 20.43	m	m	[26] 20.43	i	i
c1:	IF A.162/9 THEN m ELSE i - - insertion of date in requests and responses.						
c2:	IF A.162/19A OR A.162/19B THEN m ELSE i - - reading, adding or concatenating the Organization header.						
c3:	IF A.3/2 OR A.3/4 THEN m ELSE i - - P-CSCF or S-CSCF.						
c4:	IF A.162/19C OR A.162/19D THEN m ELSE i - - reading, adding or concatenating the Call-Info header.						
c5:	IF A.162/31 THEN m ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).						
c6:	IF A.162/31D OR A.162/31G THEN m ELSE IF A.162/31C THEN i ELSE n/a - - application of the privacy option "header" or application of the privacy option "id" or passing on of the Privacy header transparently.						
c7:	IF A.162/45 THEN m ELSE n/a - - the P-Charging-Vector header extension.						
c8:	IF A.162/46 THEN m ELSE IF A.162/45 THEN i ELSE n/a - - adding, deleting, reading or modifying the P-Charging-Vector header before proxying the request or response or the P-Charging-Vector header extension.						
c9:	IF A.162/44 THEN m ELSE n/a - - the P-Charging-Function-Addresses header extension.						
c10:	IF A.162/44A THEN m ELSE IF A.162/44 THEN i ELSE n/a - - adding, deleting or reading the P-Charging-Function-Addresses header before proxying the request or response, or the P-Charging-Function-Addresses header extension.						
c11:	IF A.162/43 THEN x ELSE IF A.162/41 THEN m ELSE n/a - - act as subsequent entity within trust network for access network information that can route outside the trust network, the P-Access-Network-Info header extension.						
c12:	IF A.162/43 THEN m ELSE IF A.162/41 THEN i ELSE n/a - - act as subsequent entity within trust network for access network information that can route outside the trust network, the P-Access-Network-Info header extension.						
c13:	IF A.162/11 OR A.162/13 THEN m ELSE i - - reading the contents of the Require header before proxying the request or response or adding or modifying the contents of the Require header before proxying the request or response for methods other than REGISTER.						

Prerequisite A.163/23 - - UPDATE response

Prerequisite: A.164/6 - - 2xx

Table A.308: Supported headers within the UPDATE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
0A	Accept	[26] 20.1	m	m	[26] 20.1	i	i

0B	Accept-Encoding	[26] 20.2	m	m	[26] 20.2	i	i
0C	Accept-Language	[26] 20.3	m	m	[26] 20.3	i	i
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
2	Authentication-Info	[26] 20.6	m	m	[26] 20.6	i	i
3	Contact	[26] 20.10	m	m	[26] 20.10	i	i
6	Supported	[26] 20.37	m	m	[26] 20.37	i	i
c3:	IF A.162/15 THEN o ELSE i - - the requirement to be able to use separate URIs in the upstream direction and downstream direction when record routeing.						

Prerequisite A.163/23 - - UPDATE response

Prerequisite: A.164/8 OR A.164/9 OR A.164/10 OR A.164/11 OR A.164/12 - - 3xx

Table A.309: Supported headers within the UPDATE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
2	Contact	[26] 20.10	m	m	[26] 20.10	c1	c1
3	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
7	Supported	[26] 20.37	m	m	[26] 20.37	i	i
c1:	IF A.162/19E THEN m ELSE i - - deleting Contact headers.						

Prerequisite A.163/23 - - UPDATE response

Prerequisite: A.164/14 - - 401 (Unauthorized)

Table A.309A: Supported headers within the UPDATE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
2	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
3	Proxy-Authenticate	[26] 20.27	m	m	[26] 20.27	m	m
5	Supported	[26] 20.37	m	m	[26] 20.37	i	i
6	WWW-Authenticate	[26] 20.44	m	m	[26] 20.44	i	i

Prerequisite A.163/23 - - UPDATE response

Prerequisite: A.164/17 OR A.164/23 OR A.164/30 OR A.164/36 OR A.164/42 OR A.164/45 OR A.164/50 OR A.164/51 - - 404, 413, 480, 486, 500, 503, 600, 603

Table A.310: Supported headers within the UPDATE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
2	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
5	Retry-After	[26] 20.33	m	m	[26] 20.33	i	i
7	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/23 - - UPDATE response

Prerequisite: A.164/18 - - 405 (Method Not Allowed)

Table A.311: Supported headers within the UPDATE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
3	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
7	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/23 - - UPDATE response

Prerequisite: A.164/20 - - 407 (Proxy Authentication Required)

Table A.312: Supported headers within the UPDATE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
2	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
4	Proxy-Authenticate	[26] 20.27	m	m	[26] 20.27	m	m
7	Supported	[26] 20.37	m	m	[26] 20.37	i	i
8	WWW-Authenticate	[26] 20.44	m	m	[26] 20.44	i	i

Prerequisite A.163/23 - - UPDATE response

Prerequisite: A.164/25 - - 415 (Unsupported Media Type)

Table A.313: Supported headers within the UPDATE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Accept	[26] 20.1	m	m	[26] 20.1	i	i
2	Accept-Encoding	[26] 20.2	m	m	[26] 20.2	i	i
3	Accept-Language	[26] 20.3	m	m	[26] 20.3	i	i
4	Allow	[26] 20.5	m	m	[26] 20.5	i	i
6	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
10	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/23 - - UPDATE response

Prerequisite: A.164/27 - - 420 (Bad Extension)

Table A.314: Supported headers within the UPDATE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
2	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
6	Supported	[26] 20.37	m	m	[26] 20.37	i	i
7	Unsupported	[26] 20.40	m	m	[26] 20.40	c3	c3
c3:	IF A.162/18 THEN m ELSE i - - reading the contents of the Unsupported header before proxying the 420 response to a method other than REGISTER.						

Prerequisite A.163/23 - - UPDATE response

Prerequisite: A.164/28 OR A.164/41A - - 421 (Extension Required), 494 (Security Agreement Required)

Table A.314A: Supported headers within the UPDATE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
2	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
3	Security-Server	[48] 2	c1	c1	[48] 2	n/a	n/a
4	Supported	[26] 20.37	m	m	[26] 20.37	m	m
c1: IF A.162/47 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol.							

Prerequisite A.163/23 - - UPDATE response

Prerequisite: A.164/35 - - 485 (Ambiguous)

Table A.315: Supported headers within the UPDATE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
2	Contact	[26] 20.10	m	m	[26] 20.10	c1	c1
3	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
7	Supported	[26] 20.37	m	m	[26] 20.37	i	i
c1: IF A.162/19E THEN m ELSE i - - deleting Contact headers.							

Prerequisite A.163/23 - - UPDATE response

Table A.316: Supported message bodies within the UPDATE response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1							

A.3 Profile definition for the Session Description Protocol as used in the present document

A.3.1 Introduction

Void.

A.3.2 User agent role

This subclause contains the ICS proforma tables related to the user role. They need to be completed only for UA implementations.

Prerequisite: A.2/1 -- user agent role

A.3.2.1 Major capabilities

Table A.317: Major capabilities

Item	Does the implementation support	Reference	RFC status	Profile status
	Capabilities within main protocol			
	Extensions			
22	Integration of resource management and SIP?	[30]	o	m
23	Grouping of media lines	[53]	o	c1
24	Mapping of Media Streams to Resource Reservation Flows	[54]	o	c1
25	SDP Bandwidth Modifiers for RTCP Bandwidth	[56]	o	o (NOTE 1)
c1: IF A.3/1 THEN m ELSE n/a -- UE role.				
NOTE 1: For "video" and "audio" media types that utilise RTP/RTCP, it shall be specified. For other media types, it may be specified.				

A.3.2.2 SDP types

Table A.318: SDP types

Item	Type	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
Session level description							
1	v= (protocol version)	[39] 6	m	m	[39] 6	m	m
2	o= (owner/creator and session identifier)	[39] 6	m	m	[39] 6	m	m
3	s= (session name)	[39] 6	m	m	[39] 6	m	m
4	i= (session information)	[39] 6	o		[39] 6		
5	u= (URI of description)	[39] 6	o	n/a	[39] 6		n/a
6	e= (email address)	[39] 6	o	n/a	[39] 6		n/a
7	p= (phone number)	[39] 6	o	n/a	[39] 6		n/a
8	c= (connection information)	[39] 6	o		[39] 6		
9	b= (bandwidth information)	[39] 6	o	o (NOTE 1)	[39] 6		
Time description (one or more per description)							
10	t= (time the session is active)	[39] 6	m	m	[39] 6	m	m
11	r= (zero or more repeat times)	[39] 6	o	n/a	[39] 6		n/a
Session level description (continued)							
12	z= (time zone adjustments)	[39] 6	o	n/a	[39] 6		n/a
13	k= (encryption key)	[39] 6	o		[39] 6		
14	a= (zero or more session attribute lines)	[39] 6	o		[39] 6		
Media description (zero or more per description)							
15	m= (media name and transport address)	[39] 6	o	o	[39] 6	m	m
16	i= (media title)	[39] 6	o		[39] 6		
17	c= (connection information)	[39] 6	c1	c1	[39] 6		
18	b= (bandwidth information)	[39] 6	o	o (NOTE 1)	[39] 6		
19	k= (encryption key)	[39] 6	o		[39] 6		
20	a= (zero or more media attribute lines)	[39] 6	o		[39] 6		
c1: IF A.318/15 THEN m ELSE n/a.							
NOTE 1: For "video" and "audio" media types that utilise RTP/RTCP, it shall be specified. For other media types, it may be specified.							

Prerequisite A.318/14 OR A.318/20 - - a= (zero or more session/media attribute lines)

Table A.319: zero or more session / media attribute lines (a=)

Item	Field	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	category (a=cat)	[39] 6			[39] 6		
2	keywords (a=keywds)	[39] 6			[39] 6		
3	name and version of tool (a=tool)	[39] 6			[39] 6		
4	packet time (a=ptime)	[39] 6			[39] 6		
5	maximum packet time (a=maxptime)	[39] 6			[39] 6		
6	receive-only mode (a=recvonly)	[39] 6			[39] 6		
7	send and receive mode (a=sendrecv)	[39] 6			[39] 6		
8	send-only mode (a=sendonly)	[39] 6			[39] 6		
9	whiteboard orientation (a=orient)	[39] 6			[39] 6		
10	conference type (a=type)	[39] 6			[39] 6		
11	character set (a=charset)	[39] 6			[39] 6		
12	language tag (a=sdplang)	[39] 6			[39] 6		
13	language tag (a=lang)	[39] 6			[39] 6		
14	frame rate (a=framerate)	[39] 6			[39] 6		
15	quality (a=quality)	[39] 6			[39] 6		
16	format specific parameters (a=fmtp)	[39] 6			[39] 6		
17	rtpmap attribute (a=rtpmap)	[39] 6			[39] 6		
18	current-status attribute (a=curr)	[30] 5	c1	c1	[30] 5	c2	c2
19	desired-status attribute (a=des)	[30] 5	c1	c1	[30] 5	c2	c2
20	confirm-status attribute (a=conf)	[30] 5	c1	c1	[30] 5	c2	c2
21	media stream identification attribute (a=mid)	[53] 3	c3	c3	[53] 3	c4	c4
22	group attribute (a=group)	[53] 4	c5	c5	[53] 3	c6	c6
c1: IF A.317/22 THEN o ELSE n/a. c2: IF A.317/22 THEN m ELSE n/a. c3: IF A.317/23 THEN o ELSE n/a. c4: IF A.317/23 THEN m ELSE n/a. c5: IF A.317/24 THEN o ELSE n/a. c6: IF A.317/24 THEN m ELSE n/a.							

A.3.2.3 SDP types parameters

Prerequisite A.318/2 - - o= (owner/creator and session identifier)

Table A.320: owner/creator and session identifier type (o=)

Item	Field	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	username	[39] 6	m	m	[39] 6	m	n/a
2	session id	[39] 6	m	m	[39] 6	m	m
3	version	[39] 6	m	m	[39] 6	m	m
4	network type	[39] 6	m	m	[39] 6	m	n/a
5	address type	[39] 6	m	m	[39] 6	m	n/a
6	address	[39] 6	m	m	[39] 6	m	n/a

Prerequisite A.318/10 - - t= (time the session is active)

Table A.321: time the session is active type (t=)

Item	Field	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	start time	[39] 6	m	m	[39] 6	m	n/a
2	stop time	[39] 6	m	m	[39] 6	m	n/a

Prerequisite A.318/11 - - r= (zero or more repeat times)

Table A.322: zero or more repeat times (r=)

Item	Field	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	repeat interval	[39] 6		n/a	[39] 6		n/a
2	active duration	[39] 6		n/a	[39] 6		n/a
3	list of offsets from start-time	[39] 6		n/a	[39] 6		n/a

Prerequisite A.318/12 - - z= (time zone adjustments)

Table A.323: time zone adjustments type (z=)

Item	Field	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	adjustment time	[39] 6		n/a	[39] 6		n/a
2	offset	[39] 6		n/a	[39] 6		n/a
3	adjustment time	[39] 6		n/a	[39] 6		n/a
4	offset	[39] 6		n/a	[39] 6		n/a

Prerequisite A.318/13 - - k= (encryption key)

Table A.324: encryption key type (k=)

Item	Field	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	method	[39] 6			[39] 6		
2	encryption key	[39] 6			[39] 6		

Prerequisite A.318/15 - - m= (media name and transport address)

Table A.325: media name and transport address type (m=)

Item	Field	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	media - ``audio'' - ``video'' - ``application'' - ``data'' - ``control''	[39] 6			[39] 6		
2	port	[39] 6			[39] 6		
3	transport	[39] 6			[39] 6		
4	fmt list	[39] 6			[39] 6		

Editor's note: It is expected that this table will be expanded, as this is the principle table that will distinguish operation of different entities within the IM CN subsystem.

Prerequisite A.318/17 -- c= (connection information)

Table A.326: connection type (c=)

Item	Field	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	network type	[39] 6			[39] 6		
2	address type	[39] 6			[39] 6		
3	connection address	[39] 6			[39] 6		

Prerequisite A.318/18 -- b= (bandwidth information)

Table A.327: bandwidth information (b=)

Item	Field	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	modifier	[39] 6, [56]		o (NOTE 1)	[39] 6, [56]		
2	bandwidth-value	[39] 6		o (NOTE 2)	[39] 6		

NOTE 1: For "video" and "audio" media types that utilise RTP/RTCP, the value shall be AS, RR or RS.
 NOTE 2: For "video" and "audio" media types that utilise RTP/RTCP, it shall be specified. For other media types, it may be specified.

A.3.2.4 SDP types parameters within attribute lines

This subclause does not intend to show an exhaustive list of all the possible attribute values

Prerequisite A.319/22 -- group attribute (a=group)

Table A.327A: group semantics (a=group)

Item	Field	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Lip Synchronization (LS)	[53] 4	o	o	[53] 4	m	m
2	Flow Identification (FID)	[53] 4	o	o	[53] 4	m	m
3	Single Reservation Flow (SRF)	[54] 2	o	m	[54] 2	m	m

A.3.3 Proxy role

This subclause contains the ICS proforma tables related to the user role. They need to be completed only for proxy implementations.

Prerequisite: A.2/2 -- proxy role

A.3.3.1 Major capabilities

Table A.328: Major capabilities

Item	Does the implementation support	Reference	RFC status	Profile status
	Capabilities within main protocol			
	Extensions			
1	Integration of resource management and SIP?	[30]	o	n/a
2	Grouping of media lines	[53]	o	c1
3	Mapping of Media Streams to Resource Reservation Flows	[54]	o	c1
4	SDP Bandwidth Modifiers for RTCP Bandwidth	[56]	o	c1
c1:	IF A.3/2 THEN m ELSE n/a - - P-CSCF role.			

A.3.3.2 SDP types

Table A.329: SDP types

Item	Type	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
Session level description							
1	v= (protocol version)	[39] 6	m	m	[39] 6	m	m
2	o= (owner/creator and session identifier).	[39] 6	m	m	[39] 6	i	i
3	s= (session name)	[39] 6	m	m	[39] 6	i	i
4	i= (session information)	[39] 6	m	m	[39] 6	i	i
5	u= (URI of description)	[39] 6	m	m	[39] 6	i	i
6	e= (email address)	[39] 6	m	m	[39] 6	i	i
7	p= (phone number)	[39] 6	m	m	[39] 6	i	i
8	c= (connection information)	[39] 6	m	m	[39] 6	i	i
9	b= (bandwidth information)	[39] 6	m	m	[39] 6	i	i
Time description (one or more per description)							
10	t= (time the session is active)	[39] 6	m	m	[39] 6	i	i
11	r= (zero or more repeat times)	[39] 6	m	m	[39] 6	i	i
Session level description (continued)							
12	z= (time zone adjustments)	[39] 6	m	m	[39] 6	i	i
13	k= (encryption key)	[39] 6	m	m	[39] 6	i	i
14	a= (zero or more session attribute lines)	[39] 6	m	m	[39] 6	i	i
Media description (zero or more per description)							
15	m= (media name and transport address)	[39] 6	m	m	[39] 6	m	m
16	i= (media title)	[39] 6	o		[39] 6		
17	c= (connection information)	[39] 6	o		[39] 6		
18	b= (bandwidth information)	[39] 6	o		[39] 6		
19	k= (encryption key)	[39] 6	o		[39] 6		
20	a= (zero or more media attribute lines)	[39] 6	o		[39] 6		

Prerequisite A.329/14 OR A.329/20 - - a= (zero or more session/media attribute lines)

Table A.330: zero or more session / media attribute lines (a=)

Item	Field	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	category (a=cat)	[39] 6			[39] 6		
2	keywords (a=keywds)	[39] 6			[39] 6		
3	name and version of tool (a=tool)	[39] 6			[39] 6		
4	packet time (a=ptime)	[39] 6			[39] 6		
5	maximum packet time (a=maxptime)	[39] 6			[39] 6		
6	receive-only mode (a=recvonly)	[39] 6			[39] 6		
7	send and receive mode (a=sendrecv)	[39] 6			[39] 6		
8	send-only mode (a=sendonly)	[39] 6			[39] 6		
9	whiteboard orientation (a=orient)	[39] 6			[39] 6		
10	conference type (a=type)	[39] 6			[39] 6		
11	character set (a=charset)	[39] 6			[39] 6		
12	language tag (a=sdplang)	[39] 6			[39] 6		
13	language tag (a=lang)	[39] 6			[39] 6		
14	frame rate (a=framerate)	[39] 6			[39] 6		
15	quality (a=quality)	[39] 6			[39] 6		
16	format specific parameters (a=fmtp)	[39] 6			[39] 6		
17	rtpmap attribute (a=rtpmap)	[39] 6			[39] 6		
18	current-status attribute (a=curr)	[30] 5	m	m	[30] 5	c2	c2
19	desired-status attribute (a=des)	[30] 5	m	m	[30] 5	c2	c2
20	confirm-status attribute (a=conf)	[30] 5	m	m	[30] 5	c2	c2
21	media stream identification attribute (a=mid)	[53] 3	c3	c3	[53] 3	c4	c4
22	group attribute (a=group)	[53] 4	c5	c6	[53] 3	c5	c6
c2:	IF A.328/1 THEN m ELSE i.						
c3:	IF A.328/2 THEN o ELSE n/a.						
c4:	IF A.328/2 THEN m ELSE n/a.						
c5:	IF A.328/3 THEN o ELSE n/a.						
c6:	IF A.328/3 THEN m ELSE n/a.						

A.3.3.3 SDP types parameters

Prerequisite A.329/2 - - o= (owner/creator and session identifier)

Table A.331: owner/creator and session identifier type (o=)

Item	Field	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	username	[39] 6	m	m	[39] 6	m	m
2	session id	[39] 6	m	m	[39] 6	m	m
3	version	[39] 6	m	m	[39] 6	m	m
4	network type	[39] 6	m	m	[39] 6	m	m
5	address type	[39] 6	m	m	[39] 6	m	m
6	address	[39] 6	m	m	[39] 6	m	m

Prerequisite A.329/10 - - t= (time the session is active)

Table A.332: time the session is active type (b=)

Item	Field	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	start time	[39] 6			[39] 6		
2	stop time	[39] 6			[39] 6		

Prerequisite A.329/11 - - r= (zero or more repeat times)

Table A.333: zero or more repeat times (r=)

Item	Field	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	repeat interval	[39] 6			[39] 6		
2	active duration	[39] 6			[39] 6		
3	list of offsets from start-time	[39] 6			[39] 6		

Prerequisite A.329/12 - - z= (time zone adjustments)

Table A.334: time zone adjustments type (z=)

Item	Field	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	adjustment time	[39] 6			[39] 6		
2	offset	[39] 6			[39] 6		
3	adjustment time	[39] 6			[39] 6		
4	offset	[39] 6			[39] 6		

Prerequisite A.329/13 - - k= (encryption key)

Table A.335: encryption key type (k=)

Item	Field	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	method	[39] 6			[39] 6		
2	encryption key	[39] 6			[39] 6		

Prerequisite A.329/15 - - m= (media name and transport address)

Table A.336: media name and transport address type (m=)

Item	Field	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	media - ``audio'' - ``video'' - ``application'' - ``data'' - ``control''	[39] 6			[39] 6		
2	port	[39] 6			[39] 6		
3	transport	[39] 6			[39] 6		
4	fmt list	[39] 6			[39] 6		

Editor's note: It is expected that this table will be expanded, as this is the principle table that will distinguish operation of different entities within the IM CN subsystem.

Prerequisite A.329/17 -- c= (connection information)

Table A.337: connection type (c=)

Item	Field	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	network type	[39] 6			[39] 6		
2	address type	[39] 6			[39] 6		
3	connection address	[39] 6			[39] 6		

Prerequisite A.329/18 -- b= (bandwidth information)

Table A.338: bandwidth information (b=)

Item	Field	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	modifier	[39] 6, [56]			[39] 6, [56]		
2	bandwidth-value	[39] 6			[39] 6		

A.3.3.4 SDP types parameters within attribute lines

The subclause does not intend to show an exhaustive list of all the possible attribute values.

Prerequisite A.330/22 -- group attribute (a=group)

Table A.339: group semantics (a=group)

Item	Field	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Lip Synchronization (LS)	[53] 4	m	m	[53] 4	i	i
2	Flow Identification (FID)	[53] 4	m	m	[53] 4	i	i
3	Single Reservation Flow (SRF)	[54] 2	o	m	[54] 2	m	m

A.4 Profile definition for other message bodies as used in the present document

Void.

3GPP TSG-CN1 Meeting #31

Sophia-Antipolis, France, 25 – 29 August 2003

Tdoc N1-031140

How to create CRs using this form:

Comprehensive information and tips about how to create CRs can be found at <http://www.3gpp.org/specs/CR.htm>. Below is a brief summary:

- 1) Fill out the above form. The symbols above marked ~~⌘~~ contain pop-up help information about the field that they are closest to.
- 2) Obtain the latest version for the release of the specification to which the change is proposed. Use the MS Word "revision marks" feature (also known as "track changes") when making the changes. All 3GPP specifications can be downloaded from the 3GPP server under <ftp://ftp.3gpp.org/specs/> For the latest version, look for the directory name with the latest date e.g. 2001-03 contains the specifications resulting from the March 2001 TSG meetings.
- 3) With "track changes" disabled, paste the entire CR form (use CTRL-A to select it) into the specification just in front of the clause containing the first piece of changed text. Delete those parts of the specification which are not relevant to the change request.

5.1.1.3 Initial subscription to the registration-state event package

Upon receipt of a 2xx response to the initial registration, the UE shall subscribe to the reg event package for the public user identity registered at the users registrar (S-CSCF) as described in draft-ietf-sipping-reg-event-00 [43].

The UE shall use the default public user identiy for subscription to the registration-state event package, if the public user identity that was used for initial registration is a barred public user identity. The UE may use either the default public user identity or the public user identity used for initial registration for the subscription to the registration-state event package, if the initial public user identity that was used for initiaial registratioin is not barred.

On sending a SUBSCRIBE request, the UE shall populate the header fields as follows:

- a) a Request URI set to the resource to which the UE wants to be subscribed to, i.e. to a SIP URI that contains the public user identity used for subscription;
- b) a From header set to a SIP URI that contains the public user identity used for subscription;
- c) a To header set to a SIP URI that contains the public user identity used for subscription;
- d) an Event header set to the "reg" event package;
- e) an Expires header, ~~or an expires parameter within the Contact header~~, set to 600 000 seconds as the value desired for the duration of the subscription; and
- f) a P-Access-Network-Info header that contains information concerning the access network technology and, if applicable, the cell ID (see subclause 7.2A.4).

Upon receipt of a 2xx response to the SUBSCRIBE request, the UE shall store the information for the established dialog and the expiration time as indicated in the Expires header of the received response.

If continued subscription is required the UE shall automatically refresh the subscription by the reg event package, for a previously registered public user identity, either 600 seconds before the expiration time if the initial subscription was for greater than 1200 seconds, or when half of the time has expired if the initial subscription was for 1200 seconds or less.

CHANGE REQUEST

⌘

24.229 CR 483

⌘ rev

3

⌘

Current version:

5.5.0

⌘

For **HELP** on using this form, see bottom of this page or look at the pop-up text over the ⌘ symbols.

Proposed change affects: UICC apps ⌘ ME Radio Access Network Core Network

Title: ⌘ 24.229 R5 CR: Alignment of IMS Compression with RFC 3486

Source: ⌘ Nokia

Work item code: ⌘ IMS-CCR

Date: ⌘ 15/08/2003

Category:

⌘ **F**

Use one of the following categories:

- F** (correction)
- A** (corresponds to a correction in an earlier release)
- B** (addition of feature),
- C** (functional modification of feature)
- D** (editorial modification)

Detailed explanations of the above categories can be found in 3GPP [TR 21.900](#).

Release: ⌘ Rel-5

Use one of the following releases:

2	(GSM Phase 2)
R96	(Release 1996)
R97	(Release 1997)
R98	(Release 1998)
R99	(Release 1999)
Rel-4	(Release 4)
Rel-5	(Release 5)
Rel-6	(Release 6)

Reason for change: ⌘ Section 8 of 24.229 (Compression) was written before [RFC 3486](#) (Compressing the Session Initiation protocol) was added as a dependency.

RFC 3486 says, that whenever a UE sets the comp=sigcomp parameter in the Via header of a request, the other side (= P-CSCF in IMS case) shall send all responses to that request compressed. This is also an indication that the Outbound-Proxy supports SIP compression.

Section 8 of 24.229 says, that the P-CSCF shall start sending messages compressed after the SA is established. As the SA is established **after** the 401 response for the initial REGISTER (which includes the comp=SigComp parameter) is sent to the UE, this statement is in contradiction to RFC 3486.

Summary of change: ⌘ The P-CSCF shall start compression based on the comp-parameter (RFC 3486)

Consequences if not approved: ⌘ 24.229 not in-line with RFC 3486

Clauses affected: ⌘ Clause 8

Other specs affected: ⌘

Y	N
X	Other core specifications
X	Test specifications
X	O&M Specifications

Other comments: ⌘

How to create CRs using this form:

Comprehensive information and tips about how to create CRs can be found at <http://www.3gpp.org/specs/CR.htm>. Below is a brief summary:

- 1) Fill out the above form. The symbols above marked  contain pop-up help information about the field that they are closest to.
- 2) Obtain the latest version for the release of the specification to which the change is proposed. Use the MS Word "revision marks" feature (also known as "track changes") when making the changes. All 3GPP specifications can be downloaded from the 3GPP server under <ftp://ftp.3gpp.org/specs/> For the latest version, look for the directory name with the latest date e.g. 2001-03 contains the specifications resulting from the March 2001 TSG meetings.
- 3) With "track changes" disabled, paste the entire CR form (use CTRL-A to select it) into the specification just in front of the clause containing the first piece of changed text. Delete those parts of the specification which are not relevant to the change request.

8 SIP compression

8.1 SIP compression procedures at the UE

8.1.1 SIP compression

The UE shall support SigComp as specified in RFC 3320 [32]. When using SigComp t~~The compartment shall UE shall send compressed SIP messages start when a SigComp message is received within a security association in accordance with RFC 3486 [55]. The compartment and~~ shall finish when the UE is no longer registered. State creations and announcements shall be allowed only for messages received in a security association.

The UE shall support the SIP dictionary specified in RFC 3485 [42]. If compression is enabled, the UE shall use the dictionary to compress the first message.

8.1.2 Compression of SIP requests and responses transmitted to the P-CSCF

The UE should compress the requests and responses transmitted to the P-CSCF according to subclause 8.1.1.

NOTE: Compression of SIP messages is an implementation option. However, compression is strongly recommended.

8.1.3 Decompression of SIP requests and responses received from the P-CSCF

The UE shall decompress the compressed requests and responses received from the P-CSCF according to subclause 8.1.1.

If the UE detects a decompression failure at the P-CSCF, the recovery mechanism is implementation specific and this may, as an example, include resetting the compartment, changing the algorithm or sending the following message(s) without compression.

8.2 SIP compression procedures at the P-CSCF

8.2.1 SIP compression

The P-CSCF shall support SigComp as specified in RFC 3320 [32]. When using SigComp t~~The compartment shall start P-CSCF shall send compressed SIP messages when a SigComp message is received within a security in accordance with RFC 3486 [55]. The compartment association and~~ shall finish when the UE is no longer registered. State creations and announcements shall be allowed only for messages received in a security association.

The P-CSCF shall support the SIP dictionary specified in RFC 3485 [42]. If compression is enabled, the P-CSCF shall use the dictionary to compress the first message.

8.2.2 Compression of SIP requests and responses transmitted to the UE

The P-CSCF should compress the requests and responses transmitted to the UE according to subclause 8.2.1.

NOTE: Compression of SIP messages is an implementation option. However, compression is strongly recommended.

8.2.3 Decompression of SIP requests and responses received from the UE

The P-CSCF shall decompress the compressed requests and responses received from the UE according to subclause 8.2.1.

If the P-CSCF detects a decompression failure at the UE, the recovery mechanism is implementation specific and this may, as an example, include resetting the compartment, changing the algorithm or sending the following message(s) without compression.