

Source: TSG CN WG 1
Title: CRs to Rel-5 (with mirror CRs) on Work Item IMS-CCR towards 24.229,- pack 1
Agenda item: 8.1
Document for: APPROVAL

Introduction:

This document contains 8 CRs, **Rel-5 with mirrors to** Work Item "IMS-CCR", that have been agreed by **TSG CN WG1 in CN1#32 meeting**, and are forwarded to TSG CN Plenary meeting #22 for approval.

TDoc #	Tdoc Title	Spec	CR #	Rev	CAT	C_Version	Rel
N1-031358	INVITE dialog amendments in profile	24.229	485	1	F	5.6.0	Rel-5
N1-031359	INVITE dialog amendments in profile	24.229	493		A	6.0.0	Rel-6
N1-031631	P-Asserted-Identity in SUBSCRIBE requests	24.229	495	1	F	5.6.0	Rel-5
N1-031632	P-Asserted-Identity in SUBSCRIBE requests	24.229	496	1	A	6.0.0	Rel-6
N1-031719	Update of HSS information at deregistration	24.229	502	2	F	5.6.0	Rel-5
N1-031720	Update of HSS information at deregistration	24.229	503	2	A	6.0.0	Rel-6
N1-031393	Reference corrections	24.229	508		F	5.6.0	Rel-5
N1-031394	Reference corrections	24.229	509		A	6.0.0	Rel-6

CHANGE REQUEST

⌘ **24.229 CR 485** ⌘ rev **1** ⌘ Current version: **5.6.0** ⌘

For **HELP** on using this form, see bottom of this page or look at the pop-up text over the ⌘ symbols.

Proposed change affects: UICC apps ME Radio Access Network Core Network

Title:	⌘ INVITE dialog amendments in profile		
Source:	⌘ Lucent Technologies		
Work item code:	⌘ IMS-CCR	Date:	⌘ 01/10/2003
Category:	⌘ F	Release:	⌘ Rel-5
	Use <u>one</u> of the following categories: F (correction) A (corresponds to a correction in an earlier release) B (addition of feature), C (functional modification of feature) D (editorial modification) Detailed explanations of the above categories can be found in 3GPP TR 21.900 .		Use <u>one</u> of the following releases: 2 (GSM Phase 2) R96 (Release 1996) R97 (Release 1997) R98 (Release 1998) R99 (Release 1999) Rel-4 (Release 4) Rel-5 (Release 5) Rel-6 (Release 6)

Reason for change:	⌘ In Table A.5, the entries relating to methods for INVITE dialogs are either incorrect (INVITE, ACK specified as mandatory, and BYE as optional) or incomplete (no entry in table at all). The fundamental correction required is to refer all these back to the major capabilities table, and build on the changes made in CR375 R1 (N1-030860 – NP-030277). In table A.163, we have various statii for these methods, and they should all be the same, which we believe to be mandatory. For both tables the CANCEL method also needs to be consistently specified. RFC 3261 defines CANCEL as a general purpose method, although currently its usage is only specified for INVITE methods. At some point in the future, a new method could be defined which uses provisional responses. It is therefore believed that both UA and proxy support for the CANCEL method is mandatory.
Summary of change:	⌘ Table A.5 is modified to refer the entries for INVITE, ACK and BYE back to corresponding entries in table A.4 by the use of new conditionals. As a result, the editor's note in table A.5 is also removed. Table A.5 is modified to make support of the CANCEL method mandatory. Table A.163 is modified to make support of all methods associated with an INVITE dialog mandatory. Table A.163 is modified to make support of the CANCEL method mandatory.
Consequences if not approved:	⌘ Incorrect specification of support of various methods

Clauses affected:	⌘ A.2.1.3, A.2.2.3		
	<table border="1" style="display: inline-table; border-collapse: collapse;"> <tr> <td style="padding: 2px 5px;">Y</td> <td style="padding: 2px 5px;">N</td> </tr> </table>	Y	N
Y	N		

Other specs affected:	⌘	<input checked="" type="checkbox"/>	Other core specifications	⌘	
		<input checked="" type="checkbox"/>	Test specifications		
		<input checked="" type="checkbox"/>	O&M Specifications		
Other comments:	⌘				

How to create CRs using this form:

Comprehensive information and tips about how to create CRs can be found at <http://www.3gpp.org/specs/CR.htm>.

Below is a brief summary:

- 1) Fill out the above form. The symbols above marked ⌘ contain pop-up help information about the field that they are closest to.
- 2) Obtain the latest version for the release of the specification to which the change is proposed. Use the MS Word "revision marks" feature (also known as "track changes") when making the changes. All 3GPP specifications can be downloaded from the 3GPP server under <ftp://ftp.3gpp.org/specs/> For the latest version, look for the directory name with the latest date e.g. 2001-03 contains the specifications resulting from the March 2001 TSG meetings.
- 3) With "track changes" disabled, paste the entire CR form (use CTRL-A to select it) into the specification just in front of the clause containing the first piece of changed text. Delete those parts of the specification which are not relevant to the change request.

A.2.1.3 PDUs

Table A.5: Supported methods

Item	PDU	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	ACK request	[26] 13	m;c10	m;c10	[26] 13	m;c11	m;c11
2	BYE request	[26] 15.1	ec12	c12	[26] 15.1	ec12	c12
3	BYE response	[26] 15.1	ec12	c12	[26] 15.1	ec12	c12
4	CANCEL request	[26] 9	em	m	[26] 9	em	m
5	CANCEL response	[26] 9	em	m	[26] 9	em	m
8	INVITE request	[26] 13	m;c10	m;c10	[26] 13	m;c11	m;c11
9	INVITE response	[26] 13	m;c11	m;c11	[26] 13	m;c10	m;c10
9A	MESSAGE request	[50] 4	c7	c7	[50] 7	c7	c7
9B	MESSAGE response	[50] 4	c7	c7	[50] 7	c7	c7
10	NOTIFY request	[28] 8.1.2	c4	c4	[28] 8.1.2	c3	c3
11	NOTIFY response	[28] 8.1.2	c3	c3	[28] 8.1.2	c4	c4
12	OPTIONS request	[26] 11	m	m	[26] 11	m	m
13	OPTIONS response	[26] 11	m	m	[26] 11	m	m
14	PRACK request	[27] 6	c5	c5	[27] 6	c5	c5
15	PRACK response	[27] 6	c5	c5	[27] 6	c5	c5
16	REFER request	[36] 3	c1	c1	[36] 3	c1	c1
17	REFER response	[36] 3	c1	c1	[36] 3	c1	c1
18	REGISTER request	[26] 10	o		[26] 10	n/a	
19	REGISTER response	[26] 10	n/a		[26] 10	m	
20	SUBSCRIBE request	[28] 8.1.1	c3	c3	[28] 8.1.1	c4	c4
21	SUBSCRIBE response	[28] 8.1.1	c4	c4	[28] 8.1.1	c3	c3
22	UPDATE request	[30] 6.1	c6	c6	[30] 6.2	c6	c6
23	UPDATE response	[30] 6.2	c6	c6	[30] 6.1	c6	c6
c1:	IF A.4/15 THEN m ELSE n/a -- the REFER method extension.						
c3:	IF A.4/23 THEN m ELSE n/a -- recipient for event information.						
c4:	IF A.4/22 THEN m ELSE n/a -- notifier of event information.						
c5:	IF A.4/14 THEN m ELSE n/a -- reliability of provisional responses extension.						
c6:	IF A.4/17 THEN m ELSE n/a -- the SIP update method extension.						
c7:	IF A.4/27 THEN m ELSE n/a -- the SIP MESSAGE method.						
c10:	IF A.4/3 THEN m ELSE n/a -- client behaviour for INVITE requests.						
c11:	IF A.4/4 THEN m ELSE n/a -- server behaviour for INVITE requests.						
c12:	IF A.4/5 THEN m ELSE n/a -- session release.						

~~Editor's note: Optional status of BYE in RFC status is given because RFC states SHOULD (client and server).~~

Editor's note: Optional status of REGISTER in RFC status is given because RFC states RECOMMENDED (client); for the UAS, not statement is made, but it is assumed that this therefore means n/a.

A.2.2.3 PDUs

Table A.163: Supported methods

Item	PDU	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	ACK request	[26] 13	m	m	[26] 13	m	m
2	BYE request	[26] 16	em	m	[26] 16	em	m
3	BYE response	[26] 16	em	m	[26] 16	em	m
4	CANCEL request	[26] 16.10	em	m	[26] 16.10	em	m
5	CANCEL response	[26] 16.10	em	m	[26] 16.10	em	m
8	INVITE request	[26] 16	m	m	[26] 16	m	m
9	INVITE response	[26] 16	m	m	[26] 16	m	m
9A	MESSAGE request	[50] 4	c5	c5	[50] 7	c5	c5
9B	MESSAGE response	[50] 4	c5	c5	[50] 7	c5	c5
10	NOTIFY request	[28] 8.1.2	c3	c3	[28] 8.1.2	c3	c3
11	NOTIFY response	[28] 8.1.2	c3	c3	[28] 8.1.2	c3	c3
12	OPTIONS request	[26] 16	m	m	[26] 16	m	m
13	OPTIONS response	[26] 16	m	m	[26] 16	m	m
14	PRACK request	[27] 6	c6	c6	[27] 6	c6	c6
15	PRACK response	[27] 6	c6	c6	[27] 6	c6	c6
16	REFER request	[36] 3	c1	c1	[36] 3	c1	c1
17	REFER response	[36] 3	c1	c1	[36] 3	c1	c1
18	REGISTER request	[26] 16	m	m	[26] 16	m	m
19	REGISTER response	[26] 16	m	m	[26] 16	m	m
20	SUBSCRIBE request	[28] 8.1.1	c3	c3	[28] 8.1.1	c3	c3
21	SUBSCRIBE response	[28] 8.1.1	c3	c3	[28] 8.1.1	c3	c3
22	UPDATE request	[30] 7	c4	c4	[30] 7	c4	c4
23	UPDATE response	[30] 7	c4	c4	[30] 7	c4	c4
c1:	IF A.162/22 THEN m ELSE n/a - - the REFER method.						
c3:	IF A.162/27 THEN m ELSE n/a - - SIP specific event notification.						
c4:	IF A.162/24 THEN m ELSE n/a - - the SIP UPDATE method.						
c5:	IF A.162/33 THEN m ELSE n/a - - the SIP MESSAGE method.						
c6:	IF A.162/21 THEN m ELSE n/a - - reliability of provisional responses.						

CHANGE REQUEST

⌘ **24.229 CR 493** ⌘ rev - ⌘ Current version: **6.0.0** ⌘

For **HELP** on using this form, see bottom of this page or look at the pop-up text over the ⌘ symbols.

Proposed change affects: UICC apps ME Radio Access Network Core Network

Title:	⌘ INVITE dialog amendments in profile		
Source:	⌘ Lucent Technologies		
Work item code:	⌘ IMS-CCR	Date:	⌘ 01/10/2003
Category:	⌘ A	Release:	⌘ Rel-6
	Use <u>one</u> of the following categories: F (correction) A (corresponds to a correction in an earlier release) B (addition of feature), C (functional modification of feature) D (editorial modification) Detailed explanations of the above categories can be found in 3GPP TR 21.900 .		Use <u>one</u> of the following releases: 2 (GSM Phase 2) R96 (Release 1996) R97 (Release 1997) R98 (Release 1998) R99 (Release 1999) Rel-4 (Release 4) Rel-5 (Release 5) Rel-6 (Release 6)

Reason for change:	⌘ In Table A.5, the entries relating to methods for INVITE dialogs are either incorrect (INVITE, ACK specified as mandatory, and BYE as optional) or incomplete (no entry in table at all). The fundamental correction required is to refer all these back to the major capabilities table, and build on the changes made in CR375 R1 (N1-030860 – NP-030277). In table A.163, we have various statii for these methods, and they should all be the same, which we believe to be mandatory. For both tables the CANCEL method also needs to be consistently specified. RFC 3261 defines CANCEL as a general purpose method, although currently its usage is only specified for INVITE methods. At some point in the future, a new method could be defined which uses provisional responses. It is therefore believed that both UA and proxy support for the CANCEL method is mandatory.
Summary of change:	⌘ Table A.5 is modified to refer the entries for INVITE, ACK and BYE back to corresponding entries in table A.4 by the use of new conditionals. As a result, the editor's note in table A.5 is also removed. Table A.5 is modified to make support of the CANCEL method mandatory. Table A.163 is modified to make support of all methods associated with an INVITE dialog mandatory. Table A.163 is modified to make support of the CANCEL method mandatory.
Consequences if not approved:	⌘ Incorrect specification of support of various methods

Clauses affected:	⌘ A.2.1.3, A.2.2.3		
	<table border="1" style="display: inline-table; border-collapse: collapse;"> <tr> <td style="padding: 2px 5px;">Y</td> <td style="padding: 2px 5px;">N</td> </tr> </table>	Y	N
Y	N		

Other specs affected:	⌘	<input checked="" type="checkbox"/>	Other core specifications	⌘	
		<input checked="" type="checkbox"/>	Test specifications		
		<input checked="" type="checkbox"/>	O&M Specifications		
Other comments:	⌘				

How to create CRs using this form:

Comprehensive information and tips about how to create CRs can be found at <http://www.3gpp.org/specs/CR.htm>.

Below is a brief summary:

- 1) Fill out the above form. The symbols above marked ⌘ contain pop-up help information about the field that they are closest to.
- 2) Obtain the latest version for the release of the specification to which the change is proposed. Use the MS Word "revision marks" feature (also known as "track changes") when making the changes. All 3GPP specifications can be downloaded from the 3GPP server under <ftp://ftp.3gpp.org/specs/> For the latest version, look for the directory name with the latest date e.g. 2001-03 contains the specifications resulting from the March 2001 TSG meetings.
- 3) With "track changes" disabled, paste the entire CR form (use CTRL-A to select it) into the specification just in front of the clause containing the first piece of changed text. Delete those parts of the specification which are not relevant to the change request.

A.2.1.3 PDUs

Table A.5: Supported methods

Item	PDU	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	ACK request	[26] 13	m;c10	m;c10	[26] 13	m;c11	m;c11
2	BYE request	[26] 15.1	ec12	c12	[26] 15.1	ec12	c12
3	BYE response	[26] 15.1	ec12	c12	[26] 15.1	ec12	c12
4	CANCEL request	[26] 9	em	m	[26] 9	em	m
5	CANCEL response	[26] 9	em	m	[26] 9	em	m
8	INVITE request	[26] 13	m;c10	m;c10	[26] 13	m;c11	m;c11
9	INVITE response	[26] 13	m;c11	m;c11	[26] 13	m;c10	m;c10
9A	MESSAGE request	[50] 4	c7	c7	[50] 7	c7	c7
9B	MESSAGE response	[50] 4	c7	c7	[50] 7	c7	c7
10	NOTIFY request	[28] 8.1.2	c4	c4	[28] 8.1.2	c3	c3
11	NOTIFY response	[28] 8.1.2	c3	c3	[28] 8.1.2	c4	c4
12	OPTIONS request	[26] 11	m	m	[26] 11	m	m
13	OPTIONS response	[26] 11	m	m	[26] 11	m	m
14	PRACK request	[27] 6	c5	c5	[27] 6	c5	c5
15	PRACK response	[27] 6	c5	c5	[27] 6	c5	c5
16	REFER request	[36] 3	c1	c1	[36] 3	c1	c1
17	REFER response	[36] 3	c1	c1	[36] 3	c1	c1
18	REGISTER request	[26] 10	o		[26] 10	n/a	
19	REGISTER response	[26] 10	n/a		[26] 10	m	
20	SUBSCRIBE request	[28] 8.1.1	c3	c3	[28] 8.1.1	c4	c4
21	SUBSCRIBE response	[28] 8.1.1	c4	c4	[28] 8.1.1	c3	c3
22	UPDATE request	[30] 6.1	c6	c6	[30] 6.2	c6	c6
23	UPDATE response	[30] 6.2	c6	c6	[30] 6.1	c6	c6
<p>c1: IF A.4/15 THEN m ELSE n/a -- the REFER method extension. c3: IF A.4/23 THEN m ELSE n/a -- recipient for event information. c4: IF A.4/22 THEN m ELSE n/a -- notifier of event information. c5: IF A.4/14 THEN m ELSE n/a -- reliability of provisional responses extension. c6: IF A.4/17 THEN m ELSE n/a -- the SIP update method extension. c7: IF A.4/27 THEN m ELSE n/a -- the SIP MESSAGE method. c10: IF A.4/3 THEN m ELSE n/a -- client behaviour for INVITE requests. c11: IF A.4/4 THEN m ELSE n/a -- server behaviour for INVITE requests. c12: IF A.4/5 THEN m ELSE n/a -- session release.</p>							

~~Editor's note: Optional status of BYE in RFC status is given because RFC states SHOULD (client and server).~~

Editor's note: Optional status of REGISTER in RFC status is given because RFC states RECOMMENDED (client); for the UAS, not statement is made, but it is assumed that this therefore means n/a.

A.2.2.3 PDUs

Table A.163: Supported methods

Item	PDU	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	ACK request	[26] 13	m	m	[26] 13	m	m
2	BYE request	[26] 16	em	m	[26] 16	em	m
3	BYE response	[26] 16	em	m	[26] 16	em	m
4	CANCEL request	[26] 16.10	em	m	[26] 16.10	em	m
5	CANCEL response	[26] 16.10	em	m	[26] 16.10	em	m
8	INVITE request	[26] 16	m	m	[26] 16	m	m
9	INVITE response	[26] 16	m	m	[26] 16	m	m
9A	MESSAGE request	[50] 4	c5	c5	[50] 7	c5	c5
9B	MESSAGE response	[50] 4	c5	c5	[50] 7	c5	c5
10	NOTIFY request	[28] 8.1.2	c3	c3	[28] 8.1.2	c3	c3
11	NOTIFY response	[28] 8.1.2	c3	c3	[28] 8.1.2	c3	c3
12	OPTIONS request	[26] 16	m	m	[26] 16	m	m
13	OPTIONS response	[26] 16	m	m	[26] 16	m	m
14	PRACK request	[27] 6	c6	c6	[27] 6	c6	c6
15	PRACK response	[27] 6	c6	c6	[27] 6	c6	c6
16	REFER request	[36] 3	c1	c1	[36] 3	c1	c1
17	REFER response	[36] 3	c1	c1	[36] 3	c1	c1
18	REGISTER request	[26] 16	m	m	[26] 16	m	m
19	REGISTER response	[26] 16	m	m	[26] 16	m	m
20	SUBSCRIBE request	[28] 8.1.1	c3	c3	[28] 8.1.1	c3	c3
21	SUBSCRIBE response	[28] 8.1.1	c3	c3	[28] 8.1.1	c3	c3
22	UPDATE request	[30] 7	c4	c4	[30] 7	c4	c4
23	UPDATE response	[30] 7	c4	c4	[30] 7	c4	c4
c1:	IF A.162/22 THEN m ELSE n/a - - the REFER method.						
c3:	IF A.162/27 THEN m ELSE n/a - - SIP specific event notification.						
c4:	IF A.162/24 THEN m ELSE n/a - - the SIP UPDATE method.						
c5:	IF A.162/33 THEN m ELSE n/a - - the SIP MESSAGE method.						
c6:	IF A.162/21 THEN m ELSE n/a - - reliability of provisional responses.						

CHANGE REQUEST

⌘ **24.229 CR 495** ⌘ rev **1** ⌘ Current version: **5.6.0** ⌘

For **HELP** on using this form, see bottom of this page or look at the pop-up text over the ⌘ symbols.

Proposed change affects: UICC apps ME Radio Access Network Core Network

Title:	⌘ P-Asserted-Identity in SUBSCRIBE requests		
Source:	⌘ Lucent Technologies		
Work item code:	⌘ IMS-CCR	Date:	⌘ 02/10/2003
Category:	⌘ F	Release:	⌘ Rel-5
	Use <u>one</u> of the following categories: F (correction) A (corresponds to a correction in an earlier release) B (addition of feature), C (functional modification of feature) D (editorial modification) Detailed explanations of the above categories can be found in 3GPP TR 21.900 .		Use <u>one</u> of the following releases: 2 (GSM Phase 2) R96 (Release 1996) R97 (Release 1997) R98 (Release 1998) R99 (Release 1999) Rel-4 (Release 4) Rel-5 (Release 5) Rel-6 (Release 6)

Reason for change:	⌘ During CN1#31 a CR was agreed (CR470r1, N1-031314, NP-030414) which specified the inclusion of the P-Asserted-Identity header in SUBSCRIBE requests from the AS to the S-CSCF. The text specifies that the SIP URI of the AS should be included, but then goes on to say that this SIP URI should be the one that appears in the subscriber profile. This latter statement is a configuration issue for the AS, and not something that can be required in the protocol. It is therefore believed that this statement should be informative (i.e. a note) rather than normative. It is also hoped that the restructuring makes the meaning of the contents clearer. Additionally, the related text in the S-CSCF is made clearer in respect of where the S-CSCF finds the information that it relates to the P-Asserted-Identity (in the initial filter criteria).
Summary of change:	⌘ In subclause 5.7.1.1, the 2 nd half of the new bullet item e) is changed to a note. In addition, the "contains" in the bullet item is changed to "set to" to align with the structure of the remainder of the bullet items. A similar change is made to subclause 5.2.3, final bullet, which was also added in the last meeting, in order to make the bullet item structure align. In subclause 5.4.2.1.1, it is made clear that the S-CSCF compares the P-Asserted-Identity with URI in the initial filter criteria.
Consequences if not approved:	⌘ Unimplementable and untestable requirement

Clauses affected:	⌘ 5.2.3, 5.4.2.1.1, 5.7.1.1						
Other specs	<table border="1" style="display: inline-table; vertical-align: middle;"> <tr> <td style="text-align: center;">Y</td> <td style="text-align: center;">N</td> </tr> <tr> <td style="text-align: center;"> </td> <td style="text-align: center;">X</td> </tr> </table> Other core specifications	Y	N		X	⌘	
Y	N						
	X						

affected:

<input checked="" type="checkbox"/>	Test specifications
<input checked="" type="checkbox"/>	O&M Specifications

Other comments: ☞

How to create CRs using this form:

Comprehensive information and tips about how to create CRs can be found at <http://www.3gpp.org/specs/CR.htm>.

Below is a brief summary:

- 1) Fill out the above form. The symbols above marked ☞ contain pop-up help information about the field that they are closest to.
- 2) Obtain the latest version for the release of the specification to which the change is proposed. Use the MS Word "revision marks" feature (also known as "track changes") when making the changes. All 3GPP specifications can be downloaded from the 3GPP server under <ftp://ftp.3gpp.org/specs/> For the latest version, look for the directory name with the latest date e.g. 2001-03 contains the specifications resulting from the March 2001 TSG meetings.
- 3) With "track changes" disabled, paste the entire CR form (use CTRL-A to select it) into the specification just in front of the clause containing the first piece of changed text. Delete those parts of the specification which are not relevant to the change request.

PROPOSED CHANGE

5.2.3 Subscription to the user's registration-state event package

Upon receipt of a 200 (OK) response to the initial REGISTER request of an user, the P-CSCF shall subscribe to the reg event package at the users registrar (S-CSCF) as described in draft-ietf-sipping-reg-event-00 [43]. The P-CSCF shall:

- 1) generate a SUBSCRIBE request with the following elements:
 - a Request-URI set to the resource to which the P-CSCF wants to be subscribed to, i.e. to a SIP URI that contains the default public user identity of the user;
 - a From header set to the P-CSCF's SIP URI;
 - a To header, set to a SIP URI that contains the default public user identity of the user;
 - an Event header set to the "reg" event package;
 - an Expires header set to a value higher then the Expires header indicated in the 200 (OK) response to the REGISTER request; and
 - a P-Asserted-Identity header ~~containing set to~~ [the SIP URI of the P-CSCF](#), which was inserted into the Path header during the registration of the user to whose registration state the P-CSCF subscribes to; and
- 2) determine the I-CSCF of the home network (e.g., by using DNS services);

before sending the SUBSCRIBE request to that I-CSCF, according to the procedures of RFC 3261 [26].

Upon receipt of a 2xx response to the SUBSCRIBE request, the P-CSCF shall store the information for the so established dialog and the expiration time as indicated in the Expires header of the received response.

If continued subscription is required the P-CSCF shall automatically refresh the subscription by the reg event package 600 seconds before the expiration time for a previously registered public user identity, either 600 seconds before the expiration time if the initial subscription was for greater than 1200 seconds, or when half of the time has expired if the initial subscription was for 1200 seconds or less.

PROPOSED CHANGE

5.4.2.1.1 Subscription to the event providing registration state

When an incoming SUBSCRIBE request addressed to S-CSCF arrives containing the Event header with the reg event package, the S-CSCF shall:

- 1) check if, based on the local policy, the request was generated by a subscriber who is authorised to subscribe to the registration state of this particular user. The authorized subscribers include:
 - all public user identities this particular user owns, that the S-CSCF is aware of, and which are not-barred;
 - all the entities identified by the Path header (i.e. the P-CSCF to which this user is attached to); and
 - all the ASs [listed in the initial filter criteria and](#) not belonging to third-party providers.

NOTE: The S-CSCF finds the identity of the originator of the SUBSCRIBE request in the P-Asserted-Identity header.

- 2) generate a 2xx response acknowledging the SUBSCRIBE request and indicating that the authorised subscription was successful as described in draft-ietf-sipping-reg-event-00 [43]. The S-CSCF shall populate the header fields as follows:
 - an Expires header, set to either the same or a decreased value as the Expires header in SUBSCRIBE request; and

- a Contact header, set to is an identifier generated within the S-CSCF that will help to correlate refreshes for the SUBSCRIBE.

Afterwards the S-CSCF shall perform the procedures for notification about registration state as described in subclause 5.4.2.1.2.

PROPOSED CHANGE

5.7.1.1 Notification about registration status

The AS may support the REGISTER method in order to discover the registration status of the user. If a REGISTER request arrives containing information about the user's registration status and the AS supports the REGISTER method, the AS shall store the Expires parameter from the request and generate a 200 (OK) response or an appropriate failure response. For the success case, the 200 (OK) response shall contain Expires value equal to the value received in the REGISTER request. The AS shall store the values received in P-Charging-Function-Addresses header. Also, the AS shall store the values of the icid parameter in the P-Charging-Vector header from the REGISTER request.

Upon receipt of a third-party REGISTER request, the AS may subscribe to the reg event package for the public user identity registered at the users registrar (S-CSCF) as described in draft-ietf-sipping-reg-event-00 [43].

On sending a SUBSCRIBE request, the AS shall populate the header fields as follows:

- a) a Request URI set to the resource to which the AS wants to be subscribed to, i.e. to a SIP URI that contains the public user identity of the user that was received in the To header field of the third-party REGISTER request;
- b) a From header field set to the AS's SIP URI;
- c) a To header field, set to a SIP URI that contains the public user identity of the user that was received in the To header field of the third-party REGISTER request;
- d) an Event header set to the "reg" event package; and
- e) a P-Asserted-Identity header field ~~containing set to~~ the SIP URI of the AS.

NOTE 1: ~~The S-CSCF expects the SIP URI used in the P-Asserted-Identity header to correspond to the SIP URI~~ which identifies this AS in the initial filter criteria of the user to whose registration state the AS subscribes to.

Upon receipt of a 2xx response to the SUBSCRIBE request, the AS shall store the information for the so established dialog and the expiration time as indicated in the Expires header of the received response.

NOTE 2: Upon receipt of a NOTIFY request with all <registration> element(s) having their state attribute set to "terminated" (i.e. all public user identities are deregistered) and the Subscription-State header set to "terminated", the AS considers the subscription to the reg event package terminated, i.e. as if the AS had sent a SUBSCRIBE request with an Expires header containing a value of zero.

CR-Form-v7

CHANGE REQUEST

⌘ **24.229 CR 496** ⌘ rev **1** ⌘ Current version: **6.0.0** ⌘

For **HELP** on using this form, see bottom of this page or look at the pop-up text over the ⌘ symbols.

Proposed change affects: UICC apps ME Radio Access Network Core Network

Title:	⌘ P-Asserted-Identity in SUBSCRIBE requests		
Source:	⌘ Lucent Technologies		
Work item code:	⌘ IMS-CCR	Date:	⌘ 02/10/2003
Category:	⌘ A	Release:	⌘ Rel-6
	Use <u>one</u> of the following categories:		Use <u>one</u> of the following releases:
	F (correction)		2 (GSM Phase 2)
	A (corresponds to a correction in an earlier release)		R96 (Release 1996)
	B (addition of feature),		R97 (Release 1997)
	C (functional modification of feature)		R98 (Release 1998)
	D (editorial modification)		R99 (Release 1999)
	Detailed explanations of the above categories can be found in 3GPP TR 21.900 .		Rel-4 (Release 4)
			Rel-5 (Release 5)
			Rel-6 (Release 6)

Reason for change:	⌘ During CN1#31 a CR was agreed (CR470r1, N1-031314, NP-030414) which specified the inclusion of the P-Asserted-Identity header in SUBSCRIBE requests from the AS to the S-CSCF. The text specifies that the SIP URI of the AS should be included, but then goes on to say that this SIP URI should be the one that appears in the subscriber profile. This latter statement is a configuration issue for the AS, and not something that can be required in the protocol. It is therefore believed that this statement should be informative (i.e. a note) rather than normative. It is also hoped that the restructuring makes the meaning of the contents clearer. Additionally, the related text in the S-CSCF is made clearer in respect of where the S-CSCF finds the information that it relates to the P-Asserted-Identity (in the initial filter criteria).
Summary of change:	⌘ In subclause 5.7.1.1, the 2 nd half of the new bullet item e) is changed to a note. In addition, the "contains" in the bullet item is changed to "set to" to align with the structure of the remainder of the bullet items. A similar change is made to subclause 5.2.3, final bullet, which was also added in the last meeting, in order to make the bullet item structure align. In subclause 5.4.2.1.1, it is made clear that the S-CSCF compares the P-Asserted-Identity with URI in the initial filter criteria.
Consequences if not approved:	⌘ Unimplementable and untestable requirement

Clauses affected:	⌘ 5.2.3, 5.4.2.1.1, 5.7.1.1							
Other specs	⌘	<table border="1" style="display: inline-table; vertical-align: middle;"> <tr> <td style="text-align: center;">Y</td> <td style="text-align: center;">N</td> </tr> <tr> <td style="text-align: center;"> </td> <td style="text-align: center;">X</td> </tr> </table>	Y	N		X	Other core specifications	⌘
Y	N							
	X							

affected:

<input checked="" type="checkbox"/>	Test specifications
<input checked="" type="checkbox"/>	O&M Specifications

Other comments: ☞

How to create CRs using this form:

Comprehensive information and tips about how to create CRs can be found at <http://www.3gpp.org/specs/CR.htm>.

Below is a brief summary:

- 1) Fill out the above form. The symbols above marked ☞ contain pop-up help information about the field that they are closest to.
- 2) Obtain the latest version for the release of the specification to which the change is proposed. Use the MS Word "revision marks" feature (also known as "track changes") when making the changes. All 3GPP specifications can be downloaded from the 3GPP server under <ftp://ftp.3gpp.org/specs/> For the latest version, look for the directory name with the latest date e.g. 2001-03 contains the specifications resulting from the March 2001 TSG meetings.
- 3) With "track changes" disabled, paste the entire CR form (use CTRL-A to select it) into the specification just in front of the clause containing the first piece of changed text. Delete those parts of the specification which are not relevant to the change request.

PROPOSED CHANGE

5.2.3 Subscription to the user's registration-state event package

Upon receipt of a 200 (OK) response to the initial REGISTER request of an user, the P-CSCF shall subscribe to the reg event package at the users registrar (S-CSCF) as described in draft-ietf-sipping-reg-event-00 [43]. The P-CSCF shall:

- 1) generate a SUBSCRIBE request with the following elements:
 - a Request-URI set to the resource to which the P-CSCF wants to be subscribed to, i.e. to a SIP URI that contains the default public user identity of the user;
 - a From header set to the P-CSCF's SIP URI;
 - a To header, set to a SIP URI that contains the default public user identity of the user;
 - an Event header set to the "reg" event package;
 - an Expires header set to a value higher then the Expires header indicated in the 200 (OK) response to the REGISTER request; and
 - a P-Asserted-Identity header ~~containing~~ [set to](#) the SIP URI of the P-CSCF, which was inserted into the Path header during the registration of the user to whose registration state the P-CSCF subscribes to; and
- 2) determine the I-CSCF of the home network (e.g., by using DNS services);

before sending the SUBSCRIBE request to that I-CSCF, according to the procedures of RFC 3261 [26].

Upon receipt of a 2xx response to the SUBSCRIBE request, the P-CSCF shall store the information for the so established dialog and the expiration time as indicated in the Expires header of the received response.

If continued subscription is required the P-CSCF shall automatically refresh the subscription by the reg event package 600 seconds before the expiration time for a previously registered public user identity, either 600 seconds before the expiration time if the initial subscription was for greater than 1200 seconds, or when half of the time has expired if the initial subscription was for 1200 seconds or less.

PROPOSED CHANGE

5.4.2.1.1 Subscription to the event providing registration state

When an incoming SUBSCRIBE request addressed to S-CSCF arrives containing the Event header with the reg event package, the S-CSCF shall:

- 1) check if, based on the local policy, the request was generated by a subscriber who is authorised to subscribe to the registration state of this particular user. The authorized subscribers include:
 - all public user identities this particular user owns, that the S-CSCF is aware of, and which are not-barred;
 - all the entities identified by the Path header (i.e. the P-CSCF to which this user is attached to); and
 - all the ASs [listed in the initial filter criteria and](#) not belonging to third-party providers.

NOTE: The S-CSCF finds the identity of the originator of the SUBSCRIBE request in the P-Asserted-Identity header.

- 2) generate a 2xx response acknowledging the SUBSCRIBE request and indicating that the authorised subscription was successful as described in draft-ietf-sipping-reg-event-00 [43]. The S-CSCF shall populate the header fields as follows:

- an Expires header, set to either the same or a decreased value as the Expires header in SUBSCRIBE request; and
- a Contact header, set to is an identifier generated within the S-CSCF that will help to correlate refreshes for the SUBSCRIBE.

Afterwards the S-CSCF shall perform the procedures for notification about registration state as described in subclause 5.4.2.1.2.

PROPOSED CHANGE

5.7.1.1 Notification about registration status

The AS may support the REGISTER method in order to discover the registration status of the user. If a REGISTER request arrives containing information about the user's registration status and the AS supports the REGISTER method, the AS shall store the Expires parameter from the request and generate a 200 (OK) response or an appropriate failure response. For the success case, the 200 (OK) response shall contain Expires value equal to the value received in the REGISTER request. The AS shall store the values received in P-Charging-Function-Addresses header. Also, the AS shall store the values of the icid parameter in the P-Charging-Vector header from the REGISTER request.

Upon receipt of a third-party REGISTER request, the AS may subscribe to the reg event package for the public user identity registered at the users registrar (S-CSCF) as described in draft-ietf-sipping-reg-event-00 [43].

On sending a SUBSCRIBE request, the AS shall populate the header fields as follows:

- a) a Request URI set to the resource to which the AS wants to be subscribed to, i.e. to a SIP URI that contains the public user identity of the user that was received in the To header field of the third-party REGISTER request;
- b) a From header field set to the AS's SIP URI;
- c) a To header field, set to a SIP URI that contains the public user identity of the user that was received in the To header field of the third-party REGISTER request;
- d) an Event header set to the "reg" event package; and
- e) P-Asserted-Identity header field ~~containing set to~~ the SIP URI of the AS.

NOTE 1: The S-CSCF expects the SIP URI used in the P-Asserted-Identity header to correspond to the SIP URI, which identifies this AS in the initial filter criteria of the user to whose registration state the AS subscribes to.

Upon receipt of a 2xx response to the SUBSCRIBE request, the AS shall store the information for the so established dialog and the expiration time as indicated in the Expires header of the received response.

NOTE 2: Upon receipt of a NOTIFY request with all <registration> element(s) having their state attribute set to "terminated" (i.e. all public user identities are deregistered) and the Subscription-State header set to "terminated", the AS considers the subscription to the reg event package terminated, i.e. as if the AS had sent a SUBSCRIBE request with an Expires header containing a value of zero.

CR-Form-v7

CHANGE REQUEST

⌘ **24.229 CR 502** ⌘ rev **2** ⌘ Current version: **5.6.0** ⌘

For **HELP** on using this form, see bottom of this page or look at the pop-up text over the ⌘ symbols.

Proposed change affects: UICC apps ME Radio Access Network Core Network

Title:	⌘ Update of HSS information at deregistration		
Source:	⌘ Orange		
Work item code:	⌘ IMS-CCR	Date:	⌘ 10/10/2003
Category:	⌘ F	Release:	⌘ Rel-5
	Use <u>one</u> of the following categories: F (correction) A (corresponds to a correction in an earlier release) B (addition of feature), C (functional modification of feature) D (editorial modification) Detailed explanations of the above categories can be found in 3GPP TR 21.900 .		Use <u>one</u> of the following releases: 2 (GSM Phase 2) R96 (Release 1996) R97 (Release 1997) R98 (Release 1998) R99 (Release 1999) Rel-4 (Release 4) Rel-5 (Release 5) Rel-6 (Release 6)

Reason for change:	⌘ When network initiated deregistration occurs, there is no statement regarding the fact that the S-CSCF shall update user registration status in the HSS.
Summary of change:	⌘ It is added that when network initiated deregistration occurs, the S-CSCF shall deregister in the HSS the public user identity found in the To header field together with the implicitly registered public user identities. It is also clarified the Cx procedure to be used for this deregistration in the HSS.
Consequences if not approved:	⌘ In the case the S-CSCF does not update HSS information on deregistration initiated by the network, the user registration status in the HSS will still indicate that the user is registered for some public user identities whereas deregistration occurred for those identities.

Clauses affected:	⌘ 5.4.1.4, 5.4.1.5						
Other specs affected:	<table border="1" style="display: inline-table; border-collapse: collapse;"> <tr> <td style="width: 20px; text-align: center;">Y</td> <td style="width: 20px; text-align: center;">N</td> </tr> <tr> <td style="text-align: center;"><input type="checkbox"/></td> <td style="text-align: center;"><input checked="" type="checkbox"/></td> </tr> </table> Other core specifications	Y	N	<input type="checkbox"/>	<input checked="" type="checkbox"/>	⌘	
Y	N						
<input type="checkbox"/>	<input checked="" type="checkbox"/>						
	<table border="1" style="display: inline-table; border-collapse: collapse;"> <tr> <td style="text-align: center;"><input checked="" type="checkbox"/></td> </tr> </table> Test specifications	<input checked="" type="checkbox"/>	⌘				
<input checked="" type="checkbox"/>							
	<table border="1" style="display: inline-table; border-collapse: collapse;"> <tr> <td style="text-align: center;"><input checked="" type="checkbox"/></td> </tr> </table> O&M Specifications	<input checked="" type="checkbox"/>	⌘				
<input checked="" type="checkbox"/>							
Other comments:	⌘						

How to create CRs using this form:

Comprehensive information and tips about how to create CRs can be found at <http://www.3gpp.org/specs/CR.htm>. Below is a brief summary:

- 1) Fill out the above form. The symbols above marked ⌘ contain pop-up help information about the field that they are closest to.

- 2) Obtain the latest version for the release of the specification to which the change is proposed. Use the MS Word "revision marks" feature (also known as "track changes") when making the changes. All 3GPP specifications can be downloaded from the 3GPP server under <ftp://ftp.3gpp.org/specs/> For the latest version, look for the directory name with the latest date e.g. 2001-03 contains the specifications resulting from the March 2001 TSG meetings.
- 3) With "track changes" disabled, paste the entire CR form (use CTRL-A to select it) into the specification just in front of the clause containing the first piece of changed text. Delete those parts of the specification which are not relevant to the change request.

*****FIRST CHANGE*****

5.4.1.4 User-initiated deregistration

When S-CSCF receives a REGISTER request with the Expires header field containing the value zero, the S-CSCF shall:

- check whether the P-CSCF included the Integrity-protection parameter into the Authorization header field set to yes, indicating that the REGISTER request was received integrity protected. The S-CSCF shall only proceed with the following steps if the integrity protection parameter is set to yes;
- release each multimedia session which was initiated with the public user identity found in the P-Asserted-Identity header field or with one of the implicitly registered public user identities by applying the steps listed in subclause 5.4.5.1.2;
- deregister the public user identity found in the To header field together with the implicitly registered public user identities;
- send a third-party REGISTER request, as described in subclause 5.4.1.7, to each AS that matches the Filter Criteria from the HSS for the REGISTER event; and
- if this is a deregistration request for the only public user identity currently registered with its associated set of implicitly registered public user identities (i.e. no other is registered) and there are still active multimedia sessions associated with this user, release each multimedia session belonging to the served user by applying the steps listed in subclause 5.4.5.1.2.

~~Based on operators' policy the S-CSCF can request of the HSS to either be kept or cleared as the S-CSCF allocated to this subscriber.~~

If all public user identities of the UE are deregistered, then the S-CSCF may consider the UE and P-CSCF subscriptions to the reg event package cancelled (i.e. as if the UE had sent a SUBSCRIBE request with an Expires header containing a value of zero).

If the Authorization header of the REGISTER request did not contain an Integrity-protection parameter, or the parameter was set to the value 'no', the S-CSCF shall respond to the request with a 403 (Forbidden) response. The response may contain a Warning header with a warn-code 399.

On completion of the above procedures in this subclause and of the Cx Server Assignment procedure with the HSS, as described in 3GPP TS 29.229 [15], for one or more public user identities, the S-CSCF shall update or remove those public user identities, their registration state and the associated service profiles from the local data (based on operators' policy the S-CSCF can request of the HSS to either be kept or cleared as the S-CSCF allocated to this subscriber).

XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX NEXT CHANGE XXX

5.4.1.5 Network-initiated deregistration

Prior to initiating the network-initiated deregistration for the only public user identity currently registered with its associated set of implicitly registered public user identities (i.e. no other is registered) while there are still active multimedia sessions belonging to this user, the S-CSCF shall release all multimedia sessions belonging to this user as described in subclause 5.4.5.1.

When a network-initiated deregistration event occurs for one or more public user identity, the S-CSCF shall send a NOTIFY request to the UE on the dialog which was generated by the UE subscribing to the reg event package. When the S-CSCF receives a final response to the NOTIFY request or upon a timeout, the S-CSCF shall release all remaining dialogs related to the public user identity being deregistered and shall generate a NOTIFY request on all remaining dialogs which have been established due to subscription to the reg event package of that user. For each NOTIFY request, the S-CSCF shall:

- 1) set the Request-URI and Route header to the saved route information during subscription;

- 2) set the Event header to the "reg" value;
- 3) in the body of the NOTIFY request, include as many <registration> elements as many public user identities the S-CSCF is aware of the user owns;
- 4) set the aor attribute within each <registration> element to one public user identity:
 - a) set the <contact> sub-element of each <registration> element to the contact address provided by the UE;
 - b) if the public user identity:
 - i) has been deregistered then:
 - set the state attribute within the <registration> element to "terminated";
 - set the state attribute within the <contact> element to "terminated"; and
 - set the event attribute within the <contact> element to "deactivated" if the S-CSCF expects the UE to reregister or "rejected" if the S-CSCF does not expect the UE to reregister; or
 - ii) has been kept registered then:
 - set the state attribute within the <registration> element to "active"; and
 - set the state attribute within the <contact> element to "active".

The S-CSCF shall only include the non-barred public user identities in the NOTIFY request.

~~Based on operators' policy the S-CSCF can request of the HSS to either be kept or cleared as the S-CSCF allocated to this subscriber.~~

Also, the S-CSCF shall send a third-party REGISTER request, as described in subclause 5.4.1.7, to each AS that matches the Filter Criteria from the HSS for the REGISTER event.

On completion of the above procedures in this subclause for one or more public user identities, the S-CSCF shall deregister those public user identities and the associated implicitly registered public user identities. On completion of the Cx Server Assignment procedure with the HSS, as described in 3GPP TS 29.229 [15], the S-CSCF shall update or remove those public user identities, their registration state and the associated service profiles from the local data (based on operators' policy the S-CSCF can request of the HSS to either be kept or cleared as the S-CSCF allocated to this subscriber).

CR-Form-v7

CHANGE REQUEST

⌘ **24.229 CR 503** ⌘ rev **2** ⌘ Current version: **6.0.0** ⌘

For **HELP** on using this form, see bottom of this page or look at the pop-up text over the ⌘ symbols.

Proposed change affects: UICC apps ME Radio Access Network Core Network

Title:	⌘ Update of HSS information at deregistration		
Source:	⌘ Orange		
Work item code:	⌘ IMS-CCR	Date:	⌘ 10/10/2003
Category:	⌘ A	Release:	⌘ Rel-6
	Use <u>one</u> of the following categories: F (correction) A (corresponds to a correction in an earlier release) B (addition of feature), C (functional modification of feature) D (editorial modification) Detailed explanations of the above categories can be found in 3GPP TR 21.900 .		Use <u>one</u> of the following releases: 2 (GSM Phase 2) R96 (Release 1996) R97 (Release 1997) R98 (Release 1998) R99 (Release 1999) Rel-4 (Release 4) Rel-5 (Release 5) Rel-6 (Release 6)

Reason for change:	⌘ When network initiated deregistration occurs, there is no statement regarding the fact that the S-CSCF shall update user registration status in the HSS.
Summary of change:	⌘ It is added that when network initiated deregistration occurs, the S-CSCF shall deregister in the HSS the public user identity found in the To header field together with the implicitly registered public user identities. It is also clarified the Cx procedure to be used for this deregistration in the HSS.
Consequences if not approved:	⌘ In the case the S-CSCF does not update HSS information on deregistration initiated by the network, the user registration status in the HSS will still indicate that the user is registered for some public user identities whereas deregistration occurred for those identities.

Clauses affected:	⌘ 5.4.1.4, 5.4.1.5						
Other specs affected:	<table border="1" style="display: inline-table; border-collapse: collapse;"> <tr> <td style="width: 20px; text-align: center;">Y</td> <td style="width: 20px; text-align: center;">N</td> </tr> <tr> <td style="text-align: center;"><input type="checkbox"/></td> <td style="text-align: center;"><input checked="" type="checkbox"/></td> </tr> </table> Other core specifications	Y	N	<input type="checkbox"/>	<input checked="" type="checkbox"/>	⌘	
Y	N						
<input type="checkbox"/>	<input checked="" type="checkbox"/>						
	<table border="1" style="display: inline-table; border-collapse: collapse;"> <tr> <td style="text-align: center;"><input checked="" type="checkbox"/></td> </tr> </table> Test specifications	<input checked="" type="checkbox"/>	⌘				
<input checked="" type="checkbox"/>							
	<table border="1" style="display: inline-table; border-collapse: collapse;"> <tr> <td style="text-align: center;"><input checked="" type="checkbox"/></td> </tr> </table> O&M Specifications	<input checked="" type="checkbox"/>	⌘				
<input checked="" type="checkbox"/>							
Other comments:	⌘						

How to create CRs using this form:

Comprehensive information and tips about how to create CRs can be found at <http://www.3gpp.org/specs/CR.htm>. Below is a brief summary:

- 1) Fill out the above form. The symbols above marked ⌘ contain pop-up help information about the field that they are closest to.

- 2) Obtain the latest version for the release of the specification to which the change is proposed. Use the MS Word "revision marks" feature (also known as "track changes") when making the changes. All 3GPP specifications can be downloaded from the 3GPP server under <ftp://ftp.3gpp.org/specs/> For the latest version, look for the directory name with the latest date e.g. 2001-03 contains the specifications resulting from the March 2001 TSG meetings.
- 3) With "track changes" disabled, paste the entire CR form (use CTRL-A to select it) into the specification just in front of the clause containing the first piece of changed text. Delete those parts of the specification which are not relevant to the change request.

*****FIRST CHANGE*****

5.4.1.4 User-initiated deregistration

When S-CSCF receives a REGISTER request with the Expires header field containing the value zero, the S-CSCF shall:

- check whether the P-CSCF included the Integrity-protection parameter into the Authorization header field set to yes, indicating that the REGISTER request was received integrity protected. The S-CSCF shall only proceed with the following steps if the integrity protection parameter is set to yes;
- release each multimedia session which was initiated with the public user identity found in the P-Asserted-Identity header field or with one of the implicitly registered public used identities by applying the steps listed in subclause 5.4.5.1.2;
- deregister the public user identity found in the To header field together with the implicitly registered public user identities;
- send a third-party REGISTER request, as described in subclause 5.4.1.7, to each AS that matches the Filter Criteria from the HSS for the REGISTER event; and
- if this is a deregistration request for the only public user identity currently registered with its associated set of implicitly registered public user identities (i.e. no other is registered) and there are still active multimedia sessions associated with this user, release each multimedia session belonging to the served user by applying the steps listed in subclause 5.4.5.1.2.

~~Based on operators' policy the S-CSCF can request of the HSS to either be kept or cleared as the S-CSCF allocated to this subscriber.~~

If all public user identities of the UE are deregistered, then the S-CSCF may consider the UE and P-CSCF subscriptions to the reg event package cancelled (i.e. as if the UE had sent a SUBSCRIBE request with an Expires header containing a value of zero).

If the Authorization header of the REGISTER request did not contain an Integrity-protection parameter, or the parameter was set to the value 'no', the S-CSCF shall respond to the request with a 403 (Forbidden) response. The response may contain a Warning header with a warn-code 399.

On completion of the above procedures in this subclause and of the Cx Server Assignment procedure with the HSS, as described in 3GPP TS 29.229 [15], for one or more public user identities, the S-CSCF shall update or remove those public user identities, their registration state and the associated service profiles from the local data (based on operators' policy the S-CSCF can request of the HSS to either be kept or cleared as the S-CSCF allocated to this subscriber).

XXX NEXT CHANGE XX

5.4.1.5 Network-initiated deregistration

Prior to initiating the network-initiated deregistration for the only public user identity currently registered with its associated set of implicitly registered public user identities (i.e. no other is registered) while there are still active multimedia sessions belonging to this user, the S-CSCF shall release all multimedia sessions belonging to this user as described in subclause 5.4.5.1.

When a network-initiated deregistration event occurs for one or more public user identity, the S-CSCF shall send a NOTIFY request to the UE on the dialog which was generated by the UE subscribing to the reg event package. When the S-CSCF receives a final response to the NOTIFY request or upon a timeout, the S-CSCF shall release all remaining dialogs related to the public user identity being deregistered and shall generate a NOTIFY request on all remaining dialogs which have been established due to subscription to the reg event package of that user. For each NOTIFY request, the S-CSCF shall:

- 1) set the Request-URI and Route header to the saved route information during subscription;
- 2) set the Event header to the "reg" value;
- 3) in the body of the NOTIFY request, include as many <registration> elements as many public user identities the S-CSCF is aware of the user owns;
- 4) set the aor attribute within each <registration> element to one public user identity:
 - a) set the <contact> sub-element of each <registration> element to the contact address provided by the UE;
 - b) if the public user identity:
 - i) has been deregistered then:
 - set the state attribute within the <registration> element to "terminated";
 - set the state attribute within the <contact> element to "terminated"; and
 - set the event attribute within the <contact> element to "deactivated" if the S-CSCF expects the UE to reregister or "rejected" if the S-CSCF does not expect the UE to reregister; or
 - ii) has been kept registered then:
 - set the state attribute within the <registration> element to "active"; and
 - set the state attribute within the <contact> element to "active".

The S-CSCF shall only include the non-barred public user identities in the NOTIFY request.

~~Based on operators' policy the S-CSCF can request of the HSS to either be kept or cleared as the S-CSCF allocated to this subscriber.~~

Also, the S-CSCF shall send a third-party REGISTER request, as described in subclause 5.4.1.7, to each AS that matches the Filter Criteria from the HSS for the REGISTER event.

On completion of the above procedures for one or more public user identities, the S-CSCF shall deregister those public user identities and the associated implicitly registered public user identities. On completion of the Cx Server Assignment procedure with the HSS, as described in 3GPP TS 29.229 [15], the S-CSCF shall update or remove those public user identities, their registration state and the associated service profiles from the local data (based on operators' policy the S-CSCF can request of the HSS to either be kept or cleared as the S-CSCF allocated to this subscriber).

CR-Form-v7

CHANGE REQUEST

⌘ **24.229 CR 508** ⌘ rev - ⌘ Current version: **5.6.0** ⌘

For **HELP** on using this form, see bottom of this page or look at the pop-up text over the ⌘ symbols.

Proposed change affects: UICC apps ⌘ ME Radio Access Network Core Network

Title:	⌘ Reference corrections		
Source:	⌘ Lucent Technologies		
Work item code:	⌘ IMS-CCR	Date:	⌘ 09/10/2003
Category:	⌘ F	Release:	⌘ Rel-5
	Use <u>one</u> of the following categories:		Use <u>one</u> of the following releases:
	F (correction)	2	(GSM Phase 2)
	A (corresponds to a correction in an earlier release)	R96	(Release 1996)
	B (addition of feature),	R97	(Release 1997)
	C (functional modification of feature)	R98	(Release 1998)
	D (editorial modification)	R99	(Release 1999)
	Detailed explanations of the above categories can be found in 3GPP TR 21.900 .	Rel-4	(Release 4)
		Rel-5	(Release 5)
		Rel-6	(Release 6)

Reason for change:	⌘ draft-ietf-sip-scvrtdisco has just been published as RFC 3608, and therefore the references clause requires revision to reflect a published document, rather than a document that is not published and which will shortly disappear from the IETF web site. There are no technical changes between the published version and the i-d, although the clause numbering has changed at some point (clause 6 is now clause 5).
Summary of change:	⌘ In clause 2, reference [38] is revised to RFC 3608. In table A.4, typos are corrected in the conditional referring to support of [38]. In table A.123 and table A.279, the reference is corrected for the Service-Route header.
Consequences if not approved:	⌘ References will be made to a specification version that is not available.

Clauses affected:	⌘ 2, A.2.1.2, A.2.1.4.12, A.2.2.4.12										
Other specs affected:	<table border="1" style="display: inline-table; border-collapse: collapse;"> <tr> <td style="width: 20px;">Y</td> <td style="width: 20px;">N</td> </tr> <tr> <td style="text-align: center;">⌘</td> <td style="text-align: center;">X</td> </tr> <tr> <td style="text-align: center;">⌘</td> <td style="text-align: center;">X</td> </tr> <tr> <td style="text-align: center;">⌘</td> <td style="text-align: center;">X</td> </tr> </table>	Y	N	⌘	X	⌘	X	⌘	X	Other core specifications	⌘
Y	N										
⌘	X										
⌘	X										
⌘	X										
		Test specifications									
		O&M Specifications									
Other comments:	⌘										

How to create CRs using this form:

Comprehensive information and tips about how to create CRs can be found at <http://www.3gpp.org/specs/CR.htm>. Below is a brief summary:

- 1) Fill out the above form. The symbols above marked ⌘ contain pop-up help information about the field that they are closest to.
- 2) Obtain the latest version for the release of the specification to which the change is proposed. Use the MS Word "revision marks" feature (also known as "track changes") when making the changes. All 3GPP specifications can be downloaded from the 3GPP server under <ftp://ftp.3gpp.org/specs/> For the latest version, look for the directory name with the latest date e.g. 2001-03 contains the specifications resulting from the March 2001 TSG meetings.
- 3) With "track changes" disabled, paste the entire CR form (use CTRL-A to select it) into the specification just in front of the clause containing the first piece of changed text. Delete those parts of the specification which are not relevant to the change request.

PROPOSED CHANGE

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 23.002: "Network architecture".
- [3] 3GPP TS 23.003: "Numbering, addressing and identification".
- [4] 3GPP TS 23.060: "General Packet Radio Service (GPRS); Service description; Stage 2".
- [4A] 3GPP TS 23.107: "Quality of Service (QoS) concept and architecture".
- [5] 3GPP TS 23.218: "IP Multimedia (IM) Session Handling; IM call model".
- [6] 3GPP TS 23.221: "Architectural requirements".
- [7] 3GPP TS 23.228: "IP multimedia subsystem; Stage 2".
- [8] 3GPP TS 24.008: "Mobile radio interface layer 3 specification; Core Network protocols; Stage 3".
- [9] 3GPP TS 25.304: "UE Procedures in Idle Mode and Procedures for Cell Reselection in Connected Mode".
- [9A] 3GPP TS 25.331: "Radio Resource Control (RRC); Protocol Specification".
- [10] 3GPP TS 26.235: "Packet switched conversational multimedia applications; Default codecs".
- [10A] 3GPP TS 27.060: "Mobile Station (MS) supporting Packet Switched Services".
- [11] 3GPP TS 29.061: "Interworking between the Public Land Mobile Network (PLMN) supporting Packet Based Services and Packet Data Networks (PDN)".
- [12] 3GPP TS 29.207: "Policy control over Gs interface".
- [13] 3GPP TS 29.208: "End to end Quality of Service (QoS) signalling flows".
- [14] 3GPP TS 29.228: "IP Multimedia (IM) Subsystem Cx and Dx Interfaces; Signalling flows and message contents".
- [15] 3GPP TS 29.229: "Cx and Dx Interfaces based on the Diameter protocol, Protocol details".
- [16] 3GPP TS 32.200: "Telecommunication management; Charging management; Charging principles".
- [17] 3GPP TS 32.225: "Telecommunication management; Charging management; Charging data description for the IP Multimedia subsystem".

- [18] 3GPP TS 33.102: "3G Security; Security architecture".
- [19] 3GPP TS 33.203: "Access security for IP based services".
- [20] 3GPP TS 44.018: "Mobile radio interface layer 3 specification, Radio Resource Control Protocol".
- [20A] RFC 2401 (November 1998): "Security Architecture for the Internet Protocol".
- [20B] RFC 1594 (March 1994): "FYI on Questions and Answers to Commonly asked "New Internet User" Questions".
- [20C] RFC 2403 (November 1998) "The Use of HMAC-MD5-96 within ESP and AH".
- [20D] RFC 2404 (November 1998) "The Use of HMAC-SHA-1-96 within ESP and AH".
- [20E] RFC 2462 (November 1998): "IPv6 Address Autoconfiguration".
- [21] RFC 2617 (June 1999): "HTTP Authentication: Basic and Digest Access Authentication".
- [22] RFC 2806 (April 2000): "URLs for Telephone Calls".
- [23] RFC 2833 (May 2000): "RTP Payload for DTMF Digits, Telephony Tones and Telephony Signals".
- [24] RFC 2916 (September 2000): "E.164 number and DNS".
- [25] RFC 2976 (October 2000): "The SIP INFO method".
- [25A] RFC 3041 (January 2001): "Privacy Extensions for Stateless Address Autoconfiguration in IPv6".
- [26] RFC 3261 (June 2002): "SIP: Session Initiation Protocol".
- [27] RFC 3262 (June 2002): "Reliability of provisional responses in Session Initiation Protocol (SIP)".
- [28] RFC 3265 (June 2002): "Session Initiation Protocol (SIP) Specific Event Notification".
- [29] RFC 3311 (September 2002): "The Session Initiation Protocol (SIP) UPDATE method".
- [30] RFC 3312 (October 2002): "Integration of resource management and Session Initiation Protocol (SIP)".
- [31] RFC 3313 (January 2003): "Private Session Initiation Protocol (SIP) Extensions for Media Authorization".
- [32] RFC 3320 (March 2002): "Signaling Compression (SigComp)".
- [33] RFC 3323 (November 2002): "A Privacy Mechanism for the Session Initiation Protocol (SIP)".
- [34] RFC 3325 (November 2002): "Private Extensions to the Session Initiation Protocol (SIP) for Network Asserted Identity within Trusted Networks".
- [35] RFC 3327 (December 2002): "Session Initiation Protocol Extension Header Field for Registering Non-Adjacent Contacts".
- [36] RFC 3515 (April 2003): "The Session Initiation Protocol (SIP) REFER method".
- [37] RFC 3420 (November 2002): "Internet Media Type message/sipfrag".
- [38] ~~draft-ietf-sip-sevrtdisco-04~~ [RFC 3608](#) (May-October 2003): "Session Initiation Protocol (SIP) Extension Header Field for Service Route Discovery During Registration".
- ~~Editor's note: The above document cannot be formally referenced until it is published as an RFC.~~
- [39] draft-ietf-mmusic-sdp-new-13 (May 2003): "SDP: Session Description Protocol".
- ~~Editor's note: The above document cannot be formally referenced until it is published as an RFC.~~
- [40] RFC 3315 (July 2003): "Dynamic Host Configuration Protocol for IPv6 (DHCPv6)".

- [41] RFC 3319 (July 2003): "Dynamic Host Configuration Protocol (DHCPv6) Options for Session Initiation Protocol (SIP) Servers".
- [42] RFC 3485 (February 2003): "The Session Initiation Protocol (SIP) and Session Description Protocol (SDP) static dictionary for Signaling Compression (SigComp)".
- [43] draft-ietf-sipping-reg-event-00 (October 2002): "A Session Initiation Protocol (SIP) Event Package for Registrations".

Editor's note: The above document cannot be formally referenced until it is published as an RFC.

- [44] Void.
- [45] Void.
- [46] Void.
- [47] Void.
- [48] RFC 3329 (January 2003): "Security Mechanism Agreement for the Session Initiation Protocol (SIP)".
- [49] RFC 3310 (September 2002): "Hypertext Transfer Protocol (HTTP) Digest Authentication Using Authentication and Key Agreement (AKA)".
- [50] RFC 3428 (December 2002): "Session Initiation Protocol (SIP) Extension for Instant Messaging".
- [51] Void.
- [52] RFC 3455 (January 2003): "Private Header (P-Header) Extensions to the Session Initiation Protocol (SIP) for the 3rd-Generation Partnership Project (3GPP)".
- [53] RFC 3388 (December 2002): "Grouping of Media Lines in Session Description Protocol".
- [54] RFC 3524 (April 2003): "Mapping of Media Streams to Resource Reservation Flows".
- [55] RFC 3486 (February 2003): "Compressing the Session Initiation Protocol (SIP)".
- [56] RFC 3556 (July 2003): "Session Description Protocol (SDP) Bandwidth Modifiers for RTP Control Protocol (RTCP) Bandwidth".
- [57] ITU-T Recommendation E.164: "The international public telecommunication numbering plan".

PROPOSED CHANGE

A.2.1.2 Major capabilities

Table A.4: Major capabilities

Item	Does the implementation support	Reference	RFC status	Profile status
	Capabilities within main protocol			
1	client behaviour for registration?	[26] subclause 10.2	m	c3
2	registrar?	[26] subclause 10.3	o	c4
2A	initiating a session?	[26] subclause 13	o	o
3	client behaviour for INVITE requests?	[26] subclause 13.2	c18	c18
4	server behaviour for INVITE requests?	[26] subclause 13.3	c18	c18
5	session release?	[26] subclause 15.1	c18	c18
6	timestamping of requests?	[26] subclause 8.2.6.1	o	o
7	authentication between UA and UA?	[26] subclause 22.2	o	o
8	authentication between UA and registrar?	[26] subclause 22.2	o	n/a
8A	authentication between UA and proxy?	[26] 20.28, 22.3	o	o
9	server handling of merged requests due to forking?	[26] 8.2.2.2	m	m
10	client handling of multiple responses due to forking?	[26] 13.2.2.4	m	m
11	insertion of date in requests and responses?	[26] subclause 20.17	o	o
12	downloading of alerting information?	[26] subclause 20.4	o	o
	Extensions			
13	the SIP INFO method?	[25]	o	n/a
14	reliability of provisional responses in SIP?	[27]	c19	c18
15	the REFER method?	[36]	o	o
16	integration of resource management and SIP?	[30]	c19	c18
17	the SIP UPDATE method?	[29]	c5	c18
19	SIP extensions for media authorization?	[31]	o	c14
20	SIP specific event notification?	[28]	o	c13
21	the use of NOTIFY to establish a dialog?	[28] 4.2	o	n/a
22	acting as the notifier of event information?	[28]	c2	c15
23	acting as the subscriber to event information?	[28]	c2	c16
24	session initiation protocol extension header field for registering non-adjacent contacts?	[35]	o	c6
25	private extensions to the Session Initiation Protocol (SIP) for network asserted identity within trusted networks	[34]	o	m
26	a privacy mechanism for the Session Initiation Protocol (SIP)	[33]	o	m
26A	request of privacy by the inclusion of a Privacy header	[33]	c9	c11
26B	application of privacy based on the received Privacy header	[33]	c9	n/a
26C	passing on of the Privacy header transparently	[33]	c9	c12
26D	application of the privacy option "header" such that those headers which cannot be completely expunged of identifying information without the assistance of intermediaries are obscured?	[33] 5.1	c10	
26E	application of the privacy option	[33] 5.2	c10	

	"session" such that anonymization for the session(s) initiated by this message occurs?			
26F	application of the privacy option "user" such that user level privacy functions are provided by the network?	[33] 5.3	c10	
26G	application of the privacy option "id" such that privacy of the network asserted identity is provided by the network?	[34] 7	c10	n/a
27	a messaging mechanism for the Session Initiation Protocol (SIP)?	[50]	o	c7
28	session initiation protocol extension header field for service route discovery during registration?	[38]	o	c17
29	compressing the session initiation protocol?	[55]	o	c8
30	private header extensions to the session initiation protocol for the 3rd-Generation Partnership Project (3GPP)?	[52]	o	m
31	the P-Associated-URI header extension?	[52] 4.1	c21	c22
32	the P-Called-Party-ID header extension?	[52] 4.2	c21	c23
33	the P-Visited-Network-ID header extension?	[52] 4.3	c21	c24
34	the P-Access-Network-Info header extension?	[52] 4.4	c21	c25
35	the P-Charging-Function-Addresses header extension?	[52] 4.5	c21	c26
36	the P-Charging-Vector header extension?	[52] 4.6	c21	c26
37	security mechanism agreement for the session initiation protocol?	[48]	o	c20

c2:	IF A.4/20 THEN o.1 ELSE n/a - - SIP specific event notification extension.
c3:	IF A.3/1 OR A.3/4 THEN m ELSE n/a - - UE or S-CSCF functional entity.
c4:	IF A.3/4 OR A.3/7 THEN m ELSE n/a - - S-CSCF or AS functional entity.
c5:	IF A.4/16 THEN m ELSE o - - integration of resource management and SIP extension.
c6:	IF A.3/4 OR A.3/1 THEN m ELSE n/a. - - S-CSCF or UE.
c7:	IF A.3/4 THEN m ELSE (IF A.3/1 OR A.3/7B OR A.3/7D THEN o ELSE n/a - - S-CSCF or UA or AS acting as originating UA, or AS performing 3 rd party call control).
c8:	IF A.3/1 THEN m ELSE n/a - - UE behaviour.
c9:	IF A.4/26 THEN o.2 ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).
c10:	IF A.4/26B THEN o.3 ELSE n/a - - application of privacy based on the received Privacy header.
c11:	IF A.3/1 OR A.3/6 THEN o ELSE n/a - - UE or MGCF.
c12:	IF A.3/7D THEN m ELSE n/a - - AS performing 3rd-party call control.
c13:	IF A.3/1 OR A.3/4 THEN m ELSE o - - UE behaviour or S-CSCF.
c14:	IF A.3/1 THEN m ELSE IF A.3/2 THEN o ELSE n/a - UE or P-CSCF.
c15:	IF A.4/20 and A.3/4 THEN m ELSE o - SIP specific event notification extensions and S-CSCF.
c16:	IF A.4/20 and (A.3/1 OR A.3/2) THEN m ELSE o - - SIP specific event notification extension and UE or P-CSCF.
c17:	IF A.3/1 or A.3/4 THEN m ELSE n/a - - UE or S-CSCF.
c18:	IF A.4/2A THEN m ELSE n/a - - initiating sessions.
c19:	IF A.4/2A THEN o ELSE n/a - - initiating sessions.
c20:	IF A.3/1 THEN m ELSE n/a - - UE behaviour.
c21:	IF A.4/30 THEN o.4 ELSE n/a - - private header extensions to the session initiation protocol for the 3rd-Generation Partnership Project (3GPP).
c22:	IF A.4/30 AND (A.3/1 OR A.3/4) THEN m ELSE n/a - - private header extensions to the session initiation protocol for the 3rd-Generation Partnership Project (3GPP) and S-CSCF or UA.
c23:	IF A.4/30 AND A.3/1 THEN o ELSE n/a - - private header extensions to the session initiation protocol for the 3rd-Generation Partnership Project (3GPP) and UE.
c24:	IF A.4/30 AND A.3/4) THEN m ELSE n/a - - private header extensions to the session initiation protocol for the 3rd-Generation Partnership Project (3GPP) and S-CSCF.
c25:	IF A.4/30 AND (A.3/1 OR A.3/4 OR A.3/7A OR A.3/7D) THEN m ELSE n/a - - private header extensions to the session initiation protocol for the 3rd-Generation Partnership Project (3GPP) and UE, S-CSCF or AS acting as terminating UA or AS acting as third-party call controller.
c26:	IF A.4/30 AND (A.3/6 OR A.3/7A OR A.3/7B or A.3/7D) THEN m ELSE n/a - - private header extensions to the session initiation protocol for the 3rd-Generation Partnership Project (3GPP) and MGCF, AS acting as a terminating UA, or AS acting as an originating UA, or AS acting as third-party call controller.
o.1:	At least one of these capabilities is supported.
o.2:	At least one of these capabilities is supported.
o.3:	At least one of these capabilities is supported.
o.4:	At least one of these capabilities is supported.

PROPOSED CHANGE

A.2.1.4.12 REGISTER method

Prerequisite A.5/18 - - REGISTER request

Table A.119: Supported headers within the REGISTER request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Accept	[26] 20.1	o	o	[26] 20.1	m	m
2	Accept-Encoding	[26] 20.2	o	o	[26] 20.2	m	m
3	Accept-Language	[26] 20.3	o	o	[26] 20.3	m	m
3A	Allow	[26] 20.5	o	o	[26] 20.5	m	m
4	Allow-Events	[28] 7.2.2	c1	c1	[28] 7.2.2	c1	c1
5	Authorization	[26] 20.7, [49]	c2	o	[26] 20.7, [49]	m	c22
6	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
7	Call-Info	[26] 20.9	o	o	[26] 20.9	o	o
8	Contact	[26] 20.10	o	o	[26] 20.10	m	m
9	Content-Disposition	[26] 20.11	o	o	[26] 20.11	m	m
10	Content-Encoding	[26] 20.12	o	o	[26] 20.12	m	m
11	Content-Language	[26] 20.13	o	o	[26] 20.13	m	m
12	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
13	Content-Type	[26] 20.15	m	m	[26] 20.15	m	m
14	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
15	Date	[26] 20.17	c3	c3	[26] 20.17	m	m
16	Expires	[26] 20.19	o	o	[26] 20.19	m	m
17	From	[26] 20.20	m	m	[26] 20.20	m	m
18	Max-Forwards	[26] 20.22	m	m	[26] 20.22	n/a	n/a
19	MIME-Version	[26] 20.24	o	o	[26] 20.24	m	m
20	Organization	[26] 20.25	o	o	[26] 20.25	o	o
20A	P-Access-Network-Info	[52] 4.4	c12	c13	[52] 4.4	c12	c14
20B	P-Charging-Function-Addresses	[52] 4.5	c17	c18	[52] 4.5	c17	c18
20C	P-Charging-Vector	[52] 4.6	c15	c16	[52] 4.6	c15	c16
20D	P-Visited-Network-ID	[52] 4.3	x (note 2)	x	[52] 4.3	c10	c11
20E	Path	[35] 4	c4	c5	[35] 4	m	c6
20F	Privacy	[33] 4.2	c9	n/a	[33] 4.2	c9	n/a
21	Proxy-Authorization	[26] 20.28	c8	c8	[26] 20.28	n/a	n/a
22	Proxy-Require	[26] 20.29	o	o (note 1)	[26] 20.29	n/a	n/a
23	Require	[26] 20.32	o	o	[26] 20.32	m	m
24	Route	[26] 20.34	o	n/a	[26] 20.34	n/a	n/a
24A	Security-Client	[48] 2.3.1	c19	c20	[48] 2.3.1	n/a	n/a
24B	Security-Verify	[48] 2.3.1	c20	c20	[48] 2.3.1	c21	n/a
25	Supported	[26] 20.37	o	o	[26] 20.37	m	m
26	Timestamp	[26] 20.38	m	m	[26] 20.38	c7	c7
27	To	[26] 20.39	m	m	[26] 20.39	m	m
28	User-Agent	[26] 20.41	o	o	[26] 20.41	o	o
29	Via	[26] 20.42	m	m	[26] 20.42	m	m

c1:	IF A.4/20 THEN m ELSE n/a - - SIP specific event notification extension.
c2:	IF A.4/8 THEN m ELSE n/a - - authentication between UA and registrar.
c3:	IF A.4/11 THEN o ELSE n/a - - insertion of date in requests and responses.
c4:	IF A.4/24 THEN o ELSE n/a - - session initiation protocol extension header field for registering non-adjacent contacts.
c5:	IF A.4/24 THEN x ELSE n/a - - session initiation protocol extension header field for registering non-adjacent contacts.
c6:	IF A.3/4 THEN m ELSE n/a. - - S-CSCF.
c7:	IF A.4/6 THEN m ELSE n/a - - timestamping of requests.
c8:	IF A.4/8A THEN m ELSE n/a - - authentication between UA and proxy.
c9:	IF A.4/26 THEN o ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).
c10:	IF A.4/33 THEN o ELSE n/a - - the P-Visited-Network-ID extension.
c11:	IF A.4/33 THEN m ELSE n/a - - the P-Visited-Network-ID extension.
c12:	IF A.4/34 THEN o ELSE n/a - - the P-Access-Network-Info header extension.
c13:	IF A.4/34 AND (A.3/1 OR A.3/4) THEN o ELSE n/a - - the P-Access-Network-Info header extension and UE or S-CSCF (note 4).
c14:	IF A.4/34 AND (A.3/4 OR A.3/7A) THEN m ELSE n/a - - the P-Access-Network-Info header extension and S-CSCF or AS acting as terminating UA.
c15:	IF A.4/36 THEN o ELSE n/a - - the P-Charging-Vector header extension.
c16:	IF A.4/36 OR A.3/4 THEN m ELSE n/a - - the P-Charging-Vector header extension (including S-CSCF as registrar).
c17:	IF A.4/35 THEN o ELSE n/a - - the P-Charging-Function-Addresses header extension.
c18:	IF A.4/35 OR A.3/4 THEN m ELSE n/a - - the P-Charging-Function-Addresses header extension (including S-CSCF as registrar).
c19:	IF A.4/37 THEN o ELSE n/a - - security mechanism agreement for the session initiation protocol (note 3).
c20:	IF A.4/37 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol.
c21:	IF A.4/37 AND A.4/2 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol and registrar.
c22:	IF A.3/4 THEN m ELSE n/a - - S-CSCF.
NOTE 1:	No distinction has been made in these tables between first use of a request on a From/To/Call-ID combination, and the usage in a subsequent one. Therefore the use of "o" etc. above has been included from a viewpoint of first usage.
NOTE 2:	The strength of this requirement in RFC 3455 [52] is SHOULD NOT, rather than MUST NOT.
NOTE 3:	Support of this header in this method is dependent on the security mechanism and the security architecture which is implemented.
NOTE 4:	Refere to subclause 5.1.1.2 for information on when the UE sets the P-Access-Network-Info header.

Prerequisite A.5/18 - - REGISTER request

Table A.120: Supported message bodies within the REGISTER request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1							

Prerequisite A.5/19 - - REGISTER response

Prerequisite: A.6/1 - - 100 (Trying)

Table A.121: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Call-ID	[26] 20.8	n/a	n/a	[26] 20.8	m	m
2	Content-Length	[26] 20.14	n/a	n/a	[26] 20.14	m	m
3	Cseq	[26] 20.16	n/a	n/a	[26] 20.16	m	m
4	Date	[26] 20.17	n/a	n/a	[26] 20.17	m	m
5	From	[26] 20.20	n/a	n/a	[26] 20.20	m	m
6	To	[26] 20.39	n/a	n/a	[26] 20.39	m	m
7	Via	[26] 20.42	n/a	n/a	[26] 20.42	m	m

Prerequisite A.5/19 - - REGISTER response

Table A.122: Supported headers within the REGISTER response - all status-codes

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
1A	Call-Info	[26] 20.9	o	o	[26] 20.9	o	o
2	Content-Disposition	[26] 20.11	o	o	[26] 20.11	m	m
3	Content-Encoding	[26] 20.12	o	o	[26] 20.12	m	m
4	Content-Language	[26] 20.13	o	o	[26] 20.13	m	m
5	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
6	Content-Type	[26] 20.15	m	m	[26] 20.15	m	m
7	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
8	Date	[26] 20.17	c1	c1	[26] 20.17	m	m
9	From	[26] 20.20	m	m	[26] 20.20	m	m
10	MIME-Version	[26] 20.24	o	o	[26] 20.24	m	m
11	Organization	[26] 20.25	o	o	[26] 20.25	o	o
11A	P-Access-Network-Info	[52] 4.4	c3	n/a	[52] 4.4	c3	n/a
11B	P-Charging-Function-Addresses	[52] 4.5	c6	c7	[52] 4.5	c6	c7
11C	P-Charging-Vector	[52] 4.6	c4	c5	[52] 4.6	c4	c5
11D	Privacy	[33] 4.2	c2	n/a	[33] 4.2	c2	n/a
11E	Require	[26] 20.32	m	m	[26] 20.32	m	m
11F	Server	[26] 20.35	o	o	[26] 20.35	o	o
12	Timestamp	[26] 20.38	c2	c2	[26] 20.38	m	m
13	To	[26] 20.39	m	m	[26] 20.39	m	m
13A	User-Agent	[26] 20.41	o	o	[26] 20.41	o	o
14	Via	[26] 20.42	m	m	[26] 20.42	m	m
15	Warning	[26] 20.43	o (note)	o	[26] 20.43	o	o
c1:	IF A.4/11 THEN o ELSE n/a - - insertion of date in requests and responses.						
c2:	IF A.4/26 THEN o ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).						
c3:	IF A.4/34 THEN o ELSE n/a - - the P-Access-Network-Info header extension.						
c4:	IF A.4/36 THEN o ELSE n/a - - the P-Charging-Vector header extension.						
c5:	IF A.4/36 OR A.3/4 THEN m ELSE n/a - - the P-Charging-Vector header extension (including S-CSCF as registrar).						
c6:	IF A.4/35 THEN o ELSE n/a - - the P-Charging-Function-Addresses header extension.						
c7:	IF A.4/35 OR A.3/4 THEN m ELSE n/a - - the P-Charging-Function-Addresses header extension (including S-CSCF as registrar).						
NOTE:	For a 606 (Not Acceptable Here) response, this status is RECOMMENDED rather than OPTIONAL.						

Prerequisite A.5/19 - - REGISTER response

Prerequisite: A.6/6 - - 2xx

Table A.123: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Accept	[26] 20.1	o		[26] 20.1	o	
1A	Accept-Encoding	[26] 20.2	o	o	[26] 20.2	m	m
1B	Accept-Language	[26] 20.3	o	o	[26] 20.3	m	m
2	Allow	[26] 20.5	o	o	[26] 20.5	m	m
3	Authentication-Info	[26] 20.6	c6	c6	[26] 20.6	c7	c7
5	Contact	[26] 20.10	o	o	[26] 20.10	m	m
5A	P-Associated-URI	[52] 4.1	c8	c9	[52] 4.1	c10	c11
6	Path	[35] 4	c3	c3	[35] 4	c4	c4
8	Service-Route	[38] 56	c5	c5	[38] 56	c5	c5
9	Supported	[26] 20.37	m	m	[26] 20.37	m	m
c1:	IF (A.3/4 AND A.4/2) THEN m ELSE n/a - - S-CSCF acting as registrar.						
c2:	IF A.3/4 OR A.3/1 THEN m ELSE n/a - - S-CSCF or UE.						
c3:	IF A.4/24 THEN m ELSE n/a - - session initiation protocol extension header field for registering non-adjacent contacts.						
c4:	IF A.4/24 THEN o ELSE n/a - - session initiation protocol extension header field for registering non-adjacent contacts.						
c5:	IF A.4/28 THEN m ELSE n/a - - session initiation protocol extension header field for service route discovery during registration.						
c6:	IF A.4/8 THEN o ELSE n/a - - authentication between UA and registrar.						
c7:	IF A.4/8 THEN m ELSE n/a - - authentication between UA and registrar.						
c8:	IF A.4/2 AND A.4/31 THEN m ELSE n/a - - P-Associated-URI header extension and registrar.						
c9:	IF A.3/1 AND A.4/31 THEN m ELSE n/a - - P-Associated-URI header extension and S-CSCF.						
c10:	IF A.4/31 THEN o ELSE n/a - - P-Associated-URI header extension.						
c11:	IF A.4/31 AND A.3/1 THEN m ELSE n/a - - P-Associated-URI header extension and UE.						

Prerequisite A.5/19 - - REGISTER response

Prerequisite: A.6/8 OR A.6/9 OR A.6/10 OR A.6/11 OR A.6/12 OR A.6/35 - - 3xx or 485 (Ambiguous)

Table A.124: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
3	Contact	[26] 20.10	o (note)	o	[26] 20.10	m	m
4	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
8	Supported	[26] 20.37	m	m	[26] 20.37	m	m
NOTE:	The strength of this requirement is RECOMMENDED rather than OPTIONAL.						

Prerequisite A.5/19 - - REGISTER response

Prerequisite: A.6/14 - - 401 (Unauthorized)

Table A.125: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
3	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
4	Proxy-Authenticate	[26] 20.27	c1	x	[26] 20.27	c1	x
6	Security-Server	[48] 2	x	x	[48] 2	n/a	c2
7	Supported	[26] 20.37	m	m	[26] 20.37	m	m
10	WWW-Authenticate	[26] 20.44	m	m	[26] 20.44	m	m
c1:		IF A.5/8 THEN m ELSE n/a - - support of authentication between UA and UA.					
c2:		IF A.4/37 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol.					

Prerequisite A.5/19 - - REGISTER response

Prerequisite: A.6/17 OR A.6/23 OR A.6/30 OR A.6/36 OR A.6/42 OR A.6/45 OR A.6/50 OR A.6/51 - - 404, 413, 480, 486, 500, 503, 600, 603

Table A.126: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
3	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
6	Retry-After	[26] 20.33	o	o	[26] 20.33	o	o
8	Supported	[26] 20.37	m	m	[26] 20.37	m	m

Prerequisite A.5/19 - - REGISTER response

Prerequisite: A.6/18 - - 405 (Method Not Allowed)

Table A.127: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
2	Allow	[26] 20.5	m	m	[26] 20.5	m	m
4	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
8	Supported	[26] 20.37	m	m	[26] 20.37	m	m

Prerequisite A.5/19 - - REGISTER response

Prerequisite: A.6/20 - - 407 (Proxy Authentication Required)

Table A.128: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
3	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
5	Proxy-Authenticate	[26] 20.27	c1	x	[26] 20.27	c1	x
8	Supported	[26] 20.37	m	m	[26] 20.37	m	m
9	WWW-Authenticate	[26] 20.44	o	o	[26] 20.44	o	o
c1:		IF A.5/8 THEN m ELSE n/a - - support of authentication between UA and UA.					

Prerequisite A.5/19 - - REGISTER response

Prerequisite: A.6/25 - - 415 (Unsupported Media Type)

Table A.129: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Accept	[26] 20.1	o.1	o.1	[26] 20.1	m	m
2	Accept-Encoding	[26] 20.2	o.1	o.1	[26] 20.2	m	m
3	Accept-Language	[26] 20.3	o.1	o.1	[26] 20.3	m	m
4	Allow	[26] 20.5	o	o	[26] 20.5	m	m
5	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
9	Supported	[26] 20.37	m	m	[26] 20.37	m	m
o.1		At least one of these capabilities is supported.					

Prerequisite A.5/19 - - REGISTER response

Prerequisite: A.6/27 - - 420 (Bad Extension)

Table A.130: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
3	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
7	Supported	[26] 20.37	m	m	[26] 20.37	m	m
8	Unsupported	[26] 20.40	m	m	[26] 20.40	m	m

Prerequisite A.5/19 - - REGISTER response

Prerequisite: A.6/28 OR A.6/41A - - 421 (Extension Required), 494 (Security Agreement Required)

Table A.130A: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
2	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
3	Security-Server	[48] 2	c2	c2	[48] 2	c1	c1
4	Supported	[26] 20.37	m	m	[26] 20.37	m	m
c1:		IF A.4/37 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol.					
c2:		IF A.4/37 AND A.4/2 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol and registrar.					

Prerequisite A.5/19 - - REGISTER response

Prerequisite: A.6/29 - - 423 (Interval Too Brief)

Table A.131: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
3	Error-Info	[26] 20.18	o		[26] 20.18	o	
5	Min-Expires	[26] 20.23	m	m	[26] 20.23	m	m
8	Supported	[26] 20.37	m	m	[26] 20.37	m	m

Prerequisite A.5/19 - - REGISTER response

Prerequisite: A.6/34 - - 484 (Address Incomplete)

Table A.132: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
3	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
7	Supported	[26] 20.37	m	m	[26] 20.37	m	m

Prerequisite A.5/19 - - REGISTER response

Table A.133: Supported message bodies within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1							

PROPOSED CHANGE

A.2.2.4.12 REGISTER method

Prerequisite A.163/18 - - REGISTER request

Table A.275: Supported headers within the REGISTER request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Accept	[26] 20.1	m	m	[26] 20.1	i	i
2	Accept-Encoding	[26] 20.2	m	m	[26] 20.2	i	i
3	Accept-Language	[26] 20.3	m	m	[26] 20.3	i	i
3A	Allow	[26] 20.5	m	m	[26] 20.5	i	i
4	Allow-Events	[28] 7.2.2	m	m	[28] 7.2.2	c1	c1
5	Authorization	[26] 20.7, [49]	m	m	[26] 20.7, [49]	i	i
6	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
7	Call-Info	[26] 20.9	m	m	[26] 20.9	c2	c2
8	Contact	[26] 20.10	m	m	[26] 20.10	i	i
9	Content-Disposition	[26] 20.11	m	m	[26] 20.11	i	i
10	Content-Encoding	[26] 20.12	m	m	[26] 20.12	i	i
11	Content-Language	[26] 20.13	m	m	[26] 20.13	i	i
12	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
13	Content-Type	[26] 20.15	m	m	[26] 20.15	i	i
14	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
15	Date	[26] 20.17	m	m	[26] 20.17	m	m
16	Expires	[26] 20.19	m	m	[26] 20.19	i	i
17	From	[26] 20.20	m	m	[26] 20.20	m	m
18	Max-Forwards	[26] 20.22	m	m	[26] 20.22	m	m
19	MIME-Version	[26] 20.24	m	m	[26] 20.24	i	i
20	Organization	[26] 20.25	m	m	[26] 20.25	c3	c3
20A	P-Access-Network-Info	[52] 4.4	c16	c16	[52] 4.4	c17	c17
20B	P-Charging-Function-Addresses	[52] 4.5	c14	c14	[52] 4.5	c15	c15
20C	P-Charging-Vector	[52] 4.6	c12	c12	[52] 4.6	c13	c13
20D	P-Visited-Network-ID	[52] 4.3	c10	c10	[52] 4.3	c11	c11
20E	Path	[35] 4.2	c6	c6	[35] 4.2	c6	c6
20F	Privacy	[33] 4.2	c8	c8	[33] 4.2	c9	c9
21	Proxy-Authorization	[26] 20.28	m	m	[26] 20.28	c7	c7
22	Proxy-Require	[26] 20.29	m	m	[26] 20.29	m	m
23	Require	[26] 20.32	m	m	[26] 20.32	c4	c4
24	Route	[26] 20.34	m	m	[26] 20.34	m	m
24A	Security-Client	[48] 2.3.1	x	x	[48] 2.3.1	c18	c18
24B	Security-Verify	[48] 2.3.1	x	x	[48] 2.3.1	c18	c18
25	Supported	[26] 20.37	m	m	[26] 20.37	c5	c5
26	Timestamp	[26] 20.38	m	m	[26] 20.38	i	i
27	To	[26] 20.39	m	m	[26] 20.39	m	m
28	User-Agent	[26] 20.41	m	m	[26] 20.41	i	i
29	Via	[26] 20.42	m	m	[26] 20.42	m	m

c1:	IF A.4/20 THEN m ELSE i - - SIP specific event notification extension.
c2:	IF A.162/19C OR A.162/19D THEN m ELSE i - - reading, adding or concatenating the Call-Info header.
c3:	IF A.162/19A OR A.162/19B THEN m ELSE i - - reading, adding or concatenating the Organization header.
c4:	IF A.162/11 OR A.162/12 THEN m ELSE i - - reading the contents of the Require header before proxying the request or response or adding or modifying the contents of the Require header before proxying the request or response for methods other than REGISTER.
c5:	IF A.162/16 THEN m ELSE i - - reading the contents of the Supported header before proxying the response.
c6:	IF A.162/29 THEN m ELSE n/a - - PATH header support.
c7:	IF A.162/8A THEN m ELSE i - - authentication between UA and proxy.
c8:	IF A.162/31 THEN m ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).
c9:	IF A.162/31D OR A.162/31G THEN m ELSE IF A.162/31C THEN i ELSE n/a - - application of the privacy option "header" or application of the privacy option "id" or passing on of the Privacy header transparently.
c10:	IF A.162/38 THEN m ELSE n/a - - the P-Visited-Network-ID header extension.
c11:	IF A.162/39 THEN m ELSE i - - reading, or deleting the P-Visited-Network-ID header before proxying the request or response.
c12:	IF A.162/45 THEN m ELSE n/a - - the P-Charging-Vector header extension.
c13:	IF A.162/46 THEN m ELSE IF A.162/45 THEN i ELSE n/a - - adding, deleting, reading or modifying the P-Charging-Vector header before proxying the request or response or the P-Charging-Vector header extension.
c14:	IF A.162/44 THEN m ELSE n/a - - the P-Charging-Function-Addresses header extension.
c15:	IF A.162/44A THEN m ELSE IF A.162/44 THEN i ELSE n/a - - adding, deleting or reading the P-Charging-Function-Addresses header before proxying the request or response, or the P-Charging-Function-Addresses header extension.
c16:	IF A.162/43 THEN x ELSE IF A.162/41 THEN m ELSE n/a - - act as subsequent entity within trust network for access network information that can route outside the trust network, the P-Access-Network-Info header extension.
c17:	IF A.162/43 THEN m ELSE IF A.162/41 THEN i ELSE n/a - - act as subsequent entity within trust network for access network information that can route outside the trust network, the P-Access-Network-Info header extension.
c18:	IF A.4/37 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol.
NOTE:	c1 refers to the UA role major capability as this is the case of a proxy that also acts as a UA specifically for SUBSCRIBE and NOTIFY.

Prerequisite A.163/18 - - REGISTER request

Table A.276: Supported message bodies within the REGISTER request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1							

Prerequisite A.163/19 - - REGISTER response

Prerequisite: A.164/1 - - 100 (Trying)

Table A.277: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
2	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
3	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
4	Date	[26] 20.17	m	m	[26] 20.17	m	m
5	From	[26] 20.20	m	m	[26] 20.20	m	m
6	To	[26] 20.39	m	m	[26] 20.39	m	m
7	Via	[26] 20.42	m	m	[26] 20.42	m	m

Prerequisite A.163/19 - - REGISTER response

Table A.278: Supported headers within the REGISTER response - all remaining status-codes

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
1A	Call-Info	[26] 20.9	m	m	[26] 20.9	c2	c2
2	Content-Disposition	[26] 20.11	m	m	[26] 20.11	i	i
3	Content-Encoding	[26] 20.12	m	m	[26] 20.12	i	i
4	Content-Language	[26] 20.13	m	m	[26] 20.13	i	i
5	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
6	Content-Type	[26] 20.15	m	m	[26] 20.15	i	i
7	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
8	Date	[26] 20.17	m	m	[26] 20.17	m	m
9	From	[26] 20.20	m	m	[26] 20.20	m	m
10	MIME-Version	[26] 20.24	m	m	[26] 20.24	i	i
11	Organization	[26] 20.25	m	m	[26] 20.25	c1	c1
11A	P-Access-Network-Info	[52] 4.4	c9	c9	[52] 4.4	c10	c10
11B	P-Charging-Function-Addresses	[52] 4.5	c7	c7	[52] 4.5	c8	c8
11C	P-Charging-Vector	[52] 4.6	c5	c5	[52] 4.6	c6	c6
11D	Privacy	[33] 4.2	c3	c3	[33] 4.2	c4	c4
11E	Require	[26] 20.32	m	m	[26] 20.32	c11	c11
11F	Server	[26] 20.35	m	m	[26] 20.35	i	i
12	Timestamp	[26] 20.38	m	m	[26] 20.38	i	i
13	To	[26] 20.39	m	m	[26] 20.39	m	m
13A	User-Agent	[26] 20.41	m	m	[26] 20.41	i	i
14	Via	[26] 20.42	m	m	[26] 20.42	m	m
15	Warning	[26] 20.43	m	m	[26] 20.43	i	i
c1:	IF A.162/19A OR A.162/19B THEN m ELSE i - - reading, adding or concatenating the Organization header.						
c2:	IF A.162/19C OR A.162/19D THEN m ELSE i - - reading, adding or concatenating the Call-Info header.						
c3:	IF A.162/31 THEN m ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).						
c4:	IF A.162/31D OR A.162/31G THEN m ELSE IF A.162/31C THEN i ELSE n/a - - application of the privacy option "header" or application of the privacy option "id" or passing on of the Privacy header transparently.						
c5:	IF A.162/45 THEN m ELSE n/a - - the P-Charging-Vector header extension.						
c6:	IF A.162/46 THEN m ELSE IF A.162/45 THEN i ELSE n/a - - adding, deleting, reading or modifying the P-Charging-Vector header before proxying the request or response or the P-Charging-Vector header extension.						
c7:	IF A.162/44 THEN m ELSE n/a - - the P-Charging-Function-Addresses header extension.						
c8:	IF A.162/44A THEN m ELSE IF A.162/44 THEN i ELSE n/a - - adding, deleting or reading the P-Charging-Function-Addresses header before proxying the request or response, or the P-Charging-Function-Addresses header extension.						
c9:	IF A.162/43 THEN x ELSE IF A.162/41 THEN m ELSE n/a - - act as subsequent entity within trust network for access network information that can route outside the trust network, the P-Access-Network-Info header extension.						
c10:	IF A.162/43 THEN m ELSE IF A.162/41 THEN i ELSE n/a - - act as subsequent entity within trust network for access network information that can route outside the trust network, the P-Access-Network-Info header extension.						
c11:	IF A.162/11 OR A.162/12 THEN m ELSE i - - reading the contents of the Require header before proxying the request or response or adding or modifying the contents of the Require header before proxying the request or response for methods other than REGISTER.						

Prerequisite A.163/19 - - REGISTER response

Prerequisite: A.164/6 - - 2xx

Table A.279: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Accept	[26] 20.1	m	m	[26] 20.1	i	i
1A	Accept-Encoding	[26] 20.2	m	m	[26] 20.2	i	i
1B	Accept-Language	[26] 20.3	m	m	[26] 20.3	i	i
2	Allow	[26] 20.5	m	m	[26] 20.5	i	i
3	Authentication-Info	[26] 20.6	m	m	[26] 20.6	i	i
5	Contact	[26] 20.10	m	m	[26] 20.10	i	i
5A	P-Associated-URI	[52] 4.1	c8	c8	[52] 4.1	c9	c10
6	Path	[35] 4.2	c3	c3	[35] 4.2	c4	c4
8	Service-Route	[38] 56	c5	c5	[38] 56	c6	c7
9	Supported	[26] 20.37	m	m	[26] 20.37	i	i
c2:	IF A.3/2 OR A.3/3A THEN m ELSE n/a - - P-CSCF or I-CSCF (THIG).						
c3:	IF A.162/29 THEN m ELSE n/a - - Path extension support.						
c4:	IF A.162/29 THEN i ELSE n/a - - Path extension support.						
c5:	IF A.162/32 THEN m ELSE n/a - - Service-Route extension support.						
c6:	IF A.162/32 THEN i ELSE n/a - - Service-Route extension support.						
c7:	IF A.162/32 THEN (IF A.3/2 THEN m ELSE i) ELSE n/a - - Service-Route extension and P-CSCF.						
c8:	IF A.162/36 THEN m ELSE n/a - - the P-Associated-URI extension.						
c9:	IF A.162/36 THEN i ELSE n/a - - the P-Associated-URI extension.						
c10:	IF A.162/36 AND A.3/2 THEN m ELSE IF A.162/36 AND A.3/3 THEN i ELSE n/a - - the P-Associated-URI extension and P-CSCF or I-CSCF.						

Prerequisite A.163/19 - - REGISTER response

Prerequisite: A.164/8 OR A.164/9 OR A.164/10 OR A.164/11 OR A.164/12 OR A.164/35 - - 3xx or 485 (Ambiguous)

Table A.280: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
3	Contact	[26] 20.10	m	m	[26] 20.10	c2	c2
4	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
8	Supported	[26] 20.37	m	m	[26] 20.37	i	i
c2:	IF A.162/19E THEN m ELSE i - - deleting Contact headers.						

Prerequisite A.163/19 - - REGISTER response

Prerequisite: A.164/14 - - 401 (Unauthorized)

Table A.281: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
3	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
4	Proxy-Authenticate	[26] 20.27	m	m	[26] 20.27	m	m
6	Security-Server	[48] 2	x	c1	[48] 2	n/a	n/a
7	Supported	[26] 20.37	m	m	[26] 20.37	i	i
10	WWW-Authenticate	[26] 20.44	m	m	[26] 20.44	i	i
c1:	IF A.162/47 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol.						

Prerequisite A.163/19 - - REGISTER response

Prerequisite: A.164/17 OR A.164/23 OR A.164/30 OR A.164/36 OR A.164/42 OR A.164/45 OR A.164/50 OR A.164/51 - - 404, 413, 480, 486, 500, 503, 600, 603

Table A.282: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
3	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
6	Retry-After	[26] 20.33	m	m	[26] 20.33	i	i
8	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/19 - - REGISTER response

Prerequisite: A.164/18 - - 405 (Method Not Allowed)

Table A.283: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
2	Allow	[26] 20.5	m	m	[26] 20.5	i	i
4	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
8	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/19 - - REGISTER response

Prerequisite: A.164/20 - - 407 (Proxy Authentication Required)

Table A.284: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
3	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
5	Proxy-Authenticate	[26] 20.27	m	m	[26] 20.27	m	m
8	Supported	[26] 20.37	m	m	[26] 20.37	i	i
9	WWW-Authenticate	[26] 20.44	m	m	[26] 20.44	i	i

Prerequisite A.163/19 - - REGISTER response

Prerequisite: A.164/25 - - 415 (Unsupported Media Type)

Table A.285: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Accept	[26] 20.1	m	m	[26] 20.1	i	i
2	Accept-Encoding	[26] 20.2	m	m	[26] 20.2	i	i
3	Accept-Language	[26] 20.3	m	m	[26] 20.3	i	i
4	Allow	[26] 20.5	m	m	[26] 20.5	i	i
5	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
9	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/19 - - REGISTER response

Prerequisite: A.164/27 - - 420 (Bad Extension)

Table A.286: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
3	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
7	Supported	[26] 20.37	m	m	[26] 20.37	i	i
8	Unsupported	[26] 20.40	m	m	[26] 20.40	c3	c3
c3:		IF A.162/17 THEN m ELSE i					

Prerequisite A.163/19 - - REGISTER response

Prerequisite: A.164/28 OR A.164/41A - - 421 (Extension Required), 494 (Security Agreement Required)

Table A.286A: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
2	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
3	Security-Server	[48] 2	c1	c1	[48] 2	n/a	n/a
4	Supported	[26] 20.37	m	m	[26] 20.37	m	m
c1:		IF A.162/47 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol.					

Prerequisite A.163/19 - - REGISTER response

Prerequisite: A.164/29 - - 423 (Interval Too Brief)

Table A.287: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
3	Error-Info	[26] 20.18	o		[26] 20.18	o	
5	Min-Expires	[26] 20.23	m	m	[26] 20.23	i	i
8	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/19 - - REGISTER response

Prerequisite: A.164/34 - - 484 (Address Incomplete)

Table A.288: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
3	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
7	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/19 - - REGISTER response

Table A.289: Supported message bodies within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1							

CR-Form-v7

CHANGE REQUEST

⌘ **24.229 CR 509** ⌘ rev - ⌘ Current version: **5.6.0** ⌘

For **HELP** on using this form, see bottom of this page or look at the pop-up text over the ⌘ symbols.

Proposed change affects: UICC apps ⌘ ME Radio Access Network Core Network

Title:	⌘ Reference corrections		
Source:	⌘ Lucent Technologies		
Work item code:	⌘ IMS-CCR	Date:	⌘ 09/10/2003
Category:	⌘ A	Release:	⌘ Rel-6
	Use <u>one</u> of the following categories:		Use <u>one</u> of the following releases:
	F (correction)	2	(GSM Phase 2)
	A (corresponds to a correction in an earlier release)	R96	(Release 1996)
	B (addition of feature),	R97	(Release 1997)
	C (functional modification of feature)	R98	(Release 1998)
	D (editorial modification)	R99	(Release 1999)
	Detailed explanations of the above categories can be found in 3GPP TR 21.900 .	Rel-4	(Release 4)
		Rel-5	(Release 5)
		Rel-6	(Release 6)

Reason for change:	⌘ draft-ietf-sip-scvrtdisco has just been published as RFC 3608, and therefore the references clause requires revision to reflect a published document, rather than a document that is not published and which will shortly disappear from the IETF web site. There are no technical changes between the published version and the i-d, although the clause numbering has changed at some point (clause 6 is now clause 5).
Summary of change:	⌘ In clause 2, reference [38] is revised to RFC 3608. In table A.4, typos are corrected in the conditional referring to support of [38]. In table A.123 and table A.279, the reference is corrected for the Service-Route header.
Consequences if not approved:	⌘ References will be made to a specification version that is not available.

Clauses affected:	⌘ 2, A.2.1.2, A.2.1.4.12, A.2.2.4.12						
Other specs affected:	<table border="1" style="display: inline-table; border-collapse: collapse;"> <tr> <td style="width: 20px; text-align: center;">Y</td> <td style="width: 20px; text-align: center;">N</td> </tr> <tr> <td style="text-align: center;"><input type="checkbox"/></td> <td style="text-align: center;"><input checked="" type="checkbox"/></td> </tr> </table>	Y	N	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Other core specifications	⌘
Y	N						
<input type="checkbox"/>	<input checked="" type="checkbox"/>						
	<input checked="" type="checkbox"/>	Test specifications					
	<input checked="" type="checkbox"/>	O&M Specifications					
Other comments:	⌘						

How to create CRs using this form:

Comprehensive information and tips about how to create CRs can be found at <http://www.3gpp.org/specs/CR.htm>. Below is a brief summary:

- 1) Fill out the above form. The symbols above marked ⌘ contain pop-up help information about the field that they are closest to.
- 2) Obtain the latest version for the release of the specification to which the change is proposed. Use the MS Word "revision marks" feature (also known as "track changes") when making the changes. All 3GPP specifications can be downloaded from the 3GPP server under <ftp://ftp.3gpp.org/specs/> For the latest version, look for the directory name with the latest date e.g. 2001-03 contains the specifications resulting from the March 2001 TSG meetings.
- 3) With "track changes" disabled, paste the entire CR form (use CTRL-A to select it) into the specification just in front of the clause containing the first piece of changed text. Delete those parts of the specification which are not relevant to the change request.

PROPOSED CHANGE

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 23.002: "Network architecture".
- [3] 3GPP TS 23.003: "Numbering, addressing and identification".
- [4] 3GPP TS 23.060: "General Packet Radio Service (GPRS); Service description; Stage 2".
- [4A] 3GPP TS 23.107: "Quality of Service (QoS) concept and architecture".
- [5] 3GPP TS 23.218: "IP Multimedia (IM) Session Handling; IM call model".
- [6] 3GPP TS 23.221: "Architectural requirements".
- [7] 3GPP TS 23.228: "IP multimedia subsystem; Stage 2".
- [8] 3GPP TS 24.008: "Mobile radio interface layer 3 specification; Core Network protocols; Stage 3".
- [9] 3GPP TS 25.304: "UE Procedures in Idle Mode and Procedures for Cell Reselection in Connected Mode".
- [9A] 3GPP TS 25.331: "Radio Resource Control (RRC); Protocol Specification".
- [10] 3GPP TS 26.235: "Packet switched conversational multimedia applications; Default codecs".
- [10A] 3GPP TS 27.060: "Mobile Station (MS) supporting Packet Switched Services".
- [11] 3GPP TS 29.061: "Interworking between the Public Land Mobile Network (PLMN) supporting Packet Based Services and Packet Data Networks (PDN)".
- [12] 3GPP TS 29.207: "Policy control over Gs interface".
- [13] 3GPP TS 29.208: "End to end Quality of Service (QoS) signalling flows".
- [14] 3GPP TS 29.228: "IP Multimedia (IM) Subsystem Cx and Dx Interfaces; Signalling flows and message contents".
- [15] 3GPP TS 29.229: "Cx and Dx Interfaces based on the Diameter protocol, Protocol details".
- [16] 3GPP TS 32.200: "Telecommunication management; Charging management; Charging principles".
- [17] 3GPP TS 32.225: "Telecommunication management; Charging management; Charging data description for the IP Multimedia subsystem".

- [18] 3GPP TS 33.102: "3G Security; Security architecture".
- [19] 3GPP TS 33.203: "Access security for IP based services".
- [19A] 3GPP TS 33.210: "IP Network Layer Security".
- [20] 3GPP TS 44.018: "Mobile radio interface layer 3 specification, Radio Resource Control Protocol".
- [20A] RFC 2401 (November 1998): "Security Architecture for the Internet Protocol".
- [20B] RFC 1594 (March 1994): "FYI on Questions and Answers to Commonly asked "New Internet User" Questions".
- [20C] RFC 2403 (November 1998) "The Use of HMAC-MD5-96 within ESP and AH".
- [20D] RFC 2404 (November 1998) "The Use of HMAC-SHA-1-96 within ESP and AH".
- [20E] RFC 2462 (November 1998): "IPv6 Address Autoconfiguration".
- [21] RFC 2617 (June 1999): "HTTP Authentication: Basic and Digest Access Authentication".
- [22] RFC 2806 (April 2000): "URLs for Telephone Calls".
- [23] RFC 2833 (May 2000): "RTP Payload for DTMF Digits, Telephony Tones and Telephony Signals".
- [24] RFC 2916 (September 2000): "E.164 number and DNS".
- [25] RFC 2976 (October 2000): "The SIP INFO method".
- [25A] RFC 3041 (January 2001): "Privacy Extensions for Stateless Address Autoconfiguration in IPv6".
- [26] RFC 3261 (June 2002): "SIP: Session Initiation Protocol".
- [27] RFC 3262 (June 2002): "Reliability of provisional responses in Session Initiation Protocol (SIP)".
- [28] RFC 3265 (June 2002): "Session Initiation Protocol (SIP) Specific Event Notification".
- [29] RFC 3311 (September 2002): "The Session Initiation Protocol (SIP) UPDATE method".
- [30] RFC 3312 (October 2002): "Integration of resource management and Session Initiation Protocol (SIP)".
- [31] RFC 3313 (January 2003): "Private Session Initiation Protocol (SIP) Extensions for Media Authorization".
- [32] RFC 3320 (March 2002): "Signaling Compression (SigComp)".
- [33] RFC 3323 (November 2002): "A Privacy Mechanism for the Session Initiation Protocol (SIP)".
- [34] RFC 3325 (November 2002): "Private Extensions to the Session Initiation Protocol (SIP) for Network Asserted Identity within Trusted Networks".
- [35] RFC 3327 (December 2002): "Session Initiation Protocol Extension Header Field for Registering Non-Adjacent Contacts".
- [36] RFC 3515 (April 2003): "The Session Initiation Protocol (SIP) REFER method".
- [37] RFC 3420 (November 2002): "Internet Media Type message/sipfrag".
- [38] [RFC 3608](#) ~~draft-ietf-sip-sevrtldisco-04~~ (May-October 2003): "Session Initiation Protocol Extension Header Field for Service Route Discovery During Registration".
- ~~Editor's note: The above document cannot be formally referenced until it is published as an RFC.~~
- [39] draft-ietf-mmusic-sdp-new-13 (May 2003): "SDP: Session Description Protocol".

Editor's note: The above document cannot be formally referenced until it is published as an RFC.

- [40] RFC 3315 (July 2003): "Dynamic Host Configuration Protocol for IPv6 (DHCPv6)".
- [41] RFC 3319 (July 2003): "Dynamic Host Configuration Protocol (DHCPv6) Options for Session Initiation Protocol (SIP) Servers".
- [42] RFC 3485 (February 2003): "The Session Initiation Protocol (SIP) and Session Description Protocol (SDP) static dictionary for Signaling Compression (SigComp)".
- [43] draft-ietf-sipping-reg-event-00 (October 2002): "A Session Initiation Protocol (SIP) Event Package for Registrations".

Editor's note: The above document cannot be formally referenced until it is published as an RFC.

- [44] Void.
- [45] Void.
- [46] Void.
- [47] Void.
- [48] RFC 3329 (January 2003): "Security Mechanism Agreement for the Session Initiation Protocol (SIP)".
- [49] RFC 3310 (September 2002): "Hypertext Transfer Protocol (HTTP) Digest Authentication Using Authentication and Key Agreement (AKA)".
- [50] RFC 3428 (December 2002): "Session Initiation Protocol (SIP) Extension for Instant Messaging".
- [51] Void.
- [52] RFC 3455 (January 2003): "Private Header (P-Header) Extensions to the Session Initiation Protocol (SIP) for the 3rd-Generation Partnership Project (3GPP)".
- [53] RFC 3388 (December 2002): "Grouping of Media Lines in Session Description Protocol".
- [54] RFC 3524 (April 2003): "Mapping of Media Streams to Resource Reservation Flows".
- [55] RFC 3486 (February 2003): "Compressing the Session Initiation Protocol (SIP)".
- [56] RFC 3556 (July 2003): "Session Description Protocol (SDP) Bandwidth Modifiers for RTP Control Protocol (RTCP) Bandwidth".
- [57] ITU-T Recommendation E.164: "The international public telecommunication numbering plan".

PROPOSED CHANGE

A.2.1.2 Major capabilities

Table A.4: Major capabilities

Item	Does the implementation support	Reference	RFC status	Profile status
	Capabilities within main protocol			
1	client behaviour for registration?	[26] subclause 10.2	m	c3
2	registrar?	[26] subclause 10.3	o	c4
2A	initiating a session?	[26] subclause 13	o	o
3	client behaviour for INVITE requests?	[26] subclause 13.2	c18	c18
4	server behaviour for INVITE requests?	[26] subclause 13.3	c18	c18
5	session release?	[26] subclause 15.1	c18	c18
6	timestamping of requests?	[26] subclause 8.2.6.1	o	o
7	authentication between UA and UA?	[26] subclause 22.2	o	o
8	authentication between UA and registrar?	[26] subclause 22.2	o	n/a
8A	authentication between UA and proxy?	[26] 20.28, 22.3	o	o
9	server handling of merged requests due to forking?	[26] 8.2.2.2	m	m
10	client handling of multiple responses due to forking?	[26] 13.2.2.4	m	m
11	insertion of date in requests and responses?	[26] subclause 20.17	o	o
12	downloading of alerting information?	[26] subclause 20.4	o	o
	Extensions			
13	the SIP INFO method?	[25]	o	n/a
14	reliability of provisional responses in SIP?	[27]	c19	c18
15	the REFER method?	[36]	o	o
16	integration of resource management and SIP?	[30]	c19	c18
17	the SIP UPDATE method?	[29]	c5	c18
19	SIP extensions for media authorization?	[31]	o	c14
20	SIP specific event notification?	[28]	o	c13
21	the use of NOTIFY to establish a dialog?	[28] 4.2	o	n/a
22	acting as the notifier of event information?	[28]	c2	c15
23	acting as the subscriber to event information?	[28]	c2	c16
24	session initiation protocol extension header field for registering non-adjacent contacts?	[35]	o	c6
25	private extensions to the Session Initiation Protocol (SIP) for network asserted identity within trusted networks	[34]	o	m
26	a privacy mechanism for the Session Initiation Protocol (SIP)	[33]	o	m
26A	request of privacy by the inclusion of a Privacy header	[33]	c9	c11
26B	application of privacy based on the received Privacy header	[33]	c9	n/a
26C	passing on of the Privacy header transparently	[33]	c9	c12
26D	application of the privacy option "header" such that those headers which cannot be completely expunged of identifying information without the assistance of intermediaries are obscured?	[33] 5.1	c10	
26E	application of the privacy option	[33] 5.2	c10	

	"session" such that anonymization for the session(s) initiated by this message occurs?			
26F	application of the privacy option "user" such that user level privacy functions are provided by the network?	[33] 5.3	c10	
26G	application of the privacy option "id" such that privacy of the network asserted identity is provided by the network?	[34] 7	c10	n/a
27	a messaging mechanism for the Session Initiation Protocol (SIP)?	[50]	o	c7
28	session initiation protocol extension header field for service route discovery during registration?	[38]	o	c17
29	compressing the session initiation protocol?	[55]	o	c8
30	private header extensions to the session initiation protocol for the 3rd-Generation Partnership Project (3GPP)?	[52]	o	m
31	the P-Associated-URI header extension?	[52] 4.1	c21	c22
32	the P-Called-Party-ID header extension?	[52] 4.2	c21	c23
33	the P-Visited-Network-ID header extension?	[52] 4.3	c21	c24
34	the P-Access-Network-Info header extension?	[52] 4.4	c21	c25
35	the P-Charging-Function-Addresses header extension?	[52] 4.5	c21	c26
36	the P-Charging-Vector header extension?	[52] 4.6	c21	c26
37	security mechanism agreement for the session initiation protocol?	[48]	o	c20

c2:	IF A.4/20 THEN o.1 ELSE n/a - - SIP specific event notification extension.
c3:	IF A.3/1 OR A.3/4 THEN m ELSE n/a - - UE or S-CSCF functional entity.
c4:	IF A.3/4 OR A.3/7 THEN m ELSE n/a - - S-CSCF or AS functional entity.
c5:	IF A.4/16 THEN m ELSE o - - integration of resource management and SIP extension.
c6:	IF A.3/4 OR A.3/1 THEN m ELSE n/a. - - S-CSCF or UE.
c7:	IF A.3/4 THEN m ELSE (IF A.3/1 OR A.3/7B OR A.3/7D THEN o ELSE n/a - - S-CSCF or UA or AS acting as originating UA, or AS performing 3 rd party call control).
c8:	IF A.3/1 THEN m ELSE n/a - - UE behaviour.
c9:	IF A.4/26 THEN o.2 ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).
c10:	IF A.4/26B THEN o.3 ELSE n/a - - application of privacy based on the received Privacy header.
c11:	IF A.3/1 OR A.3/6 THEN o ELSE n/a - - UE or MGCF.
c12:	IF A.3/7D THEN m ELSE n/a - - AS performing 3rd-party call control.
c13:	IF A.3/1 OR A.3/4 THEN m ELSE o - - UE behaviour or S-CSCF.
c14:	IF A.3/1 THEN m ELSE IF A.3/2 THEN o ELSE n/a - UE or P-CSCF.
c15:	IF A.4/20 and A.3/4 THEN m ELSE o - SIP specific event notification extensions and S-CSCF.
c16:	IF A.4/20 and (A.3/1 OR A.3/2) THEN m ELSE o - - SIP specific event notification extension and UE or P-CSCF.
c17:	IF A.3/1 or A.3/4 THEN m ELSE n/a - UE or S-CSCF.
c18:	IF A.4/2A THEN m ELSE n/a - - initiating sessions.
c19:	IF A.4/2A THEN o ELSE n/a - - initiating sessions.
c20:	IF A.3/1 THEN m ELSE n/a - - UE behaviour.
c21:	IF A.4/30 THEN o.4 ELSE n/a - - private header extensions to the session initiation protocol for the 3rd-Generation Partnership Project (3GPP).
c22:	IF A.4/30 AND (A.3/1 OR A.3/4) THEN m ELSE n/a - - private header extensions to the session initiation protocol for the 3rd-Generation Partnership Project (3GPP) and S-CSCF or UA.
c23:	IF A.4/30 AND A.3/1 THEN o ELSE n/a - - - private header extensions to the session initiation protocol for the 3rd-Generation Partnership Project (3GPP) and UE.
c24:	IF A.4/30 AND A.3/4) THEN m ELSE n/a - - private header extensions to the session initiation protocol for the 3rd-Generation Partnership Project (3GPP) and S-CSCF.
c25:	IF A.4/30 AND (A.3/1 OR A.3/4 OR A.3/7A OR A.3/7D) THEN m ELSE n/a - - private header extensions to the session initiation protocol for the 3rd-Generation Partnership Project (3GPP) and UE, S-CSCF or AS acting as terminating UA or AS acting as third-party call controller.
c26:	IF A.4/30 AND (A.3/6 OR A.3/7A OR A.3/7B or A.3/7D) THEN m ELSE n/a - - private header extensions to the session initiation protocol for the 3rd-Generation Partnership Project (3GPP) and MGCF, AS acting as a terminating UA, or AS acting as an originating UA, or AS acting as third-party call controller.
o.1:	At least one of these capabilities is supported.
o.2:	At least one of these capabilities is supported.
o.3:	At least one of these capabilities is supported.
o.4:	At least one of these capabilities is supported.

PROPOSED CHANGE

A.2.1.4.12 REGISTER method

Prerequisite A.5/18 - - REGISTER request

Table A.119: Supported headers within the REGISTER request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Accept	[26] 20.1	o	o	[26] 20.1	m	m
2	Accept-Encoding	[26] 20.2	o	o	[26] 20.2	m	m
3	Accept-Language	[26] 20.3	o	o	[26] 20.3	m	m
3A	Allow	[26] 20.5	o	o	[26] 20.5	m	m
4	Allow-Events	[28] 7.2.2	c1	c1	[28] 7.2.2	c1	c1
5	Authorization	[26] 20.7, [49]	c2	o	[26] 20.7, [49]	m	c22
6	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
7	Call-Info	[26] 20.9	o	o	[26] 20.9	o	o
8	Contact	[26] 20.10	o	o	[26] 20.10	m	m
9	Content-Disposition	[26] 20.11	o	o	[26] 20.11	m	m
10	Content-Encoding	[26] 20.12	o	o	[26] 20.12	m	m
11	Content-Language	[26] 20.13	o	o	[26] 20.13	m	m
12	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
13	Content-Type	[26] 20.15	m	m	[26] 20.15	m	m
14	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
15	Date	[26] 20.17	c3	c3	[26] 20.17	m	m
16	Expires	[26] 20.19	o	o	[26] 20.19	m	m
17	From	[26] 20.20	m	m	[26] 20.20	m	m
18	Max-Forwards	[26] 20.22	m	m	[26] 20.22	n/a	n/a
19	MIME-Version	[26] 20.24	o	o	[26] 20.24	m	m
20	Organization	[26] 20.25	o	o	[26] 20.25	o	o
20A	P-Access-Network-Info	[52] 4.4	c12	c13	[52] 4.4	c12	c14
20B	P-Charging-Function-Addresses	[52] 4.5	c17	c18	[52] 4.5	c17	c18
20C	P-Charging-Vector	[52] 4.6	c15	c16	[52] 4.6	c15	c16
20D	P-Visited-Network-ID	[52] 4.3	x (note 2)	x	[52] 4.3	c10	c11
20E	Path	[35] 4	c4	c5	[35] 4	m	c6
20F	Privacy	[33] 4.2	c9	n/a	[33] 4.2	c9	n/a
21	Proxy-Authorization	[26] 20.28	c8	c8	[26] 20.28	n/a	n/a
22	Proxy-Require	[26] 20.29	o	o (note 1)	[26] 20.29	n/a	n/a
23	Require	[26] 20.32	o	o	[26] 20.32	m	m
24	Route	[26] 20.34	o	n/a	[26] 20.34	n/a	n/a
24A	Security-Client	[48] 2.3.1	c19	c20	[48] 2.3.1	n/a	n/a
24B	Security-Verify	[48] 2.3.1	c20	c20	[48] 2.3.1	c21	n/a
25	Supported	[26] 20.37	o	o	[26] 20.37	m	m
26	Timestamp	[26] 20.38	m	m	[26] 20.38	c7	c7
27	To	[26] 20.39	m	m	[26] 20.39	m	m
28	User-Agent	[26] 20.41	o	o	[26] 20.41	o	o
29	Via	[26] 20.42	m	m	[26] 20.42	m	m

c1:	IF A.4/20 THEN m ELSE n/a - - SIP specific event notification extension.
c2:	IF A.4/8 THEN m ELSE n/a - - authentication between UA and registrar.
c3:	IF A.4/11 THEN o ELSE n/a - - insertion of date in requests and responses.
c4:	IF A.4/24 THEN o ELSE n/a - - session initiation protocol extension header field for registering non-adjacent contacts.
c5:	IF A.4/24 THEN x ELSE n/a - - session initiation protocol extension header field for registering non-adjacent contacts.
c6:	IF A.3/4 THEN m ELSE n/a. - - S-CSCF.
c7:	IF A.4/6 THEN m ELSE n/a - - timestamping of requests.
c8:	IF A.4/8A THEN m ELSE n/a - - authentication between UA and proxy.
c9:	IF A.4/26 THEN o ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).
c10:	IF A.4/33 THEN o ELSE n/a - - the P-Visited-Network-ID extension.
c11:	IF A.4/33 THEN m ELSE n/a - - the P-Visited-Network-ID extension.
c12:	IF A.4/34 THEN o ELSE n/a - - the P-Access-Network-Info header extension.
c13:	IF A.4/34 AND (A.3/1 OR A.3/4) THEN o ELSE n/a - - the P-Access-Network-Info header extension and UE or S-CSCF (note 4).
c14:	IF A.4/34 AND (A.3/4 OR A.3/7A) THEN m ELSE n/a - - the P-Access-Network-Info header extension and S-CSCF or AS acting as terminating UA.
c15:	IF A.4/36 THEN o ELSE n/a - - the P-Charging-Vector header extension.
c16:	IF A.4/36 OR A.3/4 THEN m ELSE n/a - - the P-Charging-Vector header extension (including S-CSCF as registrar).
c17:	IF A.4/35 THEN o ELSE n/a - - the P-Charging-Function-Addresses header extension.
c18:	IF A.4/35 OR A.3/4 THEN m ELSE n/a - - the P-Charging-Function-Addresses header extension (including S-CSCF as registrar).
c19:	IF A.4/37 THEN o ELSE n/a - - security mechanism agreement for the session initiation protocol (note 3).
c20:	IF A.4/37 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol.
c21:	IF A.4/37 AND A.4/2 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol and registrar.
c22:	IF A.3/4 THEN m ELSE n/a - - S-CSCF.
NOTE 1:	No distinction has been made in these tables between first use of a request on a From/To/Call-ID combination, and the usage in a subsequent one. Therefore the use of "o" etc. above has been included from a viewpoint of first usage.
NOTE 2:	The strength of this requirement in RFC 3455 [52] is SHOULD NOT, rather than MUST NOT.
NOTE 3:	Support of this header in this method is dependent on the security mechanism and the security architecture which is implemented.
NOTE 4:	Refere to subclause 5.1.1.2 for information on when the UE sets the P-Access-Network-Info header.

Prerequisite A.5/18 - - REGISTER request

Table A.120: Supported message bodies within the REGISTER request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1							

Prerequisite A.5/19 - - REGISTER response

Prerequisite: A.6/1 - - 100 (Trying)

Table A.121: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Call-ID	[26] 20.8	n/a	n/a	[26] 20.8	m	m
2	Content-Length	[26] 20.14	n/a	n/a	[26] 20.14	m	m
3	Cseq	[26] 20.16	n/a	n/a	[26] 20.16	m	m
4	Date	[26] 20.17	n/a	n/a	[26] 20.17	m	m
5	From	[26] 20.20	n/a	n/a	[26] 20.20	m	m
6	To	[26] 20.39	n/a	n/a	[26] 20.39	m	m
7	Via	[26] 20.42	n/a	n/a	[26] 20.42	m	m

Prerequisite A.5/19 - - REGISTER response

Table A.122: Supported headers within the REGISTER response - all status-codes

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
1A	Call-Info	[26] 20.9	o	o	[26] 20.9	o	o
2	Content-Disposition	[26] 20.11	o	o	[26] 20.11	m	m
3	Content-Encoding	[26] 20.12	o	o	[26] 20.12	m	m
4	Content-Language	[26] 20.13	o	o	[26] 20.13	m	m
5	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
6	Content-Type	[26] 20.15	m	m	[26] 20.15	m	m
7	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
8	Date	[26] 20.17	c1	c1	[26] 20.17	m	m
9	From	[26] 20.20	m	m	[26] 20.20	m	m
10	MIME-Version	[26] 20.24	o	o	[26] 20.24	m	m
11	Organization	[26] 20.25	o	o	[26] 20.25	o	o
11A	P-Access-Network-Info	[52] 4.4	c3	n/a	[52] 4.4	c3	n/a
11B	P-Charging-Function-Addresses	[52] 4.5	c6	c7	[52] 4.5	c6	c7
11C	P-Charging-Vector	[52] 4.6	c4	c5	[52] 4.6	c4	c5
11D	Privacy	[33] 4.2	c2	n/a	[33] 4.2	c2	n/a
11E	Require	[26] 20.32	m	m	[26] 20.32	m	m
11F	Server	[26] 20.35	o	o	[26] 20.35	o	o
12	Timestamp	[26] 20.38	c2	c2	[26] 20.38	m	m
13	To	[26] 20.39	m	m	[26] 20.39	m	m
13A	User-Agent	[26] 20.41	o	o	[26] 20.41	o	o
14	Via	[26] 20.42	m	m	[26] 20.42	m	m
15	Warning	[26] 20.43	o (note)	o	[26] 20.43	o	o
c1:	IF A.4/11 THEN o ELSE n/a - - insertion of date in requests and responses.						
c2:	IF A.4/26 THEN o ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).						
c3:	IF A.4/34 THEN o ELSE n/a - - the P-Access-Network-Info header extension.						
c4:	IF A.4/36 THEN o ELSE n/a - - the P-Charging-Vector header extension.						
c5:	IF A.4/36 OR A.3/4 THEN m ELSE n/a - - the P-Charging-Vector header extension (including S-CSCF as registrar).						
c6:	IF A.4/35 THEN o ELSE n/a - - the P-Charging-Function-Addresses header extension.						
c7:	IF A.4/35 OR A.3/4 THEN m ELSE n/a - - the P-Charging-Function-Addresses header extension (including S-CSCF as registrar).						
NOTE:	For a 606 (Not Acceptable Here) response, this status is RECOMMENDED rather than OPTIONAL.						

Prerequisite A.5/19 - - REGISTER response

Prerequisite: A.6/6 - - 2xx

Table A.123: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Accept	[26] 20.1	o		[26] 20.1	o	
1A	Accept-Encoding	[26] 20.2	o	o	[26] 20.2	m	m
1B	Accept-Language	[26] 20.3	o	o	[26] 20.3	m	m
2	Allow	[26] 20.5	o	o	[26] 20.5	m	m
3	Authentication-Info	[26] 20.6	c6	c6	[26] 20.6	c7	c7
5	Contact	[26] 20.10	o	o	[26] 20.10	m	m
5A	P-Associated-URI	[52] 4.1	c8	c9	[52] 4.1	c10	c11
6	Path	[35] 4	c3	c3	[35] 4	c4	c4
8	Service-Route	[38] 56	c5	c5	[38] 56	c5	c5
9	Supported	[26] 20.37	m	m	[26] 20.37	m	m
c1:	IF (A.3/4 AND A.4/2) THEN m ELSE n/a - - S-CSCF acting as registrar.						
c2:	IF A.3/4 OR A.3/1 THEN m ELSE n/a - - S-CSCF or UE.						
c3:	IF A.4/24 THEN m ELSE n/a - - session initiation protocol extension header field for registering non-adjacent contacts.						
c4:	IF A.4/24 THEN o ELSE n/a - - session initiation protocol extension header field for registering non-adjacent contacts.						
c5:	IF A.4/28 THEN m ELSE n/a - - session initiation protocol extension header field for service route discovery during registration.						
c6:	IF A.4/8 THEN o ELSE n/a - - authentication between UA and registrar.						
c7:	IF A.4/8 THEN m ELSE n/a - - authentication between UA and registrar.						
c8:	IF A.4/2 AND A.4/31 THEN m ELSE n/a - - P-Associated-URI header extension and registrar.						
c9:	IF A.3/1 AND A.4/31 THEN m ELSE n/a - - P-Associated-URI header extension and S-CSCF.						
c10:	IF A.4/31 THEN o ELSE n/a - - P-Associated-URI header extension.						
c11:	IF A.4/31 AND A.3/1 THEN m ELSE n/a - - P-Associated-URI header extension and UE.						

Prerequisite A.5/19 - - REGISTER response

Prerequisite: A.6/8 OR A.6/9 OR A.6/10 OR A.6/11 OR A.6/12 OR A.6/35 - - 3xx or 485 (Ambiguous)

Table A.124: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
3	Contact	[26] 20.10	o (note)	o	[26] 20.10	m	m
4	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
8	Supported	[26] 20.37	m	m	[26] 20.37	m	m
NOTE:	The strength of this requirement is RECOMMENDED rather than OPTIONAL.						

Prerequisite A.5/19 - - REGISTER response

Prerequisite: A.6/14 - - 401 (Unauthorized)

Table A.125: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
3	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
4	Proxy-Authenticate	[26] 20.27	c1	x	[26] 20.27	c1	x
6	Security-Server	[48] 2	x	x	[48] 2	n/a	c2
7	Supported	[26] 20.37	m	m	[26] 20.37	m	m
10	WWW-Authenticate	[26] 20.44	m	m	[26] 20.44	m	m
c1:		IF A.5/8 THEN m ELSE n/a - - support of authentication between UA and UA.					
c2:		IF A.4/37 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol.					

Prerequisite A.5/19 - - REGISTER response

Prerequisite: A.6/17 OR A.6/23 OR A.6/30 OR A.6/36 OR A.6/42 OR A.6/45 OR A.6/50 OR A.6/51 - - 404, 413, 480, 486, 500, 503, 600, 603

Table A.126: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
3	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
6	Retry-After	[26] 20.33	o	o	[26] 20.33	o	o
8	Supported	[26] 20.37	m	m	[26] 20.37	m	m

Prerequisite A.5/19 - - REGISTER response

Prerequisite: A.6/18 - - 405 (Method Not Allowed)

Table A.127: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
2	Allow	[26] 20.5	m	m	[26] 20.5	m	m
4	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
8	Supported	[26] 20.37	m	m	[26] 20.37	m	m

Prerequisite A.5/19 - - REGISTER response

Prerequisite: A.6/20 - - 407 (Proxy Authentication Required)

Table A.128: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
3	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
5	Proxy-Authenticate	[26] 20.27	c1	x	[26] 20.27	c1	x
8	Supported	[26] 20.37	m	m	[26] 20.37	m	m
9	WWW-Authenticate	[26] 20.44	o	o	[26] 20.44	o	o
c1:		IF A.5/8 THEN m ELSE n/a - - support of authentication between UA and UA.					

Prerequisite A.5/19 - - REGISTER response

Prerequisite: A.6/25 - - 415 (Unsupported Media Type)

Table A.129: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Accept	[26] 20.1	o.1	o.1	[26] 20.1	m	m
2	Accept-Encoding	[26] 20.2	o.1	o.1	[26] 20.2	m	m
3	Accept-Language	[26] 20.3	o.1	o.1	[26] 20.3	m	m
4	Allow	[26] 20.5	o	o	[26] 20.5	m	m
5	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
9	Supported	[26] 20.37	m	m	[26] 20.37	m	m
o.1		At least one of these capabilities is supported.					

Prerequisite A.5/19 - - REGISTER response

Prerequisite: A.6/27 - - 420 (Bad Extension)

Table A.130: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
3	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
7	Supported	[26] 20.37	m	m	[26] 20.37	m	m
8	Unsupported	[26] 20.40	m	m	[26] 20.40	m	m

Prerequisite A.5/19 - - REGISTER response

Prerequisite: A.6/28 OR A.6/41A - - 421 (Extension Required), 494 (Security Agreement Required)

Table A.130A: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
2	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
3	Security-Server	[48] 2	c2	c2	[48] 2	c1	c1
4	Supported	[26] 20.37	m	m	[26] 20.37	m	m
c1:		IF A.4/37 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol.					
c2:		IF A.4/37 AND A.4/2 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol and registrar.					

Prerequisite A.5/19 - - REGISTER response

Prerequisite: A.6/29 - - 423 (Interval Too Brief)

Table A.131: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
3	Error-Info	[26] 20.18	o		[26] 20.18	o	
5	Min-Expires	[26] 20.23	m	m	[26] 20.23	m	m
8	Supported	[26] 20.37	m	m	[26] 20.37	m	m

Prerequisite A.5/19 - - REGISTER response

Prerequisite: A.6/34 - - 484 (Address Incomplete)

Table A.132: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
3	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
7	Supported	[26] 20.37	m	m	[26] 20.37	m	m

Prerequisite A.5/19 - - REGISTER response

Table A.133: Supported message bodies within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1							

PROPOSED CHANGE

A.2.2.4.12 REGISTER method

Prerequisite A.163/18 - - REGISTER request

Table A.275: Supported headers within the REGISTER request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Accept	[26] 20.1	m	m	[26] 20.1	i	i
2	Accept-Encoding	[26] 20.2	m	m	[26] 20.2	i	i
3	Accept-Language	[26] 20.3	m	m	[26] 20.3	i	i
3A	Allow	[26] 20.5	m	m	[26] 20.5	i	i
4	Allow-Events	[28] 7.2.2	m	m	[28] 7.2.2	c1	c1
5	Authorization	[26] 20.7, [49]	m	m	[26] 20.7, [49]	i	i
6	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
7	Call-Info	[26] 20.9	m	m	[26] 20.9	c2	c2
8	Contact	[26] 20.10	m	m	[26] 20.10	i	i
9	Content-Disposition	[26] 20.11	m	m	[26] 20.11	i	i
10	Content-Encoding	[26] 20.12	m	m	[26] 20.12	i	i
11	Content-Language	[26] 20.13	m	m	[26] 20.13	i	i
12	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
13	Content-Type	[26] 20.15	m	m	[26] 20.15	i	i
14	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
15	Date	[26] 20.17	m	m	[26] 20.17	m	m
16	Expires	[26] 20.19	m	m	[26] 20.19	i	i
17	From	[26] 20.20	m	m	[26] 20.20	m	m
18	Max-Forwards	[26] 20.22	m	m	[26] 20.22	m	m
19	MIME-Version	[26] 20.24	m	m	[26] 20.24	i	i
20	Organization	[26] 20.25	m	m	[26] 20.25	c3	c3
20A	P-Access-Network-Info	[52] 4.4	c16	c16	[52] 4.4	c17	c17
20B	P-Charging-Function-Addresses	[52] 4.5	c14	c14	[52] 4.5	c15	c15
20C	P-Charging-Vector	[52] 4.6	c12	c12	[52] 4.6	c13	c13
20D	P-Visited-Network-ID	[52] 4.3	c10	c10	[52] 4.3	c11	c11
20E	Path	[35] 4.2	c6	c6	[35] 4.2	c6	c6
20F	Privacy	[33] 4.2	c8	c8	[33] 4.2	c9	c9
21	Proxy-Authorization	[26] 20.28	m	m	[26] 20.28	c7	c7
22	Proxy-Require	[26] 20.29	m	m	[26] 20.29	m	m
23	Require	[26] 20.32	m	m	[26] 20.32	c4	c4
24	Route	[26] 20.34	m	m	[26] 20.34	m	m
24A	Security-Client	[48] 2.3.1	x	x	[48] 2.3.1	c18	c18
24B	Security-Verify	[48] 2.3.1	x	x	[48] 2.3.1	c18	c18
25	Supported	[26] 20.37	m	m	[26] 20.37	c5	c5
26	Timestamp	[26] 20.38	m	m	[26] 20.38	i	i
27	To	[26] 20.39	m	m	[26] 20.39	m	m
28	User-Agent	[26] 20.41	m	m	[26] 20.41	i	i
29	Via	[26] 20.42	m	m	[26] 20.42	m	m

c1:	IF A.4/20 THEN m ELSE i - - SIP specific event notification extension.
c2:	IF A.162/19C OR A.162/19D THEN m ELSE i - - reading, adding or concatenating the Call-Info header.
c3:	IF A.162/19A OR A.162/19B THEN m ELSE i - - reading, adding or concatenating the Organization header.
c4:	IF A.162/11 OR A.162/12 THEN m ELSE i - - reading the contents of the Require header before proxying the request or response or adding or modifying the contents of the Require header before proxying the request or response for methods other than REGISTER.
c5:	IF A.162/16 THEN m ELSE i - - reading the contents of the Supported header before proxying the response.
c6:	IF A.162/29 THEN m ELSE n/a - - PATH header support.
c7:	IF A.162/8A THEN m ELSE i - - authentication between UA and proxy.
c8:	IF A.162/31 THEN m ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).
c9:	IF A.162/31D OR A.162/31G THEN m ELSE IF A.162/31C THEN i ELSE n/a - - application of the privacy option "header" or application of the privacy option "id" or passing on of the Privacy header transparently.
c10:	IF A.162/38 THEN m ELSE n/a - - the P-Visited-Network-ID header extension.
c11:	IF A.162/39 THEN m ELSE i - - reading, or deleting the P-Visited-Network-ID header before proxying the request or response.
c12:	IF A.162/45 THEN m ELSE n/a - - the P-Charging-Vector header extension.
c13:	IF A.162/46 THEN m ELSE IF A.162/45 THEN i ELSE n/a - - adding, deleting, reading or modifying the P-Charging-Vector header before proxying the request or response or the P-Charging-Vector header extension.
c14:	IF A.162/44 THEN m ELSE n/a - - the P-Charging-Function-Addresses header extension.
c15:	IF A.162/44A THEN m ELSE IF A.162/44 THEN i ELSE n/a - - adding, deleting or reading the P-Charging-Function-Addresses header before proxying the request or response, or the P-Charging-Function-Addresses header extension.
c16:	IF A.162/43 THEN x ELSE IF A.162/41 THEN m ELSE n/a - - act as subsequent entity within trust network for access network information that can route outside the trust network, the P-Access-Network-Info header extension.
c17:	IF A.162/43 THEN m ELSE IF A.162/41 THEN i ELSE n/a - - act as subsequent entity within trust network for access network information that can route outside the trust network, the P-Access-Network-Info header extension.
c18:	IF A.4/37 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol.
NOTE:	c1 refers to the UA role major capability as this is the case of a proxy that also acts as a UA specifically for SUBSCRIBE and NOTIFY.

Prerequisite A.163/18 - - REGISTER request

Table A.276: Supported message bodies within the REGISTER request

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1							

Prerequisite A.163/19 - - REGISTER response

Prerequisite: A.164/1 - - 100 (Trying)

Table A.277: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
2	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
3	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
4	Date	[26] 20.17	m	m	[26] 20.17	m	m
5	From	[26] 20.20	m	m	[26] 20.20	m	m
6	To	[26] 20.39	m	m	[26] 20.39	m	m
7	Via	[26] 20.42	m	m	[26] 20.42	m	m

Prerequisite A.163/19 - - REGISTER response

Table A.278: Supported headers within the REGISTER response - all remaining status-codes

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Call-ID	[26] 20.8	m	m	[26] 20.8	m	m
1A	Call-Info	[26] 20.9	m	m	[26] 20.9	c2	c2
2	Content-Disposition	[26] 20.11	m	m	[26] 20.11	i	i
3	Content-Encoding	[26] 20.12	m	m	[26] 20.12	i	i
4	Content-Language	[26] 20.13	m	m	[26] 20.13	i	i
5	Content-Length	[26] 20.14	m	m	[26] 20.14	m	m
6	Content-Type	[26] 20.15	m	m	[26] 20.15	i	i
7	Cseq	[26] 20.16	m	m	[26] 20.16	m	m
8	Date	[26] 20.17	m	m	[26] 20.17	m	m
9	From	[26] 20.20	m	m	[26] 20.20	m	m
10	MIME-Version	[26] 20.24	m	m	[26] 20.24	i	i
11	Organization	[26] 20.25	m	m	[26] 20.25	c1	c1
11A	P-Access-Network-Info	[52] 4.4	c9	c9	[52] 4.4	c10	c10
11B	P-Charging-Function-Addresses	[52] 4.5	c7	c7	[52] 4.5	c8	c8
11C	P-Charging-Vector	[52] 4.6	c5	c5	[52] 4.6	c6	c6
11D	Privacy	[33] 4.2	c3	c3	[33] 4.2	c4	c4
11E	Require	[26] 20.32	m	m	[26] 20.32	c11	c11
11F	Server	[26] 20.35	m	m	[26] 20.35	i	i
12	Timestamp	[26] 20.38	m	m	[26] 20.38	i	i
13	To	[26] 20.39	m	m	[26] 20.39	m	m
13A	User-Agent	[26] 20.41	m	m	[26] 20.41	i	i
14	Via	[26] 20.42	m	m	[26] 20.42	m	m
15	Warning	[26] 20.43	m	m	[26] 20.43	i	i
c1:	IF A.162/19A OR A.162/19B THEN m ELSE i - - reading, adding or concatenating the Organization header.						
c2:	IF A.162/19C OR A.162/19D THEN m ELSE i - - reading, adding or concatenating the Call-Info header.						
c3:	IF A.162/31 THEN m ELSE n/a - - a privacy mechanism for the Session Initiation Protocol (SIP).						
c4:	IF A.162/31D OR A.162/31G THEN m ELSE IF A.162/31C THEN i ELSE n/a - - application of the privacy option "header" or application of the privacy option "id" or passing on of the Privacy header transparently.						
c5:	IF A.162/45 THEN m ELSE n/a - - the P-Charging-Vector header extension.						
c6:	IF A.162/46 THEN m ELSE IF A.162/45 THEN i ELSE n/a - - adding, deleting, reading or modifying the P-Charging-Vector header before proxying the request or response or the P-Charging-Vector header extension.						
c7:	IF A.162/44 THEN m ELSE n/a - - the P-Charging-Function-Addresses header extension.						
c8:	IF A.162/44A THEN m ELSE IF A.162/44 THEN i ELSE n/a - - adding, deleting or reading the P-Charging-Function-Addresses header before proxying the request or response, or the P-Charging-Function-Addresses header extension.						
c9:	IF A.162/43 THEN x ELSE IF A.162/41 THEN m ELSE n/a - - act as subsequent entity within trust network for access network information that can route outside the trust network, the P-Access-Network-Info header extension.						
c10:	IF A.162/43 THEN m ELSE IF A.162/41 THEN i ELSE n/a - - act as subsequent entity within trust network for access network information that can route outside the trust network, the P-Access-Network-Info header extension.						
c11:	IF A.162/11 OR A.162/12 THEN m ELSE i - - reading the contents of the Require header before proxying the request or response or adding or modifying the contents of the Require header before proxying the request or response for methods other than REGISTER.						

Prerequisite A.163/19 - - REGISTER response

Prerequisite: A.164/6 - - 2xx

Table A.279: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Accept	[26] 20.1	m	m	[26] 20.1	i	i
1A	Accept-Encoding	[26] 20.2	m	m	[26] 20.2	i	i
1B	Accept-Language	[26] 20.3	m	m	[26] 20.3	i	i
2	Allow	[26] 20.5	m	m	[26] 20.5	i	i
3	Authentication-Info	[26] 20.6	m	m	[26] 20.6	i	i
5	Contact	[26] 20.10	m	m	[26] 20.10	i	i
5A	P-Associated-URI	[52] 4.1	c8	c8	[52] 4.1	c9	c10
6	Path	[35] 4.2	c3	c3	[35] 4.2	c4	c4
8	Service-Route	[38] 56	c5	c5	[38] 56	c6	c7
9	Supported	[26] 20.37	m	m	[26] 20.37	i	i
c2:	IF A.3/2 OR A.3/3A THEN m ELSE n/a - - P-CSCF or I-CSCF (THIG).						
c3:	IF A.162/29 THEN m ELSE n/a - - Path extension support.						
c4:	IF A.162/29 THEN i ELSE n/a - - Path extension support.						
c5:	IF A.162/32 THEN m ELSE n/a - - Service-Route extension support.						
c6:	IF A.162/32 THEN i ELSE n/a - - Service-Route extension support.						
c7:	IF A.162/32 THEN (IF A.3/2 THEN m ELSE i) ELSE n/a - - Service-Route extension and P-CSCF.						
c8:	IF A.162/36 THEN m ELSE n/a - - the P-Associated-URI extension.						
c9:	IF A.162/36 THEN i ELSE n/a - - the P-Associated-URI extension.						
c10:	IF A.162/36 AND A.3/2 THEN m ELSE IF A.162/36 AND A.3/3 THEN i ELSE n/a - - the P-Associated-URI extension and P-CSCF or I-CSCF.						

Prerequisite A.163/19 - - REGISTER response

Prerequisite: A.164/8 OR A.164/9 OR A.164/10 OR A.164/11 OR A.164/12 OR A.164/35 - - 3xx or 485 (Ambiguous)

Table A.280: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
3	Contact	[26] 20.10	m	m	[26] 20.10	c2	c2
4	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
8	Supported	[26] 20.37	m	m	[26] 20.37	i	i
c2:	IF A.162/19E THEN m ELSE i - - deleting Contact headers.						

Prerequisite A.163/19 - - REGISTER response

Prerequisite: A.164/14 - - 401 (Unauthorized)

Table A.281: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
3	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
4	Proxy-Authenticate	[26] 20.27	m	m	[26] 20.27	m	m
6	Security-Server	[48] 2	x	c1	[48] 2	n/a	n/a
7	Supported	[26] 20.37	m	m	[26] 20.37	i	i
10	WWW-Authenticate	[26] 20.44	m	m	[26] 20.44	i	i
c1:	IF A.162/47 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol.						

Prerequisite A.163/19 - - REGISTER response

Prerequisite: A.164/17 OR A.164/23 OR A.164/30 OR A.164/36 OR A.164/42 OR A.164/45 OR A.164/50 OR A.164/51 - - 404, 413, 480, 486, 500, 503, 600, 603

Table A.282: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
3	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
6	Retry-After	[26] 20.33	m	m	[26] 20.33	i	i
8	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/19 - - REGISTER response

Prerequisite: A.164/18 - - 405 (Method Not Allowed)

Table A.283: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
2	Allow	[26] 20.5	m	m	[26] 20.5	i	i
4	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
8	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/19 - - REGISTER response

Prerequisite: A.164/20 - - 407 (Proxy Authentication Required)

Table A.284: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
3	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
5	Proxy-Authenticate	[26] 20.27	m	m	[26] 20.27	m	m
8	Supported	[26] 20.37	m	m	[26] 20.37	i	i
9	WWW-Authenticate	[26] 20.44	m	m	[26] 20.44	i	i

Prerequisite A.163/19 - - REGISTER response

Prerequisite: A.164/25 - - 415 (Unsupported Media Type)

Table A.285: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Accept	[26] 20.1	m	m	[26] 20.1	i	i
2	Accept-Encoding	[26] 20.2	m	m	[26] 20.2	i	i
3	Accept-Language	[26] 20.3	m	m	[26] 20.3	i	i
4	Allow	[26] 20.5	m	m	[26] 20.5	i	i
5	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
9	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/19 - - REGISTER response

Prerequisite: A.164/27 - - 420 (Bad Extension)

Table A.286: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
3	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
7	Supported	[26] 20.37	m	m	[26] 20.37	i	i
8	Unsupported	[26] 20.40	m	m	[26] 20.40	c3	c3
c3: IF A.162/17 THEN m ELSE i							

Prerequisite A.163/19 - - REGISTER response

Prerequisite: A.164/28 OR A.164/41A - - 421 (Extension Required), 494 (Security Agreement Required)

Table A.286A: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	o	o	[26] 20.5	m	m
2	Error-Info	[26] 20.18	o	o	[26] 20.18	o	o
3	Security-Server	[48] 2	c1	c1	[48] 2	n/a	n/a
4	Supported	[26] 20.37	m	m	[26] 20.37	m	m
c1: IF A.162/47 THEN m ELSE n/a - - security mechanism agreement for the session initiation protocol.							

Prerequisite A.163/19 - - REGISTER response

Prerequisite: A.164/29 - - 423 (Interval Too Brief)

Table A.287: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
3	Error-Info	[26] 20.18	o		[26] 20.18	o	
5	Min-Expires	[26] 20.23	m	m	[26] 20.23	i	i
8	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/19 - - REGISTER response

Prerequisite: A.164/34 - - 484 (Address Incomplete)

Table A.288: Supported headers within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1	Allow	[26] 20.5	m	m	[26] 20.5	i	i
3	Error-Info	[26] 20.18	m	m	[26] 20.18	i	i
7	Supported	[26] 20.37	m	m	[26] 20.37	i	i

Prerequisite A.163/19 - - REGISTER response

Table A.289: Supported message bodies within the REGISTER response

Item	Header	Sending			Receiving		
		Ref.	RFC status	Profile status	Ref.	RFC status	Profile status
1							