

Technical Specification Group, Radio Access Network
Meeting #2, Fort Lauderdale, 2-4 March 1999

TSGR#2(99)073

Source: Editor
Title: S3.24: Iur Interface Data Transport and Transport Signalling for CCH data streams
Document for: Decision
Agenda Item: 7

TSG-RAN Working Group 3 meeting #2 **TSGW3#2(99)**

Nynäshamn, Sweden, 15th - 19th March 1999

Agenda Item: 14.6

Source: Editor

Title: S3.24: Iur Interface Data Transport and Transport Signalling for CCH data streams

Document for:

3GPP

**3rd Generation Partnership Project (3GPP);
Technical Specification Group (TSG) RAN;
I_{ur} Interface Data Transport & Transport
Signalling for CCH Data Streams**

[UMTS <spec>]

3GPP

Reference

<Workitem> (<Shortfilename>.PDF)

Keywords

<keyword[, keyword]>

3GPP

Postal address

Office address

Internet

secretariat@3gpp.org
Individual copies of this deliverable
can be downloaded from
<http://www.3gpp.org>

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

©
All rights reserved.

Contents

1	Scope.....	6
2	References	6
3	Definitions, symbols and abbreviations.....	6
3.1	Definitions	6
3.2	Symbols	7
3.3	Abbreviations.....	7
3.4	Notation	7
4	I_{ur} Data Transport for CCH Data Streams	7
4.1	Introduction	7
4.2	Transport Layer	7
5	I_{ur} Transport Signalling for CCH Data Streams	7
5.1	Introduction	7
5.2	Transport Signalling	7
6	Signalling Bearer for Transport Signalling on I_{ur} Interface	7
6.1	Introduction	7
6.2	Signalling Bearer	7
7	Bibliography	8
8	History	8

Intellectual Property Rights

[IPRs essential or potentially essential to the present deliverable may have been declared to ETSI/3GPP. The information pertaining to these essential IPRs, if any, is publicly available for ETSI members and non-members, free of charge. This can be found in the latest version of the ETSI Technical Report: ETR 314: "Intellectual Property Rights (IPRs); Essential or potentially Essential, IPRs notified to ETSI in respect of ETSI standards". The most recent update of ETR 314, is available on the ETSI web server or on request from the Secretariat.

Pursuant to the ETSI Interim IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in the ETR 314, which are, or may be, or may become, essential to the present document.]

Note: The content has to be reviewed according to the 3GPP IPR rules

Foreword

This Technical Specification (TS) has been produced by the 3rd Generation Partnership Project (3GPP). The contents of this TS are subject to continuing work within 3GPP TSG RAN and may change following formal TSG RAN approval. Should the TSG modify the contents of this TS, it will be re-released with an identifying change of release date and an increase in version number as follows:

Version m.t.e

where:

- m indicates [major version number]
 - x the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
 - y the third digit is incremented when editorial only changes have been incorporated into the specification.
-

Introduction

This clause is optional. If it exists, it is always the third unnumbered clause.

No text block identified.

1 Scope

This document shall provide a description of the UTRAN RNS-RNS (Iur) interface Data Transport and Transport Signalling for CCH data streams as agreed within the TSG-RAN working group 3.

2 References

References may be made to:

- a) specific versions of publications (identified by date of publication, edition number, version number, etc.), in which case, subsequent revisions to the referenced document do not apply;
- b) all versions up to and including the identified version (identified by "up to and including" before the version identity);
- c) all versions subsequent to and including the identified version (identified by "onwards" following the version identity); or
- d) publications without mention of a specific version, in which case the latest version applies.

A non-specific reference to an ETS shall also be taken to refer to later versions published as an EN with the same number.

[1] Merged ~~description~~version of Iur interface Description, V0.0.2

Editor's Note : [1] is a temporary reference only to ease the definition of what should be in the different sections of this document.

3 Definitions, symbols and abbreviations

3.1 Definitions

. [Editor's note: For list of definitions, see [1]. Only definitions specific to this document are listed below, in order to avoid inconsistency between documents. When list is stable, definitions relevant for this document should be extracted.]

3.2 Symbols

3.3 Abbreviations

[Editor's note: For list of abbreviations, see [1]. Only abbreviations specific to this document are listed below, in order to avoid inconsistency between documents. When list is stable, abbreviations relevant for this document should be extracted.]

CCH Common Channels (FACH, RACH, DSCH)

3.4 Notation

[Editor's note: This text has been copied from [1].]

Parts of the document apply only to one mode, FDD or TDD. Any such area will be tagged by [FDD — xxxxxxxx], or [TDD — yyyyyyyyyy], respectively. The tag applies to the text until the closing bracket.

4 I_{ur} Data Transport for CCH Data Streams

[Editor's Note: This chapter specifies the transport layers that support Common Channels (FACH, RACH, DSCH) data streams. Limitations in usage of options of the protocol should be described. Requirements should be given in the S3.25.]

4.1 Introduction

4.2 Transport Layer

The transport bearer for Iur RACH/FACH/DSCH data streams is FFS.

5 I_{ur} Transport Signalling for CCH Data Streams

[Editor's Note: This chapter specifies the transport signalling protocol(s) used to establish the user plane transport bearers. Limitations in usage of options of the protocol should be described]

5.1 Introduction

5.2 Transport Signalling

The AAL Type 2 Signalling Protocol (Q.aal2) developed by ITU SG11 [8] and [9] will be used for establishment of AAL2-connections over the Iur interface.

6 Signalling Bearer for Transport Signalling on I_{ur} Interface

[Editor's Note: This chapter specifies the signalling bearer protocol stack that supports the transport signalling protocol(s). Limitations in usage of options of the protocol should be described]

6.1 Introduction

6.2 Signalling Bearer

MTP3/SAAL-NNI is used as Signalling Bearer for Q.aal2 as shown in the figure below:

Transport Network Control plane




Figure 6-1: Signalling bearer for Q.aa2 on Iur.

7 Bibliography

8 History

Document history		
<u>0.0.1</u> Edition *	February 1999 <MMMM yyyy>	Document structure proposal Publication as <old doctype> <old doenumbe>
<u>0.0.2</u>	February 1999	Introduction of the related content of Merged description of Iur interface.
Editor for 3GPP RAN S3.24 is:		
Nicolas Drevon Alcatel Tel.: +33 1 3077 0916 Fax : +33 1 3077 9430 Email : nicolas.drevon@alcatel.fr		
This document is written in Microsoft Word version 7/97.		