

TSG RAN Meeting #19
Birmingham, United Kingdom, 11 - 14 March, 2003

RP-030039

Title CR (Rel-5) to TS 25.113
Source TSG RAN WG4
Agenda Item 8.4.5

RAN4 Tdoc	Spec	CR	R	Cat	Rel	Curr Ver	Title	Work Item
R4-020086	25.113	020		F	Rel-5	5.3.0	Assessment of BLER in Uplink for Immunity Test	TEI5

Madrid, Spain 17 - 22 February, 2003

CR-Form-v7

CHANGE REQUEST

⌘ **25.113 CR 020** ⌘ rev ⌘ Current version: **5.3.0** ⌘

For **HELP** on using this form, see bottom of this page or look at the pop-up text over the ⌘ symbols.

Proposed change affects: UICC apps ME Radio Access Network Core Network

Title:	⌘ Assessment of BLER in Uplink for Immunity Tests		
Source:	⌘ RAN WG4		
Work item code:	⌘ TEI5	Date:	⌘ 05/03/2003
Category:	⌘ F	Release:	⌘ Rel-5
	Use <u>one</u> of the following categories:		Use <u>one</u> of the following releases:
	F (correction)		2 (GSM Phase 2)
	A (corresponds to a correction in an earlier release)		R96 (Release 1996)
	B (addition of feature),		R97 (Release 1997)
	C (functional modification of feature)		R98 (Release 1998)
	D (editorial modification)		R99 (Release 1999)
	Detailed explanations of the above categories can be found in 3GPP TR 21.900 .		Rel-4 (Release 4)
			Rel-5 (Release 5)
			Rel-6 (Release 6)

Reason for change:	⌘ The present text is ambiguous, since there is no BLER value being "reported" over the lub interface.
Summary of change:	⌘ The text "reported by the BS" is removed from the description of how to assess BLER in the uplink.
Consequences if not approved:	⌘ The way to asses BLER in the uplink would be ambiguos and could not be done as stated in the spec.

Clauses affected:	⌘ 5.3						
Other specs affected:	<table border="1" style="display: inline-table; border-collapse: collapse;"> <tr> <td style="padding: 2px;">Y</td> <td style="padding: 2px;">N</td> </tr> <tr> <td style="text-align: center; width: 20px;">⌘</td> <td style="text-align: center; width: 20px;">X</td> </tr> </table>	Y	N	⌘	X	Other core specifications	⌘
	Y	N					
	⌘	X					
⌘	Test specifications						
⌘	O&M Specifications						
Other comments:	⌘						

5.3 Assessment of BLER in Uplink

The value of the BLER at the output of the receiver ~~reported by the BS~~ shall be monitored at Iub-interface by using a suitable test equipment.