

TSG-RAN Meeting #22
Maui, Hawaii, USA, 9 - 12 December 2003

RP-030716

TSG-RAN Working Group 4 (Radio) meeting #29
San Diego, CA, USA 17 – 21 November, 2003

R4-031143

Title: Liaison Statement on open essential parameters regarding Repeaters

Response to: TFES-03-048 (R4-030656) from ETSI TFES

Source: 3GPP TSG RAN WG4

To: ETSI TFES

Cc: ETSI TC MSG, ETSI TC ERM

Contact Person:

Name: Nadege Noisette, Orange

E-mail Address: nadege.noisette@francetelecom.com

Attachments: R4-031097

1. Overall Description:

ETSI MSG TFES has asked 3GPP RAN WG4 in a Liaison Statement to work on the two open issues of the Repeater part in the Harmonised Standard to facilitate a successful inclusion of the Repeater part in the Harmonised Standard.

These parameters are the out of band gain and the up-link spurious emission for co-existence with UTRA FDD.

To specify the out of band gain parameter it was agreed to do simulations. The work on this has been started but is not yet finalised. The schedule is to finalise the work on it at the meeting RAN WG4#30 subject to simulation outcome.

The up-link spurious emission for co-existence with UTRA FDD has been finalised at the meeting RAN WG4#29. The corresponding requirement can be found in the attached document R4-031097.

2. Date of Next Meetings:

Meeting #	Date	Host	Location
30	9 - 13 February 2004	Rohde & Schwarz	Munich, Germany
31	10 - 14 May 2004		

CHANGE REQUEST

25.106 CR 28 # rev **1** # Current version: **4.6.0**

For **HELP** on using this form, see bottom of this page or look at the pop-up text over the # symbols.

Proposed change affects: UICC apps# ME Radio Access Network Core Network

Title:	# Spurious emissions: Co-existence with UTRA-FDD BS new UL requirement		
Source:	# Mikom an Andrew Company, LGP Allgon		
Work item code:	# RInImp-REP	Date:	# 19/11/2003
Category:	# F	Release:	# R4
	Use <u>one</u> of the following categories:		Use <u>one</u> of the following releases:
	F (correction)	2	(GSM Phase 2)
	A (corresponds to a correction in an earlier release)	R96	(Release 1996)
	B (addition of feature),	R97	(Release 1997)
	C (functional modification of feature)	R98	(Release 1998)
	D (editorial modification)	R99	(Release 1999)
	Detailed explanations of the above categories can be found in 3GPP TR 21.900.		Rel-4 (Release 4)
			Rel-5 (Release 5)
			Rel-6 (Release 6)

Reason for change:	# A spurious emission requirement was missing for the UL band in the case of co-existence of a repeater with a UTRA-FDD BS.
Summary of change:	# A spurious emission requirement was added for the UL band in the case of co-existence of a repeater with a UTRA-FDD BS.
Consequences if not approved:	# Requirements for the UL band in the case of co-existence of a repeater with a UTRA-FDD BS is missing. Isolated Impact Analysis: UTRA FDD network performance could be affected by to high FDD Spurious Emission, if this CR is not approved. Approval of this CR would not affect FDD implementation behaving like indicated in the CR.

Clauses affected:	# 9.2.2.1								
Other specs affected:	#								
	<table border="1" style="display: inline-table; border-collapse: collapse;"> <tr> <td style="width: 20px; text-align: center;">Y</td> <td style="width: 20px; text-align: center;">N</td> </tr> <tr> <td style="text-align: center;">#</td> <td style="text-align: center;">X</td> </tr> <tr> <td style="text-align: center;">X</td> <td style="text-align: center;">#</td> </tr> <tr> <td style="text-align: center;">#</td> <td style="text-align: center;">X</td> </tr> </table> Other core specifications # Test specifications # O&M Specifications #	Y	N	#	X	X	#	#	X
Y	N								
#	X								
X	#								
#	X								
	TS25.143								
Other comments:	#								

How to create CRs using this form:

Comprehensive information and tips about how to create CRs can be found at <http://www.3gpp.org/specs/CR.htm>. Below is a brief summary:

- 1) Fill out the above form. The symbols above marked ¶ contain pop-up help information about the field that they are closest to.
- 2) Obtain the latest version for the release of the specification to which the change is proposed. Use the MS Word "revision marks" feature (also known as "track changes") when making the changes. All 3GPP specifications can be downloaded from the 3GPP server under <ftp://ftp.3gpp.org/specs/> For the latest version, look for the directory name with the latest date e.g. 2001-03 contains the specifications resulting from the March 2001 TSG meetings.
- 3) With "track changes" disabled, paste the entire CR form (use CTRL-A to select it) into the specification just in front of the clause containing the first piece of changed text. Delete those parts of the specification which are not relevant to the change request.

9.2.2 Co-existence with UTRA-FDD BS

9.2.2.1 Operation in the same geographic area

This requirement shall be applied for the protection of UTRA-FDD BS receivers in geographic areas in which UTRA FDD Repeater and UTRA FDD BS are deployed. ~~The requirement applies only to the down link direction of the Repeater.~~

9.2.2.1.1 Minimum Requirement

~~In the down link direction of the Repeater the power of any spurious emission shall not exceed:~~

Table 9.7A: UTRA Repeater Spurious emissions limits in geographic coverage area of UTRA FDD BS receiver for the down link direction of the Repeater

Band	Maximum Level	Measurement Bandwidth	Note
1920 - 1980MHz For operation in Frequency Bands defined in sub-clause 5.1(a)	-96 dBm	100 kHz	
1850 - 1910 MHz For operation in Frequency Bands defined in sub-clause 5.1 (b)	-96 dBm	100_kHz	

~~In the up link direction of the Repeater the power of any spurious emission shall not exceed:~~

Table 9.7B: UTRA Repeater Spurious emissions limits in geographic coverage area of UTRA FDD BS receiver for the up link direction of the Repeater

Band	Maximum Level	Measurement Bandwidth	Note
1920 - 1980MHz For operation in Frequency Bands defined in sub-clause 5.1(a)	<u>-53 dBm</u>	<u>100 kHz</u>	
1850 - 1910 MHz For operation in Frequency Bands defined in sub-clause 5.1 (b)	<u>-53 dBm</u>	<u>100 kHz</u>	

NOTE 1: These requirements in Table 9.7B for the up link direction of the Repeater reflect what can be achieved with present state of the art technology and are based on a coupling loss of 73 dB between a Repeater and a UTRA FDD BS receiver.

NOTE 2: The requirements shall be reconsidered when the state of the art technology progresses.