

<h2 style="margin: 0;">CHANGE REQUEST</h2>		Please see embedded help file at the bottom of this page for instructions on how to fill in this form correctly.	
25.224 CR 005r1		Current Version: V3.0.0	
GSM (AA.BB) or 3G (AA.BBB) specification number ↑		↑ CR number as allocated by MCC support team	
For submission to: RAN #6	for approval <input checked="" type="checkbox"/>	Strategic <input type="checkbox"/>	(for SMG use only)
list expected approval meeting # here ↑	for information <input type="checkbox"/>	non-strategic <input type="checkbox"/>	

Form: CR cover sheet, version 2 for 3GPP and SMG The latest version of this form is available from: ftp://ftp.3gpp.org/Information/CR-Form-v2.doc

Proposed change affects: (U)SIM ME UTRAN / Radio Core Network
 (at least one should be marked with an X)

Source: Siemens AG **Date:** 01 Dec 1999

Subject: Alignment of Terminology Regarding Spreading for TDD Mode

Work item: Change Request on the corrections/clarifications to the WG1 specifications

Category:	F Correction <input type="checkbox"/> A Corresponds to a correction in an earlier release <input type="checkbox"/> B Addition of feature <input type="checkbox"/> C Functional modification of feature <input type="checkbox"/> D Editorial modification <input checked="" type="checkbox"/>	Release:	Phase 2 <input type="checkbox"/> Release 96 <input type="checkbox"/> Release 97 <input type="checkbox"/> Release 98 <input type="checkbox"/> Release 99 <input checked="" type="checkbox"/> Release 00 <input type="checkbox"/>
------------------	--	-----------------	--

(only one category shall be marked with an X)

Reason for change: Alignment of the terms 'Spreading', 'Channelisation' and 'Scrambling' according to usage in FDD mode.

Clauses affected: 4.4.1

Other specs affected:	Other 3G core specifications <input checked="" type="checkbox"/> Other GSM core specifications <input type="checkbox"/> MS test specifications <input type="checkbox"/> BSS test specifications <input type="checkbox"/> O&M specifications <input type="checkbox"/>	→ List of CRs: 25.221-CR007r1, 25.223-CR003r1 → List of CRs: → List of CRs: → List of CRs: → List of CRs:
------------------------------	--	---

Other comments:



<----- double-click here for help and instructions on how to create a CR.

4.4 Synchronisation and Cell Search Procedures

4.4.1 Cell Search

During the initial cell search, the UE searches for a cell. It then determines the midamble, the downlink scrambling code and frame synchronisation of that cell. The initial cell search uses the Physical Synchronisation Channel (PSCH) described in [8]. The generation of synchronisation codes is described in [10].

This initial cell search is carried out in three steps:

Step 1: Slot synchronisation

During the first step of the initial cell search procedure the UE uses the primary synchronisation code c_p to acquire slot synchronisation to the strongest cell. Furthermore, frame synchronisation with the uncertainty of 1 out of 2 is obtained in this step. A single matched filter (or any similar device) is used for this purpose, that is matched to the primary synchronisation code which is common to all cells.

Step 2: Frame synchronisation and code-group identification

The Step 2 is described for the case where PSCH and PCCPCH are in timeslot k and $k+8$ with $k=0\dots6$.

During the second step of the initial cell search procedure, the UE uses the modulated Secondary Synchronisation Codes to find frame synchronisation and identify one out of 32 code groups. Each code group is linked to a specific t_{Offset} , thus to a specific frame timing, and is containing 4 specific scrambling codes. Each scrambling code is associated with a specific short and long basic midamble code.

In Cases 2 and 3 it is required to detect the position of the next synchronization slots. To detect the position of the next synchronization slots, the primary synchronization code is correlated with the received signal at offsets of 7 and 8 time slots from the position of the primary code that was detected in Step 1.

Then, the received signal at the positions of the synchronization codes is correlated with the primary synchronization Code C_p and the secondary synchronization codes $\{C_0, \dots, C_{15}\}$. Note that the correlations can be performed coherently over M time slots, where at each slot a phase correction is provided by the correlation with the primary code. The minimal number of time slots is $M=1$, and the performance improves with increasing M .

Step 3: Scrambling code identification

During the third and last step of the initial cell-search procedure, the UE determines the exact basic midamble code and the accompanying scrambling code used by the found cell. They are identified through correlation over the PCCPCH with all four midambles of the code group identified in the second step. Thus the third step is a one out of four decision. This step is taking into account that the PCCPCH containing the BCH is transmitted using the first spreading channelisation code ($a_{Q=16}^{(h=1)}$ in [10]) and using the first midamble $\mathbf{m}^{(1)}$ (derived from basic midamble code \mathbf{m}_p in [8]). Thus PCCPCH code and midamble can be immediately derived when knowing scrambling code and basic midamble code.

4.5 ODMA Relay Probing

This section describes the probe-response procedure used by ODMA nodes to detect neighbours which may be used as relays during a call.

4.5.1 Initial Mode Probing

The initial mode probing procedure is activated by a UE when it is switched on and has no information about its surroundings. In this case the UE will synchronise with the ODMA Random Access Channel (ORACH) which is used by all UEs to receive and broadcast system routing control information and data. The UE begins a probing session by