TSGS#18(02)0744

Source:	**SA5 (Telecom Management)**	
Title:	**2 Rel-4/5 CR 32.612 (Bulk CM IRP Information service) : Incomplete getSessionStatus**	
Document for:	**Approval**	
Agenda Item:	**7.5.3**	

Doc-1st-	Spec	CR	R	Phase	Subject	Cat	Version	Doc-2nd-	Workitem
SP-020744	32.612	005	-	Rel-4	Incomplete getSessionStatus	F	4.3.0	S5-026954	OAM-CM
SP-020744	32.612	006	-	Rel-5	Incomplete getSessionStatus	A	5.0.0	S5-026955	OAM-NIM

CR-Form-v7

CHANGE REQUEST

| ⌘ | **32.612** CR **005** | ⌘ **rev** | **-** | ⌘ | Current version: | **4.3.0** | ⌘ |

*For **HELP** on using this form, see bottom of this page or look at the pop-up text over the ⌘ symbols.*

Proposed change affects: UICC apps⌘ ☐   ME ☐ Radio Access Network **X** Core Network ☐

Title:	⌘	Incomplete getSessionStatus

Source:	⌘	SA5

Work item code:⌘	OAM-CM	**Date:** ⌘	22/11/2002

Category:	⌘	**F**		**Release:** ⌘	Rel-4

Use <u>one</u> of the following categories:
F (correction)
A (corresponds to a correction in an earlier release)
B (addition of feature),
C (functional modification of feature)
D (editorial modification)
Detailed explanations of the above categories can
be found in 3GPP TR 21.900.

Use <u>one</u> of the following releases:
2   (GSM Phase 2)
R96   (Release 1996)
R97   (Release 1997)
R98   (Release 1998)
R99   (Release 1999)
Rel-4 (Release 4)
Rel-5 (Release 5)
Rel-6 (Release 6)

Reason for change:	⌘	The action in the IRPAgent is not specified for getSessionStatus in state Idle.

Summary of change:⌘	Idle is made to be a valid value to return for getSessionStatus to the IRPManager.

Consequences if not approved:	⌘	The behaviour in the IRPAgent is not defined for getSessionStatus in state Idle.

Clauses affected:	⌘	6.2.2.9

		Y	**N**		
Other specs affected:	⌘		**X**	Other core specifications	⌘	
			X	Test specifications	
		X		O&M Specifications	Rel-5 32612

Other comments:	⌘	Rel-5 Mirror in 32612CR006.

6.2.2.9 getSessionStatus (M)

The IRPManager invokes this operation to request the IRPAgent to send the current state of the bulk data configuration file operation. The IRPAgent returns the current state. See clause 7.

This operation can be invoked in any session state within a session and does not change the session state.

Table 9: getSessionStatus parameters

Name	Qualifier	Description
sessionId	Input, M	Identifies this specific session and process associated with an earlier bulk data operation e.g. upload or download for which the current status is required.
sessionState	Output, M	Indicates current state of the configuration file operation. See clause 7, i.e. will be one of: Idle, Upload In Progress, Upload Failed, Upload Completed, Down Load In Progress, Download Failed, Download Completed, Activation In Progress, Activation Failed, Activation Partly Realised, Activation Completed, Fallback In Progress, Fallback Failed, Fallback Partly Realised, Fallback Completed,
status	Output, M	Indicates (a) start of operation is successful and (b) operation failed because of specified or unspecified reasons

---

<div align="right">CR-Form-v7</div>

CHANGE REQUEST

| ⌘ | **32.612** CR **006** | ⌘**rev** | **-** | ⌘ | Current version: | **5.0.0** | ⌘ |

*For **HELP** on using this form, see bottom of this page or look at the pop-up text over the ⌘ symbols.*

Proposed change affects: UICC apps⌘ [ ]   ME [ ]   Radio Access Network **X**   Core Network **X**

Title: ⌘	Incomplete getSessionStatus	
Source: ⌘	SA5	
Work item code: ⌘	OAM-NIM	***Date:*** ⌘ 22/11/2002
Category: ⌘ **A**		***Release:*** ⌘ Rel-5

Use <u>one</u> of the following categories:
F (correction)
A (corresponds to a correction in an earlier release)
B (addition of feature),
C (functional modification of feature)
D (editorial modification)
Detailed explanations of the above categories can
be found in 3GPP TR 21.900.

Use <u>one</u> of the following releases:
2   (GSM Phase 2)
R96   (Release 1996)
R97   (Release 1997)
R98   (Release 1998)
R99   (Release 1999)
Rel-4   (Release 4)
Rel-5   (Release 5)
Rel-6   (Release 6)

Reason for change: ⌘	The action in the IRPAgent is not specified for getSessionStatus in state Idle.
Summary of change: ⌘	Idle is made to be a valid value to return for getSessionStatus to the IRPManager.
Consequences if not approved: ⌘	The behaviour in the IRPAgent is not defined for getSessionStatus in state Idle.

Clauses affected: ⌘	7.3.5.3

	Y	N		
Other specs affected: ⌘		X	Other core specifications	⌘
		X	Test specifications	
		X	O&M Specifications	

Other comments: ⌘	Rel-5 Mirror of 32612CR005.

7.3.5.3 Output parameters

Parameter Name	Qualifier	Matching Information	Comment
sessionState	M	List of ENUM(Idle, Upload In Progress, Upload Failed, Upload Completed, Down Load In Progress, Download Failed, Download Completed, Validation In Progress, Validation Failed, Validation Completed, Preactivation In Progress, Preactivation Failed, Preactivation Partly Realised, Preactivation Completed, Activation In Progress, Activation Failed, Activation Partly Realised, Activation Completed, Fallback In Progress, Fallback Failed, Fallback Partly Realised, Fallback Completed)	Indicates current state of the configuration data file operation. See clause 9, i.e. will be one of: Idle, Upload In Progress, Upload Failed, Upload Completed, Down Load In Progress, Download Failed, Download Completed, Validation In Progress, Validation Failed, Validation Completed, Preactivation In Progress, Preactivation Failed, Preactivation Partly Realised, Preactivation Completed, Activation In Progress, Activation Failed, Activation Partly Realised, Activation Completed, Fallback In Progress, Fallback Failed, Fallback Partly Realised, Fallback Completed.
status	M		Indicates (a) start of operation is successful or (b) operation failed because of specified or unspecified reasons