

## PSEUDO-CHANGE REQUEST

33.978 CR CRNum rev - Current version: 1.0.0

For **HELP** on using this form, see bottom of this page or look at the pop-up text over the symbols.

Proposed change affects:  UICC apps  ME  Radio Access Network  Core Network

<b>Title:</b>	Correction of P-Asserted-Identity usage		
<b>Source:</b>	Ericsson		
<b>Work item code:</b>	Early IMS	<b>Date:</b>	14/02/2005
<b>Category:</b>		<b>Release:</b>	Release-6
	<i>Use one of the following categories:</i> <b>F</b> (correction) <b>A</b> (corresponds to a correction in an earlier release) <b>B</b> (addition of feature), <b>C</b> (functional modification of feature) <b>D</b> (editorial modification) Detailed explanations of the above categories can be found in 3GPP <a href="#">TR 21.900</a> .		<i>Use one of the following releases:</i> <b>Ph2</b> (GSM Phase 2) <b>R96</b> (Release 1996) <b>R97</b> (Release 1997) <b>R98</b> (Release 1998) <b>R99</b> (Release 1999) <b>Rel-4</b> (Release 4) <b>Rel-5</b> (Release 5) <b>Rel-6</b> (Release 6) <b>Rel-7</b> (Release 7)

<b>Reason for change:</b>	Section 6.2.3.1 has a small bug claiming that the UE would use P-Asserted-Identity header with registration. According to TS 24.229, P-Asserted-Identity (or P-Preferred-Identity) header is not handled by the UE during registration.
<b>Summary of change:</b>	Reference to P-Asserted-Identity header is removed.
<b>Consequences if not approved:</b>	Conflict with TS 24.229.

<b>Clauses affected:</b>									
<b>Other specs affected:</b>	<table border="1" style="display: inline-table; border-collapse: collapse;"> <tr> <td style="width: 20px; text-align: center;">Y</td> <td style="width: 20px; text-align: center;">N</td> </tr> <tr> <td style="width: 20px; text-align: center;"> </td> <td style="width: 20px; text-align: center;"> </td> </tr> <tr> <td style="width: 20px; text-align: center;"> </td> <td style="width: 20px; text-align: center;"> </td> </tr> <tr> <td style="width: 20px; text-align: center;"> </td> <td style="width: 20px; text-align: center;"> </td> </tr> </table> Other core specifications Test specifications O&M Specifications	Y	N						
Y	N								
<b>Other comments:</b>									

\*\*\*\*\* Begin of Change \*\*\*\*\*

### 6.2.3.1 Procedures at the UE

On sending a REGISTER request in order to indicate support for early IMS security procedures, the UE shall not include an Authorization header field and not include a Security-Client header field. The From header, To header, Contact header, Expires header, Request URI, [and](#) Supported header ~~and a P-Asserted-Id header~~ shall be set according clause 5.1.1.2 of TS 24.229 [7].

On receiving the 200 (OK) response to the REGISTER request, the UE shall handle the expiration time, the P-Associated-URI header field, and the Service-Route header field according clause 5.1.1.2 of TS 24.229 [7].

NOTE 1: Early IMS security does not allow SIP requests to be protected using an IPsec security association because it does not perform a key agreement procedure.

NOTE 2: The UE shall not use the temporary public user identity used for registration in any subsequent SIP requests.

\*\*\*\*\* End of Change \*\*\*\*\*