3GPP TSG-T (Terminals) Meeting #24 ***TP-040102***
Seoul, Korea
2 - 4 June, 2004

Agenda Item: 5.3.3
Source: T3
Title: CRs to TS 31.103
Document for: approval

This document contains the following change request that was approved by 3GPP TSG T3 and is forwarded to 3GPP TSG T#24 for approval:

Doc-2nd-Level	Spec	CR	rev	Phase	Subject	Cat	Version-Current	Version-New	WI
T3-040281	31.103	015		Rel-6	Clarification that the P-CSCF address shall not be used by a 3GPP terminal accessing a Interworking WLAN	F	6.3.0	6.4.0	TEI

3GPP TSG T WG3 Meeting #31
Berlin, Germany, 27th – 30th April 2004

T3-040281

CR-Form-v7

CHANGE REQUEST

⌘ **31.103** **CR** **015** ⌘ **rev** **-** ⌘ Current version: **6.3.0** ⌘

*For **HELP** on using this form, see bottom of this page or look at the pop-up text over the ⌘ symbols.*

Proposed change affects: UICC apps⌘ [X] ME [X] Radio Access Network [ ] Core Network [ ]

Title:	⌘	CR 31.103 Rel-6: Clarification that the P-CSCF address shall not be used by a 3GPP terminal accessing a Interworking WLAN
Source:	⌘	T3
Work item code:	⌘	TEI
Date:	⌘	30/04/2004
Category:	⌘	**F**
Release:	⌘	Rel-6

Use one of the following categories:
F *(correction)*
A *(corresponds to a correction in an earlier release)*
B *(addition of feature),*
C *(functional modification of feature)*
D *(editorial modification)*
Detailed explanations of the above categories can be found in 3GPP TR 21.900.

Use one of the following releases:
2 (GSM Phase 2)
R96 (Release 1996)
R97 (Release 1997)
R98 (Release 1998)
R99 (Release 1999)
Rel-4 (Release 4)
Rel-5 (Release 5)
Rel-6 (Release 6)

Reason for change:	⌘	A 3GPP interworking WLAN terminal shall not use the P-CSCF address to get service as other procedures are defined
Summary of change:	⌘	Added a statement that a 3GPP Interworking WLAN terminal shall not use the P-CSCF to get service
Consequences if not approved:	⌘	Risk of incorrect implementation leading to denial of Interworking WLAN service

Clauses affected:	⌘	4.2.8

	Y	N		
Other specs Affected: ⌘		X	Other core specifications	⌘
		X	Test specifications	
		X	O&M Specifications	

Other comments: ⌘

How to create CRs using this form:
Comprehensive information and tips about how to create CRs can be found at http://www.3gpp.org/specs/CR.htm.
Below is a brief summary:

1) Fill out the above form. The symbols above marked ⌘ contain pop-up help information about the field that they are closest to.

2) Obtain the latest version for the release of the specification to which the change is proposed. Use the MS Word "revision marks" feature (also known as "track changes") when making the changes. All 3GPP specifications can be downloaded from the 3GPP server under ftp://ftp.3gpp.org/specs/ For the latest version, look for the directory name with the latest date e.g. 2001-03 contains the specifications resulting from the March 2001 TSG meetings.

3) With "track changes" disabled, paste the entire CR form (use CTRL-A to select it) into the specification just in front of the clause containing the first piece of changed text. Delete those parts of the specification which are not relevant to the change request.

4.2.8 $EF_{P\text{-}CSCF}$ (P-CSCF Address)

This EF does not apply for 3GPP and shall not be used by a terminal using a 3GPP access network or a 3GPP Interworking WLAN.

NOTE: The current 3GPP procedures for P-CSCF discovery provide a flexible way for the UE to discover the P-CSCF address(es). Procedures include both GPRS PDP context based solution and a generic DHCP based approach that can be used for other access technologies.

This EF contains one or more Proxy Call Session Control Function addresses. The first record in the EF shall be considered to be of the highest priority. The last record in the EF shall be considered to be the lowest priority.

Identifier: '6F09'	Structure: linear fixed	Optional
Record length: X bytes	Update activity: low	

Access Conditions:

READ	PIN
UPDATE	ADM
DEACTIVATE	ADM
ACTIVATE	ADM

Bytes	Description	M/O	Length
1 to X	P-CSCF Address TLV data object	M	X bytes