

CR-Form-v7

Pseudo-CHANGE REQUEST

33.234 CR CRNum # rev - # Current version: **0.8.0**

For **HELP** on using this form, see bottom of this page or look at the pop-up text over the # symbols.

Proposed change affects: UICC apps ME Radio Access Network Core Network

Title:	# Profiling of IKEv2 and IPsec		
Source:	# Ericsson		
Work item code:	# WLAN	Date:	# 12/01/2004
Category:	# F	Release:	# Rel-6
	Use <u>one</u> of the following categories:		Use <u>one</u> of the following releases:
	F (correction)		2 (GSM Phase 2)
	A (corresponds to a correction in an earlier release)		R96 (Release 1996)
	B (addition of feature),		R97 (Release 1997)
	C (functional modification of feature)		R98 (Release 1998)
	D (editorial modification)		R99 (Release 1999)
	Detailed explanations of the above categories can be found in 3GPP TR 21.900 .		Rel-4 (Release 4)
			Rel-5 (Release 5)
			Rel-6 (Release 6)

Reason for change:	# Use of IKEv2 and IPsec ESP was approved last meeting. However, the cipher suites and algorithms need to be specified in order to ease the implementation. The chosen algorithm is AES, which is already used for temporary identities generation. Apart from the proposed algorithms for integrity and confidentiality, no encryption and/or no confidentiality must be possible to negotiate under some circumstances (for example high trust between 3GPP network and WLAN AN), according to the trust model in annex B.2 of TS 33.234 v0.8.0
Summary of change:	# Profiles for both IKEv2 and IPsec ESP are proposed. The profiles are taken from draft-ietf-ipsec-ui-suites-04.
Consequences if not approved:	# Multitude of possible implementations for IKEv2 and IPsec

Clauses affected:	# 5 Security features and 6 Security mechanisms			
Other specs affected:	#	#	Other core specifications #	
	#	#		Test specifications
	#	#		O&M Specifications
Other comments:	#			

*** BEGIN SET OF CHANGES ***

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 22.934: " Feasibility study on 3GPP system to Wireless Local Area Network (WLAN) interworking;".
- [2] 3GPP TR 23.934: "3GPP system to Wireless Local Area Network (WLAN) Interworking; Functional and architectural definition".
- [3] Draft-ietf-eap-rfc2284bis-06.txt, October 2003 "PPP Extensible Authentication Protocol (EAP)".
- [4] draft-arkko-pppext-eap-aka-11, October 2003, "EAP AKA Authentication".
- [5] draft-haverinen-pppext-eap-sim-12, October 2003, "EAP SIM Authentication".
- [6] IEEE Std 802.11i/D2.0, March 2002, "Draft Supplement to STANDARD FOR Telecommunications and Information Exchange Between Systems - LAN/MAN Specific Requirements - Part 11: Wireless Medium Access Control (MAC) and physical layer (PHY) specifications: Specification for Enhanced Security".
- [7] RFC 2716, October 1999, "PPP EAP TLS Authentication Protocol".
- [8] SHAMAN /SHA/DOC/TNO/WP1/D02/v050, 22-June-01, "Intermediate Report: Results of Review, Requirements and Reference Architecture".
- [9] ETSI TS 101 761-1 v1.3.1B "Broadband Radio Access Networks (BRAN); HIPERLAN Type 2; Data Link Control (DLC) layer; Part 1: Basic Data Transport".
- [10] ETSI TS 101 761-2 v1.2.1C "Broadband Radio Access Networks (BRAN); HIPERLAN Type 2; Data Link Control (DLC) layer; Part 2: Radio Link Control (RLC) sublayer".
- [11] ETSI TS 101 761-4v1.3.1B "Broadband Radio Access Networks (BRAN); HIPERLAN Type 2; Data Link Control (DLC) layer; Part 4 Extension for Home Environment".
- [12] ETSI TR 101 683 v1.1.1 "Broadband Radio Access Networks (BRAN); HIPERLAN Type 2; System Overview".
- [13] 3GPP TS 23.234 "3GPP system to Wireless Local Area Network (WLAN) Interworking System Description".
- [14] RFC 2486, January 1999, "The Network Access Identifier".
- [15] RFC 2865, June 2000, "Remote Authentication Dial In User Service (RADIUS)".
- [16] RFC 1421, February 1993, "Privacy Enhancement for Internet Electronic Mail: Part I: Message Encryption and Authentication Procedures".
- [17] Federal Information Processing Standard (FIPS) draft standard, "Advanced Encryption Standard (AES)", November 2001.

- [18] 3GPP TS 23.003: "Numbering, addressing and identification".
- [19] IEEE P802.1X/D11 June 2001, "Standards for Local Area and Metropolitan Area Networks: Standard for Port Based Network Access Control".
- [20] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [21] 3GPP TS 33.102: "3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; 3G Security; Security Architecture".
- [22] SIM Access Profile, Interoperability Specification, version 0.95VD - d. Document no. CAR 020 SPEC/0.95cB
- [23] draft-ietf-aaa-eap-03.txt, October 2003, " Diameter Extensible Authentication Protocol (EAP) Application".
- [24] RFC 3588, September 2003, "Diameter base protocol".
- [25] RFC 3576, July 2003, "Dynamic Authorization Extensions to Remote Authentication Dial In User Service (RADIUS)".
- [26] RFC 3579, September 2003, "RADIUS (Remote Authentication Dial In User Service) Support for Extensible Authentication Protocol (EAP)".
- [27] draft-ietf-eap-keying-01.txt, November 2003, "EAP Key Management Framework".
- [28] E. Barkan, E. Biham, N. Keller, "Instant Ciphertext-Only Cryptanalysis of GSM Encrypted Communication", Crypto 2003, August 2003
- [29] [draft-ietf-ipsec-ikev2-12.txt, January 2004, "Internet Key Exchange \(IKEv2\) Protocol"](#)
- [30] [RFC 2406, November 1998, "IP Encapsulating Security Payload \(ESP\)"](#)
- [31] [draft-ietf-ipsec-ui-suites-04.txt, August 2003, "Cryptographic Suites for IPsec"](#)

*** END SET OF CHANGES ***

*** BEGIN SET OF CHANGES ***

6.5 Profile of IKEv2

IKEv2, as specified in [ref. \[ikev229\]](#), contains a number of options which are not all needed for the purposes of this specification. IKEv2ESP is therefore profiled in this section. When IKEv2 is used in the context of this specification the profile specified in this section shall be supported.

[Access to services offered by the HPLMN \(scenario 3\) follows a VPN-like approach. In ref. \[31\] it can be found a set of recommendations of IKEv2 profiles, suitable for VPN-like solutions. For I-WLAN, it will be used the following one:](#)

- [Confidentiality: AES with fixed key length in CBC mode. The key length is set to 128 bits.](#)
- [Pseudo-random function: AES-XCBC-PRF-128](#)
- [Integrity: AES-XCBC-MAC-96](#)

The reasons to choose this one are the advantages of AES and its current support by the home network (AAA server) and the UE to for EAP SIM/AKA.

Editor's note: an example of a profile of IKE, which may be useful to study when writing this section, can be found in TS 33.210, section 5.4.

6.6 Profile of IPsec ESP

IPsec ESP, as specified in [ref. \[30\]](#), contains a number of options which are not all needed for the purposes of this specification. IPsec ESP is therefore profiled in this section. When IPsec ESP is used in the context of this specification the profile specified in this section shall be supported.

As for IKEv2, ref. [31] is used for the profile of IPsec ESP:

- Confidentiality: AES with 128-bit keys in CBC mode. The key length is set to 128 bits.
- Integrity: AES-XCBC-MAC-96
- Tunnel mode must be used

The reasons to choose this one are the same as in the case of IKEv2.

It will be possible to turn off security protection (confidentiality and/or integrity) in the tunnel (for example high trust between the 3GPP network operator and the WLAN access provider). This means that transform IDs for encryption ENCR_NULL and NONE for integrity shall be allowed to negotiate, as specified in ref. [29]

Editor's note: an example of a profile of IPsec ESP, which may be useful to study when writing this section, can be found in TS 33.210, section 5.3.

*** END SET OF CHANGES ***