

CR-Form-v7
CHANGE REQUEST
33.107 CR CRNum # rev - # Current version: 6.1.0

For **HELP** on using this form, see bottom of this page or look at the pop-up text over the # symbols.

Proposed change affects: UICC apps# ME Radio Access Network Core Network

Title:	# Correction to HLR interception event name				
Source:	# SA3-LI				
Work item code:	# SEC-LI	Date:	# 16/04/2004		
Category:	# F	Release:	# Rel-6		
	Use <u>one</u> of the following categories:		Use <u>one</u> of the following releases:		
	F (correction)		2 (GSM Phase 2)		
	A (corresponds to a correction in an earlier release)		R96 (Release 1996)		
	B (addition of feature),		R97 (Release 1997)		
	C (functional modification of feature)		R98 (Release 1998)		
	D (editorial modification)		R99 (Release 1999)		
	Detailed explanations of the above categories can be found in 3GPP TR 21.900 .		Rel-4 (Release 4)		
			Rel-5 (Release 5)		
			Rel-6 (Release 6)		

Reason for change:	# Correct the reference to a non-existent event in TS 33.107.
Summary of change:	# Changes the incorrect name ("Roaming") to the correct name ("Serving System").
Consequences if not approved:	# Misalignment within TS 33.107 and with TS 33.108. Also possible confusion to implementors.

Clauses affected:	# 7.3.2								
Other specs affected:	<table border="1" style="display: inline-table; border-collapse: collapse;"> <tr> <td style="width: 20px; text-align: center;">Y</td> <td style="width: 20px; text-align: center;">N</td> </tr> <tr> <td style="text-align: center;">#</td> <td style="text-align: center;">#</td> </tr> <tr> <td style="text-align: center;">#</td> <td style="text-align: center;">#</td> </tr> <tr> <td style="text-align: center;">#</td> <td style="text-align: center;">#</td> </tr> </table> Other core specifications # Test specifications # O&M Specifications #	Y	N	#	#	#	#	#	#
Y	N								
#	#								
#	#								
#	#								
Other comments:	#								

7.3.2 Structure of the events

There are eight different events in which the information is sent to the DF2 if this is required. Details are described in the following section. The events for interception are configurable (if they are sent to DF2) in the 3G GSN or the HLR and can be suppressed in the DF2.

The following events are applicable to 3G SGSN:

- Mobile Station Attach;
- Mobile Station Detach;
- PDP context activation;
- Start of intercept with PDP context active;
- PDP context modification;
- PDP context deactivation;
- RA update;
- SMS.

NOTE: 3G GGSN interception is a national option. Location information may not be available in this case.

The following events are applicable to the 3G GGSN:

- PDP context activation;
- PDP context modification;
- PDP context deactivation;
- Start of interception with PDP context active.

The following events are applicable to the HLR:

- ~~Roaming~~[Serving System](#).

A set of fields as shown below is used to generate the events. The events transmit the information from 3G GSN or HLR to DF2. This set of fields as shown below can be extended in the 3G GSN or HLR, if this is necessary as a national option. DF2 can extend this information if this is necessary as a national option e.g. a unique number for each surveillance warrant.

Table 2: Information Events for Packet Data Event Records

Observed MSISDN	MSISDN of the target subscriber (monitored subscriber).
Observed IMSI	IMSI of the target subscriber (monitored subscriber).
Observed IMEI	IMEI of the target subscriber (monitored subscriber), it shall be checked for each activation over the radio interface.
Event type	Description which type of event is delivered: MS attach, MS detach, PDP context activation, Start of intercept with PDP context active, PDP context deactivation, SMS, Serving System, Cell and/or RA update.
Event date	Date of the event generation in the 3G GSN or the HLR.
Event time	Time of the event generation in the 3G GSN or the HLR. Timestamp shall be generated relative to GSN or HLR internal clock.
PDP address	The PDP address of the target subscriber. Note that this address might be dynamic.
Access Point Name	The APN of the access point. (Typically the GGSN of the other party).
Location Information	Location Information is the Service Area Identity (SAI), RAI and/or location area identity that is present at the GSN at the time of event record production.
Old Location Information	Location Information of the subscriber before Routing Area Update
PDP Type	The used PDP type.
Correlation Number	The correlation number is used to correlate CC and IRI.
SMS	The SMS content with header which is sent with the SMS-service. The header also includes the SMS-Centre address.
Network Element Identifier	Unique identifier for the element reporting the ICE.
Failed attach reason	Reason for failed attach of the target subscriber.
Failed context activation reason	Reason for failed context activation of the target subscriber.
IAs	The observed Interception Areas.
Session Initiator	The initiator of the PDP context activation, deactivation or modification request either the network or the 3G MS.
Initiator	SMS indicator whether the SMS is MO or MT.
Deactivation / termination cause	The termination cause of the PDP context.
QoS	This field indicates the Quality of Service associated with the PDP Context procedure.
Serving System Address	Information about the serving system (e.g. serving SGSN number or serving SGSN address).