

CR-Form-v7

CHANGE REQUEST

33.246 CR 018 rev **4** Current version: **6.0.0**

For **HELP** on using this form, see bottom of this page or look at the pop-up text over the symbols.

Proposed change affects: UICC apps ME Radio Access Network Core Network

Title:	Clarification of the format of MTK ID and MSK ID.		
Source:	SA WG3		
Work item code:	MBMS	Date:	15/11/2004
Category:	C	Release:	Rel-6
	Use <u>one</u> of the following categories: <i>F</i> (correction) <i>A</i> (corresponds to a correction in an earlier release) <i>B</i> (addition of feature), <i>C</i> (functional modification of feature) <i>D</i> (editorial modification) Detailed explanations of the above categories can be found in 3GPP TR 21.900 .		Use <u>one</u> of the following releases: 2 (GSM Phase 2) R96 (Release 1996) R97 (Release 1997) R98 (Release 1998) R99 (Release 1999) Rel-4 (Release 4) Rel-5 (Release 5) Rel-6 (Release 6)

Reason for change:	The format of MSK ID and MTK ID is unclear. According to the TS MTK ID is a sequence number while MSK ID is not.
Summary of change:	The format of MSK ID and MTK ID are clarified. MSK ID is not a sequence number. MTK ID is a sequence number with length of 2 bytes and it shall be increased when MTK is updated.
Consequences if not approved:	MSK IDs and MTK IDs remains unclear.

Clauses affected:	6.3.3.1, 6.4.4						
Other specs affected:	<table border="1" style="display: inline-table; border-collapse: collapse;"> <tr> <td style="padding: 2px;">Y</td> <td style="padding: 2px;">N</td> </tr> <tr> <td style="padding: 2px;"><input type="checkbox"/></td> <td style="padding: 2px;"><input checked="" type="checkbox"/></td> </tr> </table>	Y	N	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Other core specifications	
	Y	N					
	<input type="checkbox"/>	<input checked="" type="checkbox"/>					
<input type="checkbox"/>	<input checked="" type="checkbox"/>	Test specifications					
<input type="checkbox"/>	<input checked="" type="checkbox"/>	O&M Specifications					
Other comments:							

6.3.3.1 MTK identification

Every MTK is uniquely identifiable by its Network ID, Key Group ID, MSK ID and MTK ID

where

Network ID, Key Group ID and MSK ID are as defined in clause 6.3.2.1.

MTK ID is 2 bytes long sequence number and is used to distinguish MTKs that have the same Network ID, Key Group ID and MSK ID. It is carried in the MTK-ID field of MIKEY extension payload. The MTK ID shall be increased every time the MTK is updated. The MTK ID shall be reset every time the MSK is updated.

~~Editor's Note: The format of MTK is ffs.~~

***** NEXT CHANGE*****

6.4.4 General extension payload

The MSK and MTK shall be delivered in messages that conform to the structure defined in RFC 3830 [9] (MIKEY). To be able to keep track of the keys, a new general Extension Payload (EXT) is defined that conforms to the structure defined in 6.15 of RFC 3830 [9] (MIKEY). The IDs of the involved keys are kept in the EXT, to enable the UE to look up the identity of the key which was used to protect the message, and which key is delivered in the message. This EXT is incorporated in the MIKEY messages (see Figure 6.4). When an MSK is delivered to a UE, the MIKEY message contains an EXT that holds the MUK ID of the MUK used to protect the delivery, and the MSK ID of the MSK delivered in the message. For messages that contain an MTK, the EXT contains the MSK ID of the MSK used to protect the delivery, and the MTK ID of the MTK contained in the message. Cf. subclauses 6.3.2.1 and 6.3.3.1 for definition of MSK ID and MTK ID. The ~~MSK ID and MTK ID are~~ is increased ~~by 1~~ every time the corresponding key is updated. It is possible that the same MTK is delivered several times in multicast, and the ME can then discard messages related to a key it already has instead of passing them to the MGV-F.

The MGV-F (see clause 6.5) protects itself from a possibly malicious ME by checking the integrity and freshness of the MIKEY message.

The format of the key IDs shall be represented by unsigned integers ~~s-counters~~, different from zero. The reason for disallowing zero is that it is reserved for future use. Note that this means that there can only be $2^n - 1$ different keys in use during the same session, where n is the number of bits in the ID field.




Figure 6.4: Extension payload used with MIKEY

The Inner Key ID is the ID of the key that is transported in the message (i.e. an MSK or MTK). The Outer Key ID is the ID of the key used as pre-shared secret for the key delivery (i.e. an MUK or MSK).