

**TSG-RAN Meeting #10  
Bangkok, Thailand, 6 - 8 December 2000**

**TSGRP#10(00)0622**

**Title:** Agreed CRs to TS 25.424

**Source:** TSG-RAN WG3

**Agenda item:** 5.3.3

<b>Tdoc_Num</b>	<b>Specification</b>	<b>CR_Num</b>	<b>Revision_Nu</b>	<b>CR_Subject</b>	<b>CR_Categor</b>	<b>WG_Status</b>	<b>Cur_Ver_Nu</b>	<b>New_Ver_Nu</b>
R3-003258	25.424	006	1	Application of AAL2 Link Characteristics on lub/lur	F	agreed	3.4.0	3.5.0

CR-Form-v3	
<b>CHANGE REQUEST</b>	
⌘ <b>25.424 CR 006</b> ⌘ rev <b>1</b> ⌘	Current version: <b>3.4.0</b> ⌘

For **HELP** on using this form, see bottom of this page or look at the pop-up text over the ⌘ symbols.

**Proposed change affects:** ⌘ (U)SIM  ME/UE  Radio Access Network  Core Network

<b>Title:</b>	⌘ Application of AAL2 Link Characteristics on Iur CCHs	
<b>Source:</b>	⌘ R-WG3	
<b>Work item code:</b>	⌘	<b>Date:</b> ⌘ 22.11.2000
<b>Category:</b>	⌘ <b>F</b>	<b>Release:</b> ⌘ R99
	<p><i>Use one of the following categories:</i></p> <p><b>F</b> (essential correction)  <b>A</b> (corresponds to a correction in an earlier release)  <b>B</b> (Addition of feature),  <b>C</b> (Functional modification of feature)  <b>D</b> (Editorial modification)</p> <p>Detailed explanations of the above categories can be found in 3GPP TR 21.900.</p>	<p><i>Use one of the following releases:</i></p> <p><b>2</b> (GSM Phase 2)  <b>R96</b> (Release 1996)  <b>R97</b> (Release 1997)  <b>R98</b> (Release 1998)  <b>R99</b> (Release 1999)  <b>REL-4</b> (Release 4)  <b>REL-5</b> (Release 5)</p>

<b>Reason for change:</b>	⌘ Currently the application of AAL2 Link Characteristics (ALC) is ambiguous as nothing has been said of it. In the given reference Q.2630 the use of ALC is optional, but meant to be used in the switched case of AAL2. From the multivendor operability viewpoint it is required to be specified whether ALC is available or not in the UTRAN interfaces.
<b>Summary of change:</b>	⌘ The ALC is a mandatory parameter in ALCAP when there is AAL2 switching in the Transport Network Layer of the interface.
<b>Consequences if not approved:</b>	⌘ The TS is ambiguous and the multivendor operability is endangered.

<b>Clauses affected:</b>	⌘ 6.2	
<b>Other specs affected:</b>	⌘ <input checked="" type="checkbox"/> Other core specifications <input type="checkbox"/> Test specifications <input type="checkbox"/> O&M Specifications	⌘ TS25.426 (CR009), TS25.434 (CR005)
<b>Other comments:</b>	⌘ The resulting revised CR of the contribution R3-003129	

---

## 6 I<sub>ur</sub> Transport Signalling for Common Transport Channel Data Streams

### 6.1 Introduction

This clause specifies the transport signalling protocol(s) used to establish the user plane transport bearers. The protocol stack is shown in [6].

### 6.2 Transport Signalling

AAL2 signalling protocol Capability Set 1, ITU-T Recommendation Q.2630.1 [4], is the signalling protocol to control the AAL2 connections on Iur interfaces. AAL2 transport layer addressing is based on embedded E.164 or AESA variants of the NSAP addressing format [5]. Native E.164 addressing shall not be used.

Binding ID provided by the radio network layer shall be copied in SUGR parameter of ESTABLISH.request primitive of [4].

If there is an AAL2 switching function in the transport network layer of the interface, the AAL2 Link Characteristics parameter (ALC) in the Establish Request message of AAL2 signalling protocol shall be used.