

TSG-RAN WG1, Meeting #15  
Berlin, Germany, 22-25 August, 2000

R1-00-1109

**Agenda item:**

**Source:** QUALCOMM Europe

**Title:** Proposed update to TR 25.926

Compressed mode in support of LCS related measurement

**Document for:** Decision

---

Several LCS techniques have been approved for inclusion in R'99. LCS should therefore be fully supported by the physical layer specification. However, the current text in 25.926 does not enable the UE to report the need for UL and/or DL compressed mode in support of LCS in general and GPS measurements in particular when this technique is supported in the UE.

The corrections proposed in the attached text proposal, together with CR 25.215-073 (R1-00-1108) would ensure that LCS techniques are fully and efficiently supported within the R'99 framework.

If and when the corresponding CR on 25.215 is approved, we propose to send the attached text update to TSG RAN WG2 for inclusion in their consolidated CR to TR 25.926.

## 4.9 Measurement related capabilities

### Need for downlink compressed mode

Defines whether the UE needs compressed mode in the downlink in order to perform inter-frequency, ~~or~~ inter-RAT or LCS measurements. There are separate parameters for measurements on each UTRA mode, on each RAT, and in each frequency band as well as for LCS related measurements.

### Need for uplink compressed mode

Defines whether the UE needs compressed mode in the uplink in order to perform inter-frequency, ~~or~~ inter-RAT or LCS measurements. There are separate parameters for measurements on each UTRA mode, on each RAT, and in each frequency band as well as for LCS related measurements.

## 5 Possible UE radio access capability parameter settings

### 5.1 Value ranges

**Table 5.1: UE radio access capability parameter value ranges**

		UE radio access capability parameter	Value range
PDCP parameters		Header compression algorithm supported	Yes/No
RLC parameters		Total RLC AM buffer size	2,10,50,100,150,500,1000 kBytes
		Maximum number of AM entities	3,4,5,6,8,16,32
PHY parameters	Transport channel parameters in downlink	Maximum sum of number of bits of all transport blocks received in TTIs that end within the same arbitrary interval of length $T < 10$ ms	640, 1280, 2560, 3840, 5120, 6400, 7680, 8960, 10240, 20480, 40960, 81920, 163840
		Maximum sum of number of bits of all convolutionally coded transport blocks received in TTIs that end within the same arbitrary interval of length $T < 10$ ms	640, 1280, 2560, 3840, 5120, 6400, 7680, 8960, 10240, 20480, 40960, 81920, 163840
		Maximum sum of number of bits of all turbo coded transport blocks received in TTIs that end within the same arbitrary interval of length $T < 10$ ms	640, 1280, 2560, 3840, 5120, 6400, 7680, 8960, 10240, 20480, 40960, 81920, 163840
		Maximum number of simultaneous transport channels	4, 8, 16, 32
		Maximum number of simultaneous CCTrCH	1, 2, 3, 4, 5, 6, 7, 8
		Maximum total number of transport blocks received within TTIs that end within the same 10 ms interval	4, 8, 16, 32, 48, 64, 96, 128, 256, 512
		Maximum number of TFC in the TFCS	16, 32, 48, 64, 96, 128, 256, 512, 1024
		Maximum number of TF	32, 64, 128, 256, 512, 1024
		Support for turbo decoding	Yes/No
		Transport channel parameters in uplink	Maximum sum of number of bits of all transport blocks transmitted in TTIs that start at the same time
	Maximum sum of number of bits of all convolutionally coded transport blocks transmitted in TTIs that start at the same time		640, 1280, 2560, 3840, 5120, 6400, 7680, 8960, 10240, 20480, 40960, 81920, 163840
	Maximum sum of number of bits of all turbo coded transport blocks transmitted in TTIs that start at the same time		640, 1280, 2560, 3840, 5120, 6400, 7680, 8960, 10240, 20480, 40960, 81920, 163840
	Maximum number of simultaneous transport channels		2, 4, 8, 16, 32
	Maximum number of simultaneous CCTrCH of DCH type (TDD only)		1, 2, 3, 4, 5, 6, 7, 8
	Maximum total number of transport blocks transmitted within TTIs that start at the same time		2, 4, 8, 16, 32, 48, 64, 96, 128, 256, 512
	Maximum number of TFC in the TFCS		4, 8, 16, 32, 48, 64, 96, 128, 256, 512, 1024
	Maximum number of TF		32, 64, 128, 256, 512, 1024
	Support for turbo encoding		Yes/No
	FDD Physical channel parameters in downlink	Maximum number of DPCH/PDSCH codes to be simultaneously received	1, 2, 3, 4, 5, 6, 7, 8

		UE radio access capability parameter	Value range
		Maximum number of physical channel bits received in any 10 ms interval (DPCH, PDSCH, S-CCPCH)	600, 1200, 2400, 3600, 4800, 7200, 9600, 14400, 19200, 28800, 38400, 48000, 57600, 67200, 76800
		Support for SF 512	Yes/No
		Support of PDSCH	Yes/No
		Simultaneous reception of SCCPCH and DPCH	Yes/No
		Simultaneous reception of SCCPCH, DPCH and PDSCH	Yes/No
		Maximum number of simultaneous S-CCPCH radio links	1 NOTE: Only the value 1 is part of R99
	FDD Physical channel parameters in uplink	Maximum number of DPDCH bits transmitted per 10 ms	600, 1200, 2400, 4800, 960, 19200, 28800, 38400, 48000, 57600
		Support of PCPCH	Yes/No
	TDD physical channel parameters in downlink	Maximum number of timeslots per frame	1..14
		Maximum number of physical channels per frame	1,2,3,..,224
		Minimum SF	16, 1
		Support of PDSCH	Yes/No
	TDD physical channel parameters in uplink	Maximum Number of timeslots per frame	1..14
		Maximum number of physical channels per timeslot	1, 2
		Minimum SF	16,8,4,2,1
Support of PUSCH		Yes/No	
RF parameters	FDD RF parameters	UE power class (25.101 subclause 6.2.1)	3, 4 NOTE: Only power classes 3 and 4 are part of R99
		Tx/Rx frequency separation (25.101 subclause 5.3) . NOTE: Not applicable if UE is not operating in frequency band a	190 MHz 174.8-205.2 MHz 134.8-245.2 MHz
RF parameters	TDD RF parameters	UE power class (25.102)	2,3 NOTE: Only power classes 2 and 3 are part of R99
		Radio frequency bands (25.102)	a), b), c), a+b), a+c), a+b+c)
		Chip rate capability (25.102)	3.84,1.28
Multi-mode related parameters		Support of UTRA FDD/TDD	FDD, TDD, FDD+TDD
Multi-RAT related parameters		Support of GSM	Yes/No
		Support of multi-carrier	Yes/No
LCS related parameters		Standalone location method(s) supported	Yes/No
		Network assisted GPS support	Network based / UE based / Both/ None
		GPS reference time capable	Yes/No
		Support for IPDL	Yes/No
		Support for OTDOA UE based method	Yes/No
Measurement related capabilities		Need for downlink compressed mode	Yes/No (per frequency band, UTRA mode and RAT, for LCS)
		Need for uplink compressed mode	Yes/No (per frequency band, UTRA mode and RAT, for LCS)