

TSG-RAN Working Group 1 meeting #15

Aug. 22nd – 25th 2000, Berlin, Germany

TSGR1#15(00)1059

Source : LGIC

Title : CR to 25.212 for correction regarding CPCH

Document for : Approval

CHANGE REQUEST

Please see embedded help file at the bottom of this page for instructions on how to fill in this form correctly.

25.212 CR 090

Current Version: **3.3.0**

GSM (AA.BB) or 3G (AA.BBB) specification number ↑

↑ CR number as allocated by MCC support team

For submission to: **TSG-RAN #9**
 list expected approval meeting # here ↑

for approval
 for information

strategic
 non-strategic (for SMG use only)

Form: CR cover sheet, version 2 for 3GPP and SMG The latest version of this form is available from: <ftp://ftp.3gpp.org/Information/CR-Form-v2.doc>

Proposed change affects: (U)SIM ME UTRAN / Radio Core Network
 (at least one should be marked with an X)

Source: LGIC **Date:** Aug. 9 2000

Subject: Correction regarding CPCH

Work item:

Category: F Correction **Release:** Phase 2
 A Corresponds to a correction in an earlier release Release 96
 (only one category shall be marked with an X) B Addition of feature Release 97
 C Functional modification of feature Release 98
 D Editorial modification Release 99
 Release 00

Reason for change: 1. TS 25.302 describes that there is only one TrCH in a CCTrCH for CPCH.
 2. In case of PCPCH, multi-code transmission is not allowed.

Clauses affected: 4.2.13.3

Other specs affected: Other 3G core specifications → List of CRs:
 Other GSM core specifications → List of CRs:
 MS test specifications → List of CRs:
 BSS test specifications → List of CRs:
 O&M specifications → List of CRs:

Other comments:



help.doc

<----- double-click here for help and instructions on how to create a CR.

4.2.13.3 Common Packet Channel (CPCH)

— The maximum value of the number of TrCHs I in a CCTrCH, the maximum value of the number of transport blocks M_i on each transport channel, and the maximum value of the number of DPDCHs P are given from the UE capability class.

NOTE: — Only the data part of the CPCH can be mapped on multiple physical channels (this note is taken from TS 25.302).

- There can only be one TrCH in each CPCH CCTrCH, i.e. $I=1$, $S_k = f_{1k}$ and $S = V_1$.

- The maximum value of the number of transport blocks M_1 on the transport channel is given from the UE capability class.

- Only one PCPCH is used, i.e. $P=1$, $u_{1k} = s_{k*}$ and $U = S$.