

Source: TSG SA1
Title: CRs to Service Principles (22.101) on USIM selection
Document for: Approval
Agenda Item: 6.1.3

Doc-1st-Level	Doc-2nd-Level	Spec	CR	Rev	Phase	Cat	Subject	Version-Current	Version-New
SP-000202	S1-000326	22.101	039		R99	F	Clarification for USIM Application selection	3.9.0	3.10.0

3GPP SA1

Document **S1-000326**

Beijing, China, 10-14 April 2000

CHANGE REQUEST

22.101 CR 039

Current Version: 3.9.0

Submitted to SA #8
TSG_SA:

for approval

strategic

for information

non-strategic

Proposed change affects:

(U)SIM

ME

UTRAN / Radio

Core Network

Source: TSG SA1

Date: 10/04/2000

Subject: Clarification for USIM Application selection

Work item:

Category:

- F Correction
- A Corresponds to a correction in an earlier release
- B Addition of feature
- C Functional modification of feature
- D Editorial modification

- Release:**
- Phase 2
 - Release 96
 - Release 97
 - Release 98
 - Release 99
 - Release 00

Reason for change:

The present CR proposes the inclusion of a clarifying text on the selection of USIM application. This behaviour needs to be properly documented in the stage 1 document. This CR proposes the clarifying text in sect. 11.1.4.

Clauses affected: 11.1.4

Other specs affected:

- Other 3G core specifications ? List of CRs:
- Other GSM core specifications ? List of CRs:
- MS test specifications ? List of CRs:
- BSS test specifications ? List of CRs:
- O&M specifications ? List of CRs:

Other comments:

11.1.4 Multiple USIMs per UICC

The standard shall support more than one USIM per UICC even when those USIMs are associated with different home environments. Only one of the USIMs or the SIM shall be active at a given time. While the UE is in idle mode, it shall be possible for the user to select/reselect one USIM from the application amongst those available on the UICC. At switch on, the Last Active USIM shall be automatically selected. The Last Active USIM shall be stored on the UICC. By default if there is no Last Active USIM defined in the UICC, the user shall be able to select the active USIM amongst those available on the UICC.

The standard must not prevent the coexistence of USIM applications, each associated with different home environments on the same UICC, so long as the security problems which arise from such a coexistence are solved.