

Source: SA5 (Telecom Management)
Title: 32.111 CR, "Split of TS - Part 1: Main part of spec – Requirements"
(S5-000328)
Document for: Approval
Agenda Item: 6.5.3

SA5 has split TS 32.111 into a multi-part TS as identified below:

Part 1: "3G Fault Management Requirements";

Part 2: "Alarm Integration Reference Point: Information Service";
Part 3: "Alarm Integration Reference Point: CORBA Solution Set";
Part 4: "Alarm Integration Reference Point: CMIP Solution Set".

Six (6) CRs are submitted to SA#8 for approval; the present one is highlighted in yellow:

Spec	CR	Phase	Subject	Cat	Version-Current	Version-New	Doc-2nd-Level
32.111	001	R99	Split of TS - Part 1: Main part of spec – Requirements	F	3.0.1	3.1.0	S5-000328
32.111	002	R99	Split of TS - Part 1: Main part of spec - Merging of Clause X into Clause 4, etc.	F	3.0.1	3.1.0	S5-000329
32.111	003	R99	Split of TS - Part 1: Main part of spec – Alignment of FM requirements with IRP, etc.	F	3.0.1	3.1.0	S5-000331
32.111	004	R99	Split of TS - Part 2: Alarm IRP Information Service (IS)	F	3.0.1	3.1.0	S5-000332
32.111	005	R99	Split of TS - Part 3: Alarm IRP CORBA Solution Set (SS)	F	3.0.1	3.1.0	S5-000333
32.111	006	R99	Split of TS - Part 4: Alarm IRP CMIP Solution Set (SS)	F	3.0.1	3.1.0	S5-000334

3G TS 32.111-1 V3.0.1a (2000-065)

Technical Specification



**3rd Generation Partnership Project;
Technical Specification Group Services and System Aspects;
PART1: 3G Fault Management
(Release 1999)**

The present document has been developed within the 3rd Generation Partnership Project (3GPP™) and may be further elaborated for the purposes of 3GPP. The present document has not been subject to any approval process by the 3GPP Organisational Partners and shall not be implemented. This Specification is provided for future development work within 3GPP only. The Organisational Partners accept no liability for any use of this Specification. Specifications and reports for implementation of the 3GPP™ system should be obtained via the 3GPP Organisational Partners' Publications Offices.

Keywords

Fault Management, Alarms

3GPP

Postal address

3GPP support office address

650 Route des Lucioles - Sophia Antipolis
Valbonne - FRANCE
Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Internet

<http://www.3gpp.org>

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© 2000, 3GPP Organizational Partners (ARIB, CWTS, ETSI, T1, TTA, TTC).
All rights reserved.

Contents

Foreword

This Technical Specification (TS) has been produced by the 3rd Generation Partnership Project (3GPP).

The present document is part 1 of multi-part 3G TS covering the 3rd Generation Partnership Project: Technical Specification Group Services and System Aspects, as identifies below:

Part 1: “3G Fault Management Requirements”;

Part 2: “ Alarm Integration Reference Point: Information Service”;

Part 3: “Alarm Integration Reference Point: CORBA Solution Set”;

Part 4: “Alarm Integration Reference Point: CMIP Solution Set”.

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

x the first digit:

- 1 presented to TSG for information;
- 2 presented to TSG for approval;
- 3 or greater indicates TSG approved document under change control.

y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.

z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

The present document is part of a set of TSs which describe the requirements and information model necessary for the Telecommunication Management (TM) of 3G systems. The TM principles and TM architecture are specified in 3G TS 32.101 and 3G TS 32.102.

A 3G system is composed of a multitude of network elements (NE) of various types and, typically, different vendors which inter-operate in a co-ordinated manner in order to satisfy the network users' communication requirements. The occurrence of failures in a network element may cause a deterioration of this NE's function and/or service quality and will, in severe cases, lead to the complete unavailability of the NE. In order to minimise the effects of such failures on the quality of service as perceived by the network users it is necessary to:

- detect failures in the network as soon as they occur and alert the operating personnel as fast as possible;
- isolate the failures (autonomously or through operator intervention), i.e. switch off faulty units and, if applicable, limit the effect of the failure as much as possible by reconfiguration of the faulty NE/adjacent NEs;
- if necessary, determine the cause of the failure using diagnosis and test routines; and,
- repair/eliminate failures in due time through the application of maintenance procedures.

This aspect of the management environment is termed "Fault Management" (FM). The purpose of FM is to detect failures as soon as they occur and to limit their effects on the network quality of service as far as possible. The latter is

achieved by bringing additional/redundant equipment into operation, reconfiguring existing equipment/NEs, or by repairing/eliminating the cause of the failure.

Fault Management encompasses all of the above functionalities except commissioning/decommissioning of NEs and potential operator triggered reconfiguration (these are a matter of Configuration Management, cf. [1]). It also includes associated features in the OS, such as the administration of a pending alarms list, the presentation of operational state information of physical and logical devices/resources/functions, and the provision and analysis of the alarm and state history of the network.

1 Scope

~~This TS 32.111-1 The present document~~ specifies the overall requirements for 3G Fault Management as it applies to the NE, EM and NM.

Clauses 4 ~~and 5~~ defines the fault management concept and functional requirements for the detection of faults and the generation, collection and presentation of alarms, operational state data and test results across 3G systems. These functions are described on a non-formal level since the formal standardisation of these functions across the different vendors' equipment is not required. The functional areas to be specified in this part of the document cover:

- fault surveillance and detection in the NEs;
- notification of alarms (including alarm cease) and operational state changes;
- retrieval of current alarms from the NEs;
- fault isolation and defence mechanisms in the NEs;
- alarm filtering;
- management of alarm severity levels;
- alarm and operational state data presentation and analysis at the OS;
- retention of alarm and operational state data in the NEs and the OS; and
- the management of tests.

Any (re)configuration activity exerted from the OMC as a consequence of faults will not be subject of the present document, these are described in [1].

~~Clauses 6 and 7 of the present document describe specific aspects of the Fault Management for the UTRAN and the CN, respectively, with particular emphasis on the exact fault definitions and alarm information to be generated. The definition of the test procedures and the relationship with the UTRAN resp. CN management architecture as defined in [3].~~

Finally, Clause 8~~5~~ of the present document defines the functional requirements for the standard Itf-N, for the purpose of Fault Management of 3G networks, as seen from the Network Manager (NM). The Itf-N is fully standardised so as to connect systems of any vendor to the NM via this interface.

CHANGE REQUEST

Please see embedded help file at the bottom of this page for instructions on how to fill in this form correctly.

32.111 CR 001

Current Version: **3.0.1**

GSM (AA.BB) or 3G (AA.BBB) specification number ↑

↑ CR number as allocated by MCC support team

For submission to: **SA#8**
list expected approval meeting # here ↑

for approval
for information

strategic
non-strategic (for SMG use only)

Form: CR cover sheet, version 2 for 3GPP and SMG The latest version of this form is available from: <ftp://ftp.3gpp.org/Information/CR-Form-v2.doc>

Proposed change affects:

(at least one should be marked with an X)

(U)SIM ME UTRAN / Radio Core Network

Source:

SA5#12

Date:

20 June 2000

Subject:

Split of TS - Part 1: Main part of spec – Requirements

Work item:

32.111 3G Fault Management

Category:

(only one category shall be marked with an X)

F Correction
A Corresponds to a correction in an earlier release
B Addition of feature
C Functional modification of feature
D Editorial modification

Release:

Phase 2
Release 96
Release 97
Release 98
Release 99
Release 00

Reason for change:

The following changes are proposed to be introduced in TS 32.111 Ver 3.0.1

The changes are derived from the decision to split the original document in four parts.

This is the Part-1 and contains the requirements for the Fault Management of the 3GPP Systems

Clauses affected:

Front page, Foreword, Scope.

Other specs affected:

Other 3G core specifications → List of CRs:
Other GSM core specifications → List of CRs:
MS test specifications → List of CRs:
BSS test specifications → List of CRs:
O&M specifications → List of CRs:

Other comments:

