

**Source:** SA1

**Title:** CRs to 22.101 Rel-4 and Rel-5 on Replacement of references to 23.121 for R4 onwards

**Document for:** Approval

**Agenda Item:** 7.1.3

---

Spec	CR	Rev	Phase	Cat	Subject	Version-Current	Version-New	Doc-2nd-Level
22.101	071		Rel-4	F	Replacement of references to 23.121 for R4 onwards	4.3.0	4.4.0	S1-010504
22.101	072		Rel-5	A	Replacement of references to 23.121 for R4 onwards	5.2.0	5.3.0	S1-010505

CR-Form-v3

**CHANGE REQUEST**⌘ **TS22.101** **CR** **071** ⌘ rev **-** ⌘ Current version: **4.3.0** ⌘For **HELP** on using this form, see bottom of this page or look at the pop-up text over the ⌘ symbols.Proposed change affects: ⌘ (U)SIM  ME/UE  Radio Access Network  Core Network 

<b>Title:</b>	⌘ Correct References to "architecture requirements" specification		
<b>Source:</b>	⌘ SA1		
<b>Work item code:</b>	⌘ IMS	<b>Date:</b>	⌘ 11/05/01
<b>Category:</b>	⌘ F	<b>Release:</b>	⌘ REL-4
	Use <u>one</u> of the following categories: <b>F</b> (essential correction) <b>A</b> (corresponds to a correction in an earlier release) <b>B</b> (Addition of feature), <b>C</b> (Functional modification of feature) <b>D</b> (Editorial modification) Detailed explanations of the above categories can be found in 3GPP TR 21.900.		Use <u>one</u> of the following releases: <b>2</b> (GSM Phase 2) <b>R96</b> (Release 1996) <b>R97</b> (Release 1997) <b>R98</b> (Release 1998) <b>R99</b> (Release 1999) <b>REL-4</b> (Release 4) <b>REL-5</b> (Release 5)

**Reason for change:** ⌘ The current document makes reference to TS 23.121 and should reference TS 23.221**Summary of change:** ⌘ Modify reference.**Consequences if not approved:** ⌘ Document will contain incorrect reference.**Clauses affected:** ⌘ Sections Reference & 4.7
**Other specs affected:** ⌘  Other core specifications ⌘   Test specifications  
 O&M Specifications
**Other comments:** ⌘**How to create CRs using this form:**Comprehensive information and tips about how to create CRs can be found at: [http://www.3gpp.org/3G\\_Specs/CRs.htm](http://www.3gpp.org/3G_Specs/CRs.htm). Below is a brief summary:

- 1) Fill out the above form. The symbols above marked ⌘ contain pop-up help information about the field that they are closest to.
- 2) Obtain the latest version for the release of the specification to which the change is proposed. Use the MS Word "revision marks" feature (also known as "track changes") when making the changes. All 3GPP specifications can be downloaded from the 3GPP server under <ftp://www.3gpp.org/specs/>. For the latest version, look for the directory name with the latest date e.g. 2000-09 contains the specifications resulting from the September 2000 TSG meetings.
- 3) With "track changes" disabled, paste the entire CR form (use CTRL-A to select it) into the specification just in front of the clause containing the first piece of changed text. Delete those parts of the specification which are not relevant to the change request.

## 2.1 Normative References

[20] 3GPP TS 23.221 “Architectural Requirements”

## 4.7 PLMN Architecture

The network is logically divided into a radio access network and a core network, connected via an open interface. From a functional point of view the core network is divided into a Packet Switched CN Domain, IP Multimedia (IM) CN subsystem and a Circuit Switched CN Domain. IM CN subsystem utilises PS CN domain (GPRS) bearer services.

CS CN domain supports bearer independent transport. There is no difference in service offering or UE functionality due to different transport.

For further information see TS ~~23.121 [20]~~23.221 [20]

**CHANGE REQUEST**

⌘ **TS22.101** CR **072** ⌘ rev **-** ⌘ Current version: **5.2.0** ⌘

For **HELP** on using this form, see bottom of this page or look at the pop-up text over the ⌘ symbols.

**Proposed change affects:** ⌘ (U)SIM  ME/UE  Radio Access Network  Core Network

<b>Title:</b>	⌘ Correct References to "architecture requirements" specification		
<b>Source:</b>	⌘ SA1		
<b>Work item code:</b>	⌘ IMS	<b>Date:</b>	⌘ 11/05/01
<b>Category:</b>	⌘ A	<b>Release:</b>	⌘ REL-5
	Use <u>one</u> of the following categories: <b>F</b> (essential correction) <b>A</b> (corresponds to a correction in an earlier release) <b>B</b> (Addition of feature), <b>C</b> (Functional modification of feature) <b>D</b> (Editorial modification) Detailed explanations of the above categories can be found in 3GPP TR 21.900.		Use <u>one</u> of the following releases: <b>2</b> (GSM Phase 2) <b>R96</b> (Release 1996) <b>R97</b> (Release 1997) <b>R98</b> (Release 1998) <b>R99</b> (Release 1999) <b>REL-4</b> (Release 4) <b>REL-5</b> (Release 5)

**Reason for change:** ⌘ The current document makes reference to TS 23.121 and should reference TS 23.221

**Summary of change:** ⌘ Modify reference.

**Consequences if not approved:** ⌘ Document will contain incorrect reference.

**Clauses affected:** ⌘ Sections Reference & 4.7

**Other specs affected:** ⌘  Other core specifications ⌘  Test specifications  
 O&M Specifications

**Other comments:** ⌘

**How to create CRs using this form:**

Comprehensive information and tips about how to create CRs can be found at: [http://www.3gpp.org/3G\\_Specs/CRs.htm](http://www.3gpp.org/3G_Specs/CRs.htm). Below is a brief summary:

- 1) Fill out the above form. The symbols above marked ⌘ contain pop-up help information about the field that they are closest to.
- 2) Obtain the latest version for the release of the specification to which the change is proposed. Use the MS Word "revision marks" feature (also known as "track changes") when making the changes. All 3GPP specifications can be downloaded from the 3GPP server under <ftp://www.3gpp.org/specs/>. For the latest version, look for the directory name with the latest date e.g. 2000-09 contains the specifications resulting from the September 2000 TSG meetings.
- 3) With "track changes" disabled, paste the entire CR form (use CTRL-A to select it) into the specification just in front of the clause containing the first piece of changed text. Delete those parts of the specification which are not relevant to the change request.

## 2.1 Normative References

[20] 3GPP TS 23.221 “Architectural Requirements”

## 4.7 PLMN Architecture

The network is logically divided into a radio access network and a core network, connected via an open interface. From a functional point of view the core network is divided into a Packet Switched CN Domain, IP Multimedia (IM) CN subsystem and a Circuit Switched CN Domain. IM CN subsystem utilises PS CN domain (GPRS) bearer services.

CS CN domain supports bearer independent transport. There is no difference in service offering or UE functionality due to different transport.

For further information see TS ~~23.121 [20]~~23.221 [20]