

CHANGE REQUEST

⌘ **33.220 CR** ⌘ rev **-** ⌘ Current version: **6.1.0** ⌘

For **HELP** on using this form, see bottom of this page or look at the pop-up text over the ⌘ symbols.

Proposed change affects: UICC apps ME Radio Access Network Core Network

Title:	⌘ Requirement on ME capabilities for GBA_U		
Source:	⌘ Axalto, Gemplus, OCS		
Work item code:	⌘ SSC-GBA	Date:	⌘ 23/06/2004
Category:	⌘ B Use <i>one of the following categories:</i> F (correction) A (corresponds to a correction in an earlier release) B (addition of feature), C (functional modification of feature) D (editorial modification) Detailed explanations of the above categories can be found in 3GPP TR 21.900 .	Release:	⌘ Rel-6 Use <i>one of the following releases:</i> 2 (GSM Phase 2) R96 (Release 1996) R97 (Release 1997) R98 (Release 1998) R99 (Release 1999) Rel-4 (Release 4) Rel-5 (Release 5) Rel-6 (Release 6)

Reason for change:	⌘ Procedure for NAF key derivation in the UICC is not mandated in MEs supporting GBA. However, the decision on running GBA_U or GBA_ME bootstrap should not depend either on ME capabilities (1) or on the existence of ME applications requiring GBA_U bootstrap (2). The following reasons are given for both assertions: (1) No indication of ME's capabilities related to GBA_U or GBA_ME is available to BSF/HSS (2) Some UE applications (e.g. STK applications, middlelets) may need GBA_U derived keys without requiring specific capabilities in any ME application. So, the scenario where GBA_U is requested by BSF and the NAF derivation is not supported by the ME shall be avoided
Summary of change:	⌘ -Additon of a requirement on UE for mandating procedures for NAF-keys derivation.
Consequences if not approved:	⌘ Complete GBA_U bootstrap will not be possible depending on ME capabilities.

Clauses affected:	⌘ 5.2.1
	<input type="checkbox"/> Y <input type="checkbox"/> N

Other specs affected:	⌘	X	Other core specifications	⌘	TS 31.102, TS 31.103
		X	Test specifications		
		X	O&M Specifications		
Other comments:	⌘	-			

BEGIN OF CHANGE

5.2.1 Requirements on UE

The 3G AKA keys CK and IK resulting from a run of the protocol over the Ub reference point shall not leave the UICC.

The UICC shall be able to distinguish between authentication requests for GBA_U, and authentication requests for other 3G authentication domains.

Upon an authentication request from the ME, which the UICC recognises as related to GBA_U, the UICC shall derive two keys from CK and IK. ~~All 3G MEs are capable of such a request.~~

Upon request from the ME, the UICC shall be able to derive further NAF-specific keys from the derived key stored on the UICC. ~~Only GBA_U aware 3G MEs are capable of such a request.~~

[The ME shall support procedures for the two previous requests.](#)

Editor's Note: The location (whether in the UICC or in the ME) of the storage of Ks_ext is ffs.