

27 February - 02 March, 2001

Gothenberg, Sweden

3GPP TSG-T2 #11
Shin Yokohama, JAPAN
November 27th - December 1th 2000

T2-000804

Liaison Statement

From: T2
To: S2, T3, N1, S3
Cc:
Subject: Re: LS for "IM Subsystem Address Storage on USIM"

Contact: Kevin Holley
BT
+44 1473 605604
kevin.holley@bt.com

Attachments: none

T2 thanks S2 for their LS entitled "IM Subsystem Address Storage on USIM", which T2 has discussed.

T2 believes that it would be beneficial for the user if the storage is provided in the same place irrespective of whether the UE SIP client is inside or outside of the MT. If the UE SIP client is outside of the MT then it should not be a problem for T2 to provide the relevant means for the SIP client to obtain this information from the USIM via the MT.

However this needs to be considered in the overall framework requirements for UE architecture in the Release 5 timeframe. If this architecture is going to be based on multiple serial links then an AT command could be added. If on the other hand there will be a newer more "IP friendly" architecture for the UE then this framework would need to provide appropriate means for the TE to request the IMS Address from the MT. Either way, T2 will be able to fulfil this need.

T2 looks forward to further discussion and development of the UE side of the IMS architecture, and will be happy to consider further suggestions in this area.